PyTan Documentation

Release 3.0.0

Jim Olsen

Feb 22, 2019

Contents

1 Table of Contents 3

2 Indices and tables 525

Python Module Index 527

PyTan is an all-in-one API wrapper for Tanium and is comprised of *multiple modular layers* that make it easy to extend or add new functionality.

Since the inception of PyTan in *October of 2014* it has grown in scope, complexity, and adoption. This version marks the fourth redesign, and it has vast improvements over the previous versions.

Read *why PyTan was created* and *the list of features* to get an understanding of the intent and capabilities of PyTan.

Installation is simple using standard Python packaging tools.

CHAPTER 1

Table of Contents

1.1 Purpose

PyTan was created for a number of reasons:

1. To provide a way for Python programmers to work with the Tanium API using native Python objects.
2. To provide workflow encapsulation for Python programmers that contains the order of steps it takes to do something. For each step in a workflow, a workflow knows what attributes need to be defined in a request, how to handle the response, and how the response should be passed on to the next step.
3. To provide a command line interface for non Python programmers that exposes the workflow encapsulation via a Python script that takes in arguments and options and passes them on to the underlying workflow.

1.2 Features

1. Automation

   Create scripts that automate any concept you can think of.

   For example: You can write a script that asks a question, gets the results, and emails it to you. Then you can schedule that script via Task Scheduler/cron/etc to run every night.

2. Integration

   Create seamless integrations with other products.

   For example: You can write an integration with a ticketing system to have it automatically ask a question and include the results in the ticket.

3. Complete API exposure

   Anything that Tanium can do can be done via PyTan.

   It is a complete exposure of the Tanium API, which is what the web browser interface uses to perform all of its functions.

4. Workflow encapsulation

   Workflows remove the need for users of the Tanium API to know how requests must be sent for a given set of operations.

   For instance:

   - Asking a question, waiting for results, and then getting result data can equate to over 100 API calls.
   - Creating a user, assigning it to various RBAC roles, user groups, and so on can take over 30 API calls.

   Todo: No workflows are shipped with PyTan as of yet. It will take time to convert all of the workflows from PyTan 2.x into the new architecture built for PyTan 3.x.

   Planned for version: *3.1.0*

5. Command Line encapsulation around Workflows

   Command Line Interfaces make it so that users of the Tanium API do not even need to know PyTan to utilize the various workflows provided by PyTan.

   There are people in the IT world that prefer to work from a command line. PyTan makes that possible for users of Tanium.

   Todo: No command line interfaces are shipped with PyTan as of yet. The workflows will need to be done first, and then the logic for how to wrap those workflows seamlessly into command line scripts will take some effort.

   Planned for version: *3.2.0*

6. Security

   PyTan version 3 enforces SSL certificate validation for each Tanium server it connects to, and will prompt on the initial connection to a Tanium server for validity by showing information from the certificate and asking the user if it is valid.

   It also provides a secure method for storing credentials to disk at state, making it so that credentials aren't stored in plain text on scripts somewhere on disk.

7. Multiplatform support

   PyTan is written with the goal of working out of the box on all major Operating systems.

8. Python 2 and 3 support

   PyTan version 3 supports both Python 2 and Python 3. Previous versions of PyTan only supported Python 2.

9. Layered concept

   PyTan version 3 has all of its functionality organized into specific *layers* that build on top of each other.

   This version has 10 layers which make it vastly easier to maintain and extend PyTan, whereas previous versions of PyTan had all of the functionality bundled into one to three layers.

   All layers utilize Abstract Base Classes to establish a contract on the implementation of that specific layer.

   This allows each layer to have a well defined interface that enforces each implementation of that layer to work the same. It also makes it easy to support new API types, API commands, API versions, and more.

   For example: Authentication methods, API Clients, API Adapters, API Results, and API objects will each work the same regardless of the underlying implementation.

10. Version checking

    Each layer in PyTan3 that relies on the Tanium API has the ability to specify that the Tanium platform servers version is an exact version, or is at least a minimum version, or is at most a maximum version.

    This allows each object in a layer to specify what version(s) it will work with.

11. Type Checking

    Each layer in PyTan3 that relies on the Tanium API has the ability to specify what type of API it supports.

1.3 Installation

PyTan is actively maintained on GitHub, where the code is always available.

Make sure you have installed a *supported version* of Python.

Installing PyTan via pip or pipenv will automatically install all of the necessary *dependencies*.

1.3.1 Install into the system site-packages using pip

```
$ pip install pytan3
```

Read more about pip

1.3.2 Install into a virtual environment using pipenv

```
$ pipenv install pytan3
```

Read more about pipenv

1.3.3 Clone the pytan3 repository using git

```
$ git clone git://github.com/tanium/pytan3.git
```

1.3.4 Directly from GitHub

Get the master branch which will always be the most recent stable release, or download a specific version from the releases page.

Todo: It is planned to create a batteries included distribution of PyTan for Windows that will include Python 3.7.x as well as PyTan and all of its dependencies.

Planned for version: *3.2.0*

1.4 Future Releases

1.4.1 3.1.0

Rough ETA: 2019-04-01

- enhancement: Add workflows from PyTan v2
- enhancement: Add API commands for ImportObject, ExportObject, VerifySignature, and UploadFile
- enhancement: Add ability for test suite to automatically use Authentication Store
- enhancement: Add utility to generate Authentication Store
- verify: Verify that options supplied in REST tanium-options header do not conflict with options supplied in URL as parameters

1.4.2 3.2.0

Rough ETA: 2019-05-01

- enhancement: Add Command Line Interfaces
- enhancement: Add API interfaces to API Clients: module API passthru, /hash API, /string API, /file API, /cache API
- enhancement: Create a batteries included distribution

1.5 Supported Versions

1.5.1 Supported Python versions

- 3.7.x
- 2.7.x

Note: While Python 2.7.x is currently supported and tested, due to it's EOL of January 2020 it will be dropped from the testing category very soon.

It will remain supported until the next major rewrite of PyTan or until pip drops support for Python 2.7.x, whichever comes first.

Note: Other versions of Python could work beyond the tested versions.

If PyTan fails to work with a supported version of Python, it will be fixed as long as the changes required do not introduce breaking changes to the PyTan API and do not break support for the supported versions.

1.5.2 Supported Operating Systems

- Windows 10
- Windows 2010 and later

- Windows Server 2008 R2 and later
- Mac OS X 10.12 "Sierra" and later
- Any recent and major Linux distribution

Tested Operating systems for Python 3.7.2

- Windows 10 Professional
- Windows Server 2008 R2
- Windows Server 2012 R2
- Mac OS X 10.14.3 "Mojave"
- Ubuntu 18.04.2 LTS (Bionic Beaver)

Tested Operating systems for Python 3.7.1

- Mac OS X 10.14.3 "Mojave"

Tested Operating systems for Python 3.7.0

- Mac OS X 10.14.3 "Mojave"

Tested Operating systems for Python 2.7.15

- Windows 10 Professional
- Windows Server 2008 R2
- Windows Server 2012 R2
- Mac OS X 10.14.3 "Mojave"
- Ubuntu 18.04.2 LTS (Bionic Beaver)

Note: PyTan is written on Mac OS X, so that will always be the most tested.

1.5.3 Supported Tanium Versions

- Tanium 7.2.314.xxxx
- Tanium 7.3.314.xxxx

Tested Tanium SOAP API versions

- Tanium 7.2.314.3181
- Tanium 7.3.314.3424
- Tanium 7.3.314.3641

Tested Tanium REST API versions

- Tanium 7.3.314.3424
- Tanium 7.3.314.3641

Note: REST API only exists in versions after 7.3.314.3424.

Note: PyTan is not supported or tested on versions earlier than 7.2.314.xxxx, but a large portion of functionality should still work.

1.6 Release Strategy

All releases will have tags and branches named after their version number, and will also be published on the releases page.

1.6.1 Major releases

A major release will include breaking changes. If the previous release was v2.0.0 the next version will be v3.0.0.

Breaking changes are changes that break backwards compatibility with prior versions. If an API command was removed or the interface for a layer is completely different, that would only happen in a Major release.

Major releases may also include miscellaneous bug fixes. The core developers of PyTan are committed to providing a good user experience. This means we're also committed to preserving backwards compatibility as much as possible. Major releases will be infrequent and will need strong justifications before they are considered.

With that in mind, PyTan version 3 is a major release and as such has a vastly different architecture than version 2.

Any scripts that were written to use version 2 will not work with version 3.

1.6.2 Minor releases

A minor release will not include breaking changes but may include miscellaneous bug fixes. If the previous version of PyTan released was v3.1.0 a minor release would be versioned as v3.2.0.

Minor releases will be backwards compatible with releases that have the same major version number. In other words, all versions that would start with v3. should be compatible with each other.

1.6.3 Micro releases

A micro release will only include bug fixes that were missed when the previous version was released. If the previous version of PyTan released v3.1.0 the hotfix release would be versioned as v3.1.1.

1.7 Getting Help

Have a bug report or feature request?

Do not hesitate to file an issue with the appropriate label and with as many details as possible.

Feature requests are always welcome, especially for new workflows.

If you need help using PyTan, please ask your Technical Account Manager for assistance or email the author and maintainer of PyTan: Jim Olsen.

1.8 Giving Help

Contributions are most welcome. If you are not familiar with how to contribute to a project on GitHub, feel free to read this.

Since the foundation of PyTan is done, the next release of PyTan is focusing on Workflows. The design of how Workflows will be implemented is still being hashed out, but when it is finalized Workflow contributions will be very welcome.

The master branch is the stable branch, and should never have pull requests. Instead, pull requests should be performed against development version branches. The current version under development will always be named after the intended release followed by -dev, for example: `3.1.0-dev`.

Maintainers:

- Jim Olsen

Contributors:

- None as of yet

1.9 API Layers

1. *HTTP Client*

   The lowest layer and the core foundation of PyTan that handles sending and receiving requests using the requests package. It provides SSL certificate validation and user verification similar to a web browser, recording of requests and responses to files, and more.

2. *Authentication Methods*

   Authentication methods use an **HTTP Client** to authenticate against a Tanium platform server and receive a session token. They provide functionalities such as login, logout, logout all, and validate token.

3. *Authentication Store*

   The Authentication Store provides a secure way to store an **Authentication method**.

4. *API Clients*

   API clients use an **HTTP Client** and an **Authentication Method** to communicate with a specific type of API.

   API Clients know how to communicate with a specific API path, but do not have any native ability to construct the request bodies or parse the response bodies.

5. *API Object Modules*

   API Object Modules contain the object definitions used by the Tanium API as native Python objects.

   They are automatically generated using the WSDL for a given Tanium Platform version, and can be modified to work with a specific platform version and API type.

6. *Models for API Object Modules*

   API Models provide the base classes that make API Objects work like Python objects. They contain the functionality for list objects from the Tanium API to work like Python lists, and for item objects from the Tanium API to work like Python objects with each of the defined attributes from the API exposed as attributes on the object.

7. *Adapters*

   Adapters use an **API client** combined with an **API object module** to create and send requests. Adapters are responsible for:

   - Exposing API commands like get, add, delete, modify, and more.
   - Converting (serializing) a Python object from an **API object module** into a text string.
   - Creating a request body that contains the converted python object in a format that a given type of API understands.
   - Sending the request body using an **API client** and returning the response in a **Result**.

8. *Results*

   Results are heavily tethered to an **Adapter**, and are responsible for:

   - Checking for errors in the response and throwing the appropriate exception when an object already exists, an object is not found, a request was not properly formed, or a response returned an error.
   - Parsing the response from a request sent by an **Adapter** into a Python dictionary object.
   - Converting (deserializing) the objects or data set in the response into a Python object from an **API object module**.

9. *Workflows*

   Workflows rely on an **Adapter** and encapsulate all of the steps needed to perform complex operations into one function. A number of workflows are planned:

   - Adding, updating, deleting users, groups, RBAC, dashboards, and more…
   - Asking saved questions and getitng the answers back in various output forms
   - Asking parsed questions and getitng the answers back in various output forms
   - Asking manually crafted questions and getitng the answers back in various output forms
   - And more…

   Todo: No workflows are shipped with PyTan as of yet. It will take time to convert all of the workflows from PyTan 2.x into the new architecture built for PyTan 3.x.

   Planned for version: *3.1.0*

10. *Command Line Interfaces*

    The highest layer that provides Python scripts that expose **Workflows** to command line users and removes the need for a user to know how to program in Python in order to utilize PyTan.

    Todo: No command line interfaces are shipped with PyTan as of yet. The workflows will need to be done first, and then the logic for how to wrap those workflows seamlessly into command line scripts will take some effort.

    Planned for version: *3.2.0*

1.10 API Reference

Python object layer and workflow encapsulation for Tanium's API.

1.10.1 HTTP Client

Client for making HTTP requests.

`pytan3.http_client.CERT_FILE = '{http_client.parsed_url.hostname}.pem'`
: `str` – Certificate filename template for `Certify.__call__()`.

`pytan3.http_client.RECORD_FILE = '%Y_%m_%dT%H_%M_%S_%fZ.json'`
: `str` – Record filename template for `HttpClient.response_hook_disk()`.

`pytan3.http_client.SHOW_CERT = 'no'`
: `bool` – Default prompt value for "Show full certificate info" in `Certify.verify_hook()`.

Will use OS Environment variable "PYTAN_SHOW_CERT" if set.

`pytan3.http_client.SHOW_CHAIN = 'no'`
: `bool` – Default prompt value for "Show certificate chain info" in `Certify.verify_hook()`.

Will use OS Environment variable "PYTAN_SHOW_CHAIN" if set.

`pytan3.http_client.CERT_VALID = 'no'`
: `bool` – Default prompt value for "Consider certificate valid" in `Certify.verify_hook()`.

Will use OS Environment variable "PYTAN_CERT_VALID" if set.

class `pytan3.http_client.HttpClient`(*url*, *timeout=5*, *lvl='info'*)
: Bases: `object`

Convenience class for requests package.

CLEAN_HOOKS = {'/api/v\\d?/session': ['clean_hook_auth_rest'], '/auth': ['clean_hook
: `dict` – URL regex matches for cleaning bodies in cleaning hooks.

CLEAN_AUTH_KEYS = ['username', 'password', 'domain', 'secondary']
: `list` of `str` – Keys to clean in cleaning hooks.

CLEAN_HIDE = '###HIDDEN###'
: `str` – Text to use to hide values in cleaning hooks.

__init__(*url*, *timeout=5*, *lvl='info'*)
: Constructor.

Parameters

- **url** (`str`) – URL to use.
- **timeout** (`int`, optional) – Connect timeout to use for requests.

  Defaults to: 5.
- **lvl** (`str`, optional) – Logging level for this object.

  Defaults to: "info".

log = None
: `logging.Logger` – Log for this object.

timeout = None
: `int` – Connect timeout used for all requests.

parsed_url = None
UrlParser – Parsed version of URL.

last_request = None
requests.PreparedRequest – Last request sent.

last_response = None
requests.Response – Last response received.

history = None
list – History of all responses received.

Used by *HttpClient.response_hook_history()*.

record_path = None
pathlib.Path – Path to store response recordings to.

session = None
requests.Session – Requests session object.

certify = None
Certify – Certificate Magic object.

url
Get the URL string from *HttpClient.parsed_url*.

Returns str

__str__()
Show object info.

Returns str

__repr__()
Show object info.

Returns str

__call__(*method='get'*, *path=''*, *data=None*, *timeout=5*, *params=None*, *headers=None*, *b64_headers=None*, *verify=True*, ***kwargs*)
Create, prepare a request, and then send it.

Parameters

- **method** (str, optional) – Method to use.

  Defaults to: "get".

- **path** (str, optional) – Path to append to *HttpClient.url* for this request.

  Defaults to: "".

- **data** (str, optional) – Data to send with POST.

  Defaults to: None.

- **timeout** (int, optional) – Response timeout.

  Defaults to: 5.

- **params** (dict, optional) – URL parameters.

  Defaults to: None.

- **headers** (dict, optional) – Headers.

  Defaults to: None.

- **b64_headers** (list of str, optional) – Headers to base 64 encode.

  Defaults to: None.

- **verify** (bool or str, optional) – Enable/Disable SSL certificate validation using built in CAs, or a path to custom cert.

  Defaults to: True.

- ****kwargs** – cause (str): String to explain purpose of request.

  Defaults to: “”.

Notes

If verify is True or None, verification is done using default/built in CA. OS env vars $REQUESTS_CA_BUNDLE, and $CURL_CA_BUNDLE are used if set and trust_env is True, and if trust_env is False session's verify is used.

If verify is False, no verification is done. This overrides OS env and session's verify for this request and no verification is done at all. Don't do this.

If verify is a str, verification is done with PEM file at path. This overrides OS env and session's verify for this request.

Caveat: If previous request made with session and close has not been called on session, the verify of the previous request will be used no matter what is supplied here.

Returns requests.Response

control_hook(*enable*, *hook*)

Add or remove a hook from *HttpClient.session*.

Parameters

- **enable** (bool) – True: Add hook to session. False: Remove hook from session.
- **hook** (object) – Hook function to add/remove to session.

Returns True/False if hook was actually removed/added.

Return type bool

control_hook_record_disk(*enable=False*, *path=None*, *path_sub='records'*)

Add or remove session hook for recording responses to disk.

Parameters

- **enable** (bool, optional) – Add/remove *HttpClient.response_hook_disk()* to session hooks.

  Defaults to: False.

- **path** (str or pathlib.Path, optional) – Storage directory to use. If empty, resolve path via *pytan3.utils.tools.get_storage_dir()*.

  Defaults to: None.

- **path_sub** (str, optional) – Sub directory under path to save records to.

  Defaults to: “records”

control_hook_record_history(*enable=False*)

Add or remove session hook for recording in local class.

Parameters **enable** (bool, optional) – Add/remove *HttpClient.response_hook_history()* to session hooks.

Defaults to: False.

response_hook_log_debug(*response*, **args*, ***kwargs*)

Response hook to log info.

Parameters

- **response** (requests.Response) – Response to process.
- ***args** – Unused, yet supplied by requests.Session.
- ****kwargs** – Unused, yet supplied by requests.Session.

Returns requests.Response

response_hook_clean(*response*, **args*, ***kwargs*)

Response hook to add cleaned versions of request/response body and headers.

Parameters

- **response** (requests.Response) – Response to process.
- ***args** – Unused, yet supplied by requests.Session.
- ****kwargs** – Unused, yet supplied by requests.Session.

Returns requests.Response

static clean_hook_auth_rest(*http_client*, *response*)

Clean hook to hide auth keys in a response from REST session route.

Parameters

- **http_client** (*HttpClient*) – Object to get *HttpClient.CLEAN_AUTH_KEYS* and *HttpClient.CLEAN_HIDE* from.
- **response** (requests.Response) – Object to add clean_body attribute to.

Returns requests.Response

static clean_hook_auth(*http_client*, *response*)

Clean hook to hide auth headers in a response from /auth API.

Parameters

- **http_client** (*HttpClient*) – Object to get *HttpClient.CLEAN_AUTH_KEYS* and *HttpClient.CLEAN_HIDE* from.
- **response** (requests.Response) – Object to add clean_headers attribute to.

Returns requests.Response

response_hook_history(*response*, **args*, ***kwargs*)

Response hook to add response to *HttpClient.history*.

Parameters

- **response** (requests.Response) – Response to process.
- ***args** – Unused, yet supplied by requests.Session.
- ****kwargs** – Unused, yet supplied by requests.Session.

response_hook_disk(*response*, **args*, ***kwargs*)

Response hook to write response to *HttpClient.record_path*.

Parameters

- **response** (requests.Response) – Response to serialize and write to disk.
- ***args** – Unused, yet supplied by requests.Session.
- ****kwargs** – Unused, yet supplied by requests.Session.

Returns requests.Response

serialize_response(*response*)

Churn a response into JSON serializeable format.

Parameters **response** (requests.Response) – Response object to churn.

Returns dict

parse_url(*url*)

Parse a URL using UrlParser.

Parameters **url** (str) – URL to parse.

Returns *UrlParser*

user_agent

Build a user agent string for use in headers.

Returns str

Certificate verification for HTTP Client

class pytan3.http_client.**Certify**(*http_client*, *lvl='info'*)

Bases: object

Certificate verification magic.

__init__(*http_client*, *lvl='info'*)

Constructor.

Parameters

- **http_client** (*HttpClient*) – Client to use for getting certificates and configuring the verify attribute on *HttpClient.session*
- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

log = None

logging.Logger – Logger for this object.

http_client = None

HttpClient – Client for this object.

using_custom_cert = None

bool – If we are using a cert from disk or not.

__call__(*path=None*, *path_sub='certs'*, *path_file='{http_client.parsed_url.hostname}.pem'*, *verify_hook=None*, *overwrite=False*, *lvl=None*)

Validate, find, or get certificate for URL.

Parameters

- **path** (str or pathlib.Path, optional) – Storage directory to use. If empty, resolve path via *pytan3.utils.tools.get_storage_dir()*.

  Defaults to: None.

- **path_sub** (str, optional) – Sub directory under path that should contain path_file.

  Defaults to: "certs"

- **path_file** (str, optional) – Filename to use for cert file under path / path_sub.

  Defaults to: *CERT_FILE*

- **verify_hook** (callable or False) – A callable used to verify a SSL cert from URL before writing it to disk.

  Only used if default cert is invalid and path/path_sub/path_file does not exist.

  If False, cert is written to disk without running any verify hook.

  If None, uses *Certify.verify_hook()* as verify hook.

  If callable, called with args: store, store_chain, and parsed_url.

  Defaults to: None.

- **overwrite** (bool, optional) – Overwrite cert at path if already exists.

  Defaults to: False.

- **lvl** (str, optional) – If not None, change logging level for this object.

  Defaults to: None.

Raises *exceptions.CertificateNotFoundWarning* – If cert at URL is not valid using default cert validation, and no cert can be found at path.

__str__()

Show object info.

Returns str

__repr__()

Show object info.

Returns str

write_pem(*path*, *overwrite=False*)

Write a certificate in PEM format to disk.

Parameters

- **path** (str or pathlib.Path) – Path to write PEM certificate to.
- **overwrite** (bool, optional) – Overwrite cert at path if already exists.

  Defaults to: False.

Returns pathlib.Path

static verify_hook(*store*, *store_chain*, *parsed_url*)

Verify cert by prompting user, default hook.

Parameters

- **store** (cert_human.CertStore) – Store from *Certify.store*.
- **store_chain** (cert_human.CertChainStore) – Chain store from *Certify.store_chain*.

- **parsed_url** (str) – Parsed URL from *HttpClient.parsed_url*.

Raises *exceptions.CertificateInvalidError* – If user replies No to validity prompt.

store

Get CertStore for URL.

Returns cert_human.CertStore

store_chain

Get CertChainStore for URL.

Returns cert_human.CertChainStore

_fetch_stores

Get the CertStore and CertChainStore for URL.

Returns (cert_human.CertStore, cert_human.CertChainStore)

check_default()

Check if cert for URL is valid without setting a specific path.

Returns bool

check_path(*path*)

Check if cert at path is valid for URL.

Parameters **path** (str or pathlib.Path) – Path to PEM certificate file.

Notes

If validation is successful, the verify attribute on *HttpClient.session* will be set to path.

Raises *exceptions.CertificateInvalidError* – If path fails verification.

URL Parser for HTTP Client

class pytan3.http_client.**UrlParser**(*url*, *default_scheme=''*)

Bases: object

Parse a URL and ensure it has the neccessary bits.

__init__(*url*, *default_scheme=''*)

Constructor.

Parameters

- **url** (str) – URL to parse
- **default_scheme** (str, optional) – If no scheme in URL, use this.

  Defaults to: ""

Raises *exceptions.ModuleError* – If parsed URL winds up without a hostname, port, or scheme.

_init_url = None

str – Initial URL provided.

_init_scheme = None

str – Default scheme provided.

_init_parsed = None
`urllib.parse.ParseResult` – First pass of parsing URL.

parsed = None
`urllib.parse.ParseResult` – Second pass of parsing URL.

__str__()
Show object info.

Returns `str`

__repr__()
Show object info.

Returns `str`

hostname
Hostname part from *`UrlParser.parsed`*.

Returns `str`

port
Port part from *`UrlParser.parsed`*.

Returns `int`

scheme
Scheme part from *`UrlParser.parsed`*.

Returns `str`

url
Get scheme, hostname, and port from *`UrlParser.parsed`*.

Returns `str`

url_full
Get full URL from *`UrlParser.parsed`*.

Returns `str`

parsed_str
Create string of *`UrlParser.parsed`*.

Returns `str`

make_netloc(*host*, *port*)
Create netloc from host and port.

Parameters

- **host** (`str`) – Host part to use in netloc.
- **port** (`str`) – Port part to use in netloc.

Returns `str`

reparse(*parsed*, *default_scheme=''*)
Reparse a parsed URL into a parsed URL with values fixed.

Parameters

- **parsed** (`urllib.parse.ParseResult`) – Parsed URL to reparse.
- **default_scheme** (`str`, optional) – If no scheme in URL, use this.

  Defaults to: ""

Returns `urllib.parse.ParseResult`

unparse_base(*p*)

Unparse a parsed URL into just the scheme, hostname, and port parts.

Parameters **p** (`urllib.parse.ParseResult`) – Parsed URL to unparse.

Returns `str`

unparse_all(*p*)

Unparse a parsed URL with all the parts.

Parameters **p** (`urllib.parse.ParseResult`) – Parsed URL to unparse.

Returns `str`

Exceptions for HTTP Client

Exceptions and warnings for *pytan3.http_client*.

exception pytan3.http_client.exceptions.**ModuleError**

Bases: *pytan3.exceptions.PyTanError*

Parent of all exceptions for *pytan3.http_client*.

Thrown by:

- *pytan3.http_client.UrlParser.__init__()*

exception pytan3.http_client.exceptions.**ModuleWarning**

Bases: *pytan3.exceptions.PyTanWarning*

Parent of all warnings for *pytan3.http_client*.

Thrown by:

exception pytan3.http_client.exceptions.**CertificateNotFoundWarning**

Bases: *pytan3.http_client.exceptions.ModuleWarning*

Thrown when a cert can not be found.

Thrown by:

- *pytan3.http_client.Certify.__call__()*

exception pytan3.http_client.exceptions.**CertificateInvalidError**

Bases: *pytan3.http_client.exceptions.ModuleError*

Thrown when cert is invalid from path or from user prompt.

Thrown by:

- *pytan3.http_client.Certify.verify_hook()*
- *pytan3.http_client.Certify.check_path()*

1.10.2 Authentication Methods

Authentication methods for the Tanium API.

pytan3.auth_methods.**DEFAULT_NAME = 'credentials'**

`str` – Default *AuthMethod* name to load in *load()*.

Abstract Base Class for all Authentication Methods

class pytan3.auth_methods.**AuthMethod**

Bases: object

Abstract base class for all AuthMethods.

classmethod get_name()

Get the ref name of this class for use by *load()*.

Returns str

classmethod get_version_req()

Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

classmethod get_args()

Get all arguments used by this class.

Returns list

classmethod get_args_required()

Get all arguments used by this class that are required.

Returns list

classmethod get_args_secure()

Get all arguments used by this class that need their prompt input hidden.

Returns list

classmethod from_store(*store*, ***kwargs*)

Create an instance of this class from an *pytan3.auth_store.AuthStore*.

Parameters **store** (*pytan3.auth_store.AuthStore*) – AuthStore to get AuthMethod arguments from.

Returns *AuthMethod*

http_client

Get the HTTP Client for this object.

Returns *pytan3.http_client.HttpClient*

token

Get or set a token.

Notes

If no token received, *login()* to get one.

If token expired, *login()* to get a new one.

If token has been received, *validate()* to validate token.

If token fails validation, `login()` to get a new one.

Returns `str`

token_headers

Get dict with `token` for use in headers.

Returns `dict`

uid

Get user ID for token if a token has been received.

Returns `str`

logged_in

Check if a token has been received.

Returns `bool`

login(***kwargs*)

Send a login request to receive a token.

Raises `exceptions.LoginError` – If status code in response is not 200.

Returns `str`

logout(***kwargs*)

Send a logout request to revoke a token.

Raises

- `exceptions.NotLoggedInError` – If `logged_in` is False.
- `exceptions.LogoutError` – If status code in response is not 200.

Returns None

logout_all(***kwargs*)

Send a logout request to revoke all tokens associated with this token.

Raises

- `exceptions.NotLoggedInError` – If `logged_in` is False.
- `exceptions.LogoutError` – If status code in response is not 200.

Returns None

validate(***kwargs*)

Send a validate request to check that token is still valid.

Raises

- `exceptions.NotLoggedInError` – If `logged_in` is False.
- `exceptions.InvalidToken` – If status code in response is not 200.

Returns `str`

create_store(***kwargs*)

Create an instance of `pytan3.auth_store.AuthStore` from this object.

Returns `pytan3.auth_store.AuthStore`

_abc_impl = <_abc_data object>

Common Mixins for all Authentication Methods

class pytan3.auth_methods.**CommonMixin**(*http_client*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)

Bases: object

Shared methods common amongst all *AuthMethod*.

__init__(*http_client*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)

Constructor.

Parameters

- **http_client** (*pytan3.http_client.HttpClient*) – Object for sending HTTP requests.
- **login_timeout** (int, optional) – Timeout for login and validate responses in seconds.

  Defaults to: 5.
- **logout_timeout** (int, optional) – Timeout for logout responses in seconds.

  Defaults to: 5.
- **expires_after** (int, optional) – Life of received tokens in seconds.

  Defaults to: 295.
- **ver_check** (bool, optional) – Perform version checks against the platform version from *pytan3.api_clients.get_version()* using *pytan3.utils.versions.version_check_obj_req()*.

  Defaults to: True.
- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

log = None

logging.Logger – Log for this object.

revalidate_after = None

int – Revalidate token if *last_used* is higher than this.

__str__()

Show object info.

Returns str

__repr__()

Show object info.

Returns str

classmethod from_store(*store*, ***kwargs*)

Create an instance of this class from an *pytan3.auth_store.AuthStore*.

Parameters

- **store** (*pytan3.auth_store.AuthStore*) – AuthStore to get AuthMethod arguments from.
- ****kwargs** – Rest of kwargs passed to *AuthMethod*.

Returns *AuthMethod*

http_client
Get the HTTP Client for this object.

Returns *pytan3.http_client.HttpClient*

token
Get a token.

Notes

If *logged_in* is False, *login()* to get one.

If *expired* is True, *login()* to get a new one.

If *logged_in* is True, and *last_used* is older than *revalidate_after*, *validate()* to revalidate token.

If *validate()* fails validation, *login()* to get a new one.

Returns str

token_headers
Get dict with *token* for use in headers.

Returns dict

uid
Get user ID for token if a token has been received.

Returns str

logged_in
Check if a token has been received.

Returns bool

expired
Check if token has expired.

Returns bool

last_used
Get the number of seconds since token was issued or last used.

Returns int

login(***kwargs*)
Send a login request to receive a token.

Parameters ****kwargs** –

cause (str): String to explain purpose of request.

Defaults to: "Get new token".

Raises *exceptions.LoginError* – If status code in response is not 200.

Returns str

logout(***kwargs*)
Send a logout request to revoke a token.

Parameters ****kwargs** –

cause (str): String to explain purpose of request.

Defaults to: "Revoke token".

headers (dict): Headers to send in request.

Defaults to: {}.

Raises

- *exceptions.NotLoggedInError* – If *logged_in* is False.
- *exceptions.LogoutError* – If status code in response is not 200.

Returns None

logout_all(***kwargs*)

Send a logout request to revoke all tokens associated with this token.

Parameters ****kwargs** –

cause (str): String to explain purpose of request.

Defaults to: "Revoke all tokens".

headers (dict): Headers to send in request.

Defaults to: {}.

Raises

- *exceptions.NotLoggedInError* – If *logged_in* is False.
- *exceptions.LogoutError* – If status code in response is not 200.

Returns None

validate(***kwargs*)

Send a validate request to check that token is still valid.

Parameters ****kwargs** –

cause (str): String to explain purpose of request.

Defaults to: "Validate token".

headers (dict): Headers to send in request.

Defaults to: {}.

Raises

- *exceptions.NotLoggedInError* – If *logged_in* is False.
- *exceptions.InvalidToken* – If status code in response is not 200.

Returns str

create_store(***kwargs*)

Create an instance of *pytan3.auth_store.AuthStore* from this object.

Returns *pytan3.auth_store.AuthStore*

Utilities for all Authentication Methods

pytan3.auth_methods.**validate_token**(*token*)

Validate that a token is properly formed.

Parameters **token** (str) – Token to validate

Returns bool

Loaders for all Authentication Methods

pytan3.auth_methods.**load**(*obj='credentials'*)

Get an AuthMethod class.

:param obj (str or AuthMethod or AuthMethod or: pytan3.auth_store.AuthStore, optional):

AuthStore object or AuthMethod object, class, or name of AuthMethod.

Defaults to: DEFAULT_NAME.

Raises

exceptions.ModuleError: If obj is not a valid type, name, obj, or cls.

Returns AuthMethod

Exceptions for all Authentication Methods

Exceptions and warnings for pytan3.auth_methods.

exception pytan3.auth_methods.exceptions.**ModuleError**

Bases: pytan3.exceptions.PyTanError

Parent of all exceptions for pytan3.auth_methods.

Thrown by:

- pytan3.auth_methods.load()

exception pytan3.auth_methods.exceptions.**ModuleWarning**

Bases: pytan3.exceptions.PyTanWarning

Parent of all warnings for pytan3.auth_methods.

Thrown by:

exception pytan3.auth_methods.exceptions.**MethodError**(*auth_method*, *info=None*, *response=None*)

Bases: pytan3.auth_methods.exceptions.ModuleError

Parent of all pytan3.auth_methods.AuthMethod exceptions.

Thrown by:

msg = 'Authentication Method Error!'

str – Error message to use in exception.

__init__(*auth_method*, *info=None*, *response=None*)

Constructor.

Parameters

- **auth_method** (pytan3.auth_methods.AuthMethod) – Object where exception was thrown from.
- **info** (str, optional) – Additional error info message to show.

  Defaults to: None.

- **response** (requests.Response, optional) – Response associated with this exception, if any.

  Defaults to: None.

error = None
str – Error message that was thrown.

exception pytan3.auth_methods.exceptions.**InvalidToken**(*auth_method*, *info=None*, *response=None*)

Bases: *pytan3.auth_methods.exceptions.MethodError*

Thrown when validate_token fails.

Thrown by:

- *pytan3.auth_methods.AuthMethod.validate()*

msg = 'Supplied token is invalid!'
str – Error message to use in exception.

exception pytan3.auth_methods.exceptions.**NotLoggedInError**(*auth_method*, *info=None*, *response=None*)

Bases: *pytan3.auth_methods.exceptions.MethodError*

Thrown when logout called before login.

Thrown by:

- *pytan3.auth_methods.AuthMethod.validate()*
- *pytan3.auth_methods.AuthMethod.logout()*
- *pytan3.auth_methods.AuthMethod.logout_all()*

msg = 'Not logged in, unable to logout/validate token. Must login first!'
str – Error message to use in exception.

exception pytan3.auth_methods.exceptions.**LoginError**(*auth_method*, *info=None*, *response=None*)

Bases: *pytan3.auth_methods.exceptions.MethodError*

Thrown when login response has any status_code other than 200.

Thrown by:

- *pytan3.auth_methods.AuthMethod.login()*

msg = 'Login failed. Response status code is not 200!'
str – Error message to use in exception.

exception pytan3.auth_methods.exceptions.**LogoutError**(*auth_method*, *info=None*, *response=None*)

Bases: *pytan3.auth_methods.exceptions.MethodError*

Thrown when logout fails.

Thrown by:

- *pytan3.auth_methods.AuthMethod.logout()*
- *pytan3.auth_methods.AuthMethod.logout_all()*

msg = 'Logout failed. Verify the supplied credentials!'
str – Error message to use in exception.

Authentication Method Types

Credentials Authentication Method

class pytan3.auth_methods.**Credentials**(*http_client*, *username*, *password*, *domain=''*, *secondary=''*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)

Bases: `pytan3.auth_methods.CommonMixin`, `pytan3.auth_methods.AuthMethod`

Method that uses credentials to interact with the '/auth' API.

__init__(*http_client*, *username*, *password*, *domain=''*, *secondary=''*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)

Constructor.

Parameters

- **http_client** (`pytan3.http_client.HttpClient`) – HTTP client.
- **username** (`str`) – Header to pass to /auth API.
- **password** (`str`) – Header to pass to /auth API.
- **domain** (`str`, optional) – Header to pass to /auth API.

  Defaults to: ""
- **secondary** (`str`, optional) – Header to pass to /auth API.

  Defaults to: ""
- **login_timeout** (`int`, optional) – Timeout for login and validate responses in seconds.

  Defaults to: 5.
- **logout_timeout** (`int`, optional) – Timeout for logout responses in seconds.

  Defaults to: 5.
- **expires_after** (`int`, optional) – Life of received tokens in seconds.

  Defaults to: 295.
- **ver_check** (`bool`, optional) – Perform version checks against the platform version from `pytan3.api_clients.get_version()` using `pytan3.utils.versions.version_check_obj_req()`.

  Defaults to: True.
- **lvl** (`str`, optional) – Logging level for this object.

  Defaults to: "info".

classmethod get_name()

Get the ref name of this class for use by `load()`.

Returns `str`

classmethod get_version_req()

Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by `pytan3.utils.versions.version_check_obj_req()` to perform version checks.

Returns `dict`

classmethod get_args()
Get all arguments used by this class.

Returns `list`

classmethod get_args_required()
Get all arguments used by this class that are required.

Returns `list`

classmethod get_args_secure()
Get all arguments used by this class that need their prompt input hidden.

Returns `list`

_abc_impl = <_abc_data object>

REST Credentials Authentication Method

class pytan3.auth_methods.**RestCredentials**(*http_client*, *username*, *password*, *domain=''*, *secondary=''*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)

Bases: `pytan3.auth_methods.CommonMixin`, `pytan3.auth_methods.AuthMethod`

Method that uses credentials to interact with the REST 'session' API.

__init__(*http_client*, *username*, *password*, *domain=''*, *secondary=''*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)
Constructor.

Parameters

- **http_client** (`pytan3.http_client.HttpClient`) – HTTP client.
- **username** (`str`) – Header to pass to /api/v2/session REST API.
- **password** (`str`) – Header to pass to /api/v2/session REST API.
- **domain** (`str`, optional) – Header to pass to /api/v2/session REST API.

  Defaults to: ""
- **secondary** (`str`, optional) – Header to pass to /api/v2/session REST API.

  Defaults to: ""
- **login_timeout** (`int`, optional) – Timeout for login and validate responses in seconds.

  Defaults to: 5.
- **logout_timeout** (`int`, optional) – Timeout for logout responses in seconds.

  Defaults to: 5.
- **expires_after** (`int`, optional) – Life of received tokens in seconds.

  Defaults to: 295.

- **ver_check** (bool, optional) – Perform version checks against the platform version from *pytan3.api_clients.get_version()* using *pytan3.utils.versions.version_check_obj_req()*.

  Defaults to: True.

- **lvl** (str, optional) – Logging level.

  Defaults to: "info".

classmethod get_name()

Get the ref name of this class for use by *load()*.

Returns str

classmethod get_version_req()

Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

classmethod get_args()

Get all arguments used by this class.

Returns list

classmethod get_args_required()

Get all arguments used by this class that are required.

Returns list

classmethod get_args_secure()

Get all arguments used by this class that need their prompt input hidden.

Returns list

_abc_impl = <_abc_data object>

rest_version

Version of REST API for this method.

Returns int

login(***kwargs*)

Send a login request to receive a token.

Parameters ****kwargs** – cause (str): String to explain purpose of request.

Defaults to: "Get new token".

Raises *exceptions.LoginError* – If status code in response is not 200.

Returns str

logout(***kwargs*)

Send a logout request to revoke a token.

Parameters ****kwargs** – cause (`str`): String to explain purpose of request.

Defaults to: "Revoke token".

Raises

- `exceptions.NotLoggedInError` – If `CommonMixin.logged_in` is False.
- `exceptions.LogoutError` – If status code in response is not 200.

Returns None

logout_all(***kwargs*)

Send a logout request to revoke all tokens associated with this token.

Raises `NotImplementedError` – REST 'session' endpoint does not have a logout all target.

validate(***kwargs*)

Send a validate request to check that token is still valid.

Parameters ****kwargs** –

cause (str): String to explain purpose of request.

Defaults to: "Validate token".

Raises

- `exceptions.NotLoggedInError` – If `CommonMixin.logged_in` is False.
- `exceptions.InvalidToken` – If status code in response is not 200.

Returns `str`

Session ID Authentication Method

class pytan3.auth_methods.**SessionId**(*http_client*, *session*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)

Bases: `pytan3.auth_methods.CommonMixin`, `pytan3.auth_methods.AuthMethod`

Method that uses session id to interact with the '/auth' API.

__init__(*http_client*, *session*, *login_timeout=5*, *logout_timeout=5*, *expires_after=295*, *ver_check=True*, *lvl='info'*)

Constructor.

Parameters

- **http_client** (`pytan3.http_client.HttpClient`) – HTTP client.
- **session** (`str`) – Header to pass to /auth API.
- **login_timeout** (`int`, optional) – Timeout for login and validate responses in seconds.

  Defaults to: 5.
- **logout_timeout** (`int`, optional) – Timeout for logout responses in seconds.

  Defaults to: 5.
- **expires_after** (`int`, optional) – Life of received tokens in seconds.

  Defaults to: 295.

- **ver_check** (bool, optional) – Perform version checks against the platform version from *pytan3.api_clients.get_version()* using *pytan3.utils.versions.version_check_obj_req()*.

  Defaults to: True.

- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

classmethod get_name()

Get the ref name of this class for use by *load()*.

Returns str

classmethod get_version_req()

Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

classmethod get_args()

Get all arguments used by this class.

Returns list

classmethod get_args_required()

Get all arguments used by this class that are required.

Returns list

classmethod get_args_secure()

Get all arguments used by this class that need their prompt input hidden.

Returns list

token

Get a token.

Notes

If *CommonMixin.logged_in* is False, can not login to get a new one with just a session.

If *CommonMixin.expired* is True, can not login to get a new one with just a session.

If *CommonMixin.logged_in* is True, and *CommonMixin.last_used* is older than *CommonMixin.revalidate_after*, *CommonMixin.validate()* to re-validate token.

If *CommonMixin.validate()* fails validation, can not login to get a new one with just a session.

Returns str

login(***kwargs*)

Send a login request to receive a token.

Raises `exceptions.LoginError` – If status code in response is not 200.

Returns `str`

_abc_impl = <_abc_data object>

1.10.3 Authentication Store

Secure storage for Authentication methods.

pytan3.auth_store.**DEFAULT_NAME = 'credentials'**

`str` – Default `pytan3.auth_methods.AuthMethod` name to load in `AuthStore`.

pytan3.auth_store.**STORE_FILE = '{http_client.parsed_url.hostname}.store'**

`str` – Store filename template filename to use in `AuthStore`.

Will use OS Environment variable "PYTAN_STORE_FILE" if set.

class pytan3.auth_store.**AuthStore**(*http_client*, *method='credentials'*, *secret=None*, *data=None*, *src='init'*, *lvl='info'*)

Bases: `object`

Secure storage for `pytan3.auth_methods.AuthMethod`.

__init__(*http_client*, *method='credentials'*, *secret=None*, *data=None*, *src='init'*, *lvl='info'*)

Constructor.

Parameters

- **http_client** (`pytan3.http_client.HttpClient`) – HTTP client.
- **method** (`str` or `pytan3.auth_methods.AuthMethod`, optional) – AuthMethod to use for this object.

  Defaults to: `DEFAULT_NAME`.
- **secret** (`str`, optional) – Encryption key.

  Will use STORE_SECRET as default if None.

  Defaults to: None.
- **data** (`dict`, optional) – Initialize data store with dict.

  Defaults to: None.
- **src** (`str`, optional) – Where this store came from.

  Defaults to: "init".
- **lvl** (`str`, optional) – Logging level.

  Defaults to: "info".

__str__()

Show object info.

Returns `str`

__repr__()

Show object info.

Returns `str`

http_client

Get the HTTP Client for this object.

Returns *pytan3.http_client.HttpClient*

set (*key*, *value*)
Set key value in data.

Parameters

- **key** (str) – Key name to set in data.
- **value** (str) – Value to set for key in data.

get (*key*, *required=True*)
Get key value from data.

Parameters

- **key** (str) – Key to get,
- **required** (bool, optional) – Raise error if key not found in store.

  Defaults to: True.

Raises *exceptions.ModuleError* – If key is required and not found.

Returns str

secret
Get the secret for this store.

Returns str

method
Get the method class for this store.

Returns *pytan3.auth_methods.AuthMethod*

create_method (***kwargs*)
Create an *pytan3.auth_methods.AuthMethod* from this store.

Parameters ****kwargs** – Rest of kwargs passed to *pytan3.auth_methods.AuthMethod.from_store()*.

Returns *pytan3.auth_methods.AuthMethod*

to_stream (*stream=None*)
Write this stores encrypted data to a file like object.

Parameters **stream** (io.IOBase, optional) – Object to write store to.

If None, create and return a six.StringIO.

Defaults to: None.

Returns io.IOBase

to_path (*path=None*, *path_sub='stores'*, *path_file='{http_client.parsed_url.hostname}.store'*, *overwrite=False*)
Write this stores encrypted data to a path.

Parameters

- **path** (str or pathlib.Path, optional) – Storage directory to use. If empty, resolve path via *pytan3.utils.tools.get_storage_dir()*.

  Defaults to: None.

- **path_sub** (str, optional) – Sub directory under path that should contain path_file.

  Defaults to: "stores"

- **path_file** (str, optional) – Filename to use for store file under path / path_sub.

  Defaults to: *STORE_FILE*

- **overwrite** (bool, optional) – If True, if store_file exists, overwrite and throw warning.

  If False, if store_file exists, do not overwrite and throw exception.

  If None, if store_file exists, do not overwrite and throw warning.

  Defaults to: False.

Raises

- *exceptions.ModuleError* – If path / path_sub / path_file exists and overwrite is False
- *exceptions.ModuleWarning* – If path / path_sub / path_file exists and overwrite is None or True.

Returns Absolute full path where store file was written.

Return type pathlib.Path

to_string()

Write this stores encrypted data to a string.

Returns str

classmethod from_stream(*http_client*, *stream*, *secret=None*, *src='stream'*, *lvl='info'*)

Create store from encrypted data in a file like object.

Parameters

- **http_client** (*pytan3.http_client.HttpClient*) – HTTP client.
- **stream** (io.IOBase) – File like object to read from.
- **secret** (str, optional) – Decryption key.

  Will use STORE_SECRET as default if None.

  Defaults to: None.

- **src** (str, optional) – Where this store came from.

  Defaults to: "stream".

- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

Returns *AuthStore*

classmethod from_string(*http_client*, *string*, *secret=None*, *lvl='info'*)

Create store from encrypted data in a string.

Parameters

- **http_client** (*pytan3.http_client.HttpClient*) – HTTP client.
- **string** (str) – String to read from.
- **secret** (str, optional) – Decryption key.

  Will use STORE_SECRET as default if None.

  Defaults to: None.

- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

Returns *AuthStore*

classmethod from_path(*http_client*, *path=None*, *path_sub='stores'*, *path_file='{http_client.parsed_url.hostname}.store'*, *secret=None*, *lvl='info'*)

Create store from encrypted data in a file.

Parameters

- **http_client** (*pytan3.http_client.HttpClient*) – HTTP client.
- **path** (str or pathlib.Path, optional) – Storage directory to use. If empty, resolve path via *pytan3.utils.tools.get_storage_dir()*.

  Defaults to: None.
- **path_sub** (str, optional) – Sub directory under path that should contain path_file.

  Defaults to: "stores"
- **path_file** (str, optional) – Filename to use for store file under path / path_sub.

  Defaults to: *STORE_FILE*
- **secret** (str, optional) – Decryption key.

  Will use STORE_SECRET as default if None.

  Defaults to: None.
- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

Raises (*exceptions.ModuleError*) – If path does not exist as a file.

Returns *AuthStore*

classmethod _decrypt(*data*, *http_client*, *secret=None*)

Decrypt data using secret.

Parameters

- **data** (str) – Data to decrypt.
- **http_client** (*pytan3.http_client.HttpClient*) – HTTP client.
- **secret** (str, optional) – Decryption key.

  Will use STORE_SECRET as default if None.

  Defaults to: None.

Returns str

classmethod _encrypt(*data*, *http_client*, *secret=None*)

Encrypt data using secret.

Parameters

- **data** (str) – Data to encrypt.
- **http_client** (*pytan3.http_client.HttpClient*) – HTTP client.

- **secret** (str, optional) – Decryption key.

  Will use STORE_SECRET as default if None.

  Defaults to: None.

Returns str

classmethod _build_key(*http_client*, *secret=None*)

Build an encryption key by combining an SSL cert PEM and a secret.

Parameters

- **http_client** (*pytan3.http_client.HttpClient*) – HTTP client.
- **secret** (str, optional) – Decryption key.

  Will use STORE_SECRET as default if None.

  Defaults to: None.

Returns str

Exceptions for Authentication Store

Exceptions and warnings for *pytan3.auth_store*.

exception pytan3.auth_store.exceptions.**ModuleError**

Bases: *pytan3.exceptions.PyTanError*

Parent of all *pytan3.auth_store* exceptions.

Thrown by:

- *pytan3.auth_store.AuthStore.get()*
- *pytan3.auth_store.AuthStore.to_path()*
- *pytan3.auth_store.AuthStore.from_path()*

exception pytan3.auth_store.exceptions.**ModuleWarning**

Bases: *pytan3.exceptions.PyTanWarning*

Parent of all *pytan3.auth_store* warnings.

Thrown by:

- *pytan3.auth_store.AuthStore.to_path()*

1.10.4 API Clients

Clients for making API requests to Tanium.

pytan3.api_clients.**DEFAULT_TYPE = 'soap'**

str – Default *ApiClient* type to load in *load_type()*.

pytan3.api_clients.**DEFAULT_NAME = 'soap'**

str – Default *ApiClient* name to load in *load()*.

pytan3.api_clients.**WSDL_PATH = '/libraries/taniumjs/console.wsdl'**

str – URL path to find console.wsdl in *get_wsdl()*.

Abstract Base Class for all API Clients

class pytan3.api_clients.**ApiClient**

Bases: object

Abstract base class for all ApiClients.

classmethod get_name()

Get the ref name of this class for use by *load()*.

Returns str

classmethod get_type()

Get the ref type of this class for use by *load_type()*.

Returns str

classmethod get_version_req()

Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

auth_method

Get the AuthMethod for this object.

Returns *pytan3.auth_methods.AuthMethod*

http_client

Get the HTTP Client for this object.

Returns *pytan3.http_client.HttpClient*

url

Get the URL from *ApiClient.http_client*.

Returns str

version

Get the platform version from *ApiClient.config*.

Returns str

config

Get the deserialized config.json from *ApiClient.url*.

Returns dict

info

Get the deserialized info.json from *ApiClient.url*.

Returns dict

_abc_impl = <_abc_data object>

All SOAP API Clients

Soap API Client

class pytan3.api_clients.**Soap**(*http_client*, *auth_method*, *ver_check=True*, *lvl='info'*)

Bases: *pytan3.api_clients.ApiClient*

Client for making SOAP API requests to Tanium.

__init__(*http_client*, *auth_method*, *ver_check=True*, *lvl='info'*)

Constructor.

Parameters

- **http_client** (*pytan3.http_client.HttpClient*) – Object for sending HTTP requests.
- **auth_method** (*pytan3.auth_methods.AuthMethod*) – Object for sending login and logout requests.
- **ver_check** (bool, optional) – Perform version checks against the platform version from *ApiClient.version* using *pytan3.utils.versions.version_check_obj_req()*.

  Defaults to: True.
- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

log = None

logging.Logger – Log for this object.

__str__()

Show object info.

Returns str

__repr__()

Show object info.

Returns str

__call__(*data*, *timeout=30*, ***kwargs*)

Get response of POST of data to /soap and return a response object.

Parameters

- **data** (str) – Body to send in request.
- **timeout** (int, optional) – Response timeout.

  Defaults to: 30.
- ****kwargs** –

  cause (str): String to explain purpose of request.

  Defaults to: "".

  headers (dict): Headers to send in request.

  Defaults to: {}.

Returns requests.Response

classmethod get_name()
Get the ref name of this object for use by *load()*.

Returns str

classmethod get_type()
Get the ref type of this object for use by *load_type()*.

Returns str

classmethod get_version_req()
Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

auth_method
Get the AuthMethod for this object.

Returns *pytan3.auth_methods.AuthMethod*

http_client
Get the HTTP Client for this object.

Returns *pytan3.http_client.HttpClient*

url
Get the URL from *ApiClient.http_client*.

Returns str

version
Get the platform version from *ApiClient.config*.

Returns str

config
Get the deserialized config.json from *ApiClient.url*.

Returns dict

info
Get the deserialized info.json from *ApiClient.url*.

Returns dict

_abc_impl = <_abc_data object>

All REST API Clients

Rest API Client

class pytan3.api_clients.**Rest**(*http_client*, *auth_method*, *ver_check=True*, *lvl='info'*)
Bases: *pytan3.api_clients.ApiClient*

Client for making REST API requests to Tanium for versions 7.3 and above.

__init__(*http_client*, *auth_method*, *ver_check=True*, *lvl='info'*)

Constructor.

Parameters

- **http_client** (*pytan3.http_client.HttpClient*) – Object for sending HTTP requests.
- **auth_method** (*pytan3.auth_methods.AuthMethod*) – Object for sending login and logout requests.
- **ver_check** (bool, optional) – Perform version checks against the platform version from *ApiClient.version* using *pytan3.utils.versions.version_check_obj_req()*.

  Defaults to: True.
- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

log = None

logging.Logger – Log for this object.

__str__()

Show object info.

Returns str

__repr__()

Show object info.

Returns str

__call__(*endpoint*, *method='get'*, *data=None*, *timeout=30*, ***kwargs*)

Get response of request of method to /api/v$version/$endpoint?$params.

Parameters

- **endpoint** (str) – Endpoint of rest api
- **method** (str, optional) – Method to use in request.

  Defaults to: "get".
- **data** (str, optional) – Body to send in request.

  Defaults to: None
- **timeout** (int, optional) – Response timeout.

  Defaults to: 30.
- ****kwargs** –

  cause (str): String to explain purpose of request.

  Defaults to: "".

  headers (dict): Headers to send in request.

  Defaults to: {}.

  version (int): Version of REST API.

  Defaults to: 2.

params (dict): Params to send encoded in URL.

Defaults to: {}.

Returns requests.Response

classmethod get_name()

Get the ref name of this object for use by *load()*.

Returns str

classmethod get_type()

Get the ref type of this object for use by *load_type()*.

Returns str

classmethod get_version_req()

Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

rest_version

Get the API version to use when communicating with the REST API.

Returns int

auth_method

Get the AuthMethod for this object.

Returns *pytan3.auth_methods.AuthMethod*

http_client

Get the HTTP Client for this object.

Returns *pytan3.http_client.HttpClient*

url

Get the URL from *ApiClient.http_client*.

Returns str

version

Get the platform version from *ApiClient.config*.

Returns str

config

Get the deserialized config.json from *ApiClient.url*.

Returns dict

info

Get the deserialized info.json from *ApiClient.url*.

Returns dict

_abc_impl = <_abc_data object>

Loaders for all API Clients

`pytan3.api_clients.load_type(obj='soap')`

Get a `ApiClient` by type from `ApiClient.get_type()`.

Parameters **obj** (`str`, optional) – ApiClient type to load.

Defaults to: `DEFAULT_TYPE`.

Raises

`exceptions.ModuleError`: Unable to find a valid `ApiClient` with the supplied type.

Returns `ApiClient`

`pytan3.api_clients.load(obj='soap')`

Get a `ApiClient` by name from `ApiClient.get_name()`.

Parameters **obj** (`str` or `ApiClient` or `ApiClient`, optional) – ApiClient object, class, or name.

Defaults to: `DEFAULT_NAME`.

Raises

`exceptions.ModuleError`: Unable to find a valid `ApiClient` with the supplied name.

Returns `ApiClient`

Utilities for all API Clients

`pytan3.api_clients.get_version(http_client)`

Get serverVersion key from `get_config()`.

Parameters **http_client** (`pytan3.http_client.HttpClient`) – Object for sending HTTP request.

Raises `exceptions.GetPlatformVersionWarning` – On error getting serverVersion key.

Returns `str`

`pytan3.api_clients.get_wsdl(http_client)`

Get response of GET to /libraries/taniumjs/console.wsdl.

Parameters **http_client** (`pytan3.http_client.HttpClient`) – Object for sending HTTP request.

Returns `str`

`pytan3.api_clients.get_config(http_client, cause='')`

Get response of GET to /config/console.json.

Parameters **http_client** (`pytan3.http_client.HttpClient`) – Object for sending HTTP request.

Returns `dict`

Exceptions for all API Clients

Exceptions and warnings for *pytan3.api_clients*.

exception pytan3.api_clients.exceptions.**ModuleError**

Bases: *pytan3.exceptions.PyTanError*

Parent of all exceptions for *pytan3.api_clients*.

Thrown by:

- *pytan3.api_clients.load_type()*
- *pytan3.api_clients.load()*

exception pytan3.api_clients.exceptions.**ModuleWarning**

Bases: *pytan3.exceptions.PyTanWarning*

Parent of all warnings for *pytan3.api_clients*.

Thrown by:

exception pytan3.api_clients.exceptions.**GetPlatformVersionWarning**

Bases: *pytan3.api_clients.exceptions.ModuleWarning*

Thrown when an issue happens while trying to get the platform version.

Thrown by:

- *pytan3.api_clients.get_version()*

1.10.5 API Object Modules

Python objects for Tanium's API.

pytan3.api_objects.**API_TYPES = ['rest', 'soap']**

`list` of `str` – All API object module types supported.

pytan3.api_objects.**DEFAULT_TYPE = 'soap'**

`str` – Default *API_TYPES* type to load in *load()*.

pytan3.api_objects.**PATTERN = '{api_type}_*.py'**

`str` – Glob pattern to find modules in *get_versions()*.

Container for API Object Modules

class pytan3.api_objects.**ApiObjects**(*module_file*, *adhoc_warn=True*)

Bases: `object`

Encapsulation object for an API Object module.

__init__(*module_file*, *adhoc_warn=True*)

Constructor.

Parameters

- **module_file** (`str`) – API Object module file name in import string format.
- **adhoc_warn** (`bool`, optional) – Enable warnings about adhoc added simple attributes to API Objects.

  Defaults to: True.

_module = None
pytan3.api_objects – Imported API Objects module.

_models = None
pytan3.api_models – API Models module.

__str__()
Show object info.

Returns str

__repr__()
Show object info.

Returns str

control_adhoc_warnings(*enable=False*)
Enable or disable warnings about adhoc added simple attributes.

Parameters **enable** (bool, optional) – Enable warnings.

Defaults to: True.

ApiModel
Get the ApiModel.

Returns *pytan3.api_models.ApiModel*

ApiItem
Get the ApiItem.

Returns *pytan3.api_models.ApiItem*

ApiList
Get the ApiList.

Returns *pytan3.api_models.ApiList*

module
Get the API objects module.

Returns object

module_type
Get the API type.

Returns str

module_version
Get the API version.

Returns str

module_dt
Get the date time format string.

Returns str

module_dt_format(*dt*)
Format a datetime string using *module_dt*.

Parameters **dt** (str) – String to format.

Returns datetime.datetime

module_version_dict
Get the API version.

Returns dict

cls_item
Get all of the ApiItem classes.

Returns list of *pytan3.api_models.ApiItem*

cls_list
Get all of the ApiItem classes.

Returns list of *pytan3.api_models.ApiList*

cls_all
Get all of the ApiItem and ApiList classes.

Returns list of *pytan3.api_models.ApiModel*

cls_name_map_item
Get a map of API key name to class for all ApiItem classes.

Returns dict

cls_name_map_list
Get a map of API key name to class for all ApiList classes.

Returns dict

cls_name_map_all
Get a map of API key name to class for all ApiItem and ApiList classes.

Returns dict

cls_item_by_name(*name*)
Get an ApiItem class by API name.

Parameters **name** (str) – Name of object used in API calls.

Returns *pytan3.api_models.ApiItem*

cls_list_by_name(*name*)
Get an ApiList class by API name.

Parameters **name** (str) – Name of object used in API calls.

Returns *pytan3.api_models.ApiList*

cls_by_name(*name*)
Get an ApiItem or ApiList by API name.

Parameters **name** (str) – Name of object used in API calls.

Returns *pytan3.api_models.ApiModel*

classmethod load(*api_type='soap'*, *veq=''*, *vmax=''*, *vmin=''*, *vshrink=True*)
Import an API module for version and type.

Parameters

- **api_type** (str, optional) – Type of object module to load, must be one of *API_TYPES*.

  Defaults to: *DEFAULT_TYPE*.

- **veq** (str, optional) – Exact version that API object module file must match.

  Defaults to: "".

- **vmin** (str, optional) – Minimum version that API object module file must match.

  Defaults to: “”.

- **vmax** (str, optional) – Maximum version that API object module file must match.

  Defaults to: “”.

- **vshrink** (bool or int, optional) – If True, shrink API object module file version down to match the same length as veq, vmax, and vmin.

  If False, do not shrink API object module file version at all.

  If int, shrink API object module file version, veq, vmax, and vmin down to this length.

  Defaults to: True.

Raises *exceptions.ModuleError* – If api_type not in *API_TYPES*.

Returns *ApiObjects*

Utilities for API Object Modules

pytan3.api_objects.**get_versions**(*api_type='soap'*)

Search for API object module files of api_type.

Parameters **api_type** (str, optional) – Type of object module to load, must be one of *API_TYPES*.

Defaults to: *DEFAULT_TYPE*.

Raises *exceptions.NoVersionFoundError* – If no API module files matching *PATTERN* are found.

Returns list of dict

pytan3.api_objects.**find_version**(*api_type='soap'*, *veq=''*, *vmax=''*, *vmin=''*, *vshrink=True*)

Find a API module files that match version and type.

Parameters

- **api_type** (str, optional) – Type of object module to find, must be one of *API_TYPES*.

  Defaults to: *DEFAULT_TYPE*.

- **veq** (str, optional) – Exact version that API object module file must match.

  Defaults to: “”.

- **vmin** (str, optional) – Minimum version that API object module file must match.

  Defaults to: “”.

- **vmax** (str, optional) – Maximum version that API object module file must match.

  Defaults to: “”.

- **vshrink** (bool, optional) – If True, shrink API object module file version down to match the same length as veq, vmax, and vmin.

  If False, do not shrink API object module file version at all.

  If int, shrink API object module file version, veq, vmax, and vmin down to this length.

  Defaults to: True.

Raises *exceptions.NoVersionFoundError* – If no API module files match api_type, veq, vmax, and vmin.

Returns dict

Loaders for API Object Modules

pytan3.api_objects.**load**(*api_type='soap'*, *veq=''*, *vmax=''*, *vmin=''*, *vshrink=True*)

Import an API module for version and type.

Parameters

- **api_type** (str, optional) – Type of object module to load, must be one of *API_TYPES*.

  Defaults to: *DEFAULT_TYPE*.

- **veq** (str, optional) – Exact version of object module of type to load.

  Defaults to: "".

- **vmin** (str, optional) – Minimum version of object module of type to load.

  Defaults to: "".

- **vmax** (str, optional) – Maximum version of object module of type to load.

  Defaults to: "".

- **vshrink** (bool or int, optional) – If True, shrink API object module file version down to match the same length as veq, vmax, and vmin.

  If False, do not shrink API object module file version at all.

  If int, shrink API object module file version, veq, vmax, and vmin down to this length.

  Defaults to: True.

Raises *exceptions.ModuleError* – If api_type not in *API_TYPES*.

Returns *ApiObjects*

Exceptions for API Object Modules

Exceptions and warnings for *pytan3.api_objects*.

exception pytan3.api_objects.exceptions.**ModuleError**

Bases: *pytan3.exceptions.PyTanError*

Parent of all exceptions for *pytan3.api_objects*.

Thrown from:

exception pytan3.api_objects.exceptions.**ModuleWarning**

Bases: *pytan3.exceptions.PyTanWarning*

Parent of all warnings for *pytan3.api_objects*.

Thrown from:

exception pytan3.api_objects.exceptions.**NoVersionFoundError**

Bases: *pytan3.api_objects.exceptions.ModuleError*

Exception handler when finding a version of an API object module.

Thrown from:

- *pytan3.api_objects.find_version()*
- *pytan3.api_objects.get_versions()*

exception pytan3.api_objects.exceptions.**UnknownApiNameError**(*name*, *name_map*, *module*)

Bases: *pytan3.api_objects.exceptions.ModuleError*

Exception handler when unable to find an API name for an API object.

Thrown from:

- *pytan3.api_objects.ApiObjects.cls_item_by_name()*
- *pytan3.api_objects.ApiObjects.cls_list_by_name()*
- *pytan3.api_objects.ApiObjects.cls_by_name()*

__init__(*name*, *name_map*, *module*)

Constructor.

Parameters

- **name** (str) – API name being searched for.
- **name_map** (dict) – Map of all API names to API objects.
- **module** (object) – Source API module of name_map.

name = None

str – API name being searched for.

name_map = None

dict – Map of all API names to API objects.

module = None

object – Source API module of name_map.

error = None

str – Error message that was thrown.

REST API Object Modules

REST API Object Module for Version 7.3.314.3424

Python objects for Tanium's API.

pytan3.api_objects.rest_7_3_314_3424.**float_types = (<class 'float'>,)**

tuple of type – Float types.

pytan3.api_objects.rest_7_3_314_3424.**integer_types = (<class 'int'>,)**

tuple of type – Integer types.

pytan3.api_objects.rest_7_3_314_3424.**string_types = (<class 'str'>,)**

tuple of type – String types.

pytan3.api_objects.rest_7_3_314_3424.**simple_types = (<class 'int'>, <class 'str'>, <class**

tuple of type – All types that should be considered simple types.

pytan3.api_objects.rest_7_3_314_3424.**TYPE = 'rest'**

str – Type of API this module was built from.

pytan3.api_objects.rest_7_3_314_3424.**API_DT = '%Y-%m-%dT%H:%M:%SZ'**

str – Datetime format for this API type and version.

pytan3.api_objects.rest_7_3_314_3424.**api_fixes**()
Fix incorrect attribute definitions on auto generated ApiModel classes.

pytan3.api_objects.rest_7_3_314_3424.**expand_cls_globals**()
Replace str values with global vars for attrs on ApiModel classes.

Quite the funky chicken dance for solving issues with order of class definition.

pytan3.api_objects.rest_7_3_314_3424.**expand_global**(*obj*)
Replace str values with global vars recursively.

Parameters **obj** (str or dict or list) – Object to expand into global var.

Returns String objects are the only ones that will be expanded.

Return type str or dict or list or object

pytan3.api_objects.rest_7_3_314_3424.**get_api_all_item**()
Get map of class name to class for all ApiItem subclasses.

Returns dict

pytan3.api_objects.rest_7_3_314_3424.**get_api_all_list**()
Get map of class name to class for all ApiList subclasses.

Returns dict

pytan3.api_objects.rest_7_3_314_3424.**get_api_all_model**()
Get map of class name to class for all ApiItem and ApiList subclasses.

Returns dict

class pytan3.api_objects.rest_7_3_314_3424.**ApiModel**
Bases: *pytan3.api_models.ApiModel*

Model for a complex item in the API.

class pytan3.api_objects.rest_7_3_314_3424.**ApiItem**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiModel*, *pytan3.api_models.ApiItem*

Model for a complex item in the API.

class pytan3.api_objects.rest_7_3_314_3424.**ApiList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiModel*, *pytan3.api_models.ApiList*

Model for an array in the API.

api_coerce_items_hook(*attr*, *value*, *op*)
Check hook that allows subclasses to modify list items.

Parameters

- **attr** (str) – Attribute being set on this object.
- **value** (*ApiList* or list or tuple) – The list object holding items.
- **op** (str) – Operation being performed that called this method.

Notes

REST arrays can include a CacheInfo object in them. This checks to see if any item is a CacheInfo object, and if so:

- "cache_info" gets added as a complex attr.

- "cache_info" attribute is set to value of item.
- item is not included in return list.

Returns The list of items modified or as is.

Return type `list`

class pytan3.api_objects.rest_7_3_314_3424.**ResultInfoList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'result_infos'

`str` – Name of object used in API calls.

API_NAME_SRC = ''

`str` – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'int'>,), 'now': (<class 'str'>,)}

`dict` – Map of simple attributes to their types.

API_COMPLEX = {}

`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}

`dict` – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']

`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_infos'

`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ResultInfo*

__repr__()

Make repr output be same as str output.

Returns `str`

class pytan3.api_objects.rest_7_3_314_3424.**ResultInfo**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'result_info'

`str` – Name of object used in API calls.

API_NAME_SRC = ''

`str` – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'er

`dict` – Map of simple attributes to their types.

API_COMPLEX = {}

`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}

`dict` – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'row_count', 'mr_tested', 'mr_passed'
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultInfoList*

API_LIST_API_NAME = 'result_infos'
`str` – Name of *API_LIST_CLS* used in API calls.

__repr__()
Make repr output be same as str output.

Returns `str`

class pytan3.api_objects.rest_7_3_314_3424.**ResultSetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'result_sets'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'int'>,), 'now': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_sets'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ResultSet*

class pytan3.api_objects.rest_7_3_314_3424.**MergedResultSet**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'merged_result_set'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'str'>,), 'now': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'result_infos': <class 'pytan3.api_objects.rest_7_3_314_3424.ResultInf
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ResultSet**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'result_set'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'ca
dict – Map of simple attributes to their types.

API_COMPLEX = {'columns': <class 'pytan3.api_objects.rest_7_3_314_3424.ColumnList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'mr_tested', 'mr_passed', 'row_count'
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultSetList*

API_LIST_API_NAME = 'result_sets'
str – Name of *API_LIST_CLS* used in API calls.

__init__(***kwargs*)
Constructor.

Notes

Sets *Column.API_DATA_SET* so column objects can access rows.

Sets *RowColumn.API_COLUMN* to the index correlated *Column* so row columns can access the column name, result type, etc.

Sets *Column.API_IDX* and *RowColumn.API_IDX* so column objects know what their index is without having to do lookups.

Parameters ****kwargs** – Passed back to parent class.

class pytan3.api_objects.rest_7_3_314_3424.**ColumnList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'cs'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['names']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'c'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Column*

__repr__()
Make repr output be same as str output.

Returns str

names
Expose column names of all *Column* in this obj.

Returns list of str

__getitem__(*value*)
Support indexing of *names*.

Parameters **value** (int or str) – If int: Index of item to retrieve from self. If str: Column name to index correlate from *ColumnList.names*

Returns The RowColumn object at index value from *names*.

Return type *RowColumn*

class pytan3.api_objects.rest_7_3_314_3424.**Column**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Manually defined API object.

API_DATA_SET = None
ResultSet – Parent of this object, set by *ResultSet.__init__()*.

API_IDX = None
int – Index of this object in *ColumnList*.

API_NAME = 'c'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'hash': (<class 'int'>,), 'name': (<class 'str'>,), 'type': (<class '
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['name', 'result_type', 'hash']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ColumnList*

API_LIST_API_NAME = 'cs'
str – Name of *API_LIST_CLS* used in API calls.

result_type
Expose simple attr "rt" as result_type.

Notes

Will try to map str from "rt" as int to constants from *Sensor.API_CONSTANTS*.

Returns str

get_values(*attr='value', join=None*)
Get values of this column from all rows.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list of str

class pytan3.api_objects.rest_7_3_314_3424.**RowList**(**args, **kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'rs'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'r'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Row*

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.rest_7_3_314_3424.**Row**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'r'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'cid': (<class 'int'>,), 'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'data': <class 'pytan3.api_objects.rest_7_3_314_3424.RowColumnList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['id', 'cid', 'columns']
list or str – Attributes to add to str formatting.

API_LIST_API_NAME = 'rs'
str – Name of *API_LIST_CLS* used in API calls.

API_LIST_CLS
ApiItem: Item class this list class holds.

alias of *RowList*

__repr__()
Make repr output be same as str output.

Returns str

__getitem__(*value*)
Support indexing of *columns*.

Parameters **value** (int or str) – If int: Index of item to retrieve from *columns*. If str: Column name to index correlate from *ColumnList.names*

Returns The RowColumn object at index value from *columns*.

Return type *RowColumn*

names
Return the names of each row column from *RowColumn.API_COLUMN*.

Returns list of str

columns
Expose complex attr "data" as "columns".

Returns *RowColumnList*

__len__()

Expose length of *columns*.

Returns int

get_values(*meta=False*, *hashes=False*, *join=None*)

Get all values from all columns in this row.

Parameters

- **meta** (bool, optional) – Include sensor hash and result type for each column.

  Defaults to: False.

- **hashes** (bool, optional) – Include hashes of values.

  Defaults to: False.

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns dict

class pytan3.api_objects.rest_7_3_314_3424.**RowColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'rc'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_columns'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *RowColumn*

class pytan3.api_objects.rest_7_3_314_3424.**RowColumn**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Manually defined API array object.

API_COLUMN = None

Column – Index correlated column, set by *ResultSet.__init__()*.

API_IDX = None

int – Index of this object in *RowColumnList*.

API_NAME = 'row_column'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = ['name', 'hash', 'result_type']
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'v'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *RowValue*

name
Expose column name from *API_COLUMN*.

Returns `str`

result_type
Expose column result type from *API_COLUMN*.

Returns `str`

hash
Expose column sensor hash from *API_COLUMN*.

Returns `str`

get_values(*attr='value'*, *join=None*)
Get all values from this row column.

Parameters

- **attr** (`str`, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (`str`, optional) – String to join multi value columns.

  Defaults to: None.

Returns `list` or `str`

class pytan3.api_objects.rest_7_3_314_3424.**RowValue**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'v'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {'hash': (<class 'int'>,), 'text': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['hash', 'value']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *RowColumn*

API_LIST_API_NAME = 'row_column'
str – Name of *API_LIST_CLS* used in API calls.

value
Expose simple attr "text" as value.

Returns str

class pytan3.api_objects.rest_7_3_314_3424.**ParseQuestionResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'parse_question_results'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_question_result'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseQuestionResult*

class pytan3.api_objects.rest_7_3_314_3424.**ParseQuestionResult**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'parse_question_result'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'force_computer_id_flag': (<class 'int'>,), 'from_canonical_text': (<c
dict – Map of simple attributes to their types.

API_COMPLEX = {'selects': <class 'pytan3.api_objects.rest_7_3_314_3424.SelectList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['hash', 'text']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseQuestionResultList*

API_LIST_API_NAME = 'questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SensorQuery**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_query'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query'
str – Name of object in source file.

API_SIMPLE = {'platform': (<class 'str'>,), 'script': (<class 'str'>,), 'script_type
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorQueryList*

API_LIST_API_NAME = 'sensor_querys'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SensorSubcolumn**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_subcolumn'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn'
str – Name of object in source file.

API_SIMPLE = {'exclude_from_parse_flag': (<class 'int'>,), 'hidden_flag': (<class 'i
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorSubcolumnList*

API_LIST_API_NAME = 'sensor_subcolumns'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SensorStat**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_stat'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<class 's
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorStatList*

API_LIST_API_NAME = 'sensor_stats'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SavedActionPolicy**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_policy'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_policy'
str – Name of object in source file.

API_SIMPLE = {'max_age': (<class 'int'>,), 'min_count': (<class 'int'>,), 'row_filte
dict – Map of simple attributes to their types.

API_COMPLEX = {'row_filter_group': <class 'pytan3.api_objects.rest_7_3_314_3424.Group
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SavedActionApproval**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_approval'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval'
str – Name of object in source file.

API_SIMPLE = {'approved_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3424.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionApprovalList*

API_LIST_API_NAME = 'saved_action_approvals'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SavedAction**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action'
str – Name of object in source file.

API_SIMPLE = {'action_group_id': (<class 'int'>,), 'approved_flag': (<class 'int'>,)
dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.rest_7_3_314_3424.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionList*

API_LIST_API_NAME = 'saved_actions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Sensor**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'category': (<class 'str'>,), 'creat
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3424.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {'BES_DATETIME_RESULT': 4, 'BES_SENSOR': 2, 'DATASIZE_RESULT': 8, 'HAS
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorList*

API_LIST_API_NAME = 'sensors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**AuditData**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'audit_data'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'creation_time': (<class 'str'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'mod_user': <class 'pytan3.api_objects.rest_7_3_314_3424.User'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditDataList*

API_LIST_API_NAME = 'audit_datas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**AuditLog**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'audit_log'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log'
str – Name of object in source file.

API_SIMPLE = {'creation_time': (<class 'str'>,), 'details': (<class 'str'>,), 'end_t
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditLogList*

API_LIST_API_NAME = 'audit_logs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Server**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'server'
str – Name of object used in API calls.

API_NAME_SRC = 'server'
str – Name of object in source file.

API_SIMPLE = {'heart_beat': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerList*

API_LIST_API_NAME = 'servers'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**MetadataItem**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'metadata_item'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_item'
str – Name of object in source file.

API_SIMPLE = {'admin_flag': (<class 'int'>,), 'name': (<class 'str'>,), 'value': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *MetadataList*

API_LIST_API_NAME = 'metadatas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Filter**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'filter'
str – Name of object used in API calls.

API_NAME_SRC = 'filter'
str – Name of object in source file.

API_SIMPLE = {'aggregation': (<class 'str'>,), 'all_times_flag': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'sensor': <class 'pytan3.api_objects.rest_7_3_314_3424.Sensor'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *FilterList*

API_LIST_API_NAME = 'filters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**IdReference**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'id_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'id_reference'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Group**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'group'
str – Name of object used in API calls.

API_NAME_SRC = 'group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'filters': <class 'pytan3.api_objects.rest_7_3_314_3424.FilterList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *GroupList*

API_LIST_API_NAME = 'groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Select**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'select'

str – Name of object used in API calls.

API_NAME_SRC = 'select'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'filter': <class 'pytan3.api_objects.rest_7_3_314_3424.Filter'>, 'grou

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SelectList*

API_LIST_API_NAME = 'selects'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**XmlError**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'xml_error'

str – Name of object used in API calls.

API_NAME_SRC = 'xml_error'

str – Name of object in source file.

API_SIMPLE = {'error_context': (<class 'str'>,), 'exception': (<class 'str'>,), 'typ

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ErrorList*

API_LIST_API_NAME = 'errors'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**CacheInfo**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'cache_info'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_info'
str – Name of object in source file.

API_SIMPLE = {'cache_id': (<class 'int'>,), 'cache_row_count': (<class 'int'>,), 'exp
dict – Map of simple attributes to their types.

API_COMPLEX = {'errors': <class 'pytan3.api_objects.rest_7_3_314_3424.ErrorList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**QuestionListInfo**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'question_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Question**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'question'
str – Name of object used in API calls.

API_NAME_SRC = 'question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'cache_row_id': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'context_group': <class 'pytan3.api_objects.rest_7_3_314_3424.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *QuestionList*

API_LIST_API_NAME = 'questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**PackageFileTemplate**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_template'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template'
str – Name of object in source file.

API_SIMPLE = {'download_seconds': (<class 'int'>,), 'hash': (<class 'str'>,), 'name'
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileTemplateList*

API_LIST_API_NAME = 'package_file_templates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**PackageFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileStatusList*

API_LIST_API_NAME = 'package_file_statuss'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**PackageFile**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_file'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_status': <class 'pytan3.api_objects.rest_7_3_314_3424.PackageFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileList*

API_LIST_API_NAME = 'package_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**PackageSpec**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec'
str – Name of object in source file.

API_SIMPLE = {'available_time': (<class 'str'>,), 'cache_row_id': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3424.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageSpecList*

API_LIST_API_NAME = 'package_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ClientStatus**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'client_status'
str – Name of object used in API calls.

API_NAME_SRC = 'client_status'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'computer_id': (<class 'str'>,), 'fu
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemStatusList*

API_LIST_API_NAME = 'system_status'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SystemSetting**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'system_setting'
str – Name of object used in API calls.

API_NAME_SRC = 'system_setting'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'default_value': (<class 'str'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'audit_data': <class 'pytan3.api_objects.rest_7_3_314_3424.AuditData'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemSettingList*

API_LIST_API_NAME = 'system_settings'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SoapError**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'soap_error'
str – Name of object used in API calls.

API_NAME_SRC = 'soap_error'
str – Name of object in source file.

API_SIMPLE = {'context': (<class 'str'>,), 'exception_name': (<class 'str'>,), 'obje
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**WhiteListedUrl**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'white_listed_url'
str – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url'
str – Name of object in source file.

API_SIMPLE = {'chunk_id': (<class 'str'>,), 'download_seconds': (<class 'int'>,), 'e
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3424.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *WhiteListedUrlList*

API_LIST_API_NAME = 'white_listed_urls'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**VersionAggregate**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'version_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'filtered': (<class 'int'>,), 'version_stri
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *VersionAggregateList*

API_LIST_API_NAME = 'version_aggregates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SystemStatusAggregate**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'system_status_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_aggregate'
str – Name of object in source file.

API_SIMPLE = {'blocked_count': (<class 'int'>,), 'leader_count': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'versions': <class 'pytan3.api_objects.rest_7_3_314_3424.VersionAggrega
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**UserRole**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user_role'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'permissions': <class 'pytan3.api_objects.rest_7_3_314_3424.Permission
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserRoleList*

API_LIST_API_NAME = 'roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**UserOwnedObjectIds**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user_owned_object_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'user_owned_object_ids'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'plugin_schedules': <class 'pytan3.api_objects.rest_7_3_314_3424.Plugi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**User**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user'

str – Name of object used in API calls.

API_NAME_SRC = 'user'

str – Name of object in source file.

API_SIMPLE = {'active_session_count': (<class 'int'>,), 'deleted_flag': (<class 'int

dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.rest_7_3_314_3424.Conte

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *UserList*

API_LIST_API_NAME = 'users'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ActionListInfo**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action_list_info'

str – Name of object used in API calls.

API_NAME_SRC = 'action_list_info'

str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Action**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action'
str – Name of object used in API calls.

API_NAME_SRC = 'action'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'comment': (<class 'str'>,), 'creati
dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.rest_7_3_314_3424.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionList*

API_LIST_API_NAME = 'actions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ActionStop**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action_stop'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.rest_7_3_314_3424.Action'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionStopList*

API_LIST_API_NAME = 'action_stops'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ArchivedQuestion**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'archived_question'
str – Name of object used in API calls.

API_NAME_SRC = 'archived_question'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ArchivedQuestionList*

API_LIST_API_NAME = 'archived_questions'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SavedQuestion**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_question'
`str` – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'archive_enabled_flag': (<cl
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'archive_owner': <class 'pytan3.api_objects.rest_7_3_314_3424.User'>,
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionList*

API_LIST_API_NAME = 'saved_questions'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ParseJob**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parse_job'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parse_job'
`str` – Name of object in source file.

API_SIMPLE = {'parser_version': (<class 'int'>,), 'question_text': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseJobList*

API_LIST_API_NAME = 'parse_jobs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Parameter**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parameter'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter'
str – Name of object in source file.

API_SIMPLE = {'key': (<class 'str'>,), 'type': (<class 'int'>,), 'value': (<class '
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParameterList*

API_LIST_API_NAME = 'parameters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ParseResult**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'parameter_definition': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameters': <class 'pytan3.api_objects.rest_7_3_314_3424.ParameterLi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultList*

API_LIST_API_NAME = 'parse_results'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SensorReference**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'real_ms_avg': (<class 'int'>,), 'start_char
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorReferenceList*

API_LIST_API_NAME = 'sensor_references'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ParseResultGroup**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result_group'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group'
str – Name of object in source file.

API_SIMPLE = {'question_text': (<class 'str'>,), 'score': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameter_values': <class 'pytan3.api_objects.rest_7_3_314_3424.Param
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultGroupList*

API_LIST_API_NAME = 'parse_result_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ClientCount**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'client_count'
str – Name of object used in API calls.

API_NAME_SRC = 'client_count'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**PluginArgument**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_argument'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'type': (<class 'str'>,), 'value': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginArgumentList*

API_LIST_API_NAME = 'plugin_arguments'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**UploadFile**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file'
str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'destination_file': (<class 'str'>,), 'file_
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UploadFileList*

API_LIST_API_NAME = 'upload_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**UploadFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_status'
str – Name of object in source file.

API_SIMPLE = {'file_cached': (<class 'int'>,), 'hash': (<class 'str'>,), 'percent_co
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_parts': <class 'pytan3.api_objects.rest_7_3_314_3424.UploadFileL
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Plugin**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'plugin'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin'
str – Name of object in source file.

API_SIMPLE = {'allow_rest': (<class 'int'>,), 'bundle': (<class 'str'>,), 'cache_row
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.rest_7_3_314_3424.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {'SCRIPT': 'Script', 'SQL': 'SQL'}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginList*

API_LIST_API_NAME = 'plugins'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**PluginSchedule**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_schedule'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'enabled': (<class 'int'>,), 'end_da
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.rest_7_3_314_3424.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginScheduleList*

API_LIST_API_NAME = 'plugin_schedules'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ComputerGroupSpec**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group_spec'

str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_spec'

str – Name of object in source file.

API_SIMPLE = {'computer_name': (<class 'str'>,), 'id': (<class 'int'>,), 'ip_address

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ComputerSpecList*

API_LIST_API_NAME = 'computer_specs'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ComputerGroup**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group'

str – Name of object used in API calls.

API_NAME_SRC = 'computer_group'

str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<c

dict – Map of simple attributes to their types.

API_COMPLEX = {'computer_specs': <class 'pytan3.api_objects.rest_7_3_314_3424.Compute

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ComputerGroupList*

API_LIST_API_NAME = 'computer_groups'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**VerifySignature**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'verify_signature'
`str` – Name of object used in API calls.

API_NAME_SRC = 'verify_signature'
`str` – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'id': (<class 'int'>,), 'type': (<class 's
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ObjectList**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'object_list'
`str` – Name of object used in API calls.

API_NAME_SRC = 'object_list'
`str` – Name of object in source file.

API_SIMPLE = {'export_id': (<class 'str'>,), 'export_version': (<class 'int'>,), 'im
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.rest_7_3_314_3424.Action'>, 'acti
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ImportConflictDetail**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'import_conflict_detail'
`str` – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail'
`str` – Name of object in source file.

API_SIMPLE = {'diff': (<class 'str'>,), 'is_new': (<class 'int'>,), 'name': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ImportConflictDetailList*

API_LIST_API_NAME = 'import_conflict_details'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**CacheFilter**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'cache_filter'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'field': (<class 'str'>,), 'not_flag':
dict – Map of simple attributes to their types.

API_COMPLEX = {'sub_filters': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheFilte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *CacheFilterList*

API_LIST_API_NAME = 'cache_filters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Options**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'options'
str – Name of object used in API calls.

API_NAME_SRC = 'options'
str – Name of object in source file.

API_SIMPLE = {'aggregate_by_value_flag': (<class 'int'>,), 'aggregate_over_time_flag'
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_filters': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSet**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3424.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetList*

API_LIST_API_NAME = 'content_sets'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRolePrivilegeOnRole**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege_on_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3424.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeOnRoleList*

API_LIST_API_NAME = 'content_set_role_privilege_on_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRole**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role'
str – Name of object in source file.

API_SIMPLE = {'all_content_sets_flag': (<class 'int'>,), 'category': (<class 'str'>,
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role_privileges': <class 'pytan3.api_objects.rest_7_3_314
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleList*

API_LIST_API_NAME = 'content_set_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_membership'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.rest_7_3_314_3424.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleMembershipList*

API_LIST_API_NAME = 'content_set_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetUserGroupRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_user_group_role_membership'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.rest_7_3_314_3424.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetUserGroupRoleMembershipList*

API_LIST_API_NAME = 'content_set_user_group_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'privilege_module':
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3424.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetPrivilegeList*

API_LIST_API_NAME = 'content_set_privileges'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRolePrivilege**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3424.IdReferenc
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeList*

API_LIST_API_NAME = 'content_set_role_privileges'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**EffectiveContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'effective_content_set_privilege'
`str` – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3424.ContentSet
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *EffectiveContentSetPrivilegeList*

API_LIST_API_NAME = 'effective_content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Dashboard**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'public_flag': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3424.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *DashboardList*

API_LIST_API_NAME = 'dashboards'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**DashboardGroup**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard_group'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_group'
str – Name of object in source file.

API_SIMPLE = {'display_index': (<class 'int'>,), 'editable_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3424.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**UserGroup**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user_group'

str – Name of object used in API calls.

API_NAME_SRC = 'user_group'

str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'exclusive_flag': (<class 'int'>,),

dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.rest_7_3_314_3424.Conte

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *UserGroupList*

API_LIST_API_NAME = 'user_groups'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**Solution**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'solution'

str – Name of object used in API calls.

API_NAME_SRC = 'solution'

str – Name of object in source file.

API_SIMPLE = {'category': (<class 'str'>,), 'delete_xml_url': (<class 'str'>,), 'dele

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SolutionList*

API_LIST_API_NAME = 'solutions'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ActionGroup**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action_group'
str – Name of object used in API calls.

API_NAME_SRC = 'action_group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'groups': <class 'pytan3.api_objects.rest_7_3_314_3424.GroupList'>, 'u
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionGroupList*

API_LIST_API_NAME = 'action_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SavedQuestionPackageSpecs**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_package_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_package_specs'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'packages': <class 'pytan3.api_objects.rest_7_3_314_3424.PackageSpecLi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SavedQuestionQuestion**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_question'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'questions': <class 'pytan3.api_objects.rest_7_3_314_3424.QuestionList
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionQuestionList*

API_LIST_API_NAME = 'saved_question_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**LdapSyncConnector**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'ldap_sync_connector'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector'
str – Name of object in source file.

API_SIMPLE = {'base_groups': (<class 'str'>,), 'base_users': (<class 'str'>,), 'disa
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *LdapSyncConnectorList*

API_LIST_API_NAME = 'ldap_sync_connectors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ServerThrottle**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle'
str – Name of object in source file.

API_SIMPLE = {'bandwidth_bytes_limit': (<class 'int'>,), 'connection_limit': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerThrottleList*

API_LIST_API_NAME = 'server_throttles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottle**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle'
str – Name of object in source file.

API_SIMPLE = {'all_subnets_flag': (<class 'int'>,), 'bandwidth_bytes_limit': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSu
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleList*

API_LIST_API_NAME = 'site_throttles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottleSubnet**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet'
str – Name of object in source file.

API_SIMPLE = {'range': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetList*

API_LIST_API_NAME = 'site_throttle_subnets'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**ServerThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle_status'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status'
str – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'id': (<class '
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerThrottleStatusList*

API_LIST_API_NAME = 'server_throttle_statuses'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSu
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleStatusList*

API_LIST_API_NAME = 'site_throttles_statuses'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottleSubnetStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status'
str – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'queue_delay_mil
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetStatusList*

API_LIST_API_NAME = 'site_throttle_subnet_statuss'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**HashedString**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'hashed_string'
str – Name of object used in API calls.

API_NAME_SRC = 'hashed_string'
str – Name of object in source file.

API_SIMPLE = {'collision_flag': (<class 'int'>,), 'error_flag': (<class 'int'>,), 'f
dict – Map of simple attributes to their types.

API_COMPLEX = {'first_computer_id': <class 'pytan3.api_objects.rest_7_3_314_3424.Comp
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *HashedStringList*

API_LIST_API_NAME = 'hashed_strings'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3424.**SensorQueryList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_querys'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'query'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorQuery*

class pytan3.api_objects.rest_7_3_314_3424.**SensorSubcolumnList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_subcolumns'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subcolumn'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorSubcolumn*

class pytan3.api_objects.rest_7_3_314_3424.**StringHintList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'string_hints'
`str` – Name of object used in API calls.

API_NAME_SRC = 'string_hint_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'string_hint'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**SensorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensors'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Sensor*

class pytan3.api_objects.rest_7_3_314_3424.**SensorStatList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_stats'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_stat'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorStat*

class pytan3.api_objects.rest_7_3_314_3424.**SavedActionApprovalList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_approvals'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action_approval'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedActionApproval*

class pytan3.api_objects.rest_7_3_314_3424.**SavedActionRowIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_row_ids'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_action_row_id_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_id'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**SavedActionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_actions'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_action_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedAction*

class pytan3.api_objects.rest_7_3_314_3424.**AuditDataList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'audit_datas'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'entry'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditData*

class pytan3.api_objects.rest_7_3_314_3424.**AuditLogList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'audit_logs'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log_list'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'type': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'entries'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditLog*

class pytan3.api_objects.rest_7_3_314_3424.**ServerList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'servers'
`str` – Name of object used in API calls.

API_NAME_SRC = 'server_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'server'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Server*

class pytan3.api_objects.rest_7_3_314_3424.**ServerHost**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_host'
`str` – Name of object used in API calls.

API_NAME_SRC = 'server_host'
`str` – Name of object in source file.

API_SIMPLE = {'heart_beat_age_in_minute': (<class 'int'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'servers'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerList*

class pytan3.api_objects.rest_7_3_314_3424.**ServerHostList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_hosts'
`str` – Name of object used in API calls.

API_NAME_SRC = 'server_host_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_host'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerHost*

class pytan3.api_objects.rest_7_3_314_3424.**MetadataList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'metadatas'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'item'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *MetadataItem*

class pytan3.api_objects.rest_7_3_314_3424.**GroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'groups'
str – Name of object used in API calls.

API_NAME_SRC = 'group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Group*

class pytan3.api_objects.rest_7_3_314_3424.**FilterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'filters'
str – Name of object used in API calls.

API_NAME_SRC = 'filter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Filter*

class pytan3.api_objects.rest_7_3_314_3424.**SelectList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'selects'
str – Name of object used in API calls.

API_NAME_SRC = 'select_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'select'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Select*

class pytan3.api_objects.rest_7_3_314_3424.**ErrorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'errors'
str – Name of object used in API calls.

API_NAME_SRC = 'error_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'error'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *XmlError*

class pytan3.api_objects.rest_7_3_314_3424.**QuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'questions'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Question*

class pytan3.api_objects.rest_7_3_314_3424.**PackageFileTemplateList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_templates'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file_template'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileTemplate*

class pytan3.api_objects.rest_7_3_314_3424.**PackageFileStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_statuss'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileStatus*

class pytan3.api_objects.rest_7_3_314_3424.**PackageFileList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_files'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFile*

class pytan3.api_objects.rest_7_3_314_3424.**PackageSpecList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'package_spec'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageSpec*

class pytan3.api_objects.rest_7_3_314_3424.**WhiteListedUrlList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'white_listed_urls'
`str` – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'white_listed_url'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *WhiteListedUrl*

class pytan3.api_objects.rest_7_3_314_3424.**VersionAggregateList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'version_aggregates'
`str` – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'version'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *VersionAggregate*

class pytan3.api_objects.rest_7_3_314_3424.**SystemStatusList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'system_status'
`str` – Name of object used in API calls.

API_NAME_SRC = 'system_status_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'aggregate': <class 'pytan3.api_objects.rest_7_3_314_3424.SystemStatusA
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'client_status'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ClientStatus*

class pytan3.api_objects.rest_7_3_314_3424.**SystemSettingList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'system_settings'
`str` – Name of object used in API calls.

API_NAME_SRC = 'system_setting_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'system_setting'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SystemSetting*

class pytan3.api_objects.rest_7_3_314_3424.**UserList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'users'
str – Name of object used in API calls.

API_NAME_SRC = 'user_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.rest_7_3_314_3424.**PermissionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'permissions'
str – Name of object used in API calls.

API_NAME_SRC = 'permission_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {'ACTION_APPROVE': 'action_approval', 'ACTION_READ': 'action_read', 'A
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'permission'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**UserRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'roles'

str – Name of object used in API calls.

API_NAME_SRC = 'user_role_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'role'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *UserRole*

class pytan3.api_objects.rest_7_3_314_3424.**ActionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'actions'

str – Name of object used in API calls.

API_NAME_SRC = 'action_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Action*

class pytan3.api_objects.rest_7_3_314_3424.**ActionStopList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'action_stops'
`str` – Name of object used in API calls.

API_NAME_SRC = 'action_stop_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_stop'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionStop*

class pytan3.api_objects.rest_7_3_314_3424.**ArchivedQuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'archived_questions'
`str` – Name of object used in API calls.

API_NAME_SRC = 'archived_question_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'archived_question'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ArchivedQuestion*

class pytan3.api_objects.rest_7_3_314_3424.**SavedQuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestion*

class pytan3.api_objects.rest_7_3_314_3424.**ParseJobList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parse_jobs'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_job_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_job'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseJob*

class pytan3.api_objects.rest_7_3_314_3424.**ParseResultGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parse_result_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result_group'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResultGroup*

class pytan3.api_objects.rest_7_3_314_3424.**ParseResultList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parse_results'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parse_result_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResult*

class pytan3.api_objects.rest_7_3_314_3424.**ParameterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parameters'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parameter_list'
`str` – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parameter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Parameter*

class pytan3.api_objects.rest_7_3_314_3424.**ParameterValueList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parameter_values'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter_value_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**SensorReferenceList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_references'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_reference'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorReference*

class pytan3.api_objects.rest_7_3_314_3424.**PluginArgumentList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_arguments'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'argument'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginArgument*

class pytan3.api_objects.rest_7_3_314_3424.**PluginSqlResultList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_results'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_result_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**PluginSqlColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_columns'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_column_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'name'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**PluginSql**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql'
str – Name of object in source file.

API_SIMPLE = {'result_count': (<class 'int'>,), 'rows_affected': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'columns': <class 'pytan3.api_objects.rest_7_3_314_3424.PluginSqlColum
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_row'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSqlResultList*

class pytan3.api_objects.rest_7_3_314_3424.**PluginCommandList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_commands'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_command_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'command'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**UploadFileList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'upload_files'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'upload_file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UploadFile*

class pytan3.api_objects.rest_7_3_314_3424.**PluginList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugins'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Plugin*

class pytan3.api_objects.rest_7_3_314_3424.**PluginScheduleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_schedules'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin_schedule'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSchedule*

class pytan3.api_objects.rest_7_3_314_3424.**ComputerSpecList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'computer_specs'

str – Name of object used in API calls.

API_NAME_SRC = 'computer_spec_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_spec'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ComputerGroupSpec*

class pytan3.api_objects.rest_7_3_314_3424.**ComputerGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'computer_groups'

str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3424.CacheInfo'>

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_group'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ComputerGroup*

class pytan3.api_objects.rest_7_3_314_3424.**ImportConflictDetailList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_details'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_detail'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ImportConflictDetail*

class pytan3.api_objects.rest_7_3_314_3424.**CacheFilterList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'cache_filters'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *CacheFilter*

class pytan3.api_objects.rest_7_3_314_3424.**ImportConflictOptions**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_options'
`str` – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_options'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_option'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_sets'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSet*

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRolePrivilegeOnRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privilege_on_roles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilegeOnRole*

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRoleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_roles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRole*

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRoleMembershipList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_memberships'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_membership'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRoleMembership*

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetUserGroupRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_user_group_role_memberships'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_user_group_role_membership'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetUserGroupRoleMembership*

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_privileges'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetPrivilege*

class pytan3.api_objects.rest_7_3_314_3424.**ContentSetRolePrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privileges'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilege*

class pytan3.api_objects.rest_7_3_314_3424.**EffectiveContentSetPrivilegeRequest**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privilege_request'
`str` – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_request'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.rest_7_3_314_3424.**EffectiveContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privileges'
`str` – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'effective_content_set_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *EffectiveContentSetPrivilege*

class pytan3.api_objects.rest_7_3_314_3424.**DashboardList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'dashboards'
`str` – Name of object used in API calls.

API_NAME_SRC = 'dashboard_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'dashboard'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Dashboard*

class pytan3.api_objects.rest_7_3_314_3424.**UserGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'user_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'user_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UserGroup*

class pytan3.api_objects.rest_7_3_314_3424.**SolutionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'solutions'
str – Name of object used in API calls.

API_NAME_SRC = 'solution_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'solution'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Solution*

class pytan3.api_objects.rest_7_3_314_3424.**ActionGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'action_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'action_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionGroup*

class pytan3.api_objects.rest_7_3_314_3424.**SavedQuestionQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_question_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestionQuestion*

class pytan3.api_objects.rest_7_3_314_3424.**LdapSyncConnectorList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'ldap_sync_connectors'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'ldap_sync_connector'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *LdapSyncConnector*

class pytan3.api_objects.rest_7_3_314_3424.**ServerThrottleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttles'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottle*

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottle*

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottleSubnetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnets'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnet*

class pytan3.api_objects.rest_7_3_314_3424.**ServerThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttle_statuses'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottleStatus*

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles_statuses'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle_status'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleStatus*

class pytan3.api_objects.rest_7_3_314_3424.**SiteThrottleSubnetStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnet_statuss'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnetStatus*

class pytan3.api_objects.rest_7_3_314_3424.**ComputerIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'computer_ids'
`str` – Name of object used in API calls.

API_NAME_SRC = 'computer_id_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3424.**HashedStringList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'hashed_strings'
str – Name of object used in API calls.

API_NAME_SRC = 'hashed_string_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'hashed_string'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *HashedString*

pytan3.api_objects.rest_7_3_314_3424.**BUILD_META = {'date': '2019-02-22 07:46:01.956314',**
dict – How this module was built (date/time in UTC format).

pytan3.api_objects.rest_7_3_314_3424.**COMMANDS = ['AddObject', 'GetObject', 'MoveObject', '**
list of str – API commands.

pytan3.api_objects.rest_7_3_314_3424.**VERSION = {'build': 3424, 'major': 7, 'minor': 3,**
dict – Tanium API version these objects are intended to be used for.

REST API Object Module for Version 7.3.314.3641

Python objects for Tanium's API.

pytan3.api_objects.rest_7_3_314_3641.**float_types = (<class 'float'>,)**
tuple of type – Float types.

pytan3.api_objects.rest_7_3_314_3641.**integer_types = (<class 'int'>,)**
tuple of type – Integer types.

pytan3.api_objects.rest_7_3_314_3641.**string_types = (<class 'str'>,)**
tuple of type – String types.

pytan3.api_objects.rest_7_3_314_3641.**simple_types = (<class 'int'>, <class 'str'>, <class**
tuple of type – All types that should be considered simple types.

pytan3.api_objects.rest_7_3_314_3641.**TYPE = 'rest'**
`str` – Type of API this module was built from.

pytan3.api_objects.rest_7_3_314_3641.**API_DT = '%Y-%m-%dT%H:%M:%SZ'**
`str` – Datetime format for this API type and version.

pytan3.api_objects.rest_7_3_314_3641.**api_fixes**()
Fix incorrect attribute definitions on auto generated ApiModel classes.

pytan3.api_objects.rest_7_3_314_3641.**expand_cls_globals**()
Replace str values with global vars for attrs on ApiModel classes.

Quite the funky chicken dance for solving issues with order of class definition.

pytan3.api_objects.rest_7_3_314_3641.**expand_global**(*obj*)
Replace str values with global vars recursively.

Parameters **obj** (`str` or `dict` or `list`) – Object to expand into global var.

Returns String objects are the only ones that will be expanded.

Return type `str` or `dict` or `list` or `object`

pytan3.api_objects.rest_7_3_314_3641.**get_api_all_item**()
Get map of class name to class for all ApiItem subclasses.

Returns `dict`

pytan3.api_objects.rest_7_3_314_3641.**get_api_all_list**()
Get map of class name to class for all ApiList subclasses.

Returns `dict`

pytan3.api_objects.rest_7_3_314_3641.**get_api_all_model**()
Get map of class name to class for all ApiItem and ApiList subclasses.

Returns `dict`

class pytan3.api_objects.rest_7_3_314_3641.**ApiModel**
Bases: *pytan3.api_models.ApiModel*

Model for a complex item in the API.

class pytan3.api_objects.rest_7_3_314_3641.**ApiItem**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiModel*, *pytan3.api_models.ApiItem*

Model for a complex item in the API.

class pytan3.api_objects.rest_7_3_314_3641.**ApiList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiModel*, *pytan3.api_models.ApiList*

Model for an array in the API.

api_coerce_items_hook(*attr*, *value*, *op*)
Check hook that allows subclasses to modify list items.

Parameters

- **attr** (`str`) – Attribute being set on this object.
- **value** (*ApiList* or `list` or `tuple`) – The list object holding items.
- **op** (`str`) – Operation being performed that called this method.

Notes

REST arrays can include a CacheInfo object in them. This checks to see if any item is a CacheInfo object, and if so:

- "cache_info" gets added as a complex attr.
- "cache_info" attribute is set to value of item.
- item is not included in return list.

Returns The list of items modified or as is.

Return type `list`

class pytan3.api_objects.rest_7_3_314_3641.**ResultInfoList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'result_infos'

`str` – Name of object used in API calls.

API_NAME_SRC = ''

`str` – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'int'>,), 'now': (<class 'str'>,)}

`dict` – Map of simple attributes to their types.

API_COMPLEX = {}

`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}

`dict` – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']

`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_infos'

`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ResultInfo*

__repr__()

Make repr output be same as str output.

Returns `str`

class pytan3.api_objects.rest_7_3_314_3641.**ResultInfo**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'result_info'

`str` – Name of object used in API calls.

API_NAME_SRC = ''

`str` – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'er
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'row_count', 'mr_tested', 'mr_passed'
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultInfoList*

API_LIST_API_NAME = 'result_infos'
str – Name of *API_LIST_CLS* used in API calls.

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.rest_7_3_314_3641.**ResultSetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'result_sets'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'int'>,), 'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_sets'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ResultSet*

class pytan3.api_objects.rest_7_3_314_3641.**MergedResultSet**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'merged_result_set'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'str'>,), 'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'result_infos': <class 'pytan3.api_objects.rest_7_3_314_3641.ResultInf
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ResultSet**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'result_set'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'ca
dict – Map of simple attributes to their types.

API_COMPLEX = {'columns': <class 'pytan3.api_objects.rest_7_3_314_3641.ColumnList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'mr_tested', 'mr_passed', 'row_count'
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultSetList*

API_LIST_API_NAME = 'result_sets'
str – Name of *API_LIST_CLS* used in API calls.

__init__(***kwargs*)
Constructor.

Notes

Sets *Column.API_DATA_SET* so column objects can access rows.

Sets *RowColumn.API_COLUMN* to the index correlated *Column* so row columns can access the column name, result type, etc.

Sets `Column.API_IDX` and `RowColumn.API_IDX` so column objects know what their index is without having to do lookups.

Parameters ****kwargs** – Passed back to parent class.

class pytan3.api_objects.rest_7_3_314_3641.**ColumnList**(**args*, ***kwargs*)

Bases: `pytan3.api_objects.rest_7_3_314_3641.ApiList`

Manually defined API array object.

API_NAME = 'cs'

`str` – Name of object used in API calls.

API_NAME_SRC = ''

`str` – Name of object in source file.

API_SIMPLE = {}

`dict` – Map of simple attributes to their types.

API_COMPLEX = {}

`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}

`dict` – Map of constants to their values.

API_STR_ADD = ['names']

`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'c'

`str` – Name of `API_ITEM_CLS` used in API calls.

API_ITEM_CLS

`ApiItem`: Item class this list class holds.

alias of `Column`

__repr__()

Make repr output be same as str output.

Returns `str`

names

Expose column names of all `Column` in this obj.

Returns `list` of `str`

__getitem__(*value*)

Support indexing of `names`.

Parameters **value** (`int` or `str`) – If int: Index of item to retrieve from self. If str: Column name to index correlate from `ColumnList.names`

Returns The RowColumn object at index value from `names`.

Return type `RowColumn`

class pytan3.api_objects.rest_7_3_314_3641.**Column**(***kwargs*)

Bases: `pytan3.api_objects.rest_7_3_314_3641.ApiItem`

Manually defined API object.

API_DATA_SET = None

`ResultSet` – Parent of this object, set by `ResultSet.__init__()`.

API_IDX = None
int – Index of this object in *ColumnList*.

API_NAME = 'c'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'hash': (<class 'int'>,), 'name': (<class 'str'>,), 'type': (<class '
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['name', 'result_type', 'hash']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ColumnList*

API_LIST_API_NAME = 'cs'
str – Name of *API_LIST_CLS* used in API calls.

result_type
Expose simple attr "rt" as result_type.

Notes

Will try to map str from "rt" as int to constants from *Sensor.API_CONSTANTS*.

Returns str

get_values(*attr='value', join=None*)
Get values of this column from all rows.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list of str

class pytan3.api_objects.rest_7_3_314_3641.**RowList**(**args, **kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'rs'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'r'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Row*

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.rest_7_3_314_3641.**Row**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'r'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'cid': (<class 'int'>,), 'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'data': <class 'pytan3.api_objects.rest_7_3_314_3641.RowColumnList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['id', 'cid', 'columns']
list or str – Attributes to add to str formatting.

API_LIST_API_NAME = 'rs'
str – Name of *API_LIST_CLS* used in API calls.

API_LIST_CLS
ApiItem: Item class this list class holds.

alias of *RowList*

__repr__()
Make repr output be same as str output.

Returns str

__getitem__(*value*)
Support indexing of *columns*.

Parameters **value** (int or str) – If int: Index of item to retrieve from *columns*. If str: Column name to index correlate from *ColumnList.names*

Returns The RowColumn object at index value from *columns*.

Return type *RowColumn*

names

Return the names of each row column from *RowColumn.API_COLUMN*.

Returns list of str

columns

Expose complex attr "data" as "columns".

Returns *RowColumnList*

__len__()

Expose length of *columns*.

Returns int

get_values(*meta=False*, *hashes=False*, *join=None*)

Get all values from all columns in this row.

Parameters

- **meta** (bool, optional) – Include sensor hash and result type for each column.

  Defaults to: False.

- **hashes** (bool, optional) – Include hashes of values.

  Defaults to: False.

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns dict

class pytan3.api_objects.rest_7_3_314_3641.**RowColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'rc'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_columns'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *RowColumn*

class pytan3.api_objects.rest_7_3_314_3641.**RowColumn**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Manually defined API array object.

API_COLUMN = None
Column – Index correlated column, set by *ResultSet.__init__()*.

API_IDX = None
int – Index of this object in *RowColumnList*.

API_NAME = 'row_column'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['name', 'hash', 'result_type']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'v'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *RowValue*

name
Expose column name from *API_COLUMN*.

Returns str

result_type
Expose column result type from *API_COLUMN*.

Returns str

hash
Expose column sensor hash from *API_COLUMN*.

Returns str

get_values(*attr='value'*, *join=None*)
Get all values from this row column.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list or str

class pytan3.api_objects.rest_7_3_314_3641.**RowValue**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'v'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'hash': (<class 'int'>,), 'text': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['hash', 'value']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *RowColumn*

API_LIST_API_NAME = 'row_column'
str – Name of *API_LIST_CLS* used in API calls.

value
Expose simple attr "text" as value.

Returns str

class pytan3.api_objects.rest_7_3_314_3641.**ParseQuestionResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'parse_question_results'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_question_result'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseQuestionResult*

class pytan3.api_objects.rest_7_3_314_3641.**ParseQuestionResult**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'parse_question_result'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'force_computer_id_flag': (<class 'int'>,), 'from_canonical_text': (<c
dict – Map of simple attributes to their types.

API_COMPLEX = {'selects': <class 'pytan3.api_objects.rest_7_3_314_3641.SelectList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['hash', 'text']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseQuestionResultList*

API_LIST_API_NAME = 'questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SensorQuery**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_query'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query'
str – Name of object in source file.

API_SIMPLE = {'platform': (<class 'str'>,), 'script': (<class 'str'>,), 'script_type
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorQueryList*

API_LIST_API_NAME = 'sensor_querys'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SensorSubcolumn**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_subcolumn'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn'
`str` – Name of object in source file.

API_SIMPLE = {'exclude_from_parse_flag': (<class 'int'>,), 'hidden_flag': (<class 'i
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorSubcolumnList*

API_LIST_API_NAME = 'sensor_subcolumns'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SensorStat**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_stat'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat'
`str` – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<class 's
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorStatList*

API_LIST_API_NAME = 'sensor_stats'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SavedActionPolicy**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_policy'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_action_policy'
`str` – Name of object in source file.

API_SIMPLE = {'max_age': (<class 'int'>,), 'min_count': (<class 'int'>,), 'row_filte
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'row_filter_group': <class 'pytan3.api_objects.rest_7_3_314_3641.Group
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SavedActionApproval**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_approval'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval'
`str` – Name of object in source file.

API_SIMPLE = {'approved_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3641.MetadataList'
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionApprovalList*

API_LIST_API_NAME = 'saved_action_approvals'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SavedAction**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action'

str – Name of object used in API calls.

API_NAME_SRC = 'saved_action'

str – Name of object in source file.

API_SIMPLE = {'action_group_id': (<class 'int'>,), 'approved_flag': (<class 'int'>,)

dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.rest_7_3_314_3641.Group'>,

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SavedActionList*

API_LIST_API_NAME = 'saved_actions'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Sensor**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor'

str – Name of object used in API calls.

API_NAME_SRC = 'sensor'

str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'category': (<class 'str'>,), 'creat

dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3641.IdReferenc

dict – Map of complex attributes to their types.

API_CONSTANTS = {'BES_DATETIME_RESULT': 4, 'BES_SENSOR': 2, 'DATASIZE_RESULT': 8, 'HAS

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SensorList*

API_LIST_API_NAME = 'sensors'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**AuditData**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'audit_data'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'creation_time': (<class 'str'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'mod_user': <class 'pytan3.api_objects.rest_7_3_314_3641.User'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditDataList*

API_LIST_API_NAME = 'audit_datas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**AuditLog**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'audit_log'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log'
str – Name of object in source file.

API_SIMPLE = {'creation_time': (<class 'str'>,), 'details': (<class 'str'>,), 'end_t
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditLogList*

API_LIST_API_NAME = 'audit_logs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Server**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'server'
str – Name of object used in API calls.

API_NAME_SRC = 'server'
str – Name of object in source file.

API_SIMPLE = {'heart_beat': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerList*

API_LIST_API_NAME = 'servers'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**MetadataItem**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'metadata_item'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_item'
str – Name of object in source file.

API_SIMPLE = {'admin_flag': (<class 'int'>,), 'name': (<class 'str'>,), 'value': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *MetadataList*

API_LIST_API_NAME = 'metadatas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Filter**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'filter'
str – Name of object used in API calls.

API_NAME_SRC = 'filter'
str – Name of object in source file.

API_SIMPLE = {'aggregation': (<class 'str'>,), 'all_times_flag': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'sensor': <class 'pytan3.api_objects.rest_7_3_314_3641.Sensor'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *FilterList*

API_LIST_API_NAME = 'filters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**IdReference**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'id_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'id_reference'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Group**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'group'
str – Name of object used in API calls.

API_NAME_SRC = 'group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'filters': <class 'pytan3.api_objects.rest_7_3_314_3641.FilterList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *GroupList*

API_LIST_API_NAME = 'groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Select**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'select'
str – Name of object used in API calls.

API_NAME_SRC = 'select'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'filter': <class 'pytan3.api_objects.rest_7_3_314_3641.Filter'>, 'grou
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SelectList*

API_LIST_API_NAME = 'selects'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**XmlError**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'xml_error'
str – Name of object used in API calls.

API_NAME_SRC = 'xml_error'
str – Name of object in source file.

API_SIMPLE = {'error_context': (<class 'str'>,), 'exception': (<class 'str'>,), 'typ
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ErrorList*

API_LIST_API_NAME = 'errors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**CacheInfo**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'cache_info'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_info'
str – Name of object in source file.

API_SIMPLE = {'cache_id': (<class 'int'>,), 'cache_row_count': (<class 'int'>,), 'exp
dict – Map of simple attributes to their types.

API_COMPLEX = {'errors': <class 'pytan3.api_objects.rest_7_3_314_3641.ErrorList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**QuestionListInfo**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'question_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Question**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'question'
str – Name of object used in API calls.

API_NAME_SRC = 'question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'cache_row_id': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'context_group': <class 'pytan3.api_objects.rest_7_3_314_3641.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *QuestionList*

API_LIST_API_NAME = 'questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**PackageFileTemplate**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_template'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template'
str – Name of object in source file.

API_SIMPLE = {'download_seconds': (<class 'int'>,), 'hash': (<class 'str'>,), 'name'
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileTemplateList*

API_LIST_API_NAME = 'package_file_templates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**PackageFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileStatusList*

API_LIST_API_NAME = 'package_file_statuss'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**PackageFile**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_file'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_status': <class 'pytan3.api_objects.rest_7_3_314_3641.PackageFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileList*

API_LIST_API_NAME = 'package_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**PackageSpec**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_spec'

str – Name of object used in API calls.

API_NAME_SRC = 'package_spec'

str – Name of object in source file.

API_SIMPLE = {'available_time': (<class 'str'>,), 'cache_row_id': (<class 'int'>,),

dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3641.IdReferenc

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *PackageSpecList*

API_LIST_API_NAME = 'package_specs'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ClientStatus**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'client_status'

str – Name of object used in API calls.

API_NAME_SRC = 'client_status'

str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'computer_id': (<class 'str'>,), 'fu

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SystemStatusList*

API_LIST_API_NAME = 'system_status'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SystemSetting**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'system_setting'
`str` – Name of object used in API calls.

API_NAME_SRC = 'system_setting'
`str` – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'default_value': (<class 'str'>,), '
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'audit_data': <class 'pytan3.api_objects.rest_7_3_314_3641.AuditData'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemSettingList*

API_LIST_API_NAME = 'system_settings'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SoapError**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'soap_error'
`str` – Name of object used in API calls.

API_NAME_SRC = 'soap_error'
`str` – Name of object in source file.

API_SIMPLE = {'context': (<class 'str'>,), 'exception_name': (<class 'str'>,), 'obje
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**WhiteListedUrl**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'white_listed_url'
`str` – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url'
str – Name of object in source file.

API_SIMPLE = {'chunk_id': (<class 'str'>,), 'download_seconds': (<class 'int'>,), 'e
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3641.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *WhiteListedUrlList*

API_LIST_API_NAME = 'white_listed_urls'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**VersionAggregate**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'version_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'filtered': (<class 'int'>,), 'version_stri
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *VersionAggregateList*

API_LIST_API_NAME = 'version_aggregates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SystemStatusAggregate**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'system_status_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_aggregate'
str – Name of object in source file.

API_SIMPLE = {'blocked_count': (<class 'int'>,), 'leader_count': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'versions': <class 'pytan3.api_objects.rest_7_3_314_3641.VersionAggrega
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**UserRole**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'user_role'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'permissions': <class 'pytan3.api_objects.rest_7_3_314_3641.Permission
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserRoleList*

API_LIST_API_NAME = 'roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**UserOwnedObjectIds**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'user_owned_object_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'user_owned_object_ids'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'plugin_schedules': <class 'pytan3.api_objects.rest_7_3_314_3641.Plugi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**User**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'user'
str – Name of object used in API calls.

API_NAME_SRC = 'user'
str – Name of object in source file.

API_SIMPLE = {'active_session_count': (<class 'int'>,), 'deleted_flag': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.rest_7_3_314_3641.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserList*

API_LIST_API_NAME = 'users'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ActionListInfo**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'action_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Action**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action'
str – Name of object used in API calls.

API_NAME_SRC = 'action'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'comment': (<class 'str'>,), 'creati
dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.rest_7_3_314_3641.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionList*

API_LIST_API_NAME = 'actions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ActionStop**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action_stop'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.rest_7_3_314_3641.Action'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionStopList*

API_LIST_API_NAME = 'action_stops'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ArchivedQuestion**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'archived_question'
str – Name of object used in API calls.

API_NAME_SRC = 'archived_question'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ArchivedQuestionList*

API_LIST_API_NAME = 'archived_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SavedQuestion**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'archive_enabled_flag': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'archive_owner': <class 'pytan3.api_objects.rest_7_3_314_3641.User'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionList*

API_LIST_API_NAME = 'saved_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ParseJob**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parse_job'

str – Name of object used in API calls.

API_NAME_SRC = 'parse_job'

str – Name of object in source file.

API_SIMPLE = {'parser_version': (<class 'int'>,), 'question_text': (<class 'str'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ParseJobList*

API_LIST_API_NAME = 'parse_jobs'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Parameter**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parameter'

str – Name of object used in API calls.

API_NAME_SRC = 'parameter'

str – Name of object in source file.

API_SIMPLE = {'key': (<class 'str'>,), 'type': (<class 'int'>,), 'value': (<class '

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ParameterList*

API_LIST_API_NAME = 'parameters'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ParseResult**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parse_result'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'parameter_definition': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'parameters': <class 'pytan3.api_objects.rest_7_3_314_3641.ParameterLi
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultList*

API_LIST_API_NAME = 'parse_results'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SensorReference**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_reference'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference'
`str` – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'real_ms_avg': (<class 'int'>,), 'start_char
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorReferenceList*

API_LIST_API_NAME = 'sensor_references'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ParseResultGroup**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result_group'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group'
str – Name of object in source file.

API_SIMPLE = {'question_text': (<class 'str'>,), 'score': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameter_values': <class 'pytan3.api_objects.rest_7_3_314_3641.Param
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultGroupList*

API_LIST_API_NAME = 'parse_result_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ClientCount**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'client_count'
str – Name of object used in API calls.

API_NAME_SRC = 'client_count'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**PluginArgument**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_argument'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'type': (<class 'str'>,), 'value': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginArgumentList*

API_LIST_API_NAME = 'plugin_arguments'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**UploadFile**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file'
str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'destination_file': (<class 'str'>,), 'file_
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UploadFileList*

API_LIST_API_NAME = 'upload_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**UploadFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_status'
str – Name of object in source file.

API_SIMPLE = {'file_cached': (<class 'int'>,), 'hash': (<class 'str'>,), 'percent_co
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_parts': <class 'pytan3.api_objects.rest_7_3_314_3641.UploadFileL
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Plugin**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'plugin'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin'
str – Name of object in source file.

API_SIMPLE = {'allow_rest': (<class 'int'>,), 'bundle': (<class 'str'>,), 'cache_row_
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.rest_7_3_314_3641.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {'SCRIPT': 'Script', 'SQL': 'SQL'}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginList*

API_LIST_API_NAME = 'plugins'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**PluginSchedule**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_schedule'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'enabled': (<class 'int'>,), 'end_da
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.rest_7_3_314_3641.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginScheduleList*

API_LIST_API_NAME = 'plugin_schedules'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ComputerGroupSpec**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_spec'
str – Name of object in source file.

API_SIMPLE = {'computer_name': (<class 'str'>,), 'id': (<class 'int'>,), 'ip_address
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ComputerSpecList*

API_LIST_API_NAME = 'computer_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ComputerGroup**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<c
dict – Map of simple attributes to their types.

API_COMPLEX = {'computer_specs': <class 'pytan3.api_objects.rest_7_3_314_3641.Compute
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ComputerGroupList*

API_LIST_API_NAME = 'computer_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**VerifySignature**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'verify_signature'
str – Name of object used in API calls.

API_NAME_SRC = 'verify_signature'
str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'id': (<class 'int'>,), 'type': (<class 's
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ObjectList**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'object_list'
str – Name of object used in API calls.

API_NAME_SRC = 'object_list'
str – Name of object in source file.

API_SIMPLE = {'export_id': (<class 'str'>,), 'export_version': (<class 'int'>,), 'im
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.rest_7_3_314_3641.Action'>, 'acti
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ImportConflictDetail**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'import_conflict_detail'

str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail'

str – Name of object in source file.

API_SIMPLE = {'diff': (<class 'str'>,), 'is_new': (<class 'int'>,), 'name': (<class

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ImportConflictDetailList*

API_LIST_API_NAME = 'import_conflict_details'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**CacheFilter**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'cache_filter'

str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter'

str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'field': (<class 'str'>,), 'not_flag':

dict – Map of simple attributes to their types.

API_COMPLEX = {'sub_filters': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheFilte

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *CacheFilterList*

API_LIST_API_NAME = 'cache_filters'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Options**(***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'options'
str – Name of object used in API calls.

API_NAME_SRC = 'options'
str – Name of object in source file.

API_SIMPLE = {'aggregate_by_value_flag': (<class 'int'>,), 'aggregate_over_time_flag'
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_filters': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSet**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3641.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetList*

API_LIST_API_NAME = 'content_sets'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRolePrivilegeOnRole**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege_on_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3641.IdReferenc
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeOnRoleList*

API_LIST_API_NAME = 'content_set_role_privilege_on_roles'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRole**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role'
`str` – Name of object in source file.

API_SIMPLE = {'all_content_sets_flag': (<class 'int'>,), 'category': (<class 'str'>,
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role_privileges': <class 'pytan3.api_objects.rest_7_3_314
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleList*

API_LIST_API_NAME = 'content_set_roles'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_membership'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.rest_7_3_314_3641.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleMembershipList*

API_LIST_API_NAME = 'content_set_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetUserGroupRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_user_group_role_membership'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.rest_7_3_314_3641.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetUserGroupRoleMembershipList*

API_LIST_API_NAME = 'content_set_user_group_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'privilege_module':
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.rest_7_3_314_3641.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetPrivilegeList*

API_LIST_API_NAME = 'content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRolePrivilege**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3641.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeList*

API_LIST_API_NAME = 'content_set_role_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**EffectiveContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'effective_content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3641.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *EffectiveContentSetPrivilegeList*

API_LIST_API_NAME = 'effective_content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Dashboard**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'public_flag': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3641.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *DashboardList*

API_LIST_API_NAME = 'dashboards'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**DashboardGroup**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard_group'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_group'
str – Name of object in source file.

API_SIMPLE = {'display_index': (<class 'int'>,), 'editable_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.rest_7_3_314_3641.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**UserGroup**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'user_group'
str – Name of object used in API calls.

API_NAME_SRC = 'user_group'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'exclusive_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.rest_7_3_314_3641.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserGroupList*

API_LIST_API_NAME = 'user_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**Solution**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'solution'
str – Name of object used in API calls.

API_NAME_SRC = 'solution'
str – Name of object in source file.

API_SIMPLE = {'category': (<class 'str'>,), 'delete_xml_url': (<class 'str'>,), 'dele
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SolutionList*

API_LIST_API_NAME = 'solutions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ActionGroup**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action_group'
str – Name of object used in API calls.

API_NAME_SRC = 'action_group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'groups': <class 'pytan3.api_objects.rest_7_3_314_3641.GroupList'>, 'u
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionGroupList*

API_LIST_API_NAME = 'action_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SavedQuestionPackageSpecs**(**kwargs)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_package_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_package_specs'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'packages': <class 'pytan3.api_objects.rest_7_3_314_3641.PackageSpecLi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SavedQuestionQuestion**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_question'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'questions': <class 'pytan3.api_objects.rest_7_3_314_3641.QuestionList
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionQuestionList*

API_LIST_API_NAME = 'saved_question_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**LdapSyncConnector**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'ldap_sync_connector'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector'
str – Name of object in source file.

API_SIMPLE = {'base_groups': (<class 'str'>,), 'base_users': (<class 'str'>,), 'disa
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *LdapSyncConnectorList*

API_LIST_API_NAME = 'ldap_sync_connectors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ServerThrottle**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle'

str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle'

str – Name of object in source file.

API_SIMPLE = {'bandwidth_bytes_limit': (<class 'int'>,), 'connection_limit': (<class

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ServerThrottleList*

API_LIST_API_NAME = 'server_throttles'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottle**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle'

str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle'

str – Name of object in source file.

API_SIMPLE = {'all_subnets_flag': (<class 'int'>,), 'bandwidth_bytes_limit': (<class

dict – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSu

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SiteThrottleList*

API_LIST_API_NAME = 'site_throttles'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottleSubnet**(**kwargs)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet'
`str` – Name of object in source file.

API_SIMPLE = {'range': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetList*

API_LIST_API_NAME = 'site_throttle_subnets'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**ServerThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle_status'
`str` – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status'
`str` – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'id': (<class '
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerThrottleStatusList*

API_LIST_API_NAME = 'server_throttle_statuses'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSu
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleStatusList*

API_LIST_API_NAME = 'site_throttles_statuses'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottleSubnetStatus**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status'
str – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'queue_delay_mil
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetStatusList*

API_LIST_API_NAME = 'site_throttle_subnet_statuss'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**HashedString**(***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'hashed_string'
str – Name of object used in API calls.

API_NAME_SRC = 'hashed_string'
str – Name of object in source file.

API_SIMPLE = {'collision_flag': (<class 'int'>,), 'error_flag': (<class 'int'>,), 'f
dict – Map of simple attributes to their types.

API_COMPLEX = {'first_computer_id': <class 'pytan3.api_objects.rest_7_3_314_3641.Comp
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *HashedStringList*

API_LIST_API_NAME = 'hashed_strings'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.rest_7_3_314_3641.**SensorQueryList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_querys'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'query'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorQuery*

class pytan3.api_objects.rest_7_3_314_3641.**SensorSubcolumnList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_subcolumns'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subcolumn'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorSubcolumn*

class pytan3.api_objects.rest_7_3_314_3641.**StringHintList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'string_hints'
str – Name of object used in API calls.

API_NAME_SRC = 'string_hint_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'string_hint'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**SensorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensors'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Sensor*

class pytan3.api_objects.rest_7_3_314_3641.**SensorStatList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_stats'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_stat'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorStat*

class pytan3.api_objects.rest_7_3_314_3641.**SavedActionApprovalList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_approvals'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action_approval'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedActionApproval*

class pytan3.api_objects.rest_7_3_314_3641.**SavedActionRowIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_row_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_row_id_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**SavedActionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_actions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedAction*

class pytan3.api_objects.rest_7_3_314_3641.**AuditDataList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'audit_datas'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'entry'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditData*

class pytan3.api_objects.rest_7_3_314_3641.**AuditLogList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'audit_logs'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log_list'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'type': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'entries'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditLog*

class pytan3.api_objects.rest_7_3_314_3641.**ServerList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'servers'
str – Name of object used in API calls.

API_NAME_SRC = 'server_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Server*

class pytan3.api_objects.rest_7_3_314_3641.**ServerHost**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_host'
str – Name of object used in API calls.

API_NAME_SRC = 'server_host'
str – Name of object in source file.

API_SIMPLE = {'heart_beat_age_in_minute': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'servers'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerList*

class pytan3.api_objects.rest_7_3_314_3641.**ServerHostList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_hosts'

str – Name of object used in API calls.

API_NAME_SRC = 'server_host_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_host'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ServerHost*

class pytan3.api_objects.rest_7_3_314_3641.**MetadataList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'metadatas'

str – Name of object used in API calls.

API_NAME_SRC = 'metadata_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'item'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *MetadataItem*

class pytan3.api_objects.rest_7_3_314_3641.**GroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'groups'

str – Name of object used in API calls.

API_NAME_SRC = 'group_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'group'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Group*

class pytan3.api_objects.rest_7_3_314_3641.**FilterList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'filters'

str – Name of object used in API calls.

API_NAME_SRC = 'filter_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Filter*

class pytan3.api_objects.rest_7_3_314_3641.**SelectList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'selects'
str – Name of object used in API calls.

API_NAME_SRC = 'select_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'select'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Select*

class pytan3.api_objects.rest_7_3_314_3641.**ErrorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'errors'
str – Name of object used in API calls.

API_NAME_SRC = 'error_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'error'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *XmlError*

class pytan3.api_objects.rest_7_3_314_3641.**QuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'questions'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Question*

class pytan3.api_objects.rest_7_3_314_3641.**PackageFileTemplateList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_templates'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file_template'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileTemplate*

class pytan3.api_objects.rest_7_3_314_3641.**PackageFileStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_statuss'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileStatus*

class pytan3.api_objects.rest_7_3_314_3641.**PackageFileList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_files'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFile*

class pytan3.api_objects.rest_7_3_314_3641.**PackageSpecList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'package_spec'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageSpec*

class pytan3.api_objects.rest_7_3_314_3641.**WhiteListedUrlList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'white_listed_urls'
str – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'white_listed_url'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *WhiteListedUrl*

class pytan3.api_objects.rest_7_3_314_3641.**VersionAggregateList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'version_aggregates'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'version'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *VersionAggregate*

class pytan3.api_objects.rest_7_3_314_3641.**SystemStatusList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'system_status'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'aggregate': <class 'pytan3.api_objects.rest_7_3_314_3641.SystemStatusA
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'client_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ClientStatus*

class pytan3.api_objects.rest_7_3_314_3641.**SystemSettingList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'system_settings'
str – Name of object used in API calls.

API_NAME_SRC = 'system_setting_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'system_setting'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SystemSetting*

class pytan3.api_objects.rest_7_3_314_3641.**UserList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'users'
str – Name of object used in API calls.

API_NAME_SRC = 'user_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.rest_7_3_314_3641.**PermissionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'permissions'
str – Name of object used in API calls.

API_NAME_SRC = 'permission_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {'ACTION_APPROVE': 'action_approval', 'ACTION_READ': 'action_read', 'A
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'permission'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**UserRoleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'roles'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'role'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UserRole*

class pytan3.api_objects.rest_7_3_314_3641.**ActionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'actions'
str – Name of object used in API calls.

API_NAME_SRC = 'action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Action*

class pytan3.api_objects.rest_7_3_314_3641.**ActionStopList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'action_stops'
`str` – Name of object used in API calls.

API_NAME_SRC = 'action_stop_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_stop'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionStop*

class pytan3.api_objects.rest_7_3_314_3641.**ArchivedQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'archived_questions'
`str` – Name of object used in API calls.

API_NAME_SRC = 'archived_question_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'archived_question'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ArchivedQuestion*

class pytan3.api_objects.rest_7_3_314_3641.**SavedQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestion*

class pytan3.api_objects.rest_7_3_314_3641.**ParseJobList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parse_jobs'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_job_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_job'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseJob*

class pytan3.api_objects.rest_7_3_314_3641.**ParseResultGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parse_result_groups'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result_group'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResultGroup*

class pytan3.api_objects.rest_7_3_314_3641.**ParseResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parse_results'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parse_result_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResult*

class pytan3.api_objects.rest_7_3_314_3641.**ParameterList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parameters'

str – Name of object used in API calls.

API_NAME_SRC = 'parameter_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parameter'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Parameter*

class pytan3.api_objects.rest_7_3_314_3641.**ParameterValueList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parameter_values'

str – Name of object used in API calls.

API_NAME_SRC = 'parameter_value_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)

ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**SensorReferenceList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_references'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_reference'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorReference*

class pytan3.api_objects.rest_7_3_314_3641.**PluginArgumentList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_arguments'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'argument'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginArgument*

class pytan3.api_objects.rest_7_3_314_3641.**PluginSqlResultList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_results'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_result_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**PluginSqlColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_columns'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_column_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'name'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**PluginSql**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql'
`str` – Name of object in source file.

API_SIMPLE = {'result_count': (<class 'int'>,), 'rows_affected': (<class 'int'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'columns': <class 'pytan3.api_objects.rest_7_3_314_3641.PluginSqlColum
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_row'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSqlResultList*

class pytan3.api_objects.rest_7_3_314_3641.**PluginCommandList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_commands'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_command_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'command'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**UploadFileList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'upload_files'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'upload_file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UploadFile*

class pytan3.api_objects.rest_7_3_314_3641.**PluginList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugins'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Plugin*

class pytan3.api_objects.rest_7_3_314_3641.**PluginScheduleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_schedules'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin_schedule'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSchedule*

class pytan3.api_objects.rest_7_3_314_3641.**ComputerSpecList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'computer_specs'
`str` – Name of object used in API calls.

API_NAME_SRC = 'computer_spec_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_spec'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroupSpec*

class pytan3.api_objects.rest_7_3_314_3641.**ComputerGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'computer_groups'
`str` – Name of object used in API calls.

API_NAME_SRC = 'computer_group_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.rest_7_3_314_3641.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_group'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroup*

class pytan3.api_objects.rest_7_3_314_3641.**ImportConflictDetailList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_details'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_detail'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ImportConflictDetail*

class pytan3.api_objects.rest_7_3_314_3641.**CacheFilterList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'cache_filters'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *CacheFilter*

class pytan3.api_objects.rest_7_3_314_3641.**ImportConflictOptions**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_options'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_options'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_option'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_sets'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSet*

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRolePrivilegeOnRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privilege_on_roles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilegeOnRole*

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_roles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRole*

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_memberships'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_membership'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRoleMembership*

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetUserGroupRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_user_group_role_memberships'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_user_group_role_membership'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetUserGroupRoleMembership*

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetPrivilege*

class pytan3.api_objects.rest_7_3_314_3641.**ContentSetRolePrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilege*

class pytan3.api_objects.rest_7_3_314_3641.**EffectiveContentSetPrivilegeRequest**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privilege_request'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_request'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.rest_7_3_314_3641.**EffectiveContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'effective_content_set_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *EffectiveContentSetPrivilege*

class pytan3.api_objects.rest_7_3_314_3641.**DashboardList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'dashboards'

str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'dashboard'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Dashboard*

class pytan3.api_objects.rest_7_3_314_3641.**UserGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'user_groups'

str – Name of object used in API calls.

API_NAME_SRC = 'user_group_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user_group'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *UserGroup*

class pytan3.api_objects.rest_7_3_314_3641.**SolutionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'solutions'
`str` – Name of object used in API calls.

API_NAME_SRC = 'solution_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'solution'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Solution*

class pytan3.api_objects.rest_7_3_314_3641.**ActionGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'action_groups'
`str` – Name of object used in API calls.

API_NAME_SRC = 'action_group_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_group'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionGroup*

class pytan3.api_objects.rest_7_3_314_3641.**SavedQuestionQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_question_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestionQuestion*

class pytan3.api_objects.rest_7_3_314_3641.**LdapSyncConnectorList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'ldap_sync_connectors'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'ldap_sync_connector'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *LdapSyncConnector*

class pytan3.api_objects.rest_7_3_314_3641.**ServerThrottleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttles'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottle*

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottle*

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottleSubnetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnets'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_list'
`str` – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnet*

class pytan3.api_objects.rest_7_3_314_3641.**ServerThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttle_statuses'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottleStatus*

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles_statuses'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleStatus*

class pytan3.api_objects.rest_7_3_314_3641.**SiteThrottleSubnetStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnet_statuss'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnetStatus*

class pytan3.api_objects.rest_7_3_314_3641.**ComputerIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'computer_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_id_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.rest_7_3_314_3641.**HashedStringList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.rest_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'hashed_strings'
str – Name of object used in API calls.

API_NAME_SRC = 'hashed_string_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'hashed_string'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *HashedString*

pytan3.api_objects.rest_7_3_314_3641.**BUILD_META = {'date': '2019-02-22 07:46:08.408656',**
dict – How this module was built (date/time in UTC format).

pytan3.api_objects.rest_7_3_314_3641.**COMMANDS = ['AddObject', 'GetObject', 'MoveObject', '**
list of str – API commands.

pytan3.api_objects.rest_7_3_314_3641.**VERSION = {'build': 3641, 'major': 7, 'minor': 3,**
dict – Tanium API version these objects are intended to be used for.

SOAP API Object Modules

SOAP API Object Module for Version 7.2.314.3181

Python objects for Tanium's API.

pytan3.api_objects.soap_7_2_314_3181.**float_types = (<class 'float'>,)**
tuple of type – Float types.

pytan3.api_objects.soap_7_2_314_3181.**integer_types = (<class 'int'>,)**
tuple of type – Integer types.

pytan3.api_objects.soap_7_2_314_3181.**string_types = (<class 'str'>,)**
tuple of type – String types.

pytan3.api_objects.soap_7_2_314_3181.**simple_types = (<class 'int'>, <class 'str'>, <class**
tuple of type – All types that should be considered simple types.

pytan3.api_objects.soap_7_2_314_3181.**TYPE = 'soap'**
str – Type of API this module was built from.

pytan3.api_objects.soap_7_2_314_3181.**API_DT = '%Y-%m-%dT%H:%M:%S'**
str – Datetime format for this API type and version.

pytan3.api_objects.soap_7_2_314_3181.**api_fixes**()
Fix incorrect attribute definitions on auto generated ApiModel classes.

pytan3.api_objects.soap_7_2_314_3181.**expand_cls_globals**()
Replace str values with global vars for attrs on ApiModel classes.

Quite the funky chicken dance for solving issues with order of class definition.

pytan3.api_objects.soap_7_2_314_3181.**expand_global**(*obj*)
Replace str values with global vars recursively.

Parameters **obj** (str or dict or list) – Object to expand into global var.

Returns String objects are the only ones that will be expanded.

Return type str or dict or list or object

pytan3.api_objects.soap_7_2_314_3181.**get_api_all_item**()
Get map of class name to class for all ApiItem subclasses.

Returns dict

pytan3.api_objects.soap_7_2_314_3181.**get_api_all_list**()
Get map of class name to class for all ApiList subclasses.

Returns dict

pytan3.api_objects.soap_7_2_314_3181.**get_api_all_model**()
Get map of class name to class for all ApiItem and ApiList subclasses.

Returns dict

class pytan3.api_objects.soap_7_2_314_3181.**ApiModel**
Bases: *pytan3.api_models.ApiModel*

Model for a complex item in the API.

class pytan3.api_objects.soap_7_2_314_3181.**ApiItem**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiModel*, *pytan3.api_models.ApiItem*

Model for a complex item in the API.

class pytan3.api_objects.soap_7_2_314_3181.**ApiList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiModel*, *pytan3.api_models.ApiList*

Model for an array in the API.

class pytan3.api_objects.soap_7_2_314_3181.**ResultInfoList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Manually defined API array object.

API_NAME = 'result_infos'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'int'>,), 'now': (<class 'str'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_info'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ResultInfo*

__repr__()

Make repr output be same as str output.

Returns str

class pytan3.api_objects.soap_7_2_314_3181.**ResultInfo**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Manually defined API object.

API_NAME = 'result_info'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'er

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'row_count', 'mr_tested', 'mr_passed'

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ResultInfoList*

API_LIST_API_NAME = 'result_infos'
str – Name of *API_LIST_CLS* used in API calls.

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.soap_7_2_314_3181.**ResultSetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Manually defined API array object.

API_NAME = 'result_sets'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_set'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ResultSet*

class pytan3.api_objects.soap_7_2_314_3181.**MergedResultSet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Manually defined API object.

API_NAME = 'merged_result'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'str'>,), 'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'result_infos': <class 'pytan3.api_objects.soap_7_2_314_3181.ResultInf
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ResultSet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Manually defined API object.

API_NAME = 'result_set'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'ca
dict – Map of simple attributes to their types.

API_COMPLEX = {'cs': <class 'pytan3.api_objects.soap_7_2_314_3181.ColumnList'>, 'rs':
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'mr_tested', 'mr_passed', 'row_count'
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultSetList*

API_LIST_API_NAME = 'result_sets'
str – Name of *API_LIST_CLS* used in API calls.

__init__(***kwargs*)
Constructor.

Notes

Sets *Column.API_DATA_SET* so column objects can access rows.

Sets *RowColumn.API_COLUMN* to the index correlated *Column* so row columns can access the column name, result type, etc.

Sets *Column.API_IDX* and *RowColumn.API_IDX* so column objects know what their index is without having to do lookups.

Parameters ****kwargs** – Passed back to parent class.

rows
Expose complex attr "rs" as "rows".

Returns list

columns
Expose complex attr "cs" as "columns".

Returns list

class pytan3.api_objects.soap_7_2_314_3181.**ColumnList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Manually defined API array object.

API_NAME = 'cs'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = ['names']
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'c'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Column*

__repr__()
Make repr output be same as str output.

Returns `str`

names
Expose column names of all *Column* in this obj.

Returns `list` of `str`

__getitem__(*value*)
Support indexing of *names*.

Parameters **value** (`int` or `str`) – If int: Index of item to retrieve from simple attr "c". If str: Column name to index correlate from *names*

Returns The RowColumn object at index value from *names*.

Return type *RowColumn*

class pytan3.api_objects.soap_7_2_314_3181.**Column**(****kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Manually defined API object.

API_DATA_SET = None
ResultSet – Parent of this object, set by *ResultSet.__init__()*.

API_IDX = None
`int` – Index of this object in *ColumnList*.

API_NAME = 'c'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {'dn': (<class 'str'>,), 'rt': (<class 'int'>,), 'wh': (<class 'int'>,
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['name', 'result_type', 'hash']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ColumnList*

API_LIST_API_NAME = 'cs'
str – Name of *API_LIST_CLS* used in API calls.

name
Expose simple attr "dn" as name.

Returns str

hash
Expose simple attr "wh" as hash.

Returns str

type
Expose simple attr "rt" as type.

Returns str

result_type
Expose simple attr "rt" as result_type.

Notes

Will try to map str from "rt" as int to constants from *Sensor.API_CONSTANTS*.

Returns str

get_values(*attr='value', join=None*)
Get values of this column from all rows.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list of str

class pytan3.api_objects.soap_7_2_314_3181.**RowList**(**args, **kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Manually defined API array object.

API_NAME = 'rs'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'r'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Row*

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.soap_7_2_314_3181.**Row**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Manually defined API object.

API_NAME = 'r'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'cid': (<class 'int'>,), 'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'c': <class 'pytan3.api_objects.soap_7_2_314_3181.RowColumnList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['id', 'cid', 'columns']
list or str – Attributes to add to str formatting.

API_LIST_API_NAME = 'rs'
str – Name of *API_LIST_CLS* used in API calls.

API_LIST_CLS
ApiItem: Item class this list class holds.

alias of *RowList*

__repr__()
Make repr output be same as str output.

Returns str

__getitem__(*value*)

Support indexing of *names*.

Parameters **value** (int or str) – If int: Index of item to retrieve from *names*. If str: Column name to index correlate from *ColumnList.names*

Returns The RowColumn object at index value from *names*.

Return type *RowColumn*

names

Return the names of each row column from *RowColumn.API_COLUMN*.

Returns list of str

columns

Expose complex attr "c" as "columns".

Returns *RowColumnList*

__len__()

Expose length of *columns*.

Returns int

get_values(*meta=False*, *hashes=False*, *join=None*)

Get all values from all columns in this row.

Parameters

- **meta** (bool, optional) – Include sensor hash and result type for each column.

  Defaults to: False.

- **hashes** (bool, optional) – Include hashes of values.

  Defaults to: False.

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns dict

class pytan3.api_objects.soap_7_2_314_3181.**RowColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Manually defined API array object.

API_NAME = 'rc'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_columns'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *RowColumn*

api_coerce_items_hook (*attr*, *value*, *op*)
Check hook that allows subclasses to modify list items.

Parameters

- **attr** (`str`) – Attribute being set on this object.
- **value** (*ApiList* or `list` or `tuple`) – The list object holding items.
- **op** (`str`) – Operation being performed that called this method.

Examples

This converts all "v" attributes of each column for this row into a list of dicts:

```
>>> # single value columns "v" is a single dict:
>>> {"v": {"h": "", "text": ""}}
>>> # multiple value columns "v" is a list of dict:
>>> {"v": [{"h": "", "text": ""}, {"h": "", "text": ""}]}
>>> # Count columns "v" is a string:
>>> {"v": "1"}
>>> # all become:
>>> {"v": [{"text": "", "hash": ""}]}
```

Notes

The driving force behind this is basically just the Count column. It returns a string of the value, instead of a dict or a list of dicts.

Returns The list of items modified or as is.

Return type `list`

class pytan3.api_objects.soap_7_2_314_3181.**RowColumn** (**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Manually defined API array object.

API_COLUMN = None
Column – Index correlated column, set by *ResultSet.__init__()*.

API_IDX = None
`int` – Index of this object in *RowColumnList*.

API_NAME = 'row_column'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['name', 'hash', 'result_type']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'v'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *RowValue*

name
Expose column name from *API_COLUMN*.

Returns str

result_type
Expose column result type from *API_COLUMN*.

Returns str

hash
Expose column sensor hash from *API_COLUMN*.

Returns str

get_values(*attr='value'*, *join=None*)
Get all values from this row column.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list or str

class pytan3.api_objects.soap_7_2_314_3181.**RowValue**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Manually defined API object.

API_NAME = 'v'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'h': (<class 'int'>,), 'text': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['hash', 'value']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *RowColumn*

API_LIST_API_NAME = 'row_column'
str – Name of *API_LIST_CLS* used in API calls.

hash
Expose simple attr "h" as hash.

Returns str

value
Expose simple attr "text" as value.

Returns str

class pytan3.api_objects.soap_7_2_314_3181.**SensorQuery**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_query'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query'
str – Name of object in source file.

API_SIMPLE = {'platform': (<class 'str'>,), 'script': (<class 'str'>,), 'script_type
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorQueryList*

API_LIST_API_NAME = 'sensor_querys'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SensorSubcolumn**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_subcolumn'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn'
`str` – Name of object in source file.

API_SIMPLE = {'exclude_from_parse_flag': (<class 'int'>,), 'hidden_flag': (<class 'i
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorSubcolumnList*

API_LIST_API_NAME = 'sensor_subcolumns'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SensorStat**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_stat'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat'
`str` – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<class 's
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorStatList*

API_LIST_API_NAME = 'sensor_stats'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SavedActionPolicy**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_policy'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_action_policy'
`str` – Name of object in source file.

API_SIMPLE = {'max_age': (<class 'int'>,), 'min_count': (<class 'int'>,), 'row_filte
dict – Map of simple attributes to their types.

API_COMPLEX = {'row_filter_group': <class 'pytan3.api_objects.soap_7_2_314_3181.Group
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SavedActionApproval**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_approval'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval'
str – Name of object in source file.

API_SIMPLE = {'approved_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_2_314_3181.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionApprovalList*

API_LIST_API_NAME = 'saved_action_approvals'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SavedAction**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action'
str – Name of object in source file.

API_SIMPLE = {'action_group_id': (<class 'int'>,), 'approved_flag': (<class 'int'>,)
dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.soap_7_2_314_3181.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionList*

API_LIST_API_NAME = 'saved_actions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Sensor**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'sensor'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'category': (<class 'str'>,), 'creat
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_2_314_3181.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {'BES_DATETIME_RESULT': 4, 'BES_SENSOR': 2, 'DATASIZE_RESULT': 8, 'HAS
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorList*

API_LIST_API_NAME = 'sensors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**AuditData**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'audit_data'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'creation_time': (<class 'str'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'mod_user': <class 'pytan3.api_objects.soap_7_2_314_3181.User'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditDataList*

API_LIST_API_NAME = 'audit_datas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**AuditLog**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'audit_log'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'type': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'entries': <class 'pytan3.api_objects.soap_7_2_314_3181.AuditDataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditLogList*

API_LIST_API_NAME = 'audit_logs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**MetadataItem**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'metadata_item'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_item'
str – Name of object in source file.

API_SIMPLE = {'admin_flag': (<class 'int'>,), 'name': (<class 'str'>,), 'value': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *MetadataList*

API_LIST_API_NAME = 'metadatas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Filter**(**kwargs)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'filter'
str – Name of object used in API calls.

API_NAME_SRC = 'filter'
str – Name of object in source file.

API_SIMPLE = {'aggregation': (<class 'str'>,), 'all_times_flag': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'sensor': <class 'pytan3.api_objects.soap_7_2_314_3181.Sensor'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *FilterList*

API_LIST_API_NAME = 'filters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**IdReference**(**kwargs)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'id_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'id_reference'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Group**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'group'
str – Name of object used in API calls.

API_NAME_SRC = 'group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'filters': <class 'pytan3.api_objects.soap_7_2_314_3181.FilterList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *GroupList*

API_LIST_API_NAME = 'groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Select**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'select'
str – Name of object used in API calls.

API_NAME_SRC = 'select'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'filter': <class 'pytan3.api_objects.soap_7_2_314_3181.Filter'>, 'grou
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SelectList*

API_LIST_API_NAME = 'selects'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**XmlError**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'xml_error'

str – Name of object used in API calls.

API_NAME_SRC = 'xml_error'

str – Name of object in source file.

API_SIMPLE = {'error_context': (<class 'str'>,), 'exception': (<class 'str'>,), 'typ

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ErrorList*

API_LIST_API_NAME = 'errors'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**CacheInfo**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'cache_info'

str – Name of object used in API calls.

API_NAME_SRC = 'cache_info'

str – Name of object in source file.

API_SIMPLE = {'cache_id': (<class 'int'>,), 'cache_row_count': (<class 'int'>,), 'ex

dict – Map of simple attributes to their types.

API_COMPLEX = {'errors': <class 'pytan3.api_objects.soap_7_2_314_3181.ErrorList'>}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**QuestionListInfo**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'question_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Question**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'question'
str – Name of object used in API calls.

API_NAME_SRC = 'question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'cache_row_id': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'context_group': <class 'pytan3.api_objects.soap_7_2_314_3181.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *QuestionList*

API_LIST_API_NAME = 'questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**PackageFileTemplate**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_template'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template'
str – Name of object in source file.

API_SIMPLE = {'download_seconds': (<class 'int'>,), 'hash': (<class 'str'>,), 'name'
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileTemplateList*

API_LIST_API_NAME = 'package_file_templates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**PackageFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileStatusList*

API_LIST_API_NAME = 'package_file_statuss'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**PackageFile**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'package_file'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_status': <class 'pytan3.api_objects.soap_7_2_314_3181.PackageFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileList*

API_LIST_API_NAME = 'package_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**PackageSpec**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'package_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec'
str – Name of object in source file.

API_SIMPLE = {'available_time': (<class 'str'>,), 'cache_row_id': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_2_314_3181.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageSpecList*

API_LIST_API_NAME = 'package_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ClientStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'client_status'
str – Name of object used in API calls.

API_NAME_SRC = 'client_status'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'computer_id': (<class 'str'>,), 'fu
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemStatusList*

API_LIST_API_NAME = 'system_status'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SystemSetting**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'system_setting'
str – Name of object used in API calls.

API_NAME_SRC = 'system_setting'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'default_value': (<class 'str'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'audit_data': <class 'pytan3.api_objects.soap_7_2_314_3181.AuditData'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemSettingList*

API_LIST_API_NAME = 'system_settings'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SoapError**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'soap_error'
str – Name of object used in API calls.

API_NAME_SRC = 'soap_error'
str – Name of object in source file.

API_SIMPLE = {'context': (<class 'str'>,), 'exception_name': (<class 'str'>,), 'obje
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**WhiteListedUrl**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'white_listed_url'
str – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url'
str – Name of object in source file.

API_SIMPLE = {'chunk_id': (<class 'str'>,), 'download_seconds': (<class 'int'>,), 'e
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_2_314_3181.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *WhiteListedUrlList*

API_LIST_API_NAME = 'white_listed_urls'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**VersionAggregate**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'version_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'filtered': (<class 'int'>,), 'version_stri
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *VersionAggregateList*

API_LIST_API_NAME = 'version_aggregates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SystemStatusAggregate**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'system_status_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_aggregate'
str – Name of object in source file.

API_SIMPLE = {'blocked_count': (<class 'int'>,), 'leader_count': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'versions': <class 'pytan3.api_objects.soap_7_2_314_3181.VersionAggrega
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**UserRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'user_role'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'permissions': <class 'pytan3.api_objects.soap_7_2_314_3181.Permission
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserRoleList*

API_LIST_API_NAME = 'roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**UserOwnedObjectIds**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'user_owned_object_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'user_owned_object_ids'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'plugin_schedules': <class 'pytan3.api_objects.soap_7_2_314_3181.Plugi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**User**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'user'
str – Name of object used in API calls.

API_NAME_SRC = 'user'
str – Name of object in source file.

API_SIMPLE = {'active_session_count': (<class 'int'>,), 'deleted_flag': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.soap_7_2_314_3181.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserList*

API_LIST_API_NAME = 'users'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ActionListInfo**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'action_list_info'

str – Name of object used in API calls.

API_NAME_SRC = 'action_list_info'

str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Action**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'action'

str – Name of object used in API calls.

API_NAME_SRC = 'action'

str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'comment': (<class 'str'>,), 'creati

dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.soap_7_2_314_3181.Group'>,

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ActionList*

API_LIST_API_NAME = 'actions'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ActionStop**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'action_stop'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.soap_7_2_314_3181.Action'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionStopList*

API_LIST_API_NAME = 'action_stops'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ArchivedQuestion**(**kwargs)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'archived_question'
str – Name of object used in API calls.

API_NAME_SRC = 'archived_question'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ArchivedQuestionList*

API_LIST_API_NAME = 'archived_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SavedQuestion**(**kwargs)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'archive_enabled_flag': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'archive_owner': <class 'pytan3.api_objects.soap_7_2_314_3181.User'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionList*

API_LIST_API_NAME = 'saved_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ParseJob**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'parse_job'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_job'
str – Name of object in source file.

API_SIMPLE = {'parser_version': (<class 'int'>,), 'question_text': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseJobList*

API_LIST_API_NAME = 'parse_jobs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Parameter**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'parameter'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter'
str – Name of object in source file.

API_SIMPLE = {'key': (<class 'str'>,), 'type': (<class 'int'>,), 'value': (<class '
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParameterList*

API_LIST_API_NAME = 'parameters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ParseResult**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'parameter_definition': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameters': <class 'pytan3.api_objects.soap_7_2_314_3181.ParameterLi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultList*

API_LIST_API_NAME = 'parse_results'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SensorReference**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'real_ms_avg': (<class 'int'>,), 'start_char
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorReferenceList*

API_LIST_API_NAME = 'sensor_references'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ParseResultGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result_group'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group'
str – Name of object in source file.

API_SIMPLE = {'question_text': (<class 'str'>,), 'score': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameter_values': <class 'pytan3.api_objects.soap_7_2_314_3181.Param
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultGroupList*

API_LIST_API_NAME = 'parse_result_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ClientCount**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'client_count'
str – Name of object used in API calls.

API_NAME_SRC = 'client_count'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**PluginArgument**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_argument'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'type': (<class 'str'>,), 'value': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginArgumentList*

API_LIST_API_NAME = 'plugin_arguments'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**UploadFile**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file'
str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'destination_file': (<class 'str'>,), 'file_
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UploadFileList*

API_LIST_API_NAME = 'upload_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**UploadFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_status'
str – Name of object in source file.

API_SIMPLE = {'file_cached': (<class 'int'>,), 'hash': (<class 'str'>,), 'percent_co
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_parts': <class 'pytan3.api_objects.soap_7_2_314_3181.UploadFileL
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Plugin**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'plugin'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin'
str – Name of object in source file.

API_SIMPLE = {'allow_rest': (<class 'int'>,), 'bundle': (<class 'str'>,), 'cache_row_
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.soap_7_2_314_3181.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {'SCRIPT': 'Script', 'SQL': 'SQL'}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginList*

API_LIST_API_NAME = 'plugins'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**PluginSchedule**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_schedule'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'enabled': (<class 'int'>,), 'end_da
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.soap_7_2_314_3181.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginScheduleList*

API_LIST_API_NAME = 'plugin_schedules'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ComputerGroupSpec**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_spec'
str – Name of object in source file.

API_SIMPLE = {'computer_name': (<class 'str'>,), 'id': (<class 'int'>,), 'ip_address
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ComputerSpecList*

API_LIST_API_NAME = 'computer_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ComputerGroup**(**kwargs)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group'

str – Name of object used in API calls.

API_NAME_SRC = 'computer_group'

str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<c

dict – Map of simple attributes to their types.

API_COMPLEX = {'computer_specs': <class 'pytan3.api_objects.soap_7_2_314_3181.Compute

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ComputerGroupList*

API_LIST_API_NAME = 'computer_groups'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ObjectList**(**kwargs)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'object_list'

str – Name of object used in API calls.

API_NAME_SRC = 'object_list'

str – Name of object in source file.

API_SIMPLE = {'export_id': (<class 'str'>,), 'export_version': (<class 'int'>,), 'im

dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.soap_7_2_314_3181.Action'>, 'acti

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**CacheFilter**(**kwargs)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'cache_filter'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'field': (<class 'str'>,), 'not_flag':
dict – Map of simple attributes to their types.

API_COMPLEX = {'sub_filters': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheFilte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *CacheFilterList*

API_LIST_API_NAME = 'cache_filters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Options**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'options'
str – Name of object used in API calls.

API_NAME_SRC = 'options'
str – Name of object in source file.

API_SIMPLE = {'aggregate_over_time_flag': (<class 'int'>,), 'allow_cdata_base64_encod
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_filters': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'content_set'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_2_314_3181.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetList*

API_LIST_API_NAME = 'content_sets'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRolePrivilegeOnRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege_on_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_2_314_3181.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeOnRoleList*

API_LIST_API_NAME = 'content_set_role_privilege_on_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role'
str – Name of object in source file.

API_SIMPLE = {'all_content_sets_flag': (<class 'int'>,), 'category': (<class 'str'>,
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role_privileges': <class 'pytan3.api_objects.soap_7_2_314
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleList*

API_LIST_API_NAME = 'content_set_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_membership'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.soap_7_2_314_3181.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleMembershipList*

API_LIST_API_NAME = 'content_set_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetUserGroupRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_user_group_role_membership'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.soap_7_2_314_3181.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetUserGroupRoleMembershipList*

API_LIST_API_NAME = 'content_set_user_group_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'privilege_module':
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_2_314_3181.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetPrivilegeList*

API_LIST_API_NAME = 'content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRolePrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_2_314_3181.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeList*

API_LIST_API_NAME = 'content_set_role_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**EffectiveContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'effective_content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_2_314_3181.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *EffectiveContentSetPrivilegeList*

API_LIST_API_NAME = 'effective_content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Dashboard**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'public_flag': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_2_314_3181.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *DashboardList*

API_LIST_API_NAME = 'dashboards'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**DashboardGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard_group'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_group'
str – Name of object in source file.

API_SIMPLE = {'display_index': (<class 'int'>,), 'editable_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_2_314_3181.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**UserGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'user_group'
str – Name of object used in API calls.

API_NAME_SRC = 'user_group'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<c
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.soap_7_2_314_3181.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserGroupList*

API_LIST_API_NAME = 'user_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**Solution**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'solution'
str – Name of object used in API calls.

API_NAME_SRC = 'solution'
str – Name of object in source file.

API_SIMPLE = {'category': (<class 'str'>,), 'delete_xml_url': (<class 'str'>,), 'del
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SolutionList*

API_LIST_API_NAME = 'solutions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**ActionGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'action_group'
str – Name of object used in API calls.

API_NAME_SRC = 'action_group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'groups': <class 'pytan3.api_objects.soap_7_2_314_3181.GroupList'>, 'u
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionGroupList*

API_LIST_API_NAME = 'action_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SavedQuestionPackageSpecs**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_package_specs'

str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_package_specs'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'packages': <class 'pytan3.api_objects.soap_7_2_314_3181.PackageSpecLi

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SavedQuestionQuestion**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_question'

str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'questions': <class 'pytan3.api_objects.soap_7_2_314_3181.QuestionList

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SavedQuestionQuestionList*

API_LIST_API_NAME = 'saved_question_questions'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**LdapSyncConnector**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'ldap_sync_connector'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector'
str – Name of object in source file.

API_SIMPLE = {'base_groups': (<class 'str'>,), 'base_users': (<class 'str'>,), 'disal
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *LdapSyncConnectorList*

API_LIST_API_NAME = 'ldap_sync_connector_list'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**HashedString**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiItem*

Automagically generated API object.

API_NAME = 'hashed_string'
str – Name of object used in API calls.

API_NAME_SRC = 'hashed_string'
str – Name of object in source file.

API_SIMPLE = {'collision_flag': (<class 'int'>,), 'error_flag': (<class 'int'>,), 'f
dict – Map of simple attributes to their types.

API_COMPLEX = {'first_computer_id': <class 'pytan3.api_objects.soap_7_2_314_3181.Comp
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *HashedStringList*

API_LIST_API_NAME = 'hashed_strings'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_2_314_3181.**SensorQueryList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_querys'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'query'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorQuery*

class pytan3.api_objects.soap_7_2_314_3181.**SensorSubcolumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_subcolumns'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'subcolumn'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorSubcolumn*

class pytan3.api_objects.soap_7_2_314_3181.**StringHintList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'string_hints'
`str` – Name of object used in API calls.

API_NAME_SRC = 'string_hint_list'
`str` – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'string_hint'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**SensorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'sensors'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Sensor*

class pytan3.api_objects.soap_7_2_314_3181.**SensorStatList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_stats'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_stat'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorStat*

class pytan3.api_objects.soap_7_2_314_3181.**SavedActionApprovalList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_approvals'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action_approval'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedActionApproval*

class pytan3.api_objects.soap_7_2_314_3181.**SavedActionRowIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_row_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_row_id_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**SavedActionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'saved_actions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedAction*

class pytan3.api_objects.soap_7_2_314_3181.**AuditDataList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'audit_datas'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'entry'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditData*

class pytan3.api_objects.soap_7_2_314_3181.**AuditLogList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'audit_logs'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'audit_log'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditLog*

class pytan3.api_objects.soap_7_2_314_3181.**MetadataList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'metadatas'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'item'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *MetadataItem*

class pytan3.api_objects.soap_7_2_314_3181.**GroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'groups'
str – Name of object used in API calls.

API_NAME_SRC = 'group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Group*

class pytan3.api_objects.soap_7_2_314_3181.**FilterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'filters'
str – Name of object used in API calls.

API_NAME_SRC = 'filter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Filter*

class pytan3.api_objects.soap_7_2_314_3181.**SelectList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'selects'

str – Name of object used in API calls.

API_NAME_SRC = 'select_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'select'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Select*

class pytan3.api_objects.soap_7_2_314_3181.**ErrorList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'errors'

str – Name of object used in API calls.

API_NAME_SRC = 'error_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'error'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *XmlError*

class pytan3.api_objects.soap_7_2_314_3181.**QuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'questions'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Question*

class pytan3.api_objects.soap_7_2_314_3181.**PackageFileTemplateList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_templates'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file_template'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileTemplate*

class pytan3.api_objects.soap_7_2_314_3181.**PackageFileStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_statuss'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileStatus*

class pytan3.api_objects.soap_7_2_314_3181.**PackageFileList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'package_files'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFile*

class pytan3.api_objects.soap_7_2_314_3181.**PackageSpecList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'package_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'package_spec'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageSpec*

class pytan3.api_objects.soap_7_2_314_3181.**WhiteListedUrlList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'white_listed_urls'
str – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'white_listed_url'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *WhiteListedUrl*

class pytan3.api_objects.soap_7_2_314_3181.**VersionAggregateList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'version_aggregates'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'version'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *VersionAggregate*

class pytan3.api_objects.soap_7_2_314_3181.**SystemStatusList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'system_status'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'aggregate': <class 'pytan3.api_objects.soap_7_2_314_3181.SystemStatus
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'client_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ClientStatus*

class pytan3.api_objects.soap_7_2_314_3181.**SystemSettingList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'system_settings'
str – Name of object used in API calls.

API_NAME_SRC = 'system_setting_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'system_setting'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SystemSetting*

class pytan3.api_objects.soap_7_2_314_3181.**UserList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'users'
str – Name of object used in API calls.

API_NAME_SRC = 'user_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.soap_7_2_314_3181.**PermissionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'permissions'
str – Name of object used in API calls.

API_NAME_SRC = 'permission_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {'ACTION_APPROVE': 'action_approval', 'ACTION_READ': 'action_read', 'A
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'permission'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**UserRoleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'roles'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'role'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UserRole*

class pytan3.api_objects.soap_7_2_314_3181.**ActionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'actions'
str – Name of object used in API calls.

API_NAME_SRC = 'action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Action*

class pytan3.api_objects.soap_7_2_314_3181.**ActionStopList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'action_stops'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_stop'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionStop*

class pytan3.api_objects.soap_7_2_314_3181.**ArchivedQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'archived_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'archived_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'archived_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ArchivedQuestion*

class pytan3.api_objects.soap_7_2_314_3181.**SavedQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'saved_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestion*

class pytan3.api_objects.soap_7_2_314_3181.**ParseJobList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'parse_jobs'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_job_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_job'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseJob*

class pytan3.api_objects.soap_7_2_314_3181.**ParseResultGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'parse_result_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResultGroup*

class pytan3.api_objects.soap_7_2_314_3181.**ParseResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'parse_results'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResult*

class pytan3.api_objects.soap_7_2_314_3181.**ParameterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'parameters'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parameter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Parameter*

class pytan3.api_objects.soap_7_2_314_3181.**ParameterValueList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'parameter_values'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter_value_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**SensorReferenceList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_references'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_reference'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorReference*

class pytan3.api_objects.soap_7_2_314_3181.**PluginArgumentList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_arguments'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'argument'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginArgument*

class pytan3.api_objects.soap_7_2_314_3181.**PluginSqlResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_results'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_result_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**PluginSqlColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_columns'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_column_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'name'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**PluginSql**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql'
str – Name of object in source file.

API_SIMPLE = {'result_count': (<class 'int'>,), 'rows_affected': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'columns': <class 'pytan3.api_objects.soap_7_2_314_3181.PluginSqlColum
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_row'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSqlResultList*

class pytan3.api_objects.soap_7_2_314_3181.**PluginCommandList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_commands'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_command_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'command'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**UploadFileList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'upload_files'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'upload_file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UploadFile*

class pytan3.api_objects.soap_7_2_314_3181.**PluginList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'plugins'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Plugin*

class pytan3.api_objects.soap_7_2_314_3181.**PluginScheduleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_schedules'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin_schedule'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSchedule*

class pytan3.api_objects.soap_7_2_314_3181.**ComputerSpecList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'computer_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_spec_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_spec'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroupSpec*

class pytan3.api_objects.soap_7_2_314_3181.**ComputerGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'computer_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_2_314_3181.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroup*

class pytan3.api_objects.soap_7_2_314_3181.**CacheFilterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'cache_filters'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *CacheFilter*

class pytan3.api_objects.soap_7_2_314_3181.**ImportConflictOptions**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_options'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_options'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_option'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'content_sets'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSet*

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRolePrivilegeOnRoleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privilege_on_roles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilegeOnRole*

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRoleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_roles'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRole*

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRoleMembershipList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_memberships'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_membership'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRoleMembership*

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetUserGroupRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_user_group_role_memberships'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_user_group_role_membership'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetUserGroupRoleMembership*

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetPrivilege*

class pytan3.api_objects.soap_7_2_314_3181.**ContentSetRolePrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilege*

class pytan3.api_objects.soap_7_2_314_3181.**EffectiveContentSetPrivilegeRequest**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privilege_request'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_request'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.soap_7_2_314_3181.**EffectiveContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'effective_content_set_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *EffectiveContentSetPrivilege*

class pytan3.api_objects.soap_7_2_314_3181.**DashboardList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'dashboards'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'dashboard'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Dashboard*

class pytan3.api_objects.soap_7_2_314_3181.**UserGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'user_groups'

str – Name of object used in API calls.

API_NAME_SRC = 'user_group_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user_group'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *UserGroup*

class pytan3.api_objects.soap_7_2_314_3181.**SolutionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'solutions'

str – Name of object used in API calls.

API_NAME_SRC = 'solution_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'solution'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Solution*

class pytan3.api_objects.soap_7_2_314_3181.**ActionGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'action_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'action_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionGroup*

class pytan3.api_objects.soap_7_2_314_3181.**SavedQuestionQuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'saved_question_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestionQuestion*

class pytan3.api_objects.soap_7_2_314_3181.**LdapSyncConnectorList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'ldap_sync_connector_list'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'ldap_sync_connector'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *LdapSyncConnector*

class pytan3.api_objects.soap_7_2_314_3181.**ComputerIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'computer_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_id_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_2_314_3181.**HashedStringList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_2_314_3181.ApiList*

Automagically generated API array object.

API_NAME = 'hashed_strings'
`str` – Name of object used in API calls.

API_NAME_SRC = 'hashed_string_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'hashed_string'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *HashedString*

pytan3.api_objects.soap_7_2_314_3181.**BUILD_META = {'date': '2019-02-22 07:46:06.368436',**
`dict` – How this module was built (date/time in UTC format).

pytan3.api_objects.soap_7_2_314_3181.**COMMANDS = ['AddObject', 'GetObject', 'MoveObject', '**
`list` of `str` – API commands.

pytan3.api_objects.soap_7_2_314_3181.**VERSION = {'build': 3181, 'major': 7, 'minor': 2,**
`dict` – Tanium API version these objects are intended to be used for.

SOAP API Object Module for Version 7.3.314.3424

Python objects for Tanium's API.

pytan3.api_objects.soap_7_3_314_3424.**float_types = (<class 'float'>,)**
`tuple` of `type` – Float types.

pytan3.api_objects.soap_7_3_314_3424.**integer_types = (<class 'int'>,)**
`tuple` of `type` – Integer types.

pytan3.api_objects.soap_7_3_314_3424.**string_types = (<class 'str'>,)**
`tuple` of `type` – String types.

pytan3.api_objects.soap_7_3_314_3424.**simple_types = (<class 'int'>, <class 'str'>, <class**
`tuple` of `type` – All types that should be considered simple types.

pytan3.api_objects.soap_7_3_314_3424.**TYPE = 'soap'**
`str` – Type of API this module was built from.

pytan3.api_objects.soap_7_3_314_3424.**API_DT = '%Y-%m-%dT%H:%M:%S'**
`str` – Datetime format for this API type and version.

pytan3.api_objects.soap_7_3_314_3424.**api_fixes**()
Fix incorrect attribute definitions on auto generated ApiModel classes.

pytan3.api_objects.soap_7_3_314_3424.**expand_cls_globals**()
Replace str values with global vars for attrs on ApiModel classes.

Quite the funky chicken dance for solving issues with order of class definition.

pytan3.api_objects.soap_7_3_314_3424.**expand_global**(*obj*)
Replace str values with global vars recursively.

Parameters **obj** (str or dict or list) – Object to expand into global var.

Returns String objects are the only ones that will be expanded.

Return type str or dict or list or object

pytan3.api_objects.soap_7_3_314_3424.**get_api_all_item**()
Get map of class name to class for all ApiItem subclasses.

Returns dict

pytan3.api_objects.soap_7_3_314_3424.**get_api_all_list**()
Get map of class name to class for all ApiList subclasses.

Returns dict

pytan3.api_objects.soap_7_3_314_3424.**get_api_all_model**()
Get map of class name to class for all ApiItem and ApiList subclasses.

Returns dict

class pytan3.api_objects.soap_7_3_314_3424.**ApiModel**
Bases: *pytan3.api_models.ApiModel*

Model for a complex item in the API.

class pytan3.api_objects.soap_7_3_314_3424.**ApiItem**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiModel*, *pytan3.api_models.ApiItem*

Model for a complex item in the API.

class pytan3.api_objects.soap_7_3_314_3424.**ApiList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiModel*, *pytan3.api_models.ApiList*

Model for an array in the API.

class pytan3.api_objects.soap_7_3_314_3424.**ResultInfoList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'result_infos'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'int'>,), 'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_info'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ResultInfo*

__repr__()
Make repr output be same as str output.

Returns `str`

class pytan3.api_objects.soap_7_3_314_3424.**ResultInfo**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'result_info'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'er
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'row_count', 'mr_tested', 'mr_passed'
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultInfoList*

API_LIST_API_NAME = 'result_infos'
`str` – Name of *API_LIST_CLS* used in API calls.

__repr__()
Make repr output be same as str output.

Returns `str`

class pytan3.api_objects.soap_7_3_314_3424.**ResultSetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'result_sets'
`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {'now': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_set'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ResultSet*

class pytan3.api_objects.soap_7_3_314_3424.**MergedResultSet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'merged_result'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'str'>,), 'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'result_infos': <class 'pytan3.api_objects.soap_7_3_314_3424.ResultInf
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ResultSet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'result_set'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'ca
dict – Map of simple attributes to their types.

API_COMPLEX = {'cs': <class 'pytan3.api_objects.soap_7_3_314_3424.ColumnList'>, 'rs':
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'mr_tested', 'mr_passed', 'row_count'
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultSetList*

API_LIST_API_NAME = 'result_sets'
str – Name of *API_LIST_CLS* used in API calls.

__init__(***kwargs*)
Constructor.

Notes

Sets *Column.API_DATA_SET* so column objects can access rows.

Sets *RowColumn.API_COLUMN* to the index correlated *Column* so row columns can access the column name, result type, etc.

Sets *Column.API_IDX* and *RowColumn.API_IDX* so column objects know what their index is without having to do lookups.

Parameters ****kwargs** – Passed back to parent class.

rows
Expose complex attr "rs" as "rows".

Returns list

columns
Expose complex attr "cs" as "columns".

Returns list

class pytan3.api_objects.soap_7_3_314_3424.**ColumnList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'cs'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['names']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'c'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Column*

__repr__()
Make repr output be same as str output.

Returns str

names
Expose column names of all *Column* in this obj.

Returns list of str

__getitem__(*value*)
Support indexing of *names*.

Parameters **value** (int or str) – If int: Index of item to retrieve from simple attr "c". If str: Column name to index correlate from *names*

Returns The RowColumn object at index value from *names*.

Return type *RowColumn*

class pytan3.api_objects.soap_7_3_314_3424.**Column**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Manually defined API object.

API_DATA_SET = None
ResultSet – Parent of this object, set by *ResultSet.__init__()*.

API_IDX = None
int – Index of this object in *ColumnList*.

API_NAME = 'c'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'dn': (<class 'str'>,), 'rt': (<class 'int'>,), 'wh': (<class 'int'>,
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['name', 'result_type', 'hash']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ColumnList*

API_LIST_API_NAME = 'cs'
str – Name of *API_LIST_CLS* used in API calls.

name
Expose simple attr "dn" as name.

Returns str

hash
Expose simple attr "wh" as hash.

Returns str

type
Expose simple attr "rt" as type.

Returns str

result_type
Expose simple attr "rt" as result_type.

Notes

Will try to map str from "rt" as int to constants from *Sensor.API_CONSTANTS*.

Returns str

get_values (*attr='value'*, *join=None*)
Get values of this column from all rows.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list of str

class pytan3.api_objects.soap_7_3_314_3424.**RowList** (**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'rs'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'r'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Row*

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.soap_7_3_314_3424.**Row**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'r'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'cid': (<class 'int'>,), 'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'c': <class 'pytan3.api_objects.soap_7_3_314_3424.RowColumnList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['id', 'cid', 'columns']
list or str – Attributes to add to str formatting.

API_LIST_API_NAME = 'rs'
str – Name of *API_LIST_CLS* used in API calls.

API_LIST_CLS
ApiItem: Item class this list class holds.

alias of *RowList*

__repr__()
Make repr output be same as str output.

Returns str

__getitem__(*value*)
Support indexing of *names*.

Parameters **value** (int or str) – If int: Index of item to retrieve from *names*. If str: Column name to index correlate from *ColumnList.names*

Returns The RowColumn object at index value from *names*.

Return type *RowColumn*

names
Return the names of each row column from *RowColumn.API_COLUMN*.

Returns list of str

columns
Expose complex attr "c" as "columns".

Returns *RowColumnList*

__len__()
Expose length of *columns*.

Returns int

get_values (*meta=False*, *hashes=False*, *join=None*)
Get all values from all columns in this row.

Parameters

- **meta** (bool, optional) – Include sensor hash and result type for each column.

  Defaults to: False.

- **hashes** (bool, optional) – Include hashes of values.

  Defaults to: False.

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns dict

class pytan3.api_objects.soap_7_3_314_3424.**RowColumnList** (**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Manually defined API array object.

API_NAME = 'rc'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_columns'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *RowColumn*

api_coerce_items_hook (*attr*, *value*, *op*)
Check hook that allows subclasses to modify list items.

Parameters

- **attr** (str) – Attribute being set on this object.
- **value** (*ApiList* or list or tuple) – The list object holding items.
- **op** (str) – Operation being performed that called this method.

Examples

This converts all "v" attributes of each column for this row into a list of dicts:

```
>>> # single value columns "v" is a single dict:
>>> {"v": {"h": "", "text": ""}}
>>> # multiple value columns "v" is a list of dict:
>>> {"v": [{"h": "", "text": ""}, {"h": "", "text": ""}]}
>>> # Count columns "v" is a string:
>>> {"v": "1"}
>>> # all become:
>>> {"v": [{"text": "", "hash": ""}]}
```

Notes

The driving force behind this is basically just the Count column. It returns a string of the value, instead of a dict or a list of dicts.

Returns The list of items modified or as is.

Return type `list`

class `pytan3.api_objects.soap_7_3_314_3424.`**`RowColumn`**(**args*, ***kwargs*)

Bases: *`pytan3.api_objects.soap_7_3_314_3424.ApiList`*

Manually defined API array object.

`API_COLUMN = None`

`Column` – Index correlated column, set by *`ResultSet.__init__()`*.

`API_IDX = None`

`int` – Index of this object in *`RowColumnList`*.

`API_NAME = 'row_column'`

`str` – Name of object used in API calls.

`API_NAME_SRC = ''`

`str` – Name of object in source file.

`API_SIMPLE = {}`

`dict` – Map of simple attributes to their types.

`API_COMPLEX = {}`

`dict` – Map of complex attributes to their types.

`API_CONSTANTS = {}`

`dict` – Map of constants to their values.

`API_STR_ADD = ['name', 'hash', 'result_type']`

`list` or `str` – Attributes to add to str formatting.

`API_ITEM_ATTR = 'v'`

`str` – Name of *`API_ITEM_CLS`* used in API calls.

`API_ITEM_CLS`

`ApiItem`: Item class this list class holds.

alias of *`RowValue`*

`name`

Expose column name from *`API_COLUMN`*.

Returns `str`

result_type
Expose column result type from *API_COLUMN*.

Returns str

hash
Expose column sensor hash from *API_COLUMN*.

Returns str

get_values(*attr='value'*, *join=None*)
Get all values from this row column.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list or str

class pytan3.api_objects.soap_7_3_314_3424.**RowValue**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Manually defined API object.

API_NAME = 'v'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'h': (<class 'int'>,), 'text': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['hash', 'value']
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *RowColumn*

API_LIST_API_NAME = 'row_column'
str – Name of *API_LIST_CLS* used in API calls.

hash
Expose simple attr "h" as hash.

Returns str

value
Expose simple attr "text" as value.

Returns str

class pytan3.api_objects.soap_7_3_314_3424.**SensorQuery**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_query'

str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query'

str – Name of object in source file.

API_SIMPLE = {'platform': (<class 'str'>,), 'script': (<class 'str'>,), 'script_type

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SensorQueryList*

API_LIST_API_NAME = 'sensor_querys'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SensorSubcolumn**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_subcolumn'

str – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn'

str – Name of object in source file.

API_SIMPLE = {'exclude_from_parse_flag': (<class 'int'>,), 'hidden_flag': (<class 'i

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SensorSubcolumnList*

API_LIST_API_NAME = 'sensor_subcolumns'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SensorStat**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_stat'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<class 's
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorStatList*

API_LIST_API_NAME = 'sensor_stats'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SavedActionPolicy**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_policy'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_policy'
str – Name of object in source file.

API_SIMPLE = {'max_age': (<class 'int'>,), 'min_count': (<class 'int'>,), 'row_filte
dict – Map of simple attributes to their types.

API_COMPLEX = {'row_filter_group': <class 'pytan3.api_objects.soap_7_3_314_3424.Group
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SavedActionApproval**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_approval'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval'
`str` – Name of object in source file.

API_SIMPLE = {'approved_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3424.MetadataList'
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionApprovalList*

API_LIST_API_NAME = 'saved_action_approvals'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SavedAction**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_action'
`str` – Name of object in source file.

API_SIMPLE = {'action_group_id': (<class 'int'>,), 'approved_flag': (<class 'int'>,)
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.soap_7_3_314_3424.Group'>,
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionList*

API_LIST_API_NAME = 'saved_actions'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Sensor**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor'
`str` – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'category': (<class 'str'>,), 'creat
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3424.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {'BES_DATETIME_RESULT': 4, 'BES_SENSOR': 2, 'DATASIZE_RESULT': 8, 'HAS
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorList*

API_LIST_API_NAME = 'sensors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**AuditData**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'audit_data'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'creation_time': (<class 'str'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'mod_user': <class 'pytan3.api_objects.soap_7_3_314_3424.User'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditDataList*

API_LIST_API_NAME = 'audit_datas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**AuditLog**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'audit_log'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log'
str – Name of object in source file.

API_SIMPLE = {'end_time': (<class 'str'>,), 'id': (<class 'int'>,), 'start_time': (
dict – Map of simple attributes to their types.

API_COMPLEX = {'entries': <class 'pytan3.api_objects.soap_7_3_314_3424.AuditDataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditLogList*

API_LIST_API_NAME = 'audit_logs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Server**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'server'
str – Name of object used in API calls.

API_NAME_SRC = 'server'
str – Name of object in source file.

API_SIMPLE = {'heart_beat': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerList*

API_LIST_API_NAME = 'servers'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**MetadataItem**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'metadata_item'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_item'
str – Name of object in source file.

API_SIMPLE = {'admin_flag': (<class 'int'>,), 'name': (<class 'str'>,), 'value': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *MetadataList*

API_LIST_API_NAME = 'metadatas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Filter**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'filter'
str – Name of object used in API calls.

API_NAME_SRC = 'filter'
str – Name of object in source file.

API_SIMPLE = {'aggregation': (<class 'str'>,), 'all_times_flag': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'sensor': <class 'pytan3.api_objects.soap_7_3_314_3424.Sensor'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *FilterList*

API_LIST_API_NAME = 'filters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**IdReference**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'id_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'id_reference'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Group**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'group'
str – Name of object used in API calls.

API_NAME_SRC = 'group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'filters': <class 'pytan3.api_objects.soap_7_3_314_3424.FilterList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *GroupList*

API_LIST_API_NAME = 'groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Select**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'select'
str – Name of object used in API calls.

API_NAME_SRC = 'select'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'filter': <class 'pytan3.api_objects.soap_7_3_314_3424.Filter'>, 'grou
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SelectList*

API_LIST_API_NAME = 'selects'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**XmlError**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'xml_error'
str – Name of object used in API calls.

API_NAME_SRC = 'xml_error'
str – Name of object in source file.

API_SIMPLE = {'error_context': (<class 'str'>,), 'exception': (<class 'str'>,), 'typ
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ErrorList*

API_LIST_API_NAME = 'errors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**CacheInfo**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'cache_info'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_info'
str – Name of object in source file.

API_SIMPLE = {'cache_id': (<class 'int'>,), 'cache_row_count': (<class 'int'>,), 'ex
dict – Map of simple attributes to their types.

API_COMPLEX = {'errors': <class 'pytan3.api_objects.soap_7_3_314_3424.ErrorList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**QuestionListInfo**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'question_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Question**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'question'
str – Name of object used in API calls.

API_NAME_SRC = 'question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'cache_row_id': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'context_group': <class 'pytan3.api_objects.soap_7_3_314_3424.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *QuestionList*

API_LIST_API_NAME = 'questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**PackageFileTemplate**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_template'

str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template'

str – Name of object in source file.

API_SIMPLE = {'download_seconds': (<class 'int'>,), 'hash': (<class 'str'>,), 'name'

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *PackageFileTemplateList*

API_LIST_API_NAME = 'package_file_templates'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**PackageFileStatus**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_status'

str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status'

str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *PackageFileStatusList*

API_LIST_API_NAME = 'package_file_statuss'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**PackageFile**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_file'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_status': <class 'pytan3.api_objects.soap_7_3_314_3424.PackageFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileList*

API_LIST_API_NAME = 'package_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**PackageSpec**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'package_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec'
str – Name of object in source file.

API_SIMPLE = {'available_time': (<class 'str'>,), 'cache_row_id': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3424.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageSpecList*

API_LIST_API_NAME = 'package_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ClientStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'client_status'
str – Name of object used in API calls.

API_NAME_SRC = 'client_status'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'computer_id': (<class 'str'>,), 'fu
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemStatusList*

API_LIST_API_NAME = 'system_status'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SystemSetting**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'system_setting'
str – Name of object used in API calls.

API_NAME_SRC = 'system_setting'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'default_value': (<class 'str'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'audit_data': <class 'pytan3.api_objects.soap_7_3_314_3424.AuditData'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemSettingList*

API_LIST_API_NAME = 'system_settings'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SoapError**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'soap_error'
str – Name of object used in API calls.

API_NAME_SRC = 'soap_error'
str – Name of object in source file.

API_SIMPLE = {'context': (<class 'str'>,), 'exception_name': (<class 'str'>,), 'obje
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**WhiteListedUrl**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'white_listed_url'
str – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url'
str – Name of object in source file.

API_SIMPLE = {'chunk_id': (<class 'str'>,), 'download_seconds': (<class 'int'>,), 'e
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3424.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *WhiteListedUrlList*

API_LIST_API_NAME = 'white_listed_urls'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**VersionAggregate**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'version_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'filtered': (<class 'int'>,), 'version_stri
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *VersionAggregateList*

API_LIST_API_NAME = 'version_aggregates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SystemStatusAggregate**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'system_status_aggregate'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_aggregate'
str – Name of object in source file.

API_SIMPLE = {'blocked_count': (<class 'int'>,), 'leader_count': (<class 'int'>,), '
dict – Map of simple attributes to their types.

API_COMPLEX = {'versions': <class 'pytan3.api_objects.soap_7_3_314_3424.VersionAggrega
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**UserRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user_role'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'permissions': <class 'pytan3.api_objects.soap_7_3_314_3424.Permission
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserRoleList*

API_LIST_API_NAME = 'roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**UserOwnedObjectIds**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user_owned_object_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'user_owned_object_ids'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'plugin_schedules': <class 'pytan3.api_objects.soap_7_3_314_3424.Plugi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**User**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user'
str – Name of object used in API calls.

API_NAME_SRC = 'user'
str – Name of object in source file.

API_SIMPLE = {'active_session_count': (<class 'int'>,), 'deleted_flag': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.soap_7_3_314_3424.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserList*

API_LIST_API_NAME = 'users'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ActionListInfo**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'action_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Action**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action'
str – Name of object used in API calls.

API_NAME_SRC = 'action'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'comment': (<class 'str'>,), 'creati
dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.soap_7_3_314_3424.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionList*

API_LIST_API_NAME = 'actions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ActionStop**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action_stop'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.soap_7_3_314_3424.Action'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionStopList*

API_LIST_API_NAME = 'action_stops'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ArchivedQuestion**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'archived_question'
str – Name of object used in API calls.

API_NAME_SRC = 'archived_question'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ArchivedQuestionList*

API_LIST_API_NAME = 'archived_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SavedQuestion**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question'

str – Name of object used in API calls.

API_NAME_SRC = 'saved_question'

str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'archive_enabled_flag': (<cla

dict – Map of simple attributes to their types.

API_COMPLEX = {'archive_owner': <class 'pytan3.api_objects.soap_7_3_314_3424.User'>,

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *SavedQuestionList*

API_LIST_API_NAME = 'saved_questions'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ParseJob**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parse_job'

str – Name of object used in API calls.

API_NAME_SRC = 'parse_job'

str – Name of object in source file.

API_SIMPLE = {'parser_version': (<class 'int'>,), 'question_text': (<class 'str'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ParseJobList*

API_LIST_API_NAME = 'parse_jobs'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Parameter**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parameter'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parameter'
`str` – Name of object in source file.

API_SIMPLE = {'key': (<class 'str'>,), 'type': (<class 'int'>,), 'value': (<class '
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParameterList*

API_LIST_API_NAME = 'parameters'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ParseResult**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parse_result'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'parameter_definition': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'parameters': <class 'pytan3.api_objects.soap_7_3_314_3424.ParameterLi
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultList*

API_LIST_API_NAME = 'parse_results'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SensorReference**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'real_ms_avg': (<class 'int'>,), 'start_char
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorReferenceList*

API_LIST_API_NAME = 'sensor_references'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ParseResultGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result_group'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group'
str – Name of object in source file.

API_SIMPLE = {'question_text': (<class 'str'>,), 'score': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameter_values': <class 'pytan3.api_objects.soap_7_3_314_3424.Param
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultGroupList*

API_LIST_API_NAME = 'parse_result_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ClientCount**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'client_count'
str – Name of object used in API calls.

API_NAME_SRC = 'client_count'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**PluginArgument**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_argument'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'type': (<class 'str'>,), 'value': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginArgumentList*

API_LIST_API_NAME = 'plugin_arguments'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**UploadFile**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file'
str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'destination_file': (<class 'str'>,), 'file_
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UploadFileList*

API_LIST_API_NAME = 'upload_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**UploadFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_status'
str – Name of object in source file.

API_SIMPLE = {'file_cached': (<class 'int'>,), 'hash': (<class 'str'>,), 'percent_co
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_parts': <class 'pytan3.api_objects.soap_7_3_314_3424.UploadFileL
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Plugin**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'plugin'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin'
str – Name of object in source file.

API_SIMPLE = {'allow_rest': (<class 'int'>,), 'bundle': (<class 'str'>,), 'cache_row_
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.soap_7_3_314_3424.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {'SCRIPT': 'Script', 'SQL': 'SQL'}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginList*

API_LIST_API_NAME = 'plugins'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**PluginSchedule**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_schedule'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'enabled': (<class 'int'>,), 'end_da
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.soap_7_3_314_3424.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginScheduleList*

API_LIST_API_NAME = 'plugin_schedules'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ComputerGroupSpec**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_spec'
str – Name of object in source file.

API_SIMPLE = {'computer_name': (<class 'str'>,), 'id': (<class 'int'>,), 'ip_address
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ComputerSpecList*

API_LIST_API_NAME = 'computer_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ComputerGroup**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<c
dict – Map of simple attributes to their types.

API_COMPLEX = {'computer_specs': <class 'pytan3.api_objects.soap_7_3_314_3424.Compute
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ComputerGroupList*

API_LIST_API_NAME = 'computer_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**VerifySignature**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'verify_signature'
str – Name of object used in API calls.

API_NAME_SRC = 'verify_signature'
str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'id': (<class 'int'>,), 'type': (<class 's
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ObjectList**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'object_list'
str – Name of object used in API calls.

API_NAME_SRC = 'object_list'
str – Name of object in source file.

API_SIMPLE = {'export_id': (<class 'str'>,), 'export_version': (<class 'int'>,), 'imp
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.soap_7_3_314_3424.Action'>, 'acti
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ImportConflictDetail**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'import_conflict_detail'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail'
str – Name of object in source file.

API_SIMPLE = {'diff': (<class 'str'>,), 'is_new': (<class 'int'>,), 'name': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ImportConflictDetailList*

API_LIST_API_NAME = 'import_conflict_details'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**CacheFilter**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'cache_filter'

str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter'

str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'field': (<class 'str'>,), 'not_flag':

dict – Map of simple attributes to their types.

API_COMPLEX = {'sub_filters': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheFilte

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *CacheFilterList*

API_LIST_API_NAME = 'cache_filters'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Options**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'options'

str – Name of object used in API calls.

API_NAME_SRC = 'options'

str – Name of object in source file.

API_SIMPLE = {'aggregate_by_value_flag': (<class 'int'>,), 'aggregate_over_time_flag'

dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_filters': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheFil

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSet**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3424.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetList*

API_LIST_API_NAME = 'content_sets'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRolePrivilegeOnRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege_on_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3424.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeOnRoleList*

API_LIST_API_NAME = 'content_set_role_privilege_on_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role'
str – Name of object in source file.

API_SIMPLE = {'all_content_sets_flag': (<class 'int'>,), 'category': (<class 'str'>,
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role_privileges': <class 'pytan3.api_objects.soap_7_3_314
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleList*

API_LIST_API_NAME = 'content_set_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_membership'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.soap_7_3_314_3424.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleMembershipList*

API_LIST_API_NAME = 'content_set_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetUserGroupRoleMembership**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_user_group_role_membership'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.soap_7_3_314_3424.IdRef
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetUserGroupRoleMembershipList*

API_LIST_API_NAME = 'content_set_user_group_role_memberships'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'privilege_module':
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3424.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetPrivilegeList*

API_LIST_API_NAME = 'content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRolePrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3424.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeList*

API_LIST_API_NAME = 'content_set_role_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**EffectiveContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'effective_content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3424.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *EffectiveContentSetPrivilegeList*

API_LIST_API_NAME = 'effective_content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Dashboard**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'public_flag': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3424.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *DashboardList*

API_LIST_API_NAME = 'dashboards'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**DashboardGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard_group'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_group'
str – Name of object in source file.

API_SIMPLE = {'display_index': (<class 'int'>,), 'editable_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3424.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**UserGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'user_group'
str – Name of object used in API calls.

API_NAME_SRC = 'user_group'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'exclusive_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.soap_7_3_314_3424.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserGroupList*

API_LIST_API_NAME = 'user_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**Solution**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'solution'
str – Name of object used in API calls.

API_NAME_SRC = 'solution'
str – Name of object in source file.

API_SIMPLE = {'category': (<class 'str'>,), 'delete_xml_url': (<class 'str'>,), 'del
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SolutionList*

API_LIST_API_NAME = 'solutions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ActionGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'action_group'
str – Name of object used in API calls.

API_NAME_SRC = 'action_group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'groups': <class 'pytan3.api_objects.soap_7_3_314_3424.GroupList'>, 'u
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionGroupList*

API_LIST_API_NAME = 'action_groups'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SavedQuestionPackageSpecs**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_package_specs'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_question_package_specs'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'packages': <class 'pytan3.api_objects.soap_7_3_314_3424.PackageSpecLi
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SavedQuestionQuestion**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_question'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'questions': <class 'pytan3.api_objects.soap_7_3_314_3424.QuestionList
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionQuestionList*

API_LIST_API_NAME = 'saved_question_questions'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**LdapSyncConnector**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'ldap_sync_connector'

str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector'

str – Name of object in source file.

API_SIMPLE = {'base_groups': (<class 'str'>,), 'base_users': (<class 'str'>,), 'disal

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *LdapSyncConnectorList*

API_LIST_API_NAME = 'ldap_sync_connectors'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ServerThrottle**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle'

str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle'

str – Name of object in source file.

API_SIMPLE = {'bandwidth_bytes_limit': (<class 'int'>,), 'connection_limit': (<class

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ServerThrottleList*

API_LIST_API_NAME = 'server_throttles'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottle**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle'
`str` – Name of object in source file.

API_SIMPLE = {'all_subnets_flag': (<class 'int'>,), 'bandwidth_bytes_limit': (<class
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSu
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleList*

API_LIST_API_NAME = 'site_throttles'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottleSubnet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet'
`str` – Name of object in source file.

API_SIMPLE = {'range': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetList*

API_LIST_API_NAME = 'site_throttle_subnets'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**ServerThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle_status'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status'
str – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'id': (<class '
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerThrottleStatusList*

API_LIST_API_NAME = 'server_throttle_statuses'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSu
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleStatusList*

API_LIST_API_NAME = 'site_throttles_statuses'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottleSubnetStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status'
`str` – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'queue_delay_mil
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetStatusList*

API_LIST_API_NAME = 'site_throttle_subnet_statuss'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**HashedString**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiItem*

Automagically generated API object.

API_NAME = 'hashed_string'
`str` – Name of object used in API calls.

API_NAME_SRC = 'hashed_string'
`str` – Name of object in source file.

API_SIMPLE = {'collision_flag': (<class 'int'>,), 'error_flag': (<class 'int'>,), 'f
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'first_computer_id': <class 'pytan3.api_objects.soap_7_3_314_3424.Comp
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *HashedStringList*

API_LIST_API_NAME = 'hashed_strings'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3424.**SensorQueryList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_querys'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_query_list'
`str` – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'query'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorQuery*

class pytan3.api_objects.soap_7_3_314_3424.**SensorSubcolumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_subcolumns'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subcolumn'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorSubcolumn*

class pytan3.api_objects.soap_7_3_314_3424.**StringHintList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'string_hints'
str – Name of object used in API calls.

API_NAME_SRC = 'string_hint_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'string_hint'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**SensorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensors'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Sensor*

class pytan3.api_objects.soap_7_3_314_3424.**SensorStatList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_stats'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_stat'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorStat*

class pytan3.api_objects.soap_7_3_314_3424.**SavedActionApprovalList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_approvals'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action_approval'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedActionApproval*

class pytan3.api_objects.soap_7_3_314_3424.**SavedActionRowIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_row_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_row_id_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**SavedActionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_actions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedAction*

class pytan3.api_objects.soap_7_3_314_3424.**AuditDataList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'audit_datas'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'entry'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditData*

class pytan3.api_objects.soap_7_3_314_3424.**AuditLogList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'audit_logs'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'audit_log'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditLog*

class pytan3.api_objects.soap_7_3_314_3424.**ServerList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'servers'
str – Name of object used in API calls.

API_NAME_SRC = 'server_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Server*

class pytan3.api_objects.soap_7_3_314_3424.**ServerHost**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_host'

str – Name of object used in API calls.

API_NAME_SRC = 'server_host'

str – Name of object in source file.

API_SIMPLE = {'heart_beat_age_in_minute': (<class 'int'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'servers'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ServerList*

class pytan3.api_objects.soap_7_3_314_3424.**ServerHostList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_hosts'

str – Name of object used in API calls.

API_NAME_SRC = 'server_host_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_host'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ServerHost*

class pytan3.api_objects.soap_7_3_314_3424.**MetadataList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'metadatas'

str – Name of object used in API calls.

API_NAME_SRC = 'metadata_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'item'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *MetadataItem*

class pytan3.api_objects.soap_7_3_314_3424.**GroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'groups'

str – Name of object used in API calls.

API_NAME_SRC = 'group_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'group'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Group*

class pytan3.api_objects.soap_7_3_314_3424.**FilterList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'filters'
`str` – Name of object used in API calls.

API_NAME_SRC = 'filter_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Filter*

class pytan3.api_objects.soap_7_3_314_3424.**SelectList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'selects'
`str` – Name of object used in API calls.

API_NAME_SRC = 'select_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'select'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Select*

class pytan3.api_objects.soap_7_3_314_3424.**ErrorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'errors'
str – Name of object used in API calls.

API_NAME_SRC = 'error_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'error'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *XmlError*

class pytan3.api_objects.soap_7_3_314_3424.**QuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'questions'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Question*

class pytan3.api_objects.soap_7_3_314_3424.**PackageFileTemplateList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_templates'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file_template'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileTemplate*

class pytan3.api_objects.soap_7_3_314_3424.**PackageFileStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_statuss'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileStatus*

class pytan3.api_objects.soap_7_3_314_3424.**PackageFileList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_files'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFile*

class pytan3.api_objects.soap_7_3_314_3424.**PackageSpecList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'package_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'package_spec'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageSpec*

class pytan3.api_objects.soap_7_3_314_3424.**WhiteListedUrlList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'white_listed_urls'
str – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'white_listed_url'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *WhiteListedUrl*

class pytan3.api_objects.soap_7_3_314_3424.**VersionAggregateList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'version_aggregates'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'version'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *VersionAggregate*

class pytan3.api_objects.soap_7_3_314_3424.**SystemStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'system_status'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'aggregate': <class 'pytan3.api_objects.soap_7_3_314_3424.SystemStatusA
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'client_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ClientStatus*

class pytan3.api_objects.soap_7_3_314_3424.**SystemSettingList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'system_settings'
str – Name of object used in API calls.

API_NAME_SRC = 'system_setting_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'system_setting'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SystemSetting*

class pytan3.api_objects.soap_7_3_314_3424.**UserList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'users'
str – Name of object used in API calls.

API_NAME_SRC = 'user_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.soap_7_3_314_3424.**PermissionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'permissions'
str – Name of object used in API calls.

API_NAME_SRC = 'permission_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {'ACTION_APPROVE': 'action_approval', 'ACTION_READ': 'action_read', 'A
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'permission'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**UserRoleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'roles'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'role'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UserRole*

class pytan3.api_objects.soap_7_3_314_3424.**ActionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'actions'
str – Name of object used in API calls.

API_NAME_SRC = 'action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Action*

class pytan3.api_objects.soap_7_3_314_3424.**ActionStopList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'action_stops'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_stop'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionStop*

class pytan3.api_objects.soap_7_3_314_3424.**ArchivedQuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'archived_questions'
`str` – Name of object used in API calls.

API_NAME_SRC = 'archived_question_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'archived_question'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ArchivedQuestion*

class pytan3.api_objects.soap_7_3_314_3424.**SavedQuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_questions'
`str` – Name of object used in API calls.

API_NAME_SRC = 'saved_question_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestion*

class pytan3.api_objects.soap_7_3_314_3424.**ParseJobList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parse_jobs'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_job_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_job'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseJob*

class pytan3.api_objects.soap_7_3_314_3424.**ParseResultGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parse_result_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResultGroup*

class pytan3.api_objects.soap_7_3_314_3424.**ParseResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parse_results'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parse_result_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResult*

class pytan3.api_objects.soap_7_3_314_3424.**ParameterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parameters'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parameter_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'parameter'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Parameter*

class pytan3.api_objects.soap_7_3_314_3424.**ParameterValueList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'parameter_values'
`str` – Name of object used in API calls.

API_NAME_SRC = 'parameter_value_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**SensorReferenceList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_references'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_reference'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorReference*

class pytan3.api_objects.soap_7_3_314_3424.**PluginArgumentList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_arguments'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'argument'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginArgument*

class pytan3.api_objects.soap_7_3_314_3424.**PluginSqlResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_results'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_result_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**PluginSqlColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_columns'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_column_list'
`str` – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'name'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**PluginSql**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql'
str – Name of object in source file.

API_SIMPLE = {'result_count': (<class 'int'>,), 'rows_affected': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'columns': <class 'pytan3.api_objects.soap_7_3_314_3424.PluginSqlColum
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_row'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSqlResultList*

class pytan3.api_objects.soap_7_3_314_3424.**PluginCommandList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_commands'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_command_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'command'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**UploadFileList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'upload_files'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'upload_file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UploadFile*

class pytan3.api_objects.soap_7_3_314_3424.**PluginList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugins'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Plugin*

class pytan3.api_objects.soap_7_3_314_3424.**PluginScheduleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_schedules'
`str` – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin_schedule'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSchedule*

class pytan3.api_objects.soap_7_3_314_3424.**ComputerSpecList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'computer_specs'
`str` – Name of object used in API calls.

API_NAME_SRC = 'computer_spec_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_spec'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroupSpec*

class pytan3.api_objects.soap_7_3_314_3424.**ComputerGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'computer_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3424.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroup*

class pytan3.api_objects.soap_7_3_314_3424.**ImportConflictDetailList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_details'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_detail'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ImportConflictDetail*

class pytan3.api_objects.soap_7_3_314_3424.**CacheFilterList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'cache_filters'
`str` – Name of object used in API calls.

API_NAME_SRC = 'cache_filter_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *CacheFilter*

class pytan3.api_objects.soap_7_3_314_3424.**ImportConflictOptions**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_options'
`str` – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_options'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_option'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_sets'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSet*

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRolePrivilegeOnRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privilege_on_roles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilegeOnRole*

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_roles'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRole*

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_memberships'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_membership'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRoleMembership*

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetUserGroupRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_user_group_role_memberships'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_user_group_role_membership'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetUserGroupRoleMembership*

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_privileges'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetPrivilege*

class pytan3.api_objects.soap_7_3_314_3424.**ContentSetRolePrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privileges'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilege*

class pytan3.api_objects.soap_7_3_314_3424.**EffectiveContentSetPrivilegeRequest**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privilege_request'
`str` – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_request'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.soap_7_3_314_3424.**EffectiveContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'effective_content_set_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *EffectiveContentSetPrivilege*

class pytan3.api_objects.soap_7_3_314_3424.**DashboardList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'dashboards'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'dashboard'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Dashboard*

class pytan3.api_objects.soap_7_3_314_3424.**UserGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'user_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'user_group_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'user_group'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UserGroup*

class pytan3.api_objects.soap_7_3_314_3424.**SolutionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'solutions'
`str` – Name of object used in API calls.

API_NAME_SRC = 'solution_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'solution'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Solution*

class pytan3.api_objects.soap_7_3_314_3424.**ActionGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'action_groups'
`str` – Name of object used in API calls.

API_NAME_SRC = 'action_group_list'
`str` – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionGroup*

class pytan3.api_objects.soap_7_3_314_3424.**SavedQuestionQuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'saved_question_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestionQuestion*

class pytan3.api_objects.soap_7_3_314_3424.**LdapSyncConnectorList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'ldap_sync_connectors'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'ldap_sync_connector'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *LdapSyncConnector*

class pytan3.api_objects.soap_7_3_314_3424.**ServerThrottleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttles'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottle*

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottle*

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottleSubnetList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnets'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnet*

class pytan3.api_objects.soap_7_3_314_3424.**ServerThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttle_statuses'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottleStatus*

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles_statuses'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleStatus*

class pytan3.api_objects.soap_7_3_314_3424.**SiteThrottleSubnetStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnet_statuss'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnetStatus*

class pytan3.api_objects.soap_7_3_314_3424.**ComputerIdList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'computer_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_id_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3424.**HashedStringList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3424.ApiList*

Automagically generated API array object.

API_NAME = 'hashed_strings'
str – Name of object used in API calls.

API_NAME_SRC = 'hashed_string_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'hashed_string'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *HashedString*

pytan3.api_objects.soap_7_3_314_3424.**BUILD_META = {'date': '2019-02-22 07:46:01.956314',**
`dict` – How this module was built (date/time in UTC format).

pytan3.api_objects.soap_7_3_314_3424.**COMMANDS = ['AddObject', 'GetObject', 'MoveObject', '**
`list` of `str` – API commands.

pytan3.api_objects.soap_7_3_314_3424.**VERSION = {'build': 3424, 'major': 7, 'minor': 3,**
`dict` – Tanium API version these objects are intended to be used for.

SOAP API Object Module for Version 7.3.314.3641

Python objects for Tanium's API.

pytan3.api_objects.soap_7_3_314_3641.**float_types = (<class 'float'>,)**
`tuple` of `type` – Float types.

pytan3.api_objects.soap_7_3_314_3641.**integer_types = (<class 'int'>,)**
`tuple` of `type` – Integer types.

pytan3.api_objects.soap_7_3_314_3641.**string_types = (<class 'str'>,)**
`tuple` of `type` – String types.

pytan3.api_objects.soap_7_3_314_3641.**simple_types = (<class 'int'>, <class 'str'>, <class**
`tuple` of `type` – All types that should be considered simple types.

pytan3.api_objects.soap_7_3_314_3641.**TYPE = 'soap'**
`str` – Type of API this module was built from.

pytan3.api_objects.soap_7_3_314_3641.**API_DT = '%Y-%m-%dT%H:%M:%S'**
`str` – Datetime format for this API type and version.

pytan3.api_objects.soap_7_3_314_3641.**api_fixes**()
Fix incorrect attribute definitions on auto generated ApiModel classes.

pytan3.api_objects.soap_7_3_314_3641.**expand_cls_globals**()
Replace str values with global vars for attrs on ApiModel classes.

Quite the funky chicken dance for solving issues with order of class definition.

pytan3.api_objects.soap_7_3_314_3641.**expand_global**(*obj*)
Replace str values with global vars recursively.

Parameters **obj** (`str` or `dict` or `list`) – Object to expand into global var.

Returns String objects are the only ones that will be expanded.

Return type `str` or `dict` or `list` or `object`

pytan3.api_objects.soap_7_3_314_3641.**get_api_all_item**()
Get map of class name to class for all ApiItem subclasses.

Returns `dict`

pytan3.api_objects.soap_7_3_314_3641.**get_api_all_list**()
Get map of class name to class for all ApiList subclasses.

Returns dict

pytan3.api_objects.soap_7_3_314_3641.**get_api_all_model**()
Get map of class name to class for all ApiItem and ApiList subclasses.

Returns dict

class pytan3.api_objects.soap_7_3_314_3641.**ApiModel**
Bases: *pytan3.api_models.ApiModel*

Model for a complex item in the API.

class pytan3.api_objects.soap_7_3_314_3641.**ApiItem**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiModel*, *pytan3.api_models.ApiItem*

Model for a complex item in the API.

class pytan3.api_objects.soap_7_3_314_3641.**ApiList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiModel*, *pytan3.api_models.ApiList*

Model for an array in the API.

class pytan3.api_objects.soap_7_3_314_3641.**ResultInfoList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'result_infos'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'int'>,), 'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_info'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ResultInfo*

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.soap_7_3_314_3641.**ResultInfo**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'result_info'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'er
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'row_count', 'mr_tested', 'mr_passed'
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ResultInfoList*

API_LIST_API_NAME = 'result_infos'
str – Name of *API_LIST_CLS* used in API calls.

__repr__()
Make repr output be same as str output.

Returns str

class pytan3.api_objects.soap_7_3_314_3641.**ResultSetList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'result_sets'
str – Name of object used in API calls.

API_NAME_SRC = ''
str – Name of object in source file.

API_SIMPLE = {'now': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = ['now']
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_set'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ResultSet*

class pytan3.api_objects.soap_7_3_314_3641.**MergedResultSet**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'merged_result'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {'max_available_age': (<class 'str'>,), 'now': (<class 'str'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {'result_infos': <class 'pytan3.api_objects.soap_7_3_314_3641.ResultInf

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = ['now', 'max_available_age']

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ResultSet**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'result_set'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {'age': (<class 'int'>,), 'archived_question_id': (<class 'int'>,), 'ca

dict – Map of simple attributes to their types.

API_COMPLEX = {'cs': <class 'pytan3.api_objects.soap_7_3_314_3641.ColumnList'>, 'rs':

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = ['question_id', 'estimated_total', 'mr_tested', 'mr_passed', 'row_count'

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ResultSetList*

API_LIST_API_NAME = 'result_sets'

str – Name of *API_LIST_CLS* used in API calls.

__init__(***kwargs*)

Constructor.

Notes

Sets `Column.API_DATA_SET` so column objects can access rows.

Sets `RowColumn.API_COLUMN` to the index correlated `Column` so row columns can access the column name, result type, etc.

Sets `Column.API_IDX` and `RowColumn.API_IDX` so column objects know what their index is without having to do lookups.

Parameters ****kwargs** – Passed back to parent class.

rows

Expose complex attr "rs" as "rows".

Returns `list`

columns

Expose complex attr "cs" as "columns".

Returns `list`

class pytan3.api_objects.soap_7_3_314_3641.**ColumnList**(**args*, ***kwargs*)

Bases: `pytan3.api_objects.soap_7_3_314_3641.ApiList`

Manually defined API array object.

API_NAME = 'cs'

`str` – Name of object used in API calls.

API_NAME_SRC = ''

`str` – Name of object in source file.

API_SIMPLE = {}

`dict` – Map of simple attributes to their types.

API_COMPLEX = {}

`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}

`dict` – Map of constants to their values.

API_STR_ADD = ['names']

`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'c'

`str` – Name of `API_ITEM_CLS` used in API calls.

API_ITEM_CLS

`ApiItem`: Item class this list class holds.

alias of `Column`

__repr__()

Make repr output be same as str output.

Returns `str`

names

Expose column names of all `Column` in this obj.

Returns `list` of `str`

__getitem__(*value*)

Support indexing of `names`.

Parameters **value** (int or str) – If int: Index of item to retrieve from simple attr "c". If str: Column name to index correlate from *names*

Returns The RowColumn object at index value from *names*.

Return type *RowColumn*

class pytan3.api_objects.soap_7_3_314_3641.**Column**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Manually defined API object.

API_DATA_SET = None

ResultSet – Parent of this object, set by *ResultSet.__init__()*.

API_IDX = None

int – Index of this object in *ColumnList*.

API_NAME = 'c'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {'dn': (<class 'str'>,), 'rt': (<class 'int'>,), 'wh': (<class 'int'>,

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = ['name', 'result_type', 'hash']

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ColumnList*

API_LIST_API_NAME = 'cs'

str – Name of *API_LIST_CLS* used in API calls.

name

Expose simple attr "dn" as name.

Returns str

hash

Expose simple attr "wh" as hash.

Returns str

type

Expose simple attr "rt" as type.

Returns str

result_type

Expose simple attr "rt" as result_type.

Notes

Will try to map str from "rt" as int to constants from `Sensor.API_CONSTANTS`.

Returns `str`

get_values(*attr='value', join=None*)

Get values of this column from all rows.

Parameters

- **attr** (`str`, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (`str`, optional) – String to join multi value columns.

  Defaults to: None.

Returns `list` of `str`

class pytan3.api_objects.soap_7_3_314_3641.**RowList**(**args, **kwargs*)

Bases: `pytan3.api_objects.soap_7_3_314_3641.ApiList`

Manually defined API array object.

API_NAME = 'rs'

`str` – Name of object used in API calls.

API_NAME_SRC = ''

`str` – Name of object in source file.

API_SIMPLE = {}

`dict` – Map of simple attributes to their types.

API_COMPLEX = {}

`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}

`dict` – Map of constants to their values.

API_STR_ADD = []

`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'r'

`str` – Name of `API_ITEM_CLS` used in API calls.

API_ITEM_CLS

`ApiItem`: Item class this list class holds.

alias of `Row`

__repr__()

Make repr output be same as str output.

Returns `str`

class pytan3.api_objects.soap_7_3_314_3641.**Row**(***kwargs*)

Bases: `pytan3.api_objects.soap_7_3_314_3641.ApiItem`

Manually defined API object.

API_NAME = 'r'

`str` – Name of object used in API calls.

API_NAME_SRC = ''
`str` – Name of object in source file.

API_SIMPLE = {'cid': (<class 'int'>,), 'id': (<class 'int'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'c': <class 'pytan3.api_objects.soap_7_3_314_3641.RowColumnList'>}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = ['id', 'cid', 'columns']
`list` or `str` – Attributes to add to str formatting.

API_LIST_API_NAME = 'rs'
`str` – Name of *API_LIST_CLS* used in API calls.

API_LIST_CLS
ApiItem: Item class this list class holds.

alias of *RowList*

__repr__()
Make repr output be same as str output.

Returns `str`

__getitem__(*value*)
Support indexing of *names*.

Parameters **value** (`int` or `str`) – If int: Index of item to retrieve from *names*. If str: Column name to index correlate from *ColumnList.names*

Returns The RowColumn object at index value from *names*.

Return type *RowColumn*

names
Return the names of each row column from *RowColumn.API_COLUMN*.

Returns `list` of `str`

columns
Expose complex attr "c" as "columns".

Returns *RowColumnList*

__len__()
Expose length of *columns*.

Returns `int`

get_values(*meta=False*, *hashes=False*, *join=None*)
Get all values from all columns in this row.

Parameters

- **meta** (`bool`, optional) – Include sensor hash and result type for each column.

  Defaults to: False.

- **hashes** (`bool`, optional) – Include hashes of values.

  Defaults to: False.

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns dict

class pytan3.api_objects.soap_7_3_314_3641.**RowColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Manually defined API array object.

API_NAME = 'rc'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_columns'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *RowColumn*

api_coerce_items_hook(*attr*, *value*, *op*)

Check hook that allows subclasses to modify list items.

Parameters

- **attr** (str) – Attribute being set on this object.
- **value** (*ApiList* or list or tuple) – The list object holding items.
- **op** (str) – Operation being performed that called this method.

Examples

This converts all "v" attributes of each column for this row into a list of dicts:

```
>>> # single value columns "v" is a single dict:
>>> {"v": {"h": "", "text": ""}}
>>> # multiple value columns "v" is a list of dict:
>>> {"v": [{"h": "", "text": ""}, {"h": "", "text": ""}]}
>>> # Count columns "v" is a string:
>>> {"v": "1"}
>>> # all become:
>>> {"v": [{"text": "", "hash": ""}]}
```

Notes

The driving force behind this is basically just the Count column. It returns a string of the value, instead of a dict or a list of dicts.

Returns The list of items modified or as is.

Return type `list`

class `pytan3.api_objects.soap_7_3_314_3641.`**`RowColumn`**(**args*, ***kwargs*)

Bases: `pytan3.api_objects.soap_7_3_314_3641.ApiList`

Manually defined API array object.

`API_COLUMN = None`

`Column` – Index correlated column, set by `ResultSet.__init__()`.

`API_IDX = None`

`int` – Index of this object in `RowColumnList`.

`API_NAME = 'row_column'`

`str` – Name of object used in API calls.

`API_NAME_SRC = ''`

`str` – Name of object in source file.

`API_SIMPLE = {}`

`dict` – Map of simple attributes to their types.

`API_COMPLEX = {}`

`dict` – Map of complex attributes to their types.

`API_CONSTANTS = {}`

`dict` – Map of constants to their values.

`API_STR_ADD = ['name', 'hash', 'result_type']`

`list` or `str` – Attributes to add to str formatting.

`API_ITEM_ATTR = 'v'`

`str` – Name of `API_ITEM_CLS` used in API calls.

`API_ITEM_CLS`

`ApiItem`: Item class this list class holds.

alias of `RowValue`

`name`

Expose column name from `API_COLUMN`.

Returns `str`

`result_type`

Expose column result type from `API_COLUMN`.

Returns `str`

`hash`

Expose column sensor hash from `API_COLUMN`.

Returns `str`

`get_values`(*attr='value'*, *join=None*)

Get all values from this row column.

Parameters

- **attr** (str, optional) – Attribute to get values of.

  Defaults to: "value".

- **join** (str, optional) – String to join multi value columns.

  Defaults to: None.

Returns list or str

class pytan3.api_objects.soap_7_3_314_3641.**RowValue**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Manually defined API object.

API_NAME = 'v'

str – Name of object used in API calls.

API_NAME_SRC = ''

str – Name of object in source file.

API_SIMPLE = {'h': (<class 'int'>,), 'text': (<class 'str'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = ['hash', 'value']

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *RowColumn*

API_LIST_API_NAME = 'row_column'

str – Name of *API_LIST_CLS* used in API calls.

hash

Expose simple attr "h" as hash.

Returns str

value

Expose simple attr "text" as value.

Returns str

class pytan3.api_objects.soap_7_3_314_3641.**SensorQuery**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_query'

str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query'

str – Name of object in source file.

API_SIMPLE = {'platform': (<class 'str'>,), 'script': (<class 'str'>,), 'script_type

dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorQueryList*

API_LIST_API_NAME = 'sensor_querys'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SensorSubcolumn**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_subcolumn'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn'
str – Name of object in source file.

API_SIMPLE = {'exclude_from_parse_flag': (<class 'int'>,), 'hidden_flag': (<class 'i
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorSubcolumnList*

API_LIST_API_NAME = 'sensor_subcolumns'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SensorStat**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_stat'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<class 's
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorStatList*

API_LIST_API_NAME = 'sensor_stats'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SavedActionPolicy**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_policy'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_policy'
str – Name of object in source file.

API_SIMPLE = {'max_age': (<class 'int'>,), 'min_count': (<class 'int'>,), 'row_filte
dict – Map of simple attributes to their types.

API_COMPLEX = {'row_filter_group': <class 'pytan3.api_objects.soap_7_3_314_3641.Group
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SavedActionApproval**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action_approval'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval'
str – Name of object in source file.

API_SIMPLE = {'approved_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3641.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionApprovalList*

API_LIST_API_NAME = 'saved_action_approvals'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SavedAction**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_action'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action'
str – Name of object in source file.

API_SIMPLE = {'action_group_id': (<class 'int'>,), 'approved_flag': (<class 'int'>,)
dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.soap_7_3_314_3641.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedActionList*

API_LIST_API_NAME = 'saved_actions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Sensor**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'category': (<class 'str'>,), 'creat
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3641.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {'BES_DATETIME_RESULT': 4, 'BES_SENSOR': 2, 'DATASIZE_RESULT': 8, 'HAS
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorList*

API_LIST_API_NAME = 'sensors'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**AuditData**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'audit_data'
`str` – Name of object used in API calls.

API_NAME_SRC = 'audit_data'
`str` – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'creation_time': (<class 'str'>,), '
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'mod_user': <class 'pytan3.api_objects.soap_7_3_314_3641.User'>}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditDataList*

API_LIST_API_NAME = 'audit_datas'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**AuditLog**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'audit_log'
`str` – Name of object used in API calls.

API_NAME_SRC = 'audit_log'
`str` – Name of object in source file.

API_SIMPLE = {'end_time': (<class 'str'>,), 'id': (<class 'int'>,), 'start_time': (
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'entries': <class 'pytan3.api_objects.soap_7_3_314_3641.AuditDataList'
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *AuditLogList*

API_LIST_API_NAME = 'audit_logs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Server**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'server'
str – Name of object used in API calls.

API_NAME_SRC = 'server'
str – Name of object in source file.

API_SIMPLE = {'heart_beat': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerList*

API_LIST_API_NAME = 'servers'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**MetadataItem**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'metadata_item'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_item'
str – Name of object in source file.

API_SIMPLE = {'admin_flag': (<class 'int'>,), 'name': (<class 'str'>,), 'value': (<
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *MetadataList*

API_LIST_API_NAME = 'metadatas'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Filter**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'filter'

str – Name of object used in API calls.

API_NAME_SRC = 'filter'

str – Name of object in source file.

API_SIMPLE = {'aggregation': (<class 'str'>,), 'all_times_flag': (<class 'int'>,), '

dict – Map of simple attributes to their types.

API_COMPLEX = {'sensor': <class 'pytan3.api_objects.soap_7_3_314_3641.Sensor'>}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *FilterList*

API_LIST_API_NAME = 'filters'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**IdReference**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'id_reference'

str – Name of object used in API calls.

API_NAME_SRC = 'id_reference'

str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS = None

ApiList – List class that holds this item class.

API_LIST_API_NAME = ''

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Group**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'group'
str – Name of object used in API calls.

API_NAME_SRC = 'group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'filters': <class 'pytan3.api_objects.soap_7_3_314_3641.FilterList'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *GroupList*

API_LIST_API_NAME = 'groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Select**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'select'
str – Name of object used in API calls.

API_NAME_SRC = 'select'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'filter': <class 'pytan3.api_objects.soap_7_3_314_3641.Filter'>, 'grou
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SelectList*

API_LIST_API_NAME = 'selects'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**XmlError**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'xml_error'
str – Name of object used in API calls.

API_NAME_SRC = 'xml_error'
str – Name of object in source file.

API_SIMPLE = {'error_context': (<class 'str'>,), 'exception': (<class 'str'>,), 'typ
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ErrorList*

API_LIST_API_NAME = 'errors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**CacheInfo**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'cache_info'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_info'
str – Name of object in source file.

API_SIMPLE = {'cache_id': (<class 'int'>,), 'cache_row_count': (<class 'int'>,), 'exp
dict – Map of simple attributes to their types.

API_COMPLEX = {'errors': <class 'pytan3.api_objects.soap_7_3_314_3641.ErrorList'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**QuestionListInfo**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'question_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Question**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'question'
str – Name of object used in API calls.

API_NAME_SRC = 'question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'cache_row_id': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'context_group': <class 'pytan3.api_objects.soap_7_3_314_3641.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *QuestionList*

API_LIST_API_NAME = 'questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**PackageFileTemplate**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_template'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template'
str – Name of object in source file.

API_SIMPLE = {'download_seconds': (<class 'int'>,), 'hash': (<class 'str'>,), 'name'
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileTemplateList*

API_LIST_API_NAME = 'package_file_templates'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**PackageFileStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileStatusList*

API_LIST_API_NAME = 'package_file_statuss'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**PackageFile**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_file'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file'
str – Name of object in source file.

API_SIMPLE = {'bytes_downloaded': (<class 'int'>,), 'bytes_total': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_status': <class 'pytan3.api_objects.soap_7_3_314_3641.PackageFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageFileList*

API_LIST_API_NAME = 'package_files'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**PackageSpec**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'package_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'package_spec'
str – Name of object in source file.

API_SIMPLE = {'available_time': (<class 'str'>,), 'cache_row_id': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3641.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PackageSpecList*

API_LIST_API_NAME = 'package_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ClientStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'client_status'
str – Name of object used in API calls.

API_NAME_SRC = 'client_status'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'computer_id': (<class 'str'>,), 'fu
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemStatusList*

API_LIST_API_NAME = 'system_status'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SystemSetting**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'system_setting'
`str` – Name of object used in API calls.

API_NAME_SRC = 'system_setting'
`str` – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'default_value': (<class 'str'>,), '
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'audit_data': <class 'pytan3.api_objects.soap_7_3_314_3641.AuditData'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SystemSettingList*

API_LIST_API_NAME = 'system_settings'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SoapError**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'soap_error'
`str` – Name of object used in API calls.

API_NAME_SRC = 'soap_error'
`str` – Name of object in source file.

API_SIMPLE = {'context': (<class 'str'>,), 'exception_name': (<class 'str'>,), 'obje
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**WhiteListedUrl**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'white_listed_url'

str – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url'

str – Name of object in source file.

API_SIMPLE = {'chunk_id': (<class 'str'>,), 'download_seconds': (<class 'int'>,), 'e

dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3641.MetadataList'

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *WhiteListedUrlList*

API_LIST_API_NAME = 'white_listed_urls'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**VersionAggregate**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'version_aggregate'

str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate'

str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,), 'filtered': (<class 'int'>,), 'version_stri

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *VersionAggregateList*

API_LIST_API_NAME = 'version_aggregates'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SystemStatusAggregate**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'system_status_aggregate'
`str` – Name of object used in API calls.

API_NAME_SRC = 'system_status_aggregate'
`str` – Name of object in source file.

API_SIMPLE = {'blocked_count': (<class 'int'>,), 'leader_count': (<class 'int'>,), '
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'versions': <class 'pytan3.api_objects.soap_7_3_314_3641.VersionAggrega
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS = None
`ApiList` – List class that holds this item class.

API_LIST_API_NAME = ''
`str` – Name of *`API_LIST_CLS`* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**UserRole**(***kwargs*)
Bases: *`pytan3.api_objects.soap_7_3_314_3641.ApiItem`*

Automagically generated API object.

API_NAME = 'user_role'
`str` – Name of object used in API calls.

API_NAME_SRC = 'user_role'
`str` – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cla
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'permissions': <class 'pytan3.api_objects.soap_7_3_314_3641.Permission
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
`ApiList`: List class that holds this item class.

alias of *`UserRoleList`*

API_LIST_API_NAME = 'roles'
`str` – Name of *`API_LIST_CLS`* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**UserOwnedObjectIds**(***kwargs*)
Bases: *`pytan3.api_objects.soap_7_3_314_3641.ApiItem`*

Automagically generated API object.

API_NAME = 'user_owned_object_ids'
`str` – Name of object used in API calls.

API_NAME_SRC = 'user_owned_object_ids'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'plugin_schedules': <class 'pytan3.api_objects.soap_7_3_314_3641.Plugi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**User**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'user'
str – Name of object used in API calls.

API_NAME_SRC = 'user'
str – Name of object in source file.

API_SIMPLE = {'active_session_count': (<class 'int'>,), 'deleted_flag': (<class 'int
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.soap_7_3_314_3641.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserList*

API_LIST_API_NAME = 'users'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ActionListInfo**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action_list_info'
str – Name of object used in API calls.

API_NAME_SRC = 'action_list_info'
str – Name of object in source file.

API_SIMPLE = {'highest_id': (<class 'int'>,), 'total_count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Action**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action'
str – Name of object used in API calls.

API_NAME_SRC = 'action'
str – Name of object in source file.

API_SIMPLE = {'cache_row_id': (<class 'int'>,), 'comment': (<class 'str'>,), 'creati
dict – Map of simple attributes to their types.

API_COMPLEX = {'action_group': <class 'pytan3.api_objects.soap_7_3_314_3641.Group'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionList*

API_LIST_API_NAME = 'actions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ActionStop**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action_stop'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.soap_7_3_314_3641.Action'>}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionStopList*

API_LIST_API_NAME = 'action_stops'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ArchivedQuestion**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'archived_question'
str – Name of object used in API calls.

API_NAME_SRC = 'archived_question'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ArchivedQuestionList*

API_LIST_API_NAME = 'archived_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SavedQuestion**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question'
str – Name of object in source file.

API_SIMPLE = {'action_tracking_flag': (<class 'int'>,), 'archive_enabled_flag': (<cla
dict – Map of simple attributes to their types.

API_COMPLEX = {'archive_owner': <class 'pytan3.api_objects.soap_7_3_314_3641.User'>,
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionList*

API_LIST_API_NAME = 'saved_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ParseJob**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parse_job'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_job'
str – Name of object in source file.

API_SIMPLE = {'parser_version': (<class 'int'>,), 'question_text': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseJobList*

API_LIST_API_NAME = 'parse_jobs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Parameter**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parameter'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter'
str – Name of object in source file.

API_SIMPLE = {'key': (<class 'str'>,), 'type': (<class 'int'>,), 'value': (<class '
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParameterList*

API_LIST_API_NAME = 'parameters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ParseResult**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'parameter_definition': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameters': <class 'pytan3.api_objects.soap_7_3_314_3641.ParameterLi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultList*

API_LIST_API_NAME = 'parse_results'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SensorReference**(**kwargs)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'sensor_reference'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference'
str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'real_ms_avg': (<class 'int'>,), 'start_char
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SensorReferenceList*

API_LIST_API_NAME = 'sensor_references'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ParseResultGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'parse_result_group'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group'
str – Name of object in source file.

API_SIMPLE = {'question_text': (<class 'str'>,), 'score': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'parameter_values': <class 'pytan3.api_objects.soap_7_3_314_3641.Param
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ParseResultGroupList*

API_LIST_API_NAME = 'parse_result_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ClientCount**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'client_count'
str – Name of object used in API calls.

API_NAME_SRC = 'client_count'
str – Name of object in source file.

API_SIMPLE = {'count': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**PluginArgument**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_argument'

str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument'

str – Name of object in source file.

API_SIMPLE = {'name': (<class 'str'>,), 'type': (<class 'str'>,), 'value': (<class

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *PluginArgumentList*

API_LIST_API_NAME = 'plugin_arguments'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**UploadFile**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file'

str – Name of object used in API calls.

API_NAME_SRC = 'upload_file'

str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'destination_file': (<class 'str'>,), 'file_

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *UploadFileList*

API_LIST_API_NAME = 'upload_files'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**UploadFileStatus**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'upload_file_status'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_status'
str – Name of object in source file.

API_SIMPLE = {'file_cached': (<class 'int'>,), 'hash': (<class 'str'>,), 'percent_co
dict – Map of simple attributes to their types.

API_COMPLEX = {'file_parts': <class 'pytan3.api_objects.soap_7_3_314_3641.UploadFileL
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Plugin**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'plugin'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin'
str – Name of object in source file.

API_SIMPLE = {'allow_rest': (<class 'int'>,), 'bundle': (<class 'str'>,), 'cache_row_
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.soap_7_3_314_3641.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {'SCRIPT': 'Script', 'SQL': 'SQL'}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginList*

API_LIST_API_NAME = 'plugins'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**PluginSchedule**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'plugin_schedule'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'enabled': (<class 'int'>,), 'end_da
dict – Map of simple attributes to their types.

API_COMPLEX = {'arguments': <class 'pytan3.api_objects.soap_7_3_314_3641.PluginArgume
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *PluginScheduleList*

API_LIST_API_NAME = 'plugin_schedules'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ComputerGroupSpec**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group_spec'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_spec'
str – Name of object in source file.

API_SIMPLE = {'computer_name': (<class 'str'>,), 'id': (<class 'int'>,), 'ip_address
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ComputerSpecList*

API_LIST_API_NAME = 'computer_specs'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ComputerGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'computer_group'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'id': (<class 'int'>,), 'name': (<c
dict – Map of simple attributes to their types.

API_COMPLEX = {'computer_specs': <class 'pytan3.api_objects.soap_7_3_314_3641.Compute
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ComputerGroupList*

API_LIST_API_NAME = 'computer_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**VerifySignature**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'verify_signature'
str – Name of object used in API calls.

API_NAME_SRC = 'verify_signature'
str – Name of object in source file.

API_SIMPLE = {'bytes': (<class 'str'>,), 'id': (<class 'int'>,), 'type': (<class 's
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ObjectList**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'object_list'
str – Name of object used in API calls.

API_NAME_SRC = 'object_list'
str – Name of object in source file.

API_SIMPLE = {'export_id': (<class 'str'>,), 'export_version': (<class 'int'>,), 'imp
dict – Map of simple attributes to their types.

API_COMPLEX = {'action': <class 'pytan3.api_objects.soap_7_3_314_3641.Action'>, 'acti
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ImportConflictDetail**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'import_conflict_detail'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail'
str – Name of object in source file.

API_SIMPLE = {'diff': (<class 'str'>,), 'is_new': (<class 'int'>,), 'name': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ImportConflictDetailList*

API_LIST_API_NAME = 'import_conflict_details'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**CacheFilter**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'cache_filter'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'field': (<class 'str'>,), 'not_flag':
dict – Map of simple attributes to their types.

API_COMPLEX = {'sub_filters': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheFilte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *CacheFilterList*

API_LIST_API_NAME = 'cache_filters'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Options**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'options'
str – Name of object used in API calls.

API_NAME_SRC = 'options'
str – Name of object in source file.

API_SIMPLE = {'aggregate_by_value_flag': (<class 'int'>,), 'aggregate_over_time_flag'
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_filters': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheFil
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set'
str – Name of object in source file.

API_SIMPLE = {'description': (<class 'str'>,), 'id': (<class 'int'>,), 'name': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3641.MetadataList'
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetList*

API_LIST_API_NAME = 'content_sets'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRolePrivilegeOnRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege_on_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3641.IdReferenc
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeOnRoleList*

API_LIST_API_NAME = 'content_set_role_privilege_on_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRole**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role'
str – Name of object in source file.

API_SIMPLE = {'all_content_sets_flag': (<class 'int'>,), 'category': (<class 'str'>,
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role_privileges': <class 'pytan3.api_objects.soap_7_3_314
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRoleList*

API_LIST_API_NAME = 'content_set_roles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRoleMembership**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_membership'

str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership'

str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.soap_7_3_314_3641.IdRef

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ContentSetRoleMembershipList*

API_LIST_API_NAME = 'content_set_role_memberships'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetUserGroupRoleMembership**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_user_group_role_membership'

str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership'

str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}

dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_role': <class 'pytan3.api_objects.soap_7_3_314_3641.IdRef

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *ContentSetUserGroupRoleMembershipList*

API_LIST_API_NAME = 'content_set_user_group_role_memberships'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetPrivilege**(***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_privilege'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'privilege_module':
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'metadata': <class 'pytan3.api_objects.soap_7_3_314_3641.MetadataList'
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetPrivilegeList*

API_LIST_API_NAME = 'content_set_privileges'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRolePrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'content_set_role_privilege'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege'
`str` – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3641.IdReferenc
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ContentSetRolePrivilegeList*

API_LIST_API_NAME = 'content_set_role_privileges'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**EffectiveContentSetPrivilege**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'effective_content_set_privilege'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3641.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *EffectiveContentSetPrivilegeList*

API_LIST_API_NAME = 'effective_content_set_privileges'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Dashboard**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,), 'public_flag': (<cl
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3641.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *DashboardList*

API_LIST_API_NAME = 'dashboards'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**DashboardGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'dashboard_group'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_group'
str – Name of object in source file.

API_SIMPLE = {'display_index': (<class 'int'>,), 'editable_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set': <class 'pytan3.api_objects.soap_7_3_314_3641.ContentSet
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**UserGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'user_group'
str – Name of object used in API calls.

API_NAME_SRC = 'user_group'
str – Name of object in source file.

API_SIMPLE = {'deleted_flag': (<class 'int'>,), 'exclusive_flag': (<class 'int'>,),
dict – Map of simple attributes to their types.

API_COMPLEX = {'content_set_roles': <class 'pytan3.api_objects.soap_7_3_314_3641.Conte
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *UserGroupList*

API_LIST_API_NAME = 'user_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**Solution**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'solution'
str – Name of object used in API calls.

API_NAME_SRC = 'solution'
str – Name of object in source file.

API_SIMPLE = {'category': (<class 'str'>,), 'delete_xml_url': (<class 'str'>,), 'del
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SolutionList*

API_LIST_API_NAME = 'solutions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ActionGroup**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'action_group'
str – Name of object used in API calls.

API_NAME_SRC = 'action_group'
str – Name of object in source file.

API_SIMPLE = {'and_flag': (<class 'int'>,), 'deleted_flag': (<class 'int'>,), 'id':
dict – Map of simple attributes to their types.

API_COMPLEX = {'groups': <class 'pytan3.api_objects.soap_7_3_314_3641.GroupList'>, 'u
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ActionGroupList*

API_LIST_API_NAME = 'action_groups'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SavedQuestionPackageSpecs**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_package_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_package_specs'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'packages': <class 'pytan3.api_objects.soap_7_3_314_3641.PackageSpecLi
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS = None
ApiList – List class that holds this item class.

API_LIST_API_NAME = ''
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SavedQuestionQuestion**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'saved_question_question'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'questions': <class 'pytan3.api_objects.soap_7_3_314_3641.QuestionList
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SavedQuestionQuestionList*

API_LIST_API_NAME = 'saved_question_questions'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**LdapSyncConnector**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'ldap_sync_connector'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector'
str – Name of object in source file.

API_SIMPLE = {'base_groups': (<class 'str'>,), 'base_users': (<class 'str'>,), 'disa
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *LdapSyncConnectorList*

API_LIST_API_NAME = 'ldap_sync_connectors'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ServerThrottle**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle'
str – Name of object in source file.

API_SIMPLE = {'bandwidth_bytes_limit': (<class 'int'>,), 'connection_limit': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerThrottleList*

API_LIST_API_NAME = 'server_throttles'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottle**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle'
str – Name of object in source file.

API_SIMPLE = {'all_subnets_flag': (<class 'int'>,), 'bandwidth_bytes_limit': (<class
dict – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSu
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleList*

API_LIST_API_NAME = 'site_throttles'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottleSubnet**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet'
`str` – Name of object in source file.

API_SIMPLE = {'range': (<class 'str'>,)}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetList*

API_LIST_API_NAME = 'site_throttle_subnets'
`str` – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**ServerThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'server_throttle_status'
`str` – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status'
`str` – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'id': (<class '
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *ServerThrottleStatusList*

API_LIST_API_NAME = 'server_throttle_statuses'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottleStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status'
str – Name of object in source file.

API_SIMPLE = {'id': (<class 'int'>,), 'name': (<class 'str'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'subnets': <class 'pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSu
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleStatusList*

API_LIST_API_NAME = 'site_throttles_statuses'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottleSubnetStatus**(***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'site_throttle_subnet_status'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status'
str – Name of object in source file.

API_SIMPLE = {'download_queue_delay_milliseconds': (<class 'int'>,), 'queue_delay_mil
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_LIST_CLS
ApiList: List class that holds this item class.

alias of *SiteThrottleSubnetStatusList*

API_LIST_API_NAME = 'site_throttle_subnet_statuss'
str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**HashedString**(**kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiItem*

Automagically generated API object.

API_NAME = 'hashed_string'

str – Name of object used in API calls.

API_NAME_SRC = 'hashed_string'

str – Name of object in source file.

API_SIMPLE = {'collision_flag': (<class 'int'>,), 'error_flag': (<class 'int'>,), 'f

dict – Map of simple attributes to their types.

API_COMPLEX = {'first_computer_id': <class 'pytan3.api_objects.soap_7_3_314_3641.Comp

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_LIST_CLS

ApiList: List class that holds this item class.

alias of *HashedStringList*

API_LIST_API_NAME = 'hashed_strings'

str – Name of *API_LIST_CLS* used in API calls.

class pytan3.api_objects.soap_7_3_314_3641.**SensorQueryList**(*args, **kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_querys'

str – Name of object used in API calls.

API_NAME_SRC = 'sensor_query_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'query'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *SensorQuery*

class pytan3.api_objects.soap_7_3_314_3641.**SensorSubcolumnList**(*args, **kwargs)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_subcolumns'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_subcolumn_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'subcolumn'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorSubcolumn*

class pytan3.api_objects.soap_7_3_314_3641.**StringHintList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'string_hints'
`str` – Name of object used in API calls.

API_NAME_SRC = 'string_hint_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'string_hint'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**SensorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensors'
`str` – Name of object used in API calls.

API_NAME_SRC = 'sensor_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Sensor*

class pytan3.api_objects.soap_7_3_314_3641.**SensorStatList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_stats'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_stat_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_stat'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorStat*

class pytan3.api_objects.soap_7_3_314_3641.**SavedActionApprovalList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_approvals'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_approval_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action_approval'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedActionApproval*

class pytan3.api_objects.soap_7_3_314_3641.**SavedActionRowIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_action_row_ids'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_row_id_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'row_id'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**SavedActionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_actions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_action'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedAction*

class pytan3.api_objects.soap_7_3_314_3641.**AuditDataList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'audit_datas'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_data_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'entry'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditData*

class pytan3.api_objects.soap_7_3_314_3641.**AuditLogList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'audit_logs'
str – Name of object used in API calls.

API_NAME_SRC = 'audit_log_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'audit_log'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *AuditLog*

class pytan3.api_objects.soap_7_3_314_3641.**ServerList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'servers'
str – Name of object used in API calls.

API_NAME_SRC = 'server_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Server*

class pytan3.api_objects.soap_7_3_314_3641.**ServerHost**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_host'
str – Name of object used in API calls.

API_NAME_SRC = 'server_host'
str – Name of object in source file.

API_SIMPLE = {'heart_beat_age_in_minute': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'servers'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerList*

class pytan3.api_objects.soap_7_3_314_3641.**ServerHostList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_hosts'
str – Name of object used in API calls.

API_NAME_SRC = 'server_host_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_host'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerHost*

class pytan3.api_objects.soap_7_3_314_3641.**MetadataList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'metadatas'
str – Name of object used in API calls.

API_NAME_SRC = 'metadata_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'item'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *MetadataItem*

class pytan3.api_objects.soap_7_3_314_3641.**GroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'groups'
str – Name of object used in API calls.

API_NAME_SRC = 'group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Group*

class pytan3.api_objects.soap_7_3_314_3641.**FilterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'filters'
str – Name of object used in API calls.

API_NAME_SRC = 'filter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Filter*

class pytan3.api_objects.soap_7_3_314_3641.**SelectList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'selects'
str – Name of object used in API calls.

API_NAME_SRC = 'select_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'select'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Select*

class pytan3.api_objects.soap_7_3_314_3641.**ErrorList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'errors'
str – Name of object used in API calls.

API_NAME_SRC = 'error_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'error'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *XmlError*

class pytan3.api_objects.soap_7_3_314_3641.**QuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'questions'
str – Name of object used in API calls.

API_NAME_SRC = 'question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Question*

class pytan3.api_objects.soap_7_3_314_3641.**PackageFileTemplateList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_templates'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_template_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file_template'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileTemplate*

class pytan3.api_objects.soap_7_3_314_3641.**PackageFileStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_file_statuss'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFileStatus*

class pytan3.api_objects.soap_7_3_314_3641.**PackageFileList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_files'
str – Name of object used in API calls.

API_NAME_SRC = 'package_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageFile*

class pytan3.api_objects.soap_7_3_314_3641.**PackageSpecList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'package_specs'
`str` – Name of object used in API calls.

API_NAME_SRC = 'package_spec_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'package_spec'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PackageSpec*

class pytan3.api_objects.soap_7_3_314_3641.**WhiteListedUrlList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'white_listed_urls'
`str` – Name of object used in API calls.

API_NAME_SRC = 'white_listed_url_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'white_listed_url'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *WhiteListedUrl*

class pytan3.api_objects.soap_7_3_314_3641.**VersionAggregateList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'version_aggregates'
str – Name of object used in API calls.

API_NAME_SRC = 'version_aggregate_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'version'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *VersionAggregate*

class pytan3.api_objects.soap_7_3_314_3641.**SystemStatusList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'system_status'
str – Name of object used in API calls.

API_NAME_SRC = 'system_status_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'aggregate': <class 'pytan3.api_objects.soap_7_3_314_3641.SystemStatus
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'client_status'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ClientStatus*

class pytan3.api_objects.soap_7_3_314_3641.**SystemSettingList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'system_settings'
str – Name of object used in API calls.

API_NAME_SRC = 'system_setting_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'system_setting'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SystemSetting*

class pytan3.api_objects.soap_7_3_314_3641.**UserList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'users'
str – Name of object used in API calls.

API_NAME_SRC = 'user_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.soap_7_3_314_3641.**PermissionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'permissions'
str – Name of object used in API calls.

API_NAME_SRC = 'permission_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {'ACTION_APPROVE': 'action_approval', 'ACTION_READ': 'action_read', 'A
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'permission'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**UserRoleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'roles'
str – Name of object used in API calls.

API_NAME_SRC = 'user_role_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'role'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UserRole*

class pytan3.api_objects.soap_7_3_314_3641.**ActionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'actions'
str – Name of object used in API calls.

API_NAME_SRC = 'action_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Action*

class pytan3.api_objects.soap_7_3_314_3641.**ActionStopList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'action_stops'
str – Name of object used in API calls.

API_NAME_SRC = 'action_stop_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_stop'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ActionStop*

class pytan3.api_objects.soap_7_3_314_3641.**ArchivedQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'archived_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'archived_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'archived_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ArchivedQuestion*

class pytan3.api_objects.soap_7_3_314_3641.**SavedQuestionList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestion*

class pytan3.api_objects.soap_7_3_314_3641.**ParseJobList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parse_jobs'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_job_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_job'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseJob*

class pytan3.api_objects.soap_7_3_314_3641.**ParseResultGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parse_result_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResultGroup*

class pytan3.api_objects.soap_7_3_314_3641.**ParseResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parse_results'
str – Name of object used in API calls.

API_NAME_SRC = 'parse_result_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parse_result'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ParseResult*

class pytan3.api_objects.soap_7_3_314_3641.**ParameterList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parameters'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'parameter'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Parameter*

class pytan3.api_objects.soap_7_3_314_3641.**ParameterValueList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'parameter_values'
str – Name of object used in API calls.

API_NAME_SRC = 'parameter_value_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**SensorReferenceList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'sensor_references'
str – Name of object used in API calls.

API_NAME_SRC = 'sensor_reference_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'sensor_reference'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SensorReference*

class pytan3.api_objects.soap_7_3_314_3641.**PluginArgumentList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_arguments'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_argument_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'argument'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginArgument*

class pytan3.api_objects.soap_7_3_314_3641.**PluginSqlResultList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_results'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_result_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'value'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**PluginSqlColumnList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql_columns'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql_column_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'name'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**PluginSql**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_sql'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_sql'
str – Name of object in source file.

API_SIMPLE = {'result_count': (<class 'int'>,), 'rows_affected': (<class 'int'>,)}
dict – Map of simple attributes to their types.

API_COMPLEX = {'columns': <class 'pytan3.api_objects.soap_7_3_314_3641.PluginSqlColum
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'result_row'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSqlResultList*

class pytan3.api_objects.soap_7_3_314_3641.**PluginCommandList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_commands'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_command_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'command'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'str'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**UploadFileList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'upload_files'
str – Name of object used in API calls.

API_NAME_SRC = 'upload_file_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'upload_file'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UploadFile*

class pytan3.api_objects.soap_7_3_314_3641.**PluginList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugins'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Plugin*

class pytan3.api_objects.soap_7_3_314_3641.**PluginScheduleList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'plugin_schedules'
str – Name of object used in API calls.

API_NAME_SRC = 'plugin_schedule_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'plugin_schedule'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *PluginSchedule*

class pytan3.api_objects.soap_7_3_314_3641.**ComputerSpecList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'computer_specs'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_spec_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_spec'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroupSpec*

class pytan3.api_objects.soap_7_3_314_3641.**ComputerGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'computer_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'computer_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {'cache_info': <class 'pytan3.api_objects.soap_7_3_314_3641.CacheInfo'>
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'computer_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ComputerGroup*

class pytan3.api_objects.soap_7_3_314_3641.**ImportConflictDetailList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_details'
str – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_detail_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_detail'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ImportConflictDetail*

class pytan3.api_objects.soap_7_3_314_3641.**CacheFilterList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'cache_filters'
str – Name of object used in API calls.

API_NAME_SRC = 'cache_filter_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'filter'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *CacheFilter*

class pytan3.api_objects.soap_7_3_314_3641.**ImportConflictOptions**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'import_conflict_options'
`str` – Name of object used in API calls.

API_NAME_SRC = 'import_conflict_options'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'import_conflict_option'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_sets'
`str` – Name of object used in API calls.

API_NAME_SRC = 'content_set_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSet*

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRolePrivilegeOnRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privilege_on_roles'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_on_role_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilegeOnRole*

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRoleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_roles'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRole*

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_memberships'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_membership_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_membership'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRoleMembership*

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetUserGroupRoleMembershipList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_user_group_role_memberships'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_user_group_role_membership_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_user_group_role_membership'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetUserGroupRoleMembership*

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetPrivilege*

class pytan3.api_objects.soap_7_3_314_3641.**ContentSetRolePrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'content_set_role_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'content_set_role_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'content_set_role_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ContentSetRolePrivilege*

class pytan3.api_objects.soap_7_3_314_3641.**EffectiveContentSetPrivilegeRequest**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privilege_request'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_request'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *User*

class pytan3.api_objects.soap_7_3_314_3641.**EffectiveContentSetPrivilegeList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'effective_content_set_privileges'
str – Name of object used in API calls.

API_NAME_SRC = 'effective_content_set_privilege_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'effective_content_set_privilege'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *EffectiveContentSetPrivilege*

class pytan3.api_objects.soap_7_3_314_3641.**DashboardList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'dashboards'
str – Name of object used in API calls.

API_NAME_SRC = 'dashboard_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'dashboard'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *Dashboard*

class pytan3.api_objects.soap_7_3_314_3641.**UserGroupList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'user_groups'
str – Name of object used in API calls.

API_NAME_SRC = 'user_group_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'user_group'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *UserGroup*

class pytan3.api_objects.soap_7_3_314_3641.**SolutionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'solutions'

str – Name of object used in API calls.

API_NAME_SRC = 'solution_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'solution'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *Solution*

class pytan3.api_objects.soap_7_3_314_3641.**ActionGroupList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'action_groups'

str – Name of object used in API calls.

API_NAME_SRC = 'action_group_list'

str – Name of object in source file.

API_SIMPLE = {}

dict – Map of simple attributes to their types.

API_COMPLEX = {}

dict – Map of complex attributes to their types.

API_CONSTANTS = {}

dict – Map of constants to their values.

API_STR_ADD = []

list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'action_group'

str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS

ApiItem: Item class this list class holds.

alias of *ActionGroup*

class pytan3.api_objects.soap_7_3_314_3641.**SavedQuestionQuestionList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'saved_question_questions'
str – Name of object used in API calls.

API_NAME_SRC = 'saved_question_question_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'saved_question_question'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SavedQuestionQuestion*

class pytan3.api_objects.soap_7_3_314_3641.**LdapSyncConnectorList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'ldap_sync_connectors'
str – Name of object used in API calls.

API_NAME_SRC = 'ldap_sync_connector_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'ldap_sync_connector'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *LdapSyncConnector*

class pytan3.api_objects.soap_7_3_314_3641.**ServerThrottleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttles'
str – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottle*

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottleList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles'
str – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_list'
str – Name of object in source file.

API_SIMPLE = {}
dict – Map of simple attributes to their types.

API_COMPLEX = {}
dict – Map of complex attributes to their types.

API_CONSTANTS = {}
dict – Map of constants to their values.

API_STR_ADD = []
list or str – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle'
str – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottle*

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottleSubnetList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnets'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnet*

class pytan3.api_objects.soap_7_3_314_3641.**ServerThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'server_throttle_statuses'
`str` – Name of object used in API calls.

API_NAME_SRC = 'server_throttle_status_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'server_throttle_status'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *ServerThrottleStatus*

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottleStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttles_statuses'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_status_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'site_throttle_status'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleStatus*

class pytan3.api_objects.soap_7_3_314_3641.**SiteThrottleSubnetStatusList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'site_throttle_subnet_statuss'
`str` – Name of object used in API calls.

API_NAME_SRC = 'site_throttle_subnet_status_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'subnet'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *SiteThrottleSubnetStatus*

class pytan3.api_objects.soap_7_3_314_3641.**ComputerIdList**(**args*, ***kwargs*)

Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'computer_ids'
`str` – Name of object used in API calls.

API_NAME_SRC = 'computer_id_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'id'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS = (<class 'int'>,)
ApiItem – Item class this list class holds.

class pytan3.api_objects.soap_7_3_314_3641.**HashedStringList**(**args*, ***kwargs*)
Bases: *pytan3.api_objects.soap_7_3_314_3641.ApiList*

Automagically generated API array object.

API_NAME = 'hashed_strings'
`str` – Name of object used in API calls.

API_NAME_SRC = 'hashed_string_list'
`str` – Name of object in source file.

API_SIMPLE = {}
`dict` – Map of simple attributes to their types.

API_COMPLEX = {}
`dict` – Map of complex attributes to their types.

API_CONSTANTS = {}
`dict` – Map of constants to their values.

API_STR_ADD = []
`list` or `str` – Attributes to add to str formatting.

API_ITEM_ATTR = 'hashed_string'
`str` – Name of *API_ITEM_CLS* used in API calls.

API_ITEM_CLS
ApiItem: Item class this list class holds.

alias of *HashedString*

pytan3.api_objects.soap_7_3_314_3641.**BUILD_META = {'date': '2019-02-22 07:46:08.408656',**
`dict` – How this module was built (date/time in UTC format).

pytan3.api_objects.soap_7_3_314_3641.**COMMANDS = ['AddObject', 'GetObject', 'MoveObject', '**
`list` of `str` – API commands.

pytan3.api_objects.soap_7_3_314_3641.**VERSION = {'build': 3641, 'major': 7, 'minor': 3,**
`dict` – Tanium API version these objects are intended to be used for.

1.10.6 Models for API Object Modules

Models for Python objects in Tanium's API.

pytan3.api_models.**float_types = (<class 'float'>,)**
tuple of type – Float types.

pytan3.api_models.**integer_types = (<class 'int'>,)**
tuple of type – Integer types.

pytan3.api_models.**simple_types = (<class 'int'>, <class 'str'>, <class 'float'>)**
tuple of type – All types that should be considered simple types.

pytan3.api_models.**string_types = (<class 'str'>,)**
tuple of type – String types.

Base class for all API Objects

class pytan3.api_models.**ApiModel**
Bases: object

Base class for all models in the API.

API_NAME = None
str – Name of object used in API calls.

API_NAME_SRC = None
str – Name of object in source file.

API_SIMPLE = None
dict – Map of simple attributes to their types.

API_COMPLEX = None
dict – Map of complex attributes to their types.

API_CONSTANTS = None
dict – Map of constants to their values.

API_STR_ADD = None
list or str – Added to *API_STR* in str.

T_ATTR_REPR = '{attr}={value!r}'
str – Template for simple attrs in str and all attr in repr.

T_ATTR_STR = '{attr}={value}'
str – Template for complex attrs in str.

T_ATTR_JOIN = ', '
str – String used to join attr vals in str and repr.

T_CLS_STR = '{obj.__class__.__name__}({attrs})'
str – Template for class name and attrs in str.

T_CLS_REPR = '{obj.__class__.__name__}({attrs})'
str – Template for class name and attrs in repr.

T_ATTR_DESC = ' - {api_type} attribute {attr!r} of type {attr_type!r}'
str – Template for attr line in *api_attrs_desc()*.

T_DESC = 'Defined attributes:'
str – Template for first line in *api_attrs_desc()*.

API_STR = ['id', 'name', 'display_name', 'value', 'type', 'public_flag', 'hidden_flag'
list of str – Attrs to display in str or to put first in repr.

__copy__()
Support shallow copy for self.

Returns *ApiItem*

__deepcopy__(*memo*)
Support deep copy for self.

Returns *ApiItem*

__eq__(*value*)
Support for self == value.

Parameters **value** (dict or list or *ApiModel* or object) – Value for comparison.

Notes

- If value is a dict, it will be turned into an ApiModel.
- If this object is an ApiList and value is a list, it will be turned into an ApiList.
- If value is turned into or already is an ApiModel, it will be serialized into a dict/list.
- Finally, actual comparison of value is done against this object serialized into a dict/list.

Returns bool

__ne__(*value*)
Support for self != value.

Parameters **value** (dict or list or *ApiModel* or object) – Value for comparison.

Returns bool

classmethod api_attrs()
Get simple and complex attributes combined.

Returns dict

classmethod api_attrs_repr()
Get attributes for repr formatting.

Notes

Will return attrs without dupes in order of priority to show on format string from *API_STR*, *API_STR_ADD*, and *api_attrs()*.

Returns list of str

classmethod api_attrs_str()
Get attributes for str formatting.

Notes

Will return attrs without dupes in order of priority to show on format string from *API_STR* and *API_STR_ADD*.

If no attrs from *API_STR* and *API_STR_ADD* exist in *api_attrs()*, return all attrs from *api_attrs()*.

Returns `list` of `str`

classmethod api_attrs_desc()

Get description of attrs from *API_SIMPLE* and *API_COMPLEX*.

Notes

Used by exceptions to add defined attributes to error messages.

Returns `list` of `str`

classmethod api_coerce_int(*value*)

Try to coerce value into `int` if possible.

Parameters **value** (`object`) – Object to coerce into int.

Returns `int` or `object` if unchanged.

classmethod api_coerce_float(*value*)

Try to coerce value into `float` if possible.

Parameters **value** (`object`) – Object to coerce into float.

Returns `float` or `object` if unchanged.

classmethod api_coerce_list(*value*)

Coerce value into `list` if it is not already.

Parameters **value** (`object`) – Object to coerce into list. If value is None, will return empty list.

Returns `list` or `object` if unchanged.

classmethod api_coerce_simple(*value*, *be_type*)

Try to coerce a value into a simple type.

Parameters

- **value** (`object`) – Value that should be coerced.
- **be_type** (`object`) – Type that value should be coerced to.

Returns `float` or `int` or `str` or `object` if unchanged.

classmethod api_coerce_complex(*value*, *be_type*)

Try to coerce a value into a complex type.

Parameters

- **value** (`object`) – Value that should be coerced.
- **be_type** (`object`) – Type that value should be coerced to.

Returns *ApiItem* or *ApiList* or `object` if unchanged.

api_coerce_value(*attr*, *value*)

Perform type checking of value.

Will coerce value into expected type if needed and possible.

Parameters

- **attr** (str) – Attribute that is being set with value on obj.
- **value** (object) – Value of attr being checked.

Raises

- *pytan3.api_models.exceptions.AttrTypeError* – If value is not the expected type after all of this magic.
- *pytan3.api_models.exceptions.AttrUndefinedError* – If value type is not *simple_types* and attr is not in *api_attrs*.
- *pytan3.api_models.exceptions.AttrUndefinedWarning* – If value type is *simple_types* and attr not in *api_attrs*.

Notes

No checking or coercion is done if:

- value is None
- attr starts with "_"
- attr is all upper case

Returns object

Base class for all API item objects

class pytan3.api_models.**ApiItem**(***kwargs*)

Bases: *pytan3.api_models.ApiModel*

Model for a complex item in the API.

API_LIST_API_NAME = None

str – Name of *API_LIST_CLS* used in API calls.

API_LIST_CLS = None

ApiList – List class that holds this item class.

__init__(***kwargs*)

Constructor.

Parameters ****kwargs** – Set and checked using *ApiModel.api_attrs()*.

__len__()

Return number of *ApiModel.api_attrs()* that are not None.

Returns int

__str__()

Show object info using *ApiModel.api_attrs_str()*.

Returns str

__repr__()

Show object info using *ApiModel.api_attrs_repr()*.

Returns str

__setattr__(*attr*, *value*)
Enforce type using `ApiModel.api_coerce_value()`.

serialize(*empty=False*, *list_attrs=False*, *exclude_attrs=None*, *only_attrs=None*, *wrap_name=True*, *wrap_item_attr=True*)
Serialize this object into a dict.

Parameters

- **empty** (`bool`, optional) – Include attrs that have a value of None when serializing.

  Defaults to: False.
- **list_attrs** (`bool`, optional) – Include simple attrs of `ApiList` when serializing.

  Defaults to: False.
- **exclude_attrs** (`list` of `str`, optional) – Exclude these attrs when serializing.

  Defaults to: None.
- **only_attrs** (`list` of `str`, optional) – Include only these attrs when serializing.

  Defaults to: None.
- **wrap_name** (`bool`, optional) – Wrap return in a dict with key of `ApiModel.API_NAME` and value of return.

  Defaults to: True.
- **wrap_item_attr** (`bool`, optional) – Wrap return in a dict with key of `ApiList.API_ITEM_ATTR` and value of return.

  Only used when serializing items of type `ApiList`.

  Defaults to: True.

Notes

All child objects will get wrap_name=False.

Returns `dict`

Base class for all API array objects

class pytan3.api_models.**ApiList**(**args*, ***kwargs*)
Bases: `pytan3.api_models.ApiModel`

Model for an array in the API.

API_ITEM_ATTR = None
`str` – Name of `API_ITEM_CLS` used in API calls.

API_ITEM_CLS = None
`ApiItem` – Item class this list class holds.

T_CLS_STR = '{obj.__class__.__name__}({attrs}) with {count} {item_cls} objects'
`str` – Template for class name and attrs in str.

__init__(**args*, ***kwargs*)
Constructor.

Parameters

- ***args** –

  Items of type *API_ITEM_CLS*: Will be added to *LIST*.

- ****kwargs** –

  attr from *API_ITEM_ATTR* (list): List of *API_ITEM_CLS* to add to *LIST*.

  rest of kwargs: Set on this object with type checking using.

LIST = None

list of *API_ITEM_CLS* – List container for this class.

__str__()

Show object info using *ApiModel.api_attrs_str()*.

Returns str

__repr__()

Show object info using *ApiModel.api_attrs_repr()*.

Returns str

__len__()

Return length of list container *LIST*.

Returns int

__contains__(*value*)

Support in operand.

Parameters **value** (object) – Check if this value in *LIST*.

Notes

Will call *api_coerce_item()* to check value is of type defined in *API_ITEM_CLS*, but will return False if value is of wrong type and can not be coerced.

Returns

Return type bool

__add__(*value*)

Support + operand.

Parameters **value** (*ApiList* or list or tuple) – ApiList of this same type or a python list type to combine with this object.

Notes

This will use *api_coerce_items()* to perform type checking on each item in value.

Returns A new instance with list items from this object combined with list items from value.

Return type *ApiList*

__iadd__(*value*)

Support += operand.

Parameters **value** (*ApiList* or `list` or `tuple`) – ApiList of this same type or a python list type to combine with this object.

Notes

This will use *api_coerce_items()* to perform type checking on each item in value.

Returns This object with list items from value appended.

Return type *ApiList*

__getitem__(*value*)

Support indexing of list container.

Parameters **value** (`int`) – Index of item to retrieve from *LIST*.

Returns The type of object this list contains.

Return type *API_ITEM_CLS*

__setattr__(*attr*, *value*)

Enforce type checking for attr and value.

Parameters

- **attr** (`str`) – Attribute to set on this object.
- **value** (`object`) – Value to perform type checking on using *ApiModel.api_coerce_value()*.

Notes

If attr is either "LIST" or *API_ITEM_ATTR*, will use *api_coerce_items()* to perform type checking on each item in value.

If attr is same as *API_ITEM_ATTR*, the attr will be changed to "LIST".

---

api_coerce_items(*attr*, *value*, *op*)

Check that value is a list type and that all items value are the proper type.

Parameters

- **attr** (`str`) – Attribute being set on this object.
- **value** (*ApiList* or `list` or `tuple`) – The list object holding items that should have type checking.
- **op** (`str`) – Operation being performed that called this method.

  Used in exception messages.

Raises *pytan3.api_models.exceptions.ListTypeError* – If value is not a `list` or `tuple` or an *ApiList* that is the same type as this objects class.

Notes

Will call *api_coerce_items_hook()* before checking each item in value, which can be overridden by subclasses to modify value.

Will call `api_coerce_item()` to check each item in value is of type defined in `API_ITEM_CLS`.

Returns The list of items with their values checked and coerced.

Return type `list`

api_coerce_items_hook(*attr*, *value*, *op*)

Check hook that allows subclasses to modify list items.

Parameters

- **attr** (`str`) – Attribute being set on this object.
- **value** (`ApiList` or `list` or `tuple`) – The list object holding items.
- **op** (`str`) – Operation being performed that called this method.

Notes

By default, this does nothing but return value unchanged.

Returns The list of items modified or as is.

Return type `list`

api_coerce_item(*item*, *items*, *attr*, *op*)

Perform type checking of a list item.

Parameters

- **item** (`object`) – Item that is being checked.
- **items** (`ApiList` or `list` or `tuple`) – The list object that item came from.
- **op** (`str`) – Operation being performed that called this method.

  Used in exception messages.

Notes

Will coerce item into expected type if needed and possible.

Raises `pytan3.api_models.exceptions.ListItemTypeError` – If item does not match the type from `API_ITEM_CLS` and it can not be coerced into the expected type.

Returns `object`

classmethod api_attrs_desc()

Get simple and complex attributes of an ApiModel object in string format.

Notes

Used by exceptions to add defined attributes to error messages.

Returns `list` of `str`

classmethod api_item_cls_str()
Get str of *API_ITEM_CLS*.

Returns str

classmethod api_item_cls_is_complex()
Check if *API_ITEM_CLS* is an ApiModel sub class.

Returns bool

append(*value*)
Support appending an item to list container.

Parameters **value** (object) – Item to append to *LIST*.

Notes

Will call *api_coerce_item()* to check value is of type defined in *API_ITEM_CLS*.

---

remove(*value*)
Support removing an item from list container.

Parameters **value** (object) – Item to remove from *LIST*.

pop(*value=-1*)
Support pop of an item from list container.

Parameters **value** (object, optional) – Item to pop from *LIST*.

Defaults to: -1.

reverse()
Support reverse on list container.

get_item_by_attr(*value*, *attr='name'*, *regex_value=False*)
Support getting an item from list container by attr value.

Parameters

- **value** (object) – Value to check against the attr value of each item in *LIST*.
- **attr** (str, optional) – Attribute to check if value matches.

  Defaults to: "name".
- **regex_value** (bool, optional) – Treat value as a regex pattern instead of comparing equality of value to attr value.

  Defaults to: False.

Raises *pytan3.api_models.exceptions.GetSingleItemError* – If number of items in *LIST* whose attr value matches value is either 0 or more than 1.

Returns The object from *LIST* whose attr value matches value.

Return type object

get_items_by_attr(*value*, *attr='name'*, *regex_value=False*, *new_list=False*)
Support getting items from list container by attr value.

Parameters

- **value** (object) – Value to check against the attr value of each item in *LIST*.

- **attr** (str, optional) – Attribute to check if value matches.

  Defaults to: "name".

- **regex_value** (bool, optional) – Treat value as a regex pattern instead of comparing equality of value to attr value.

  Defaults to: False.

- **new_list** (bool, optional) – Return a new class of this objects type with matching items instead of a regular python list type.

  Defaults to: False.

Returns All objects from *LIST* whose attr value matches value.

Return type list of object

pop_item_by_attr(*value*, *attr='name'*, *regex_value=False*)

Support popping an item from list container by attr value.

Parameters

- **value** (object) – Value to check against the attr value of each item in *LIST*.
- **attr** (str, optional) – Attribute to check if value matches.

  Defaults to: "name".

- **regex_value** (bool, optional) – Treat value as a regex pattern instead of comparing equality of value to attr value.

  Defaults to: False.

Raises *pytan3.api_models.exceptions.GetSingleItemError* – If number of items in *LIST* whose attr value matches value is either 0 or more than 1.

Returns The object popped from *LIST* whose attr value matches value.

Return type object

pop_items_by_attr(*value*, *attr='name'*, *regex_value=False*, *new_list=False*)

Support popping items from list container by attr value.

Parameters

- **value** (object) – Value to check against the attr value of each item in *LIST*.
- **attr** (str, optional) – Attribute to check if value matches.

  Defaults to: "name".

- **regex_value** (bool, optional) – Treat value as a regex pattern instead of comparing equality of value to attr value.

  Defaults to: False.

- **new_list** (bool, optional) – Return a new class of this objects type with matching items instead of a regular python list type.

  Defaults to: False.

Returns All objects popped from *LIST* whose attr value matches value.

Return type list of object

sort(*key=operator.attrgetter('id')*, *reverse=False*)

Support sorting items in list container in place.

Parameters

- **key** (object, optional) – Key to sort items in *LIST* on.

  Defaults to: operator.attrgetter("id").

- **reverse** (bool, optional) – Reverse the sort mechanism.

  Defaults to: False.

serialize(*empty=False*, *list_attrs=False*, *exclude_attrs=None*, *only_attrs=None*, *wrap_name=True*, *wrap_item_attr=True*)

Serialize this object into a dict.

Parameters

- **empty** (bool, optional) – Include attrs that have a value of None when serializing.

  Defaults to: False.

- **list_attrs** (bool, optional) – Include simple attrs of *ApiList* when serializing.

  Defaults to: False.

- **exclude_attrs** (list of str, optional) – Exclude these attrs when serializing.

  Defaults to: None.

- **only_attrs** (list of str, optional) – Include only these attrs when serializing.

  Defaults to: None.

- **wrap_name** (bool, optional) – Wrap return in a dict with key of *ApiModel.API_NAME* and value of return.

  Defaults to: True.

- **wrap_item_attr** (bool, optional) – Wrap return in a dict with key of *ApiList.API_ITEM_ATTR* and value of return.

  Only used when serializing items of type *ApiList*.

  Defaults to: True.

Notes

All child objects will get wrap_name=False.

If wrap_name and wrap_item_attr are both False, return will be list of dict, otherwise return will be a dict.

Returns list of object or dict

Exceptions for API Models

Exceptions and warnings for *pytan3.api_models*.

exception pytan3.api_models.exceptions.**ModuleError**

Bases: *pytan3.exceptions.PyTanError*

Parent of all exceptions for *pytan3.api_models*.

Thrown from:

exception pytan3.api_models.exceptions.**ModuleWarning**

Bases: *pytan3.exceptions.PyTanWarning*

Parent of all warnings for *pytan3.api_models*.

Thrown from:

exception pytan3.api_models.exceptions.**AttrUndefinedWarning**(*obj*, *attr*, *value*)

Bases: *pytan3.api_models.exceptions.ModuleWarning*

Warning handler for a simple value being set on an undefined attribute.

Thrown from:

- *pytan3.api_models.ApiModel.api_coerce_value()*.

__init__(*obj*, *attr*, *value*)

Constructor.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – Object that warning was thrown from.
- **attr** (str) – Simple attribute that was adhoc added.
- **value** (int or str or bool) – Value of attr.

obj = None

pytan3.api_models.ApiModel – Object that warning was thrown from.

attr = None

str – Simple attribute that was adhoc added.

value = None

int or str or bool – Value of attr.

error = None

str – Warning message that was thrown.

exception pytan3.api_models.exceptions.**AttrUndefinedError**(*obj*, *attr*, *value*)

Bases: *pytan3.api_models.exceptions.ModuleError*

Exception handler for a complex value being set on an undefined attribute.

Thrown from:

- *pytan3.api_models.ApiModel.api_coerce_value()*.

__init__(*obj*, *attr*, *value*)

Constructor.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – Object that exception was thrown from.
- **attr** (str) – Complex attribute that was supplied.
- **value** (dict or list) – Value of attr.

obj = None

pytan3.api_models.ApiModel – Object that exception was thrown from.

attr = None

str – Complex attribute that was supplied.

value = None

dict or list – Value of attr.

error = None
str – Error message that was thrown.

exception pytan3.api_models.exceptions.**AttrTypeError**(*obj*, *attr*, *value*, *be_type*)
Bases: *pytan3.api_models.exceptions.ModuleError*

Exception handler for type mismatch of a value being set on a defined attribute.

Thrown from:

- *pytan3.api_models.ApiModel.api_coerce_value()*.

__init__(*obj*, *attr*, *value*, *be_type*)
Constructor.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – Object that exception was thrown from.
- **attr** (str) – Attribute that had a type mismatch.
- **value** (object) – Value of attr.
- **be_type** (object) – Type that value should be, but is not.

obj = None
pytan3.api_models.ApiModel – Object that exception was thrown from.

attr = None
str – Attribute that had a type mismatch.

value = None
object – Value of attr.

be_type = None
object – Type that value should be, but is not.

error = None
str – Error message that was thrown.

exception pytan3.api_models.exceptions.**ListTypeError**(*obj*, *attr*, *value*, *op*)
Bases: *pytan3.api_models.exceptions.ModuleError*

Exception handler for type mismatch on a list action.

Thrown from:

- *pytan3.api_models.ApiList.api_coerce_items()*.

__init__(*obj*, *attr*, *value*, *op*)
Constructor.

Parameters

- **obj** (*pytan3.api_models.ApiList*) – Object that exception was thrown from.
- **attr** (str) – Attribute that had a type mismatch.
- **value** (object) – Value of attr.
- **op** (str) – Operation being performed with type mismatch.

obj = None
pytan3.api_models.ApiList – Object that exception was thrown from.

attr = None
str – Attribute that had a type mismatch.

value = None
object – Value of attr.

op = None
str – Operation being performed with type mismatch.

error = None
str – Error message that was thrown.

exception pytan3.api_models.exceptions.**ListItemTypeError**(*obj*, *item*, *items*, *attr*, *op*, *be_type*)

Bases: *pytan3.api_models.exceptions.ModuleError*

Exception handler for type mismatch when adding an item to a list.

Thrown from:

- *pytan3.api_models.ApiList.api_coerce_item()*.

__init__(*obj*, *item*, *items*, *attr*, *op*, *be_type*)
Constructor.

Parameters

- **obj** (*pytan3.api_models.ApiList*) – Object that exception was thrown from.
- **item** (object) – Item being added in items that is the wrong type.
- **items** (list) – All items being added to list.
- **attr** (str) – Attribute that had a type mismatch.
- **op** (str) – Operation being performed with type mismatch.
- **be_type** (object) – Type that item should be, but is not.

obj = None
pytan3.api_models.ApiList – Object that exception was thrown from.

item = None
object – Item being added in items that is the wrong type.

items = None
list – Full list of items containing item passed to op.

attr = None
str – Attribute that had a type mismatch.

op = None
str – Operation being performed with type mismatch.

be_type = None
object – Type that item should be, but is not.

error = None
str – Error message that was thrown.

exception pytan3.api_models.exceptions.**GetSingleItemError**(*obj*, *attr*, *value*, *regex_value*, *items*)

Bases: *pytan3.api_models.exceptions.ModuleError*

Exception handler when no items found.

Thrown from:

- *pytan3.api_models.ApiList.get_item_by_attr()*.

- *pytan3.api_models.ApiList.pop_item_by_attr()*.

__init__(*obj*, *attr*, *value*, *regex_value*, *items*)
Constructor.

Parameters

- **obj** (*pytan3.api_models.ApiList*) – Object that exception was thrown from.
- **attr** (*str*) – Attribute to search for value of in items.
- **value** (*object*) – Value of attr that was being used to match against items.
- **regex_value** (*bool*) – If regex matching was being used for value.
- **items** (*list*) – All items in list object.

obj = None
pytan3.api_models.ApiList – Object that exception was thrown from.

attr = None
str – Attribute used to search for value of in items.

value = None
object – Value of attr that was being used to match against items.

regex_value = None
bool – If regex matching was being used for value.

items = None
list – All items found in list object.

error = None
str – Error message that was thrown.

1.10.7 Adapters

Adapter objects that serialize requests to the Tanium API.

pytan3.adapters.**DEFAULT_TYPE = 'soap'**
str – Default *Adapter* type to load in *load_type()*.

pytan3.adapters.**DEFAULT_NAME = 'soap'**
str – Default *Adapter* name to load in *load()*.

Abstract Base Class for all Adapters

class pytan3.adapters.**Adapter**
Bases: *object*

Abstract base class for all Adapters.

api_objects
Get the API objects container.

Returns *pytan3.api_objects.ApiObjects*

api_client
Get the API client.

Returns *pytan3.api_clients.ApiClient*

http_client
Get the HTTP client.

Returns *pytan3.http_client.HttpClient*

auth_method
Get the Auth Method.

Returns *pytan3.auth_methods.AuthMethod*

classmethod get_name()
Get the ref name of this class for use by *load()*.

Returns str

classmethod get_type()
Get the ref type of this class for use by *load_type()*.

Returns str

classmethod get_version_req()
Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

result_cls
Get the result deserializer class.

Returns *pytan3.results.Result*

api_get(*obj*, ***kwargs*)
Send an API request to get an object.

Parameters **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.

Returns *pytan3.results.Result*

api_add(*obj*, ***kwargs*)
Send an API request to add an object.

Parameters **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.

Returns *pytan3.results.Result*

api_delete(*obj*, ***kwargs*)
Send an API request to delete an object.

Parameters **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.

Returns *pytan3.results.Result*

api_update(*obj*, ***kwargs*)
Send an API request to update an object.

Parameters **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.

Returns *pytan3.results.Result*

api_get_audit_logs(*type*, *target*, ***kwargs*)
Send an API request to get audit logs for an object.

Parameters

- **type** (str) – Type of object to get audit logs of.
- **target** (int) – ID of object type to get audit logs for.

Returns *pytan3.results.Result*

api_get_client_count(***kwargs*)
Send an API request to get the client count.

Returns *pytan3.results.Result*

api_parse_question(*text*, ***kwargs*)
Send an API request to parse text.

Parameters **text** (str) – Text to parse into question objects.

Returns *pytan3.results.Result*

api_add_parsed_question(*obj*, ***kwargs*)
Send an API request to add a parsed question object.

Parameters **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.

Returns *pytan3.results.Result*

api_get_result_info(*obj*, ***kwargs*)
Send an API request to get result info for an object.

Parameters **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.

Returns *pytan3.results.Result*

api_get_result_data(*obj*, ***kwargs*)
Send an API request to get result data for an object.

Parameters **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.

Returns *pytan3.results.Result*

api_get_merged_result_data(*objlist*, ***kwargs*)
Send an API request to get merged result data for a list of objects.

Parameters **objlist** (list) – List of API Objects to use for request.

Returns *pytan3.results.Result*

_abc_impl = <_abc_data object>

All SOAP API Adapters

Soap Adapter

class pytan3.adapters.**Soap**(*api_client*, *api_objects*, *ver_check=True*, *lvl='info'*)
Bases: *pytan3.adapters.Adapter*

Tanium SOAP request adapter.

DEFAULT_OPTIONS = {'include_hashes_flag': True, 'json_pretty_print': True}
dict – Default options to use in *build_options_from_kwargs()*.

AUDIT_LOG_TYPES = ['authentication', 'content_set', 'content_set_role', 'content_set_r

`list` of `str` – Valid types for *api_get_audit_logs()*.

__init__(*api_client*, *api_objects*, *ver_check=True*, *lvl='info'*)

Constructor.

Parameters

- **api_client** (*pytan3.api_clients.ApiClient*) – Client to use for sending API requests.
- **api_objects** (*pytan3.api_objects.ApiObjects*) – API objects container to use for this adapter.
- **ver_check** (`bool`, optional) – Perform version checks against *pytan3.api_clients.get_version()*.

  Defaults to: True.
- **lvl** (`str`, optional) – Logging level.

  Defaults to: "info".

log = None

`logging.Logger` – Log.

__str__()

Show object info.

Returns `str`

__repr__()

Show object info.

Returns `str`

api_objects

Get the API objects container.

Returns *pytan3.api_objects.ApiObjects*

api_client

Get the API client.

Returns *pytan3.api_clients.ApiClient*

http_client

Get the HTTP client.

Returns *pytan3.http_client.HttpClient*

auth_method

Get the Auth Method.

Returns *pytan3.auth_methods.AuthMethod*

classmethod get_name()

Get the ref name of this class for use by *load()*.

Returns `str`

classmethod get_type()

Get the ref type of this class for use by *load_type()*.

Returns `str`

classmethod get_version_req()

Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by `pytan3.utils.versions.version_check_obj_req()` to perform version checks.

Returns `dict`

result_cls

Get the result deserializer class.

Returns `pytan3.results.Result`

build_options_from_kwargs(***kwargs*)

Build an Options API object from kwargs and return the serialized form.

Parameters ****kwargs** –

options_obj (*pytan3.api_models.ApiItem*): A pre-established Options object.

Defaults to: new Options object from `api_objects`.

rest of kwargs: Set on Options object if key is an attr on object and attrs value is None.

Notes

Will set `DEFAULT_OPTIONS` as defaults to kwargs before applying values to Options object attributes.

Returns `dict`

send(*obj*, *cmd*, ***kwargs*)

Build and send a SOAP API request.

Parameters

- **obj** (`pytan3.api_models.ApiModel`) – ApiModel to serialize and send as part of request.
- **cmd** (`str`) – SOAP Command to use in request.
- ****kwargs** –

  body_re_limit (int): Value to limit regex search of response body for <session> tag.

  Defaults to: 4000.

  empty (bool): Include attributes that have a value of None when serializing.

  Defaults to: False

  list_attrs (bool): Include simple attributes of `pytan3.api_models.ApiList` when serializing.

  Defaults to: False.

exclude_attrs (list of str): Exclude these attributes when serializing.

Defaults to: [].

only_attrs (list of str): Include only these attributes when serializing.

Defaults to: [].

wrap_name (bool): Wrap the return in another dict whose key is set to the API name.

Defaults to: True.

wrap_item_attr (bool): Wrap list items in dict whose key is set to the API list item attribute.

Defaults to: True.

rest of kwargs: Passed to `build_options_from_kwargs()`.

Raises `exceptions.SessionNotFoundWarning` – If the <session> tag can not be found in the response body.

Returns `pytan3.results.Result`

api_get(*obj*, ***kwargs*)

Send an API request to get an object.

Parameters

- **obj** (`pytan3.api_models.ApiModel`) – API Object to use for request.
- ****kwargs** –

  rest of kwargs: Passed to `send()`.

Returns `pytan3.results.Result`

api_add(*obj*, ***kwargs*)

Send an API request to add an object.

Parameters

- **obj** (`pytan3.api_models.ApiModel`) – API Object to use for request.
- ****kwargs** –

  rest of kwargs: Passed to `send()`.

Returns `pytan3.results.Result`

api_delete(*obj*, ***kwargs*)

Send an API request to delete an object.

Parameters

- **obj** (`pytan3.api_models.ApiModel`) – API Object to use for request.
- ****kwargs** –

  rest of kwargs: Passed to `send()`.

Returns `pytan3.results.Result`

api_update(*obj*, ***kwargs*)

Send an API request to update an object.

Parameters

- **obj** (`pytan3.api_models.ApiModel`) – API Object to use for request.

- ****kwargs** –

  rest of kwargs: Passed to `send()`.

Returns `pytan3.results.Result`

api_get_audit_logs (*type*, *target*, ***kwargs*)
Send an API request to get audit logs for an object.

Parameters

- **type** (`str`) – Type of object to get audit logs of.
- **target** (`int`) – ID of object type to get audit logs for. SOAP allows target of 'None' to get all objects of *type*.
- ****kwargs** –

  count (int): Limit number of audit logs returned to this.

  Defaults to: 1.

  rest of kwargs: Passed to `send()`.

Raises `exceptions.InvalidTypeError` – If type is not one of `AUDIT_LOG_TYPES`.

Returns `pytan3.results.Result`

api_get_client_count (***kwargs*)
Send an API request to get the client count.

Parameters ****kwargs** –

count (int): Number of days to get client count for.

Defaults to: 30.

rest of kwargs: Passed to `send()`.

Returns `pytan3.results.Result`

api_parse_question (*text*, ***kwargs*)
Send an API request to parse text.

Parameters

- **text** (`str`) – Text to parse into question objects.
- ****kwargs** –

  rest of kwargs: Passed to `send()`.

Returns `pytan3.results.Result`

api_add_parsed_question (*obj*, ***kwargs*)
Send an API request to add a parsed question object.

Parameters

- **obj** (`pytan3.api_models.ApiModel`) – API Object to use for request.
- ****kwargs** –

  for_merge (bool): Value for force_computer_id_flag attr on question object.

  Defaults to: True.

  rest of kwargs: Passed to `send()`.

Returns `pytan3.results.Result`

api_get_result_info(*obj*, ***kwargs*)
Send an API request to get result info for an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

  rest of kwargs: Passed to *send()*.

Returns *pytan3.results.Result*

api_get_result_data(*obj*, ***kwargs*)
Send an API request to get result data for an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

  rest of kwargs: Passed to *send()*.

Returns *pytan3.results.Result*

api_get_merged_result_data(*objlist*, ***kwargs*)
Send an API request to get merged result data for a list of objects.

Parameters

- **objlist** (*list*) – List of API Objects to use for request.
- ****kwargs** –

  rest of kwargs: Passed to *send()*.

Returns *pytan3.results.Result*

_abc_impl = <_abc_data object>

All REST API Adapters

Rest Adapter

class pytan3.adapters.**Rest**(*api_client*, *api_objects*, *ver_check=True*, *lvl='info'*)
Bases: *pytan3.adapters.Adapter*

Tanium REST API request adapter.

DEFAULT_OPTIONS = {'include_hashes_flag': True, 'json_pretty_print': True}
dict – Default options to use in *build_options_from_kwargs()*.

AUDIT_LOG_TYPES = ['content_set', 'content_set_role', 'dashboard', 'dashboard_group',
list of *str* – Valid types for *api_get_audit_logs()*.

__init__(*api_client*, *api_objects*, *ver_check=True*, *lvl='info'*)
Constructor.

Parameters

- **api_client** (*pytan3.api_clients.ApiClient*) – Client to use for sending API requests.

- **api_objects** (*pytan3.api_objects.ApiObjects*) – API objects container to use for this adapter.
- **ver_check** (bool, optional) – Perform version checks against *pytan3.api_clients.get_version()*.

  Defaults to: True.
- **lvl** (str, optional) – Logging level.

  Defaults to: "info".

log = None
logging.Logger – Log.

__str__()
Show object info.

Returns str

__repr__()
Show object info.

Returns str

api_objects
Get the API objects container.

Returns *pytan3.api_objects.ApiObjects*

api_client
Get the API client.

Returns *pytan3.api_clients.ApiClient*

http_client
Get the HTTP client.

Returns *pytan3.http_client.HttpClient*

auth_method
Get the Auth Method.

Returns *pytan3.auth_methods.AuthMethod*

classmethod get_name()
Get the ref name of this class for use by *load()*.

Returns str

classmethod get_type()
Get the ref type of this class for use by *load_type()*.

Returns str

classmethod get_version_req()
Get the min, max, and eq version requirements of this class.

Notes

Dict can specify keys: "vmin", "vmax", "veq".

This class method gets called by *pytan3.utils.versions.version_check_obj_req()* to perform version checks.

Returns dict

result_cls

Get the result deserializer class.

Returns *pytan3.results.Result*

build_options_from_kwargs(***kwargs*)

Build an Options API object from kwargs and return the serialized form.

Parameters ****kwargs** –

options_obj (*pytan3.api_models.ApiItem*): A pre-established Options object.

Defaults to: new Options object from *api_objects*.

rest of kwargs: Set on Options object if key is an attr on object and attrs value is None.

Notes

Will set *DEFAULT_OPTIONS* as defaults to kwargs before applying values to Options object attributes.

Returns dict

api_get(*obj*, ***kwargs*)

Send an API request to get an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

headers (dict): Headers to supply to request.

Defaults to: {}.

params (dict): Parameters to supply to request.

Defaults to: {}.

rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_add(*obj*, ***kwargs*)

Send an API request to add an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

headers (dict): Headers to supply to request.

Defaults to: {}.

params (dict): Parameters to supply to request.

Defaults to: {}.

rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_delete(*obj*, ***kwargs*)
Send an API request to delete an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_update(*obj*, ***kwargs*)
Send an API request to update an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_get_audit_logs(*type*, *target*, ***kwargs*)
Send an API request to get audit logs for an object.

Parameters

- **type** (*str*) – Type of object to get audit logs of.
- **target** (*int*) – ID of object type to get audit logs for.
- ****kwargs** –

  count (int): Limit number of audit logs returned to this.

  Defaults to: 1.

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Raises *exceptions.InvalidTypeError* – If type is not one of *AUDIT_LOG_TYPES*.

Returns *pytan3.results.Result*

api_parse_question(*text*, ***kwargs*)
Send an API request to parse text.

Parameters

- **text** (str) – Text to parse into question objects.
- ****kwargs** –

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_get_client_count(***kwargs*)
Send an API request to get the client count.

Parameters ****kwargs** –

headers (dict): Headers to supply to request.

Defaults to: {}.

params (dict): Parameters to supply to request.

Defaults to: {}.

rest of kwargs: Passed to *build_options_from_kwargs()*.

Notes

Unlike the SOAP API, "count" does not seem to be used by REST API.

Returns *pytan3.results.Result*

api_add_parsed_question(*obj*, ***kwargs*)
Send an API request to add a parsed question object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

  for_merge (bool): Set option "force_computer_id_flag".

  Defaults to: True.

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_get_result_info(*obj*, ***kwargs*)
Send an API request to get result info for an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_get_result_data(*obj*, ***kwargs*)
Send an API request to get result data for an object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API Object to use for request.
- ****kwargs** –

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

api_get_merged_result_data(*objlist*, ***kwargs*)
Send an API request to get merged result data for a list of objects.

Parameters

- **objlist** (*list*) – List of API Objects to use for request.
- ****kwargs** –

  headers (dict): Headers to supply to request.

  Defaults to: {}.

  params (dict): Parameters to supply to request.

  Defaults to: {}.

  rest of kwargs: Passed to *build_options_from_kwargs()*.

Returns *pytan3.results.Result*

_abc_impl = <_abc_data object>

Loaders for all Adapters

pytan3.adapters.**load_type**(*obj='soap'*)
Get a *Adapter* by type from *Adapter.get_type()*.

Parameters **obj** (*str*, optional) – Type of Adapter.

Defaults to: *DEFAULT_TYPE*.

Raises *exceptions.ModuleError* – Unable to find a valid *Adapter* with the supplied type.

Returns *Adapter*

pytan3.adapters.**load**(*obj='soap'*)
Get a *Adapter* by name from *Adapter.get_name()*.

Parameters **obj** (*str* or *Adapter* or *Adapter*, optional) – Adapter object, class, or name Adapter.

Defaults to: *DEFAULT_NAME*.

Raises *exceptions.ModuleError* – Unable to find a valid *Adapter* with the supplied name.

Returns *Adapter*

Utilities for all Adapters

pytan3.adapters.**check_adapter_types**(*adapter*)
Check *Adapter.get_type()* against api_client and objects type.

Parameters **adapter** (*Adapter*) – Adapter to perform type checking on.

Raises *exceptions.TypeMismatchError* – If *Adapter.get_type()* is not equal to *pytan3.api_objects.ApiObjects.module_type* or *pytan3.api_clients.ApiClient.get_type()*.

pytan3.adapters.**check_adapter_version**(*adapter*)
Check *Adapter.get_version_req()* against api_client and objects version.

Parameters **adapter** (*Adapter*) – Adapter to perform version checking on.

Raises *pytan3.utils.exceptions.VersionMismatchError* – If the version requirements from *Adapter.get_version_req()* fail to match *pytan3.api_clients.ApiClient.version* or *pytan3.api_objects.ApiObjects.module_version*.

pytan3.adapters.**check_object_attrs**(*obj*, *attrs*)
Check if any attributes of an obj are set.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API object to check.
- **attrs** (*list* of *str*) – Attributes to check on obj.

Raises *exceptions.EmptyAttributeError* – If none of the attributes in attrs on obj are not set to None.

pytan3.adapters.**check_object_type**(*obj*, *types*)
Check if an obj is an instance of types.

Parameters

- **obj** (*object*) – Object to check against types.
- **types** (*tuple* of *type*) – Types to check against obj.

Raises `exceptions.InvalidTypeError` – If type of obj is not on of types.

Utilities for SOAP API Adapters

`pytan3.adapters.`**`soap_envelope`**(*cmd*, *obj*, *opts=None*)

Construct a SOAP envelope with the request command, obj, and options.

Parameters

- **cmd** (`str`) – Command to use for request.
- **obj** (`dict`) – Object(s) to use for request.
- **options** (`dict`, optional) – Options to use for request.

  Defaults to: None.

Returns `dict`

`pytan3.adapters.`**`re_soap_tag`**(*text*, *tag*, *limit=4000*, *pattern='<{t}>(.*?)</{t}>'*)

Search for tag in text[:limit] using pattern.

Parameters

- **text** (`str`) – Text to search for pattern.
- **tag** (`str`) – Tag name to use in pattern as 't'.
- **limit** (`int`, optional) – Length to limit text to when searching for pattern.

  Defaults to: 4000.
- **pattern** (`str`, optional) – Pattern to use when searching for tag.

  Defaults to: r'<{e}>(.*?)</{e}>'

Notes

Given text is 4 GB and pattern is expected at top of text:

- if head is None and pattern not found: 131 seconds
- if head is None and pattern found: 0 seconds
- if head is 4000 and pattern not found: 0 seconds
- if head is 4000 and pattern found: 0 seconds

Returns `str`

`pytan3.adapters.`**`serialize_xml`**(*obj*, ***kwargs*)

Encode python object into an XML string.

Parameters

- **obj** (`object`) – Python object to encode into a string.
- ****kwargs** –

  full_document (`bool`): Include xml stanza at top.

  Defaults to: True.

pretty (bool): Indent the output doc.

Defaults to: True.

rest of kwargs: Passed to xmltodict.unparse.

Returns str

Utilities for REST API Adapters

pytan3.adapters.**magic_endpoint**(*obj*, *target=None*, *auto_target=True*, *needs_target=False*)

Build a REST API endpoint from an API object.

Parameters

- **obj** (*pytan3.api_models.ApiModel*) – API object to get route and target from in order to build endpoint.
- **target** (str, optional) – Manually provided target.

  Defaults to: None.
- **auto_target** (bool, optional) – Try to identify the target from obj by getting "id" or "name" attributes if their values are not None.

  Defaults to: True.
- **needs_target** (bool, optional) – Throw an exception if a target is not automatically determined from obj.

  Defaults to: False.

Raises *exceptions.ModuleError* – If needs_target is True and resolved target is None.

Returns str

pytan3.adapters.**build_endpoint**(*route*, *target=None*)

Build a REST endpoint string by joining route and target.

Parameters

- **route** (str) – Route part of endpoint.
- **target** (str, optional) – Target part of endpoint.

  Defaults to None.

Returns str

pytan3.adapters.**serialize_json**(*obj*, ***kwargs*)

Encode python object into a JSON string.

Parameters

- **obj** (object) – Python object to encode into a string.
- ****kwargs** –

  indent (int): Indent spacing for prettifying.

  Defaults to: 2.

  rest of kwargs: Passed to `json.dumps()`.

Returns str

Exceptions for all Adapters

Exceptions and warnings for *pytan3.adapters*.

exception pytan3.adapters.exceptions.**ModuleError**

Bases: *pytan3.exceptions.PyTanError*

Parent of all exceptions for *pytan3.adapters*.

Thrown by:

- *pytan3.adapters.load_type()*
- *pytan3.adapters.load()*

exception pytan3.adapters.exceptions.**ModuleWarning**

Bases: *pytan3.exceptions.PyTanWarning*

Parent of all warnings for *pytan3.adapters*.

Thrown by:

exception pytan3.adapters.exceptions.**InvalidTypeError**

Bases: *pytan3.adapters.exceptions.ModuleError*

Thrown when an object of an invalid type is supplied.

Thrown by:

- *pytan3.adapters.Adapter.api_get_audit_logs()*
- *pytan3.adapters.check_object_type()*

exception pytan3.adapters.exceptions.**EmptyAttributeError**

Bases: *pytan3.adapters.exceptions.ModuleError*

Thrown when an object is supplied that does not have required attributes set.

Thrown by:

- *pytan3.adapters.check_object_attrs()*

exception pytan3.adapters.exceptions.**TypeMismatchError**

Bases: *pytan3.adapters.exceptions.ModuleError*

Thrown when an API module type does not match an adapters type.

Thrown by:

- *pytan3.adapters.check_adapter_types()*

exception pytan3.adapters.exceptions.**SessionNotFoundWarning**

Bases: *pytan3.adapters.exceptions.ModuleWarning*

Thrown when a session XML tag can not be found in a response body.

Thrown by:

- *pytan3.adapters.Soap.send()*

1.10.8 Results

Result objects that deserialize responses from Tanium API.

Results Abstract Base Class

class pytan3.results.**Result**

Bases: object

Deserialize API responses from Tanium API.

classmethod from_response(*api_objects*, *response*, *lvl='info'*)

Create *Result* from requests.Response.

Parameters

- **api_objects** (*pytan3.api_objects.ApiObjects*) – API Objects Container to use.
- **response** (requests.Response) – Response object received from Tanium API request.
- **lvl** (str, optional) – Logging level.

  Defaults to: "info".

Returns *Result*

error_check()

Check for errors in *response_body_str*.

Raises

- *exceptions.ObjectExistsError*
- *exceptions.ObjectNotFoundError*
- *exceptions.ResponseError*

error_text

Get the error text from *response_body_str*.

Returns str

api_objects()

Get the API objects container.

Returns *pytan3.api_objects.ApiObjects*

url()

Get the URL used in request.

Returns str

status_code

Get the status code received in response.

Returns int

method

Get the method used in request.

Returns str

request_body_str

Get the full request body.

Returns str

request_body_obj

Get *request_body_str* deserialized into a python object.

Returns `object`

request_object_obj
Get the request objects from `request_body_obj`.

Returns `dict`

response_body_str
Get the full response body.

Returns `str`

response_body_obj
Get `response_body_str` deserialized into a python object.

Returns `object`

data_obj
Get the response data from `response_body_obj`.

Returns `object`

data_api(***kwargs*)
Get `data_obj` deserialized into an ApiModel object.

Returns `pytan3.api_models.ApiModel`

object_obj
Get the response objects from `response_body_obj`.

Returns `dict`

object_api(***kwargs*)
Get `object_obj` deserialized into an ApiModel object.

Returns `pytan3.api_models.ApiModel`

str_to_obj(*text*, *src*, ***kwargs*)
Deserialize string into a python object.

Parameters

- **text** (`str`) – String to decode into python object
- **src** (`str`) – Where text came from, used in error text.

Raises `exceptions.TextDeserializeError`

Returns `object`

obj_to_api(*obj*, *src*)
Deserialize a python object into `pytan3.api_models.ApiModel`.

Parameters

- **obj** (`object`) – Python object to deserialize into a PyTan API object.
- **src** (`str`) – Where obj came from, used in error text.

Returns `pytan3.api_models.ApiModel`

_abc_impl = <_abc_data object>

Results Common Mixins

class pytan3.results.**CommonMixin**(*api_objects*, *response_body*, *request_body*, *method*, *url*, *status_code*, *origin=None*, *lvl='info'*)

Bases: object

Shared methods common amongst all *Result*.

__init__(*api_objects*, *response_body*, *request_body*, *method*, *url*, *status_code*, *origin=None*, *lvl='info'*)

Constructor.

Parameters

- **api_objects** (*pytan3.api_objects.ApiObjects*) – API Objects Container to use.
- **response_body** (str) – Response body received from Tanium API.
- **request_body** (str) – Request body sent to Tanium API.
- **method** (str) – HTTP method used in request to Tanium API.
- **url** (str) – URL used in request to Tanium API.
- **status_code** (int) – Status code in response from Tanium API.
- **origin** (requests.Response, optional) – Original response object received from Tanium API request.

  Defaults to: None.
- **lvl** (str, optional) – Logging level.

  Defaults to: "info".

log = None

logging.Logger – Log for this object.

origin = None

requests.Response – Original response object.

__str__()

Show object info.

Returns str

__repr__()

Show object info.

Returns str

classmethod from_response(*api_objects*, *response*, *lvl='info'*)

Create Result from a requests response object.

Parameters

- **api_objects** (*pytan3.api_objects.ApiObjects*) – API Objects Container to use.
- **response** (requests.Response) – Response object received from Tanium API request.
- **lvl** (str, optional) – Logging level.

  Defaults to: "info".

Returns *Result*

api_objects
Get the API objects container.

Returns *pytan3.api_objects.ApiObjects*

url
Get the URL used in request.

Returns *str*

status_code
Get the status code received in response.

Returns *int*

method
Get the method used in request.

Returns *str*

request_body_str
Get the full request body.

Returns *str*

response_body_str
Get the full response body.

Returns *str*

obj_to_api (*api_name*, *obj*, *src*)
Deserialize a python object into *pytan3.api_models.ApiModel*.

Parameters

- **api_name** (*str*) – API name of obj.
- **obj** (*object*) – Python object to deserialize into a PyTan API object.
- **src** (*str*) – Where obj came from, used in error text.

Returns *pytan3.api_models.ApiModel*

get_dict_path (*obj*, *path*, *src*)
Traverse a dict using a / seperated string.

Parameters

- **obj** (*dict*) – Dictionary to traverse using path.
- **path** (*str*) – Nested dictionary keys seperated by / to traverse in obj.
- **src** (*str*) – Where obj came from, used in error text.

Raises *exceptions.DictionaryPathError* – If any error occurs while traversing path in obj.

Returns *object*

Results for SOAP API

Soap Result

class pytan3.results.**Soap**(*api_objects*, *response_body*, *request_body*, *method*, *url*, *status_code*, *origin=None*, *lvl='info'*)

Bases: *pytan3.results.CommonMixin*, *pytan3.results.Result*

Deserialize SOAP API responses from Tanium API.

DATA_ROUTES = ['GetResultInfo', 'GetResultData', 'GetMergedResultData']

__call__(*raw=False*, ***kwargs*)

Get *data_api* or *object_api*.

Parameters

- **raw** (bool, optional) – Return the serialized object instead of the object deserialized into an ApiModel.

  Defaults to: False.

- ****kwargs** –

  rest of kwargs: passed to *object_api()* or *data_api()*.

Notes

Will return *object_api()* or *data_api()* by determining if *command_request* is an object or data request.

Returns *pytan3.api_models.ApiModel* or object

error_map

Map of status codes to regex patterns and exceptions.

Notes

Keys should be int of a status code to check patterns of.

Values should be list of [pattern, exc], where pattern is a regex pattern to search response body, and exc is exception to throw if pattern match is found.

Raises

- *exceptions.ObjectExistsError*
- *exceptions.ObjectNotFoundError*
- *exceptions.ResponseError*

Returns dict

error_check()

Check for errors in *CommonMixin.response_body_str*.

Raises

- *exceptions.ObjectExistsError*
- *exceptions.ObjectNotFoundError*

- *exceptions.ResponseError*

error_check_response()

Check *Soap.command_response* for errors.

Notes

For each key value pair in *error_map*, if key matches *CommonMixin.status_code* or key is None, the patterns in value are checked against response body, and if matched the patterns associated exception is thrown.

---

error_check_code()

Check if *CommonMixin.status_code* is one of *valid_codes*.

Raises *exceptions.ResponseError*

valid_codes

List of valid status codes.

Returns list of int

error_text

Get the error text from *CommonMixin.response_body_str*.

Returns str

command_request

Get the "command" element from *request_body_obj*.

Returns str

command_response

Get the "command" element from *response_body_obj*.

Returns str

request_body_obj

Deserialize *CommonMixin.request_body_str* into a python object.

Returns dict

request_object_obj

Get the request objects from *request_body_obj*.

Returns dict

response_body_obj

Get *CommonMixin.response_body_str* deserialized into a python object.

Returns dict

data_xml

Get the "ResultXML" element from *response_body_obj*.

Returns str

data_obj

Get the response data from *data_xml*.

Returns object

data_api(***kwargs*)

Get *data_obj* deserialized into an ApiModel object.

Parameters ****kwargs** –

rest of kwargs: passed to `CommonMixin.obj_to_api()`

Returns `pytan3.api_models.ApiModel`

object_obj

Get the response objects from `response_body_obj`.

Returns `dict`

object_api (***kwargs*)

Get `object_obj` deserialized into an ApiModel object.

Parameters ****kwargs** –

rest of kwargs: passed to `CommonMixin.obj_to_api()`

Returns `pytan3.api_models.ApiModel`

str_to_obj (*text*, *src*, *use_dict=True*, *try_int=True*, *flat_attrs=True*, ***kwargs*)

Deserialize string into a python object.

Parameters

- **text** (`str`) – String to decode into python object
- **src** (`str`) – Where text came from, used in error text.
- **use_dict** (`bool`) – Use `dict` instead of `collections.OrderedDict` when deserializing.

  Defaults to: True.
- **try_int** (`bool`) – Try to convert str into int when deserializing.

  Defaults to: True.
- **flat_attrs** (`bool`) – Make attr_prefix "" and cdata_key "text".

  Defaults to: True.
- ****kwargs** –

  rest of kwargs: Passed to xmltodict.parse.

Raises `exceptions.TextDeserializeError` – If an exception is thrown from xmltodict.parse.

Returns `dict`

_abc_impl = <_abc_data object>

Results for REST API

Rest Result

class pytan3.results.**Rest** (*api_objects*, *response_body*, *request_body*, *method*, *url*, *status_code*, *origin=None*, *lvl='info'*)

Bases: `pytan3.results.CommonMixin`, `pytan3.results.Result`

Deserialize REST API responses from Tanium API.

MANUAL_OBJECT_ROUTES = {'audit_logs': 'audit_logs', 'parse_question': 'parse_questio

`dict` – Manual route defs for `object_api()`.

DATA_ROUTES = {'merged_result_data': 'merged_result_set', 'result_data': 'result_set
dict – Manual route defs for *data_api()*.

__call__(*raw=False*, ***kwargs*)
Get *data_api* or *object_api*.

Parameters

- **raw** (bool, optional) – Return the serialized object instead of the object deserialized into an ApiModel.

  Defaults to: False.

- ****kwargs** –

  rest of kwargs: passed to *object_api()* or *data_api()*.

Notes

Will return *object_api()* or *data_api()* by determining if *RestUrlPath.route* is an object or data request.

Returns *pytan3.api_models.ApiModel* or object

error_map
Map of status codes to regex patterns and exceptions.

Notes

Keys should be int of a status code to check patterns of.

Values should be list of [pattern, exc], where pattern is a regex pattern to search response body, and exc is exception to throw if pattern match is found.

Raises

- *exceptions.ObjectExistsError*
- *exceptions.ObjectNotFoundError*
- *exceptions.ResponseError*

Returns dict

error_check()
Check for errors in *CommonMixin.response_body_str*.

Raises

- *exceptions.ObjectExistsError*
- *exceptions.ObjectNotFoundError*
- *exceptions.ResponseError*

error_check_response()
Check *CommonMixin.response_body_str* for errors.

Notes

For each key value pair in `error_map`, if key matches `CommonMixin.status_code` or key is None, the patterns in value are checked against response body, and if matched the patterns associated exception is thrown.

---

error_check_code()

Check if `CommonMixin.status_code` is one of `valid_codes`.

Raises `exceptions.ResponseError`

valid_codes

List of valid status codes.

Returns `list` of `int`

error_text

Get the error text from `CommonMixin.response_body_str`.

Returns `str`

url_path

Parse `CommonMixin.url` using `RestUrlPath`.

Returns (`RestUrlPath`)

request_body_obj

Deserialize `CommonMixin.request_body_str` into a python object.

Returns `dict`

request_object_obj

Get the request objects from `request_body_obj`.

Returns `dict`

response_body_obj

Get `CommonMixin.response_body_str` deserialized into a python object.

Returns `dict`

data_obj

Get the response data from `response_body_obj`.

Returns `dict`

data_api(***kwargs*)

Get `data_obj` deserialized into an ApiModel object.

Parameters ****kwargs** –

rest of kwargs: passed to `CommonMixin.obj_to_api()`

Returns `pytan3.api_models.ApiModel`

object_obj

Get the response objects from `response_body_obj`.

Returns `dict`

object_api(***kwargs*)

Get `object_obj` deserialized into an ApiModel object.

Parameters ****kwargs** –

rest of kwargs: passed to `CommonMixin.obj_to_api()`

Returns `pytan3.api_models.ApiModel`

str_to_obj (*text*, *src*, ***kwargs*)
Deserialize string into a python object.

Parameters

- **text** (str) – String to decode into python object
- **src** (str) – Where text came from, used in error text.
- ****kwargs** –

  rest of kwargs: Passed to `json.loads()`.

Raises *exceptions.TextDeserializeError* – If an exception is thrown from `json.loads()`.

Returns object

_abc_impl = <_abc_data object>

Utilities for SOAP API Results

pytan3.results.**try_int_xml** (*path*, *key*, *value*)
Parser hook for xmltodict.parse to try to convert str to int.

Parameters

- **path** (list) – Path from root of document to key.
- **key** (str) – Element name being parsed.
- **value** (object) – Element value of key being parsed.

Returns original key supplied and value as int if successfully converted.

Return type (str, object)

Utilities for REST API Results

class pytan3.results.**RestUrlPath** (*url*)
Bases: object

Parser to get path parts from a REST API URL.

__init__ (*url*)
Constructor.

Parameters **url** (str) – URL to parse.

Raises *exceptions.ModuleError* – If *version* and *route* can not be parsed from *path_parts*.

url_original = None
str – Original URL supplied.

url = None
str – Percent decoded version of *url_original*.

url_path = None
urllib.parse.ParseResult – Parsed version of *url*.

path_parts = None
list of str – Parts of URL split on /.

version = None
int – REST API version from *path_parts*.

route = None
str – REST API route from *path_parts*.

by_name = None
bool – If *target* is doing targeting by name or by id.

target = None
str – If found, target supplied for *route* in *url*.

__str__()
Show object info.

Returns str

__repr__()
Show object info.

Returns str

Exceptions for Results

Exceptions and warnings for *pytan3.results*.

exception pytan3.results.exceptions.**ModuleError**
Bases: *pytan3.exceptions.PyTanError*

Parent of all exceptions for *pytan3.results*.

Thrown by:

- *pytan3.results.RestUrlPath.__init__()*

exception pytan3.results.exceptions.**ModuleWarning**
Bases: *pytan3.exceptions.PyTanWarning*

Parent of all warnings for *pytan3.results*.

Thrown by:

exception pytan3.results.exceptions.**ResponseError**(*result*, *error*)
Bases: *pytan3.results.exceptions.ModuleError*

Thrown when a response has an general/uncategorized error.

Thrown by:

- *pytan3.results.Result.error_check()*

__init__(*result*, *error*)
Constructor.

Parameters

- **result** (*pytan3.results.Result*) – Object exception was thrown from.
- **error** (str) – Error string.

result = None
pytan3.results.Result – Object exception was thrown from.

response_body = None
str – Trimmed response body.

request_object_obj = None
object – Pretty printed objects from request.

error = None
str – Error message that was thrown.

exception pytan3.results.exceptions.**ObjectExistsError**(*result*, *error*)
Bases: *pytan3.results.exceptions.ResponseError*

Thrown when a response tells us the object already exists.

Thrown by:

- *pytan3.results.Result.error_check()*

exception pytan3.results.exceptions.**ObjectNotFoundError**(*result*, *error*)
Bases: *pytan3.results.exceptions.ResponseError*

Thrown when a response tells us the object already exists.

Thrown by:

- *pytan3.results.Result.error_check()*

exception pytan3.results.exceptions.**TextDeserializeError**(*result*, *text*, *src*, *exc*)
Bases: *pytan3.results.exceptions.ModuleError*

Thrown when deserializing a string into python object.

Thrown by:

- *pytan3.results.Result.str_to_obj()*

__init__(*result*, *text*, *src*, *exc*)
Constructor.

Parameters

- **result** (*pytan3.results.Result*) – Object exception was thrown from.
- **text** (str) – Text that was being deserialized into python object.
- **src** (str) – Description of where text came from.
- **exc** (Exception) – Exception that occurred during deserialization.

result = None
pytan3.results.Result – Object exception was thrown from.

text = None
str – Text that was being deserialized into python object.

src = None
str – Description of where text came from.

exc = None
Exception – Exception that occurred during deserialization.

error = None
str – Error message that was thrown.

exception pytan3.results.exceptions.**ApiWrongRequestType**(*result*, *error*)
Bases: *pytan3.results.exceptions.ModuleError*

Thrown when get result data/object API obj but request is not of that type.

Thrown by:

- *pytan3.results.Result.data_api()*
- *pytan3.results.Result.object_api()*

__init__(*result*, *error*)
Constructor.

Parameters **result** (*pytan3.results.Result*) – Object exception was thrown from.

result = None
pytan3.results.Result – Object exception was thrown from.

error = None
str – Error message that was thrown.

exception pytan3.results.exceptions.**DictionaryPathError**(*result*, *obj*, *path*, *src*, *exc*)
Bases: *pytan3.results.exceptions.ModuleError*

Thrown when a response has an error when deserializing.

Thrown by:

- *pytan3.results.CommonMixin.get_dict_path()*

__init__(*result*, *obj*, *path*, *src*, *exc*)
Constructor.

Parameters

- **result** (*pytan3.results.Result*) – Object exception was thrown from.
- **obj** (dict) – Dictionary to traverse using path.
- **path** (str) – Nested dictionary keys seperated by / to traverse in obj.
- **src** (str) – Where obj came from, used in error text.
- **exc** (Exception) – Original exception thrown.

result = None
pytan3.results.Result – Object exception was thrown from.

obj = None
dict – Dictionary to traverse using path.

path = None
str – Nested dictionary keys seperated by / to traverse in obj.

src = None
str – Where obj came from.

exc = None
Exception – Original exception thrown.

error = None
str – Error message that was thrown.

1.10.9 Utilities

PyTan utilities module.

Crypt Utilities

PyTan encryption/decryption utilities module.

`pytan3.utils.crypt.encrypt`(*data*, *key*)
Encrypt data with key using privy.

Parameters

- **data** (`str`) – Data to encrypt with key.
- **key** (`str`) – Key to encrypt data with.

Returns `str`

`pytan3.utils.crypt.decrypt`(*data*, *key*)
Decrypt data with key using privy.

Parameters

- **data** (`str`) – Data to decrypt with key.
- **key** (`str`) – Key data was encrypted with.

Raises *`pytan3.utils.exceptions.ModuleError`* – On ValueError from privy when decryption fails.

Returns `str`

Logging Utilities

PyTan logging module.

`pytan3.utils.logs.LOG = <Logger pytan3 (DEBUG)>`
`logging.Logger` – Package logger.

`pytan3.utils.logs.LOG_FILE = 'pytan3.log'`
`str` – Log filename for *`add_file()`* and *`remove_file()`*.

`pytan3.utils.logs.LOG_CON_FMT = '%(levelname)-8s [%(name)s:%(funcName)s()] %(message)s'`
`str` – Logging format for *`add_stderr()`* and *`add_stdout()`*.

`pytan3.utils.logs.LOG_PATH_FMT = '[%(asctime)s] PID:%(process)s %(levelname)-8s [%(name)s:%`
`str` – Logging format for *`add_file()`*.

`pytan3.utils.logs.LVL_DICT = {'CRITICAL': 50, 'DEBUG': 10, 'ERROR': 40, 'FATAL': 50, 'INFO`
`dict` – Logging level names to ints, python version dependent.

`pytan3.utils.logs.LVL_STR = 'CRITICAL, FATAL, ERROR, WARN, WARNING, INFO, DEBUG, NOTSET, O`
`str` – CSV str of logging level names.

`pytan3.utils.logs.is_enabled`(*lvl='debug'*, *obj=<Logger pytan3 (DEBUG)>*)
Determine if a logger or handler is enabled for a log level.

Parameters

- **lvl** (`str` or `int`, optional) – Level to check if obj is enabled for.

  Defaults to: "debug".

- **obj** (`logging.Logger` or `logging.Handler`, optional) – Object to check if enabled for lvl.

  Defaults to: *`LOG`*.

Returns bool

pytan3.utils.logs.**is_disabled**(*obj=<Logger pytan3 (DEBUG)>*)

Determine if a logger or handler is disabled.

Parameters **obj** (logging.Logger or logging.Handler, optional) – Object to check if disabled.

Defaults to: *LOG*.

Notes

Will traverse up the logger tree to see if any parents are disabled.

Returns bool

pytan3.utils.logs.**enable_capture_exc**()

Enable the exception hook to capture exceptions to the logging system.

pytan3.utils.logs.**disable_capture_exc**()

Disable the exception hook to capture exceptions to the logging system.

pytan3.utils.logs.**enable_capture_warn**()

Enable the warning hook to capture warnings to the logging system.

pytan3.utils.logs.**disable_capture_warn**()

Disable the warning hook to capture warnings to the logging system.

pytan3.utils.logs.**enable_format_warning**()

Replace warnings.formatwarning() with *customformatwarning()*.

pytan3.utils.logs.**disable_format_warning**()

Restore warnings.formatwarning() to the default.

pytan3.utils.logs.**use_gmt**()

Set the logging system to use GMT for time strings.

pytan3.utils.logs.**use_localtime**()

Set the logging system to use local time for time strings.

pytan3.utils.logs.**exception_hook**(*type*, *value*, *tb*)

Exception hook to send exceptions to the logging system.

Notes

If the package logger has no logging output at "error" level, the default excepthook will be used to print the exception to STDERR.

pytan3.utils.logs.**warning_hook**(*message*, *category*, *filename*, *lineno*, *file=None*, *line=None*)

Warning hook to send warnings to the logging system.

Notes

If the package logger has no logging output at "warning" level, the default warning will be used to print the warning to STDERR.

`pytan3.utils.logs.customformatwarning`(*message*, *category*, *filename*, *lineno*, *file=None*, *line=None*)

Return a custom warning format.

`pytan3.utils.logs.set_level`(*lvl='info'*, *obj=<Logger pytan3 (DEBUG)>*)

Set a logger or handler to a log level.

Parameters

- **lvl** (`str` or `int`, optional) – Level to set obj to.

  Defaults to: "info".

- **obj** (`logging.Logger` or `logging.Handler`, optional) – Object to set lvl on.

  Defaults to: *LOG*.

Notes

If lvl is "OFF" the disabled attr on obj will be set to True.

Returns `bool`

`pytan3.utils.logs.get_obj_log`(*obj*, *lvl='debug'*)

Get a logger object for an object.

Parameters

- **obj** (`object`) – Object to get a logger for using the objects class module and name.
- **lvl** (`str` or `int`, optional) – Level to set logger created for obj to initially.

  Defaults to: "debug".

Returns `logging.Logger`

`pytan3.utils.logs.get_log`(*name*, *lvl='debug'*)

Get a logger object.

Parameters

- **name** (`str`) – Path of logger to get/create.
- **lvl** (`str` or `int`, optional) – Level to set logger created using name initially.

  Defaults to: "debug".

Returns `logging.Logger`

`pytan3.utils.logs.level_name`(*lvl*)

Get a logging level in str format.

Parameters **lvl** (`str` or `int`) – Level to get str format of.

Raises *pytan3.utils.exceptions.ModuleError* – If int is not in values of *LVL_DICT* or if str is not in keys of *LVL_DICT*.

Returns `str`

`pytan3.utils.logs.level_int`(*lvl*)

Get a logging level in int format.

Parameters **lvl** (`str` or `int`) – Level to get int format of.

Raises *pytan3.utils.exceptions.ModuleError* – If int is not in values of *LVL_DICT* or if str is not in keys of *LVL_DICT*.

Returns int

pytan3.utils.logs.**log_str**(*obj*)

Get a str format of a logger object showing level and attached handlers.

Parameters **obj** (logging.Logger) – Logger object to get str format of.

Returns str

pytan3.utils.logs.**handler_str**(*obj*)

Get a str format of a handler object showing level.

Parameters **obj** (logging.Handler) – Handler object to get str format of.

Returns str

pytan3.utils.logs.**add_stdout**(*lvl='info', fmt='%(levelname)-8s [%(name)s:%(funcName)s()] %(message)s', obj=<Logger pytan3 (DEBUG)>*)

Add a STDOUT handler to a logger object.

Parameters

- **lvl** (str or int, optional) – Level to set on handler.

  Defaults to: "info".

- **fmt** (str, optional) – Formatting string to use for logging.

  Defaults to: *LOG_CON_FMT*.

- **obj** (logging.Logger, optional) – Logger object to add handler to.

  Defaults to: *LOG*.

Notes

Will remove handler from obj if exists before adding.

Returns logging.StreamHandler

pytan3.utils.logs.**add_stderr**(*lvl='info', fmt='%(levelname)-8s [%(name)s:%(funcName)s()] %(message)s', obj=<Logger pytan3 (DEBUG)>*)

Add a STDERR handler to a logger object.

Parameters

- **lvl** (str or int, optional) – Level to set on handler.

  Defaults to: "info".

- **fmt** (str, optional) – Formatting string to use for logging.

  Defaults to: *LOG_CON_FMT*.

- **obj** (logging.Logger, optional) – Logger object to add handler to.

  Defaults to: *LOG*.

Notes

Will remove handler from obj if exists before adding.

Returns `logging.StreamHandler`

`pytan3.utils.logs.add_file`(*lvl='debug', path=None, path_sub='logs', path_file='pytan3.log', max_mb=10, max_num=5, fmt='[%(asctime)s] PID:%(process)s %(levelname)-8s [%(name)s:%(funcName)s()] %(message)s', obj=<Logger pytan3 (DEBUG)>*)

Add a rotating log file handler to a logger object.

Parameters

- **lvl** (`str` or `int`, optional) – Level to set on handler.

  Defaults to: "debug".
- **path** (`str` or `pathlib.Path`, optional) – Storage directory to use.

  If empty, resolve path via `pytan3.utils.tools.get_storage_dir()`.

  Defaults to: None.
- **path_sub** (`str`, optional) – Sub directory under path that should contain path_file.

  Defaults to: "logs"
- **path_file** (`str`, optional) – Filename to write logs to under path / path_sub.

  Defaults to: `LOG_FILE`
- **max_mb** (`int`, optional) – Rotate log file when it reaches this many MB.

  Defaults to: 10.
- **max_num** (`int`, optional) – Only keep up to this number of rotated logs.

  Defaults to: 5.
- **fmt** (`str`, optional) – Formatting string to use for logging.

  Defaults to: `LOG_PATH_FMT`.
- **obj** (`logging.Logger`, optional) – Logger object to add handler to.

  Defaults to: `LOG`.

Notes

Will remove handler from obj if exists before adding.

Returns `logging.handlers.RotatingFileHandler`

`pytan3.utils.logs.remove_stdout`(*obj=<Logger pytan3 (DEBUG)>*)

Remove a STDOUT handler from a logger object.

Parameters **obj** (`logging.Logger`, optional) – Logger object to remove handler from.

Defaults to: `LOG`.

Returns `logging.Handler`

`pytan3.utils.logs.remove_stderr`(*obj=<Logger pytan3 (DEBUG)>*)

Remove a STDERR handler from a logger object.

Parameters **obj** (logging.Logger, optional) – Logger object to remove handler from.

Defaults to: *LOG*.

Returns logging.Handler

pytan3.utils.logs.**remove_file**(*path=None*, *path_sub='logs'*, *path_file='pytan3.log'*, *obj=<Logger pytan3 (DEBUG)>*)

Remove a STDERR handler from a logger object.

Parameters

- **path** (str or pathlib.Path, optional) – Storage directory to use.

  If empty, resolve path via *pytan3.utils.tools.get_storage_dir()*.

  Defaults to: None.

- **path_sub** (str, optional) – Sub directory under path that should contain path_file.

  Defaults to: "logs"

- **path_file** (str, optional) – Filename to write logs to under path / path_sub.

  Defaults to: *LOG_FILE*

- **obj** (logging.Logger, optional) – Logger object to remove handler from.

  Defaults to: *LOG*.

Returns logging.handlers.RotatingFileHandler

pytan3.utils.logs.**add_null**(*obj=<Logger pytan3 (DEBUG)>*)

Add a Null handler to a logger object.

Parameters **obj** (logging.Logger, optional) – Logger object to add handler to.

Defaults to: *LOG*.

Returns logging.NullHandler

pytan3.utils.logs.**remove_null**(*obj=<Logger pytan3 (DEBUG)>*)

Remove a Null handler from a logger object.

Parameters **obj** (logging.Logger, optional) – Logger object to remove handler from.

Defaults to: *LOG*.

Returns logging.NullHandler

pytan3.utils.logs.**remove_handler**(*handler*, *obj=<Logger pytan3 (DEBUG)>*)

Remove a handler from a logger.

Parameters

- **handler** (logging.Handler) – Handler object to add to logger object.
- **obj** (logging.Logger, optional) – Logger object to remove handler from.

  Defaults to: *LOG*.

Returns logging.Handler

pytan3.utils.logs.**find_handler_by_name**(*name*, *obj=<Logger pytan3 (DEBUG)>*)

Find handler object that is attached to a logger.

Parameters

- **name** (str) – Name of handler object to find.

- **obj** (logging.Logger, optional) – Logger object to find handler in.

  Defaults to: *LOG*.

Returns logging.Handler or None

pytan3.utils.logs.**get_output_handlers**(*lvl=None*, *obj=<Logger pytan3 (DEBUG)>*)

Find handlers attached to a logger that show output at a given level.

Parameters

- **lvl** (str or int, optional) – Level to check if handler outputs at.

  Defaults to: None.

- **obj** (logging.Logger, optional) – Logger object to find output handlers in.

  Defaults to: *LOG*.

Notes

If lvl is None logging levels of handlers will not be checked and the return will be handlers that are not logging.NullHandler.

Returns list of logging.Handler

pytan3.utils.logs.**will_print_at**(*lvl='debug'*, *obj=<Logger pytan3 (DEBUG)>*)

Check if a logger will show output at a given level.

Parameters

- **lvl** (str or int, optional) – Level to check if obj has any handlers that will output logs at.

  Defaults to: "debug".

- **obj** (logging.Logger, optional) – Logger to check if disabled and for handlers that output at lvl.

  Defaults to: *LOG*.

Returns bool

Prompting Utilities

PyTan prompting module.

class pytan3.utils.prompts.**ColorWrap**(*mode=''*)

Bases: object

Wrapper for colorama.

MODE_MAP = {'BACK': <colorama.ansi.AnsiBack object at 0x7f65eda165c0>, 'FORE': <colora

dict – Map of modes this wrapper can expose.

__init__(*mode=''*)

Constructor.

Parameters **mode** (str, optional) – One of keys in *MODE_MAP*.

Defaults to: "".

MODE = ''
str – Mode to wrap around colorama.

__getattr__(*attr*)
Get an attribute from colorama.

Parameters **attr** (str) – If *MODE* is in *MODE_MAP*, get uppercased attr from MODE.

Returns an empty string if MODE is not in MODE_MAP or attr is not available in MODE_CLS from MODE_MAP[MODE].

Returns str

class pytan3.utils.prompts.**Promptness**(*input_stream=<_io.TextIOWrapper name='<stdin>' mode='r' encoding='UTF-8'>, output_stream=<colorama.ansitowin32.StreamWrapper object>, lvl='info'*)

Bases: object

Prompt utility class.

YES_VALUES = ['y.*', 'true', '1']
list of str – Valid regex values for truthy-ness.

NO_VALUES = ['n.*', 'false', '0']
list of str – Valid regex values for falsey-ness.

USE_COLOR = True
bool – Use color in *prepare()*.

OVERRIDES = None
dict – Default overrides for *Promptness.ask_dict()*.

TMPLS = {'env_value': '\n{{f.green}}OS Environment Variable {env!r} has value {env_va
dict – String templates used throughout.

__init__(*input_stream=<_io.TextIOWrapper name='<stdin>' mode='r' encoding='UTF-8'>, output_stream=<colorama.ansitowin32.StreamWrapper object>, lvl='info'*)
Constructor.

Parameters

- **input_stream** (io.IOBase, optional) – Stream to get input from.

  Defaults to: sys.stdin.

- **output_stream** (io.IOBase, optional) – Stream to send output to.

  Defaults to: sys.stderr.

- **lvl** (str, optional) – Logging level for this object.

  Defaults to: "info".

input_stream = None
io.IOBase – Stream to get input from.

output_stream = None
io.IOBase – Stream to send output to.

log = None
logging.Logger – Log for this object.

__str__()
Show object info.

Returns str

__repr__()
Show object info.

Returns str

spew(*text*, ***kwargs*)
Print output to stream.

Parameters

- **text** (str) – String to print.
- ****kwargs** –

  stream (io.IOBase): Stream print to.

  Defaults to: *output_stream*.

prepare(*text*, ***kwargs*)
Format text with colors.

Parameters

- **text** (str) – String to format.
- ****kwargs** –

  use_color (bool): True: Replace fore, back, and style with color codes.

  False: Replace fore, back, and style with empty vals.

  Defaults to: *USE_COLOR*.

get_prompter(*secure=False*)
Get a prompt function.

Parameters **secure** (bool, optional) – Return getpass.getpass instead of input.

Defaults to: False.

Returns object

prompt(*text*, *default=None*, ***kwargs*)
Prompt for a value.

Parameters

- **text** (str) – Prompt text from parent for error/warning messages.
- **default** (object, optional) – Default value to use if no value supplied.

  Defaults to: None.
- ****kwargs** –

  secure (bool, optional): If value should have its input hidden or not.

  Defaults to: False.

  check_tty (bool): Skip TTY checks for input/output stream.

  Defaults to: False.

  env_var (str): Replace default with contents of this OS Env.

  Defaults to: “”.

  rest of kwargs: Passed to *spew()* and *prepare()*.

Raises *NoTtyError* – If the input or output stream is not attached to a console and check_tty is False.

Returns str

ask_choice(*text*, *choices*, *default=None*, *attempts=5*, ***kwargs*)

Prompt user to select from a list of choices.

Parameters

- **text** (str) – Text to use when prompting.
- **choices** (list of str) – List of choices for user to pick from.
- **default** (str, optional) – Default value to use if no value supplied.

  Defaults to: None.
- **attempts** (int, optional) – Number of attempts to allow empty/invalid input.

  Defaults to: 5.
- ****kwargs** – Passed to :meth'prepare' and *spew()*.

Raises

- *InvalidValueError* – If value supplied is not one of choices.
- *EmptyValueError* – If no value supplied and no default.

Returns str

ask_bool(*text*, *default=None*, *attempts=5*, ***kwargs*)

Prompt user to provide yes or no.

Parameters

- **text** (str) – Text to use when prompting.
- **default** (bool or str, optional) – Default value to use if no value supplied.

  Defaults to: None.
- **attempts** (int, optional) – Number of attempts to allow empty/invalid input.

  Defaults to: 5.
- ****kwargs** –

  rest of kwargs: Passed to *prepare()* and *spew()*.

Raises

- *InvalidValueError* – If value supplied is not a valid yes/no string.
- *EmptyValueError* – If no value supplied and no default.

Returns bool

ask_int(*text*, *default=None*, *attempts=5*, ***kwargs*)

Prompt user to provide yes or no.

Parameters

- **text** (str) – Text to use when prompting.
- **default** (int, optional) – Default value to use if no value supplied.

  Defaults to: None.

- **attempts** (int, optional) – Number of attempts to allow empty/invalid input.

  Defaults to: 5.

- ****kwargs** –

  rest of kwargs: Passed to *prompt()* and *prepare()*.

Raises

- *InvalidValueError* – If value supplied is not an int.
- *EmptyValueError* – If no value supplied and no default.

Returns int

ask_str (*text*, *default=None*, *attempts=5*, ***kwargs*)

Prompt user to provide yes or no.

Parameters

- **text** (str) – Text to use when prompting.
- **default** (str, optional) – Default value to use if no value supplied.

  Defaults to: “”.

- **attempts** (int, optional) – Number of attempts to allow empty/invalid input.

  Defaults to: 5.

- ****kwargs** –

  empty_ok (bool, optional): Empty input is allowed.

  Defaults to: False.

  validate (str, optional): Regex string to validate value.

  Defaults to: “”.

  rest of kwargs: Passed to *prompt()* and *prepare()*.

Raises *EmptyValueError* – If no value supplied and no default and not empty_ok.

Returns str

ask_dict (*asks*, *overrides=None*)

Prompt for input from a list of dict.

Parameters

- **asks** (list of dict) – List of dicts with valid kwargs for the various ask methods.
- **overrides** – (dict, optional): Dictionary of key / value pairs to over ride the defaults of asks.

  Defaults to: None.

Notes

Keys for ask dict in asks:

“method”, required: Ask method to use for this ask dict.

“key”, required: Key to store value returned from ask method in return dict.

“text”, required: String to use for prompting.

"choices", required for *ask_choice()*: List of valid choices for user to pick.

"secure", optional for *ask_str()*: Use prompt that hides user input while typing.

"default", optional: Default value to use if user does not provide one.

"attempts", optional: Number of attempts to allow empty/invalid input.

"check_tty", optional: Skip TTY checks for input/output stream.

Returns dict

exception pytan3.utils.prompts.**PromptError**(*text*, *attempts*)

Bases: Exception

Parent exception for any errors when prompting.

Thrown by: *Promptness.ask_dict()*

msg = '{text}'

__init__(*text*, *attempts*)

Constructor.

Parameters

- **text** (str) – Text to insert into exception message
- **attempts** (int, optional) – Number of attempts tried before this exception

exception pytan3.utils.prompts.**InvalidValueError**(*text*, *attempts*)

Bases: *pytan3.utils.prompts.PromptError*

Thrown when a user provides an invalid value.

Thrown by: *Promptness.ask_choice() Promptness.ask_bool() Promptness.ask_int()*

msg = 'Invalid value supplied for prompt {text!r} after {attempts} attempts'

exception pytan3.utils.prompts.**EmptyValueError**(*text*, *attempts*)

Bases: *pytan3.utils.prompts.PromptError*

Thrown when no default defined and user provides no value.

Thrown by: *Promptness.ask_choice() Promptness.ask_bool() Promptness.ask_int() Promptness.ask_str()*

msg = 'No value supplied for prompt {text!r} after {attempts} attempts'

exception pytan3.utils.prompts.**NoTtyError**(*stream*, *text*)

Bases: *pytan3.utils.prompts.PromptError*

Thrown when a TTY is not attached to a console.

Thrown by: *Promptness.prompt()*

__init__(*stream*, *text*)

Constructor.

Parameters

- **stream** (io.IOBase) – Stream that was not attached to a console.
- **text** (str) – Text to insert into exception message

`pytan3.utils.prompts.stream_name(stream)`
Get the name of a stream.

Parameters **stream** (io.IOBase) – Stream to get name of.

Returns str

`pytan3.utils.prompts.isatty(stream)`
Check if a stream is attached to a console.

Parameters **stream** (io.IOBase) – Stream to check.

Returns bool

`pytan3.utils.prompts.promptness = pytan3.utils.prompts.Promptness(input='<stdin>', output=`
Promptness – Pre-established object for easy usage.

Tools

PyTan tools module.

`pytan3.utils.tools.STORAGE_DIR = 'pytan3_local'`
str – Default sub-directory to use for *STORAGE_PATH*.

`pytan3.utils.tools.STORAGE_PATH = '~/pytan3_local'`
str – Default path to use for *get_storage_dir()* if path is None.

Will use OS Environment variable "PYTAN_STORAGE_PATH" if set.

`pytan3.utils.tools.get_env(key, default)`
Get an environment variables value.

Parameters

- **key** (str) – Name of OS environment variable value to get.
- **default** (str) – Default value to return if key is not set or is empty.

Returns str

`pytan3.utils.tools.get_storage_dir(path=None, path_sub='', mkdir=False)`
Get the directory for PyTan to use for storing local state.

Parameters

- **path** (str or pathlib.Path, optional) – Path to use as base storage directory.

  If None, will use OS environment variable "PYTAN_STORAGE_PATH" if set.

  If None and "PYTAN_STORAGE_PATH" is not set, will use *STORAGE_PATH*.

  Defaults to: None.
- **path_sub** (str or pathlib.Path, optional) – Subdirectory to get under path.

  Defaults to: "".
- **mkdir** (bool, optional) – Create path and path / sub with perms 0700.

  Defaults to: False.

Returns pathlib.Path

`pytan3.utils.tools.str_to_intfloat(s)`
Convert str to int or float.

Parameters **s** (str) – String to convert to float if it has a period or int if not.

Returns `int` or `float`

`pytan3.utils.tools.`**`secs_ago`**(*secs*)
Get a datetime object from N seconds ago.

Parameters **`secs`** (`int` or `float`) – Number of seconds ago to get datetime object of.

Returns `datetime.datetime`

`pytan3.utils.tools.`**`secs_age`**(*dt*)
Get the number of seconds ago of a datetime object.

Parameters **`dt`** (`datetime.datetime`) – Datetime object to calculate age in seconds of.

Returns `int`

`pytan3.utils.tools.`**`b64_encode`**(*s*)
Encode s as base64 using `base64.b64encode()`.

Parameters **`s`** (`str`) – Text to base64 encode.

Returns `str`

`pytan3.utils.tools.`**`b64_decode`**(*s*)
Decode text as base64 using `base64.b64decode()`.

Parameters **`s`** (`str`) – Text to base64 decode.

Returns `str`

`pytan3.utils.tools.`**`trim_txt`**(*txt*, *limit=10000*)
Trim a str if it is over n characters.

Parameters

- **`txt`** (`str`) – String to trim.
- **`limit`** (`int`, optional) – Number of characters to trim txt to.

  Defaults to: 10000.

Returns `str`

`pytan3.utils.tools.`**`get_dict_path`**(*obj*, *path*)
Traverse a dict using a / seperated string.

Parameters

- **`obj`** (`dict`) – Dictionary to traverse using path.
- **`path`** (`str`) – Nested dictionary keys seperated by / to traverse in obj.

Raises `ValueError` – If a part of a path can not be found.

Returns `object`

`pytan3.utils.tools.`**`human_size`**(*size*)
Format a byte count as human readable using `humanfriendly.format_size()`.

Parameters **`size`** (`int` or `str`) – Size to format as an int or as a human readable str.

Notes

Given "13", "13b", "13 bytes", or 13 will return: "13 bytes".

Returns `str`

`pytan3.utils.tools.human_delta(delta, ms=False, short=True)`

Format a delta as human readable using `humanfriendly.format_timespan()`.

Parameters

- **delta** (`int` or `float` or `str` or `datetime.timedelta`) – Number of seconds to format.
- **ms** (`bool`, optional) – Represent milliseconds separately instead of as fractional seconds.

  Defaults to: False.
- **short** (`bool`, optional) – Return shortened version of minutes, seconds, milliseconds.

  Defaults to: True.

Notes

Given 300.1 or "300.1" or datetime.timedelta(seconds=300, microseconds=100000), will return: "5 minutes and 100 milliseconds" or "5m100ms".

Returns `str`

class `pytan3.utils.tools.Timer`

Bases: `object`

Context manager to get a human readable elapsed timespan.

__init__()

Constructor.

start = None

`datetime.datetime` – Start of timespan.

end = None

`datetime.datetime` – End of timespan.

__call__()

Return the current time.

Returns `datetime.datetime`

__enter__()

Set the start time.

Returns `datetime.datetime`

__exit__(*exc_type*, *exc_value*, *exc_traceback*)

Set *end* to now.

__str__()

Get elapsed details.

Returns `str`

__repr__()

Get elapsed details.

Returns `str`

elapsed_delta

Get elapsed time since *start*.

Returns `datetime.timedelta`

elapsed_int

Get elapsed seconds since *start*.

Returns `int`

elapsed

Get elapsed seconds since *start* in human readable format.

ms (bool, optional): Represent milliseconds separately instead of as fractional seconds.

Defaults to: True.

short (bool, optional): Return shortened version of minutes, seconds, millseconds.

Defaults to: True.

Returns `str`

Versioning Utilities

PyTan versioning utilities module.

`pytan3.utils.versions.`**`version_recomp`**(*v1*, *v2*, *vshrink=True*)

Recompile version strings into lists.

Parameters

- **v1** (`str` or `list`) – Version that is being compared against v2.

  Will be shrunk down to the same dotted length as v2 if vshrink is True.

  Will be split into list using period.

- **v2** (`str` or `list`) – Version that v1 is being compared against.

  Will be split into list using period.

- **vshrink** (`bool` or `int`, optional) – If True, shrink v1 down to match the same length as v2.

  If False, do not shrink v1 at all.

  If int, shrink both v1 and v2 down to this length.

  Defaults to: True.

Notes

If any non-integers found in v1 or v2, they will be returned as joined strings using periods.

Default python string comparison leads to a less-than-perfect comparison for ints mixed with strs.

Returns (`list` of `str`, `list` of `str`) or (`str`, `str`)

`pytan3.utils.versions.`**`version_eq`**(*v1*, *v2*, *vshrink=True*)

Check if v1 is equal to v2.

Parameters

- **v1** (str or list) – Version that is being compared against v2.

  Will be shrunk down to the same dotted length as v2 if vshrink is True.

- **v2** (str or list) – Version that v1 is being compared against.
- **vshrink** (bool or int, optional) – If True, shrink v1 down to match the same length as v2.

  If False, do not shrink v1 at all.

  If int, shrink both v1 and v2 down to this length.

  Defaults to: True.

Returns bool

pytan3.utils.versions.**version_min**(*v1*, *v2*, *vshrink=True*)

Check if v1 is greater than or equal to v2.

Parameters

- **v1** (str or list) – Version that is being compared against v2.

  Will be shrunk down to the same dotted length as v2 if vshrink is True.

- **v2** (str or list) – Version that v1 is being compared against.
- **vshrink** (bool or int, optional) – If True, shrink v1 down to match the same length as v2.

  If False, do not shrink v1 at all.

  If int, shrink both v1 and v2 down to this length.

  Defaults to: True.

Returns bool

pytan3.utils.versions.**version_max**(*v1*, *v2*, *vshrink=True*)

Check if v1 is less than or equal to v2.

Parameters

- **v1** (str or list) – Version that is being compared against veq, vmax, and vmin.

  Will be be shrunk down to the same dotted length as veq, vmax, and vmin if vshrink is True.

- **v2** (str or list) – Version that v1 is being compared against.
- **vshrink** (bool or int, optional) – If True, shrink v1 down to match the same length as v2.

  If False, do not shrink v1 at all.

  If int, shrink both v1 and v2 down to this length.

  Defaults to: True.

Returns bool

pytan3.utils.versions.**version_check**(*version*, *veq=''*, *vmax=''*, *vmin=''*, *vshrink=True*)

Check if version meets veq, vmax, and vmin.

Parameters

- **version** (str or list) – Version that is being compared against veq, vmax, and vmin.

  Will be be shrunk down to the same dotted length as veq, vmax, and vmin if vshrink is True.

- **veq** (str, optional) – Exact version that version must match.

  No comparison performed if empty.

  Defaults to: “”.

- **vmin** (str, optional) – Minimum version that version must match.

  No comparison performed if empty.

  Defaults to: “”.

- **vmax** (str, optional) – Maximum version that version must match.

  No comparison performed if empty.

  Defaults to: “”.

- **vshrink** (bool or int, optional) – If True, shrink version down to match the same length as veq, vmax, and vmin.

  If False, do not shrink version at all.

  If int, shrink version, veq, vmax, and vmin down to this length.

  Defaults to: True.

Returns bool

pytan3.utils.versions.**version_check_obj_req**(*version*, *src*, *obj*)

Check if veq, vmax, and vmin from a classes get_version_req meets version.

Parameters

- **version** (str or list) – Version that is being compared against veq, vmax, and vmin keys in the dict returned from the get_version_req class of obj.

  Will be be shrunk down to the same dotted length as veq, vmax, and vmin if vshrink is True.

- **src** (str) – Where version came from, used in exception message.
- **obj** (object) – Object or class that has get_version_req class method.

Raises *pytan3.utils.exceptions.VersionMismatchError* – If any of veq, vmax, vmin keys in dict returned by get_version_req do not match version.

pytan3.utils.versions.**split_ver**(*v*)

Split v into a list of integers.

Parameters **v** (str or list of int or int) – Version string to split using periods.

Returns list of int or str

pytan3.utils.versions.**join_ver**(*v*)

Join v into a dot string.

Parameters **v** (str or list of int or int) – Version string to join using periods.

Returns str

Exceptions for Utilities

Exceptions and warnings for *pytan3.utils*.

exception pytan3.utils.exceptions.**ModuleError**

Bases: *pytan3.exceptions.PyTanError*

Parent of all exceptions for *pytan3.utils*.

Thrown by:

- *pytan3.utils.logs.level_name()*
- *pytan3.utils.logs.level_int()*

exception pytan3.utils.exceptions.**ModuleWarning**

Bases: *pytan3.exceptions.PyTanWarning*

Parent of all warnings for *pytan3.utils*.

Thrown by:

exception pytan3.utils.exceptions.**VersionMismatchError**

Bases: *pytan3.utils.exceptions.ModuleError*

Exception handler when matching a version.

Thrown from:

- *pytan3.utils.versions.version_check_obj_req()*

1.10.10 Command Line Interfaces

Todo: No command line interfaces are shipped with PyTan as of yet. The workflows will need to be done first, and then the logic for how to wrap those workflows seamlessly into command line scripts will take some effort.

Planned for version: *3.2.0*

1.10.11 Workflows

Todo: No workflows are shipped with PyTan as of yet. It will take time to convert all of the workflows from PyTan 2.x into the new architecture built for PyTan 3.x.

Planned for version: *3.1.0*

Workflow encapsulation package for performing actions using the Tanium API.

1.10.12 Environment Variables used throughout PyTan

- *PYTAN_STORE_FILE*
- *PYTAN_SHOW_CERT*
- *PYTAN_SHOW_CHAIN*
- *PYTAN_CERT_VALID*
- *PYTAN_STORAGE_PATH*

1.10.13 Version Information

Version information for PyTan.

`pytan3.version.__version__ = '3.0.0'`
: `str` – Version of package.

`pytan3.version.__url__ = 'https://github.com/tanium/pytan3'`
: `str` – URL of package.

`pytan3.version.__author__ = 'Jim Olsen'`
: `str` – Auth of package.

`pytan3.version.__title__ = 'pytan3'`
: `str` – Title of package.

`pytan3.version.__project__ = 'PyTan'`
: `str` – Name of package.

`pytan3.version.__author_email__ = 'jim.olsen@tanium.com'`
: `str` – Author email of package.

`pytan3.version.__description__ = 'Tanium API workflow encapsulation.'`
: `str` – Description of package.

`pytan3.version.__license__ = 'MIT'`
: `str` – License of package.

`pytan3.version.__copyright__ = 'Copyright Tanium Inc. 2019'`
: `str` – Copyright of package.

1.10.14 Exceptions for all of PyTan

Parent exceptions and warnings for the PyTan package.

exception `pytan3.exceptions.PyTanError`
: Parent exception for all *`pytan3`* errors.

exception `pytan3.exceptions.PyTanWarning`
: Parent warning for all *`pytan3`* warnings.

1.11 Dependencies

- `requests`:

  Used by *HTTP Client* to send requests.

- `cert_human.CertStore` and `cert_human.CertChainStore`:

  Used by *Certificate verification for HTTP Client* to validate and prompt user for verification of SSL Certificates.

- `humanfriendly`:

  Used by *Tools* to show times and file sizes in human readable format.

- xmltodict:

  Used by *Adapters* and *Results* to convert XML text into Python dictionaries and back.

- colorama:

  Used by *Prompting Utilities* to add colors to prompts in order to have them stand out more.

- privy:

  Used by *Crypt Utilities* to provide AES encryption when writing an *Authentication Store*.

- `six`:

  Used throughout PyTan to make code work on Python v2 and Python v3.

- dotenv:

  Used by PyTan to allow use of a `.env` file for *Environment Variables used throughout PyTan*.

1.12 Changelog

1.12.1 Current Major release

3.0.0 (2019-02-21)

- rewrite: Fourth rewrite and redesign (started 2018-09-01)
- todo: No workflows done as of yet, planned for 3.1.0
- todo: No command line interfaces done as of yet, planned for 3.2.0
- enhancement: Support REST and SOAP API types
- enhancement: Uses pip for all dependencies, no more bundled libraries
- enhancement: Package listed on pypi to allow for pip install
- enhancement: Docs now hosted on readthedocs
- enhancement: Support for Python v2.7.x and Python v3.7.x
- enhancement: Modularity everywhere - no more tightly bundled objects that do everything
- enhancement: SSL Certification validation now built-in and required
- enhancement: Specialized prompting module for getting user input from console
- enhancement: Specialized SSL cert module for getting SSL Certs in PEM format and displaying their contents in a human friendly way (like a browser)

Commit history

- **A typo was not a typo.** by *Jim Olsen* at *2019-02-22 22:52:34* I need to wake up.
- **typo in coverage ignores** by *Jim Olsen* at *2019-02-22 22:39:01*
- **add codecov badges and yaml** by *Jim Olsen* at *2019-02-22 22:30:29*
- **typo fix** by *Jim Olsen* at *2019-02-22 22:07:57*
- **add black and vuln to doc index** by *Jim Olsen* at *2019-02-22 22:03:57*
- **Add Tanium to doc nav bar** by *Jim Olsen* at *2019-02-22 22:01:29*
- **add vuln badge** by *Jim Olsen* at *2019-02-22 21:56:30*
- **typo fix** by *Jim Olsen* at *2019-02-22 21:03:07*

- **First push to public repo of 3.0.0** by *Jim Olsen* at *2019-02-22 20:56:15*
- **First push to public repo of 3.0.0** by *Jim Olsen* at *2019-02-22 20:56:02*

1.12.2 Older Major releases

2.0.0 (2015-08-07)

- rewrite: Third rewrite and redesign
- Added Tanium Platform v6.2 and v6.5 support
- Automated API workflow capture
- Automated API examples
- Much more

1.0.0 (2014-12-01)

- rewrite: Second rewrite and redesign
- Added more and better workflows
- Re-worked command line interface
- More and better docs

0.0.5 (2014-11-05)

- rewrite: First rewrite and redesign
- Initial testing framework added

0.0.1 (2014-10-10)

- initial: Birth of PyTan!
- Only Tanium Platform v6.0 supported

CHAPTER 2

Indices and tables

- genindex
- modindex
- search

Python Module Index

p

pytan3, 11
pytan3.adapters, 473
pytan3.adapters.exceptions, 489
pytan3.api_clients, 36
pytan3.api_clients.exceptions, 43
pytan3.api_models, 459
pytan3.api_models.exceptions, 469
pytan3.api_objects, 43
pytan3.api_objects.exceptions, 47
pytan3.api_objects.rest_7_3_314_3424, 48
pytan3.api_objects.rest_7_3_314_3641, 132
pytan3.api_objects.soap_7_2_314_3181, 216
pytan3.api_objects.soap_7_3_314_3424, 291
pytan3.api_objects.soap_7_3_314_3641, 375
pytan3.auth_methods, 19
pytan3.auth_methods.exceptions, 25
pytan3.auth_store, 32
pytan3.auth_store.exceptions, 36
pytan3.exceptions, 522
pytan3.http_client, 11
pytan3.http_client.exceptions, 19
pytan3.results, 489
pytan3.results.exceptions, 500
pytan3.utils, 502
pytan3.utils.crypt, 503
pytan3.utils.exceptions, 520
pytan3.utils.logs, 503
pytan3.utils.prompts, 509
pytan3.utils.tools, 515
pytan3.utils.versions, 518
pytan3.version, 522
pytan3.workflows, 521

Index

Symbols

__add__() (pytan3.api_models.ApiList method), 464
__author__ (in module pytan3.version), 522
__author_email__ (in module pytan3.version), 522
__call__() (pytan3.api_clients.Rest method), 40
__call__() (pytan3.api_clients.Soap method), 38
__call__() (pytan3.http_client.Certify method), 15
__call__() (pytan3.http_client.HttpClient method), 12
__call__() (pytan3.results.Rest method), 497
__call__() (pytan3.results.Soap method), 494
__call__() (pytan3.utils.tools.Timer method), 517
__contains__() (pytan3.api_models.ApiList method), 464
__copy__() (pytan3.api_models.ApiModel method), 460
__copyright__ (in module pytan3.version), 522
__deepcopy__() (pytan3.api_models.ApiModel method), 460
__description__ (in module pytan3.version), 522
__enter__() (pytan3.utils.tools.Timer method), 517
__eq__() (pytan3.api_models.ApiModel method), 460
__exit__() (pytan3.utils.tools.Timer method), 517
__getattr__() (pytan3.utils.prompts.ColorWrap method), 510
__getitem__() (pytan3.api_models.ApiList method), 465
__getitem__() (pytan3.api_objects.rest_7_3_314_3424.ColumnList method), 53
__getitem__() (pytan3.api_objects.rest_7_3_314_3424.Row method), 55
__getitem__() (pytan3.api_objects.rest_7_3_314_3641.ColumnList method), 137
__getitem__() (pytan3.api_objects.rest_7_3_314_3641.Row method), 139
__getitem__() (pytan3.api_objects.soap_7_2_314_3181.ColumnList method), 221
__getitem__() (pytan3.api_objects.soap_7_2_314_3181.Row method), 224
__getitem__() (pytan3.api_objects.soap_7_3_314_3424.ColumnList method), 296
__getitem__() (pytan3.api_objects.soap_7_3_314_3424.Row method), 298
__getitem__() (pytan3.api_objects.soap_7_3_314_3641.ColumnList method), 379
__getitem__() (pytan3.api_objects.soap_7_3_314_3641.Row method), 382
__iadd__() (pytan3.api_models.ApiList method), 464
__init__() (pytan3.adapters.Rest method), 480
__init__() (pytan3.adapters.Soap method), 476
__init__() (pytan3.api_clients.Rest method), 40
__init__() (pytan3.api_clients.Soap method), 38
__init__() (pytan3.api_models.ApiItem method), 462
__init__() (pytan3.api_models.ApiList method), 463
__init__() (pytan3.api_models.exceptions.AttrTypeError method), 471
__init__() (pytan3.api_models.exceptions.AttrUndefinedError method), 470
__init__() (pytan3.api_models.exceptions.AttrUndefinedWarning method), 470
__init__() (pytan3.api_models.exceptions.GetSingleItemError method), 473
__init__() (pytan3.api_models.exceptions.ListItemTypeError method), 472
__init__() (pytan3.api_models.exceptions.ListTypeError method), 471
__init__() (pytan3.api_objects.ApiObjects method), 43
__init__() (pytan3.api_objects.exceptions.UnknownApiNameError method), 48
__init__() (pytan3.api_objects.rest_7_3_314_3424.ResultSet method), 52
__init__() (pytan3.api_objects.rest_7_3_314_3641.ResultSet method), 136
__init__() (pytan3.api_objects.soap_7_2_314_3181.ResultSet method), 220
__init__() (pytan3.api_objects.soap_7_3_314_3424.ResultSet method), 295
__init__() (pytan3.api_objects.soap_7_3_314_3641.ResultSet method), 378
__init__() (pytan3.auth_methods.CommonMixin method), 22
__init__() (pytan3.auth_methods.Credentials method), 27
__init__() (pytan3.auth_methods.RestCredentials

method), 28
__init__() (pytan3.auth_methods.SessionId method), 30
__init__() (pytan3.auth_methods.exceptions.MethodError method), 25
__init__() (pytan3.auth_store.AuthStore method), 32
__init__() (pytan3.http_client.Certify method), 15
__init__() (pytan3.http_client.HttpClient method), 11
__init__() (pytan3.http_client.UrlParser method), 17
__init__() (pytan3.results.CommonMixin method), 492
__init__() (pytan3.results.RestUrlPath method), 499
__init__() (pytan3.results.exceptions.ApiWrongRequestType method), 502
__init__() (pytan3.results.exceptions.DictionaryPathError method), 502
__init__() (pytan3.results.exceptions.ResponseError method), 500
__init__() (pytan3.results.exceptions.TextDeserializeError method), 501
__init__() (pytan3.utils.prompts.ColorWrap method), 509
__init__() (pytan3.utils.prompts.NoTtyError method), 514
__init__() (pytan3.utils.prompts.PromptError method), 514
__init__() (pytan3.utils.prompts.Promptness method), 510
__init__() (pytan3.utils.tools.Timer method), 517
__len__() (pytan3.api_models.ApiItem method), 462
__len__() (pytan3.api_models.ApiList method), 464
__len__() (pytan3.api_objects.rest_7_3_314_3424.Row method), 56
__len__() (pytan3.api_objects.rest_7_3_314_3641.Row method), 140
__len__() (pytan3.api_objects.soap_7_2_314_3181.Row method), 224
__len__() (pytan3.api_objects.soap_7_3_314_3424.Row method), 298
__len__() (pytan3.api_objects.soap_7_3_314_3641.Row method), 382
__license__ (in module pytan3.version), 522
__ne__() (pytan3.api_models.ApiModel method), 460
__project__ (in module pytan3.version), 522
__repr__() (pytan3.adapters.Rest method), 481
__repr__() (pytan3.adapters.Soap method), 476
__repr__() (pytan3.api_clients.Rest method), 40
__repr__() (pytan3.api_clients.Soap method), 38
__repr__() (pytan3.api_models.ApiItem method), 462
__repr__() (pytan3.api_models.ApiList method), 464
__repr__() (pytan3.api_objects.ApiObjects method), 44
__repr__() (pytan3.api_objects.rest_7_3_314_3424.ColumnList method), 53
__repr__() (pytan3.api_objects.rest_7_3_314_3424.ResultInfo method), 51
__repr__() (pytan3.api_objects.rest_7_3_314_3424.ResultInfoList method), 50
__repr__() (pytan3.api_objects.rest_7_3_314_3424.Row method), 55
__repr__() (pytan3.api_objects.rest_7_3_314_3424.RowList method), 55
__repr__() (pytan3.api_objects.rest_7_3_314_3641.ColumnList method), 137
__repr__() (pytan3.api_objects.rest_7_3_314_3641.ResultInfo method), 135
__repr__() (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList method), 134
__repr__() (pytan3.api_objects.rest_7_3_314_3641.Row method), 139
__repr__() (pytan3.api_objects.rest_7_3_314_3641.RowList method), 139
__repr__() (pytan3.api_objects.soap_7_2_314_3181.ColumnList method), 221
__repr__() (pytan3.api_objects.soap_7_2_314_3181.ResultInfo method), 219
__repr__() (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList method), 218
__repr__() (pytan3.api_objects.soap_7_2_314_3181.Row method), 223
__repr__() (pytan3.api_objects.soap_7_2_314_3181.RowList method), 223
__repr__() (pytan3.api_objects.soap_7_3_314_3424.ColumnList method), 296
__repr__() (pytan3.api_objects.soap_7_3_314_3424.ResultInfo method), 293
__repr__() (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList method), 293
__repr__() (pytan3.api_objects.soap_7_3_314_3424.Row method), 298
__repr__() (pytan3.api_objects.soap_7_3_314_3424.RowList method), 297
__repr__() (pytan3.api_objects.soap_7_3_314_3641.ColumnList method), 379
__repr__() (pytan3.api_objects.soap_7_3_314_3641.ResultInfo method), 377
__repr__() (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList method), 376
__repr__() (pytan3.api_objects.soap_7_3_314_3641.Row method), 382
__repr__() (pytan3.api_objects.soap_7_3_314_3641.RowList method), 381
__repr__() (pytan3.auth_methods.CommonMixin method), 22
__repr__() (pytan3.auth_store.AuthStore method), 32
__repr__() (pytan3.http_client.Certify method), 16
__repr__() (pytan3.http_client.HttpClient method), 12
__repr__() (pytan3.http_client.UrlParser method), 18
__repr__() (pytan3.results.CommonMixin method), 492
__repr__() (pytan3.results.RestUrlPath method), 500
__repr__() (pytan3.utils.prompts.Promptness method), 511

__repr__() (pytan3.utils.tools.Timer method), 517
__setattr__() (pytan3.api_models.ApiItem method), 462
__setattr__() (pytan3.api_models.ApiList method), 465
__str__() (pytan3.adapters.Rest method), 481
__str__() (pytan3.adapters.Soap method), 476
__str__() (pytan3.api_clients.Rest method), 40
__str__() (pytan3.api_clients.Soap method), 38
__str__() (pytan3.api_models.ApiItem method), 462
__str__() (pytan3.api_models.ApiList method), 464
__str__() (pytan3.api_objects.ApiObjects method), 44
__str__() (pytan3.auth_methods.CommonMixin method), 22
__str__() (pytan3.auth_store.AuthStore method), 32
__str__() (pytan3.http_client.Certify method), 16
__str__() (pytan3.http_client.HttpClient method), 12
__str__() (pytan3.http_client.UrlParser method), 18
__str__() (pytan3.results.CommonMixin method), 492
__str__() (pytan3.results.RestUrlPath method), 500
__str__() (pytan3.utils.prompts.Promptness method), 510
__str__() (pytan3.utils.tools.Timer method), 517
__title__ (in module pytan3.version), 522
__url__ (in module pytan3.version), 522
__version__ (in module pytan3.version), 522
_abc_impl (pytan3.adapters.Adapter attribute), 475
_abc_impl (pytan3.adapters.Rest attribute), 485
_abc_impl (pytan3.adapters.Soap attribute), 480
_abc_impl (pytan3.api_clients.ApiClient attribute), 37
_abc_impl (pytan3.api_clients.Rest attribute), 41
_abc_impl (pytan3.api_clients.Soap attribute), 39
_abc_impl (pytan3.auth_methods.AuthMethod attribute), 21
_abc_impl (pytan3.auth_methods.Credentials attribute), 28
_abc_impl (pytan3.auth_methods.RestCredentials attribute), 29
_abc_impl (pytan3.auth_methods.SessionId attribute), 32
_abc_impl (pytan3.results.Rest attribute), 499
_abc_impl (pytan3.results.Result attribute), 491
_abc_impl (pytan3.results.Soap attribute), 496
_build_key() (pytan3.auth_store.AuthStore class method), 36
_decrypt() (pytan3.auth_store.AuthStore class method), 35
_encrypt() (pytan3.auth_store.AuthStore class method), 35
_fetch_stores (pytan3.http_client.Certify attribute), 17
_init_parsed (pytan3.http_client.UrlParser attribute), 17
_init_scheme (pytan3.http_client.UrlParser attribute), 17
_init_url (pytan3.http_client.UrlParser attribute), 17
_models (pytan3.api_objects.ApiObjects attribute), 44
_module (pytan3.api_objects.ApiObjects attribute), 43

A

Action (class in pytan3.api_objects.rest_7_3_314_3424), 74
Action (class in pytan3.api_objects.rest_7_3_314_3641), 159
Action (class in pytan3.api_objects.soap_7_2_314_3181), 242
Action (class in pytan3.api_objects.soap_7_3_314_3424), 317
Action (class in pytan3.api_objects.soap_7_3_314_3641), 401
ActionGroup (class in pytan3.api_objects.rest_7_3_314_3424), 90
ActionGroup (class in pytan3.api_objects.rest_7_3_314_3641), 175
ActionGroup (class in pytan3.api_objects.soap_7_2_314_3181), 257
ActionGroup (class in pytan3.api_objects.soap_7_3_314_3424), 333
ActionGroup (class in pytan3.api_objects.soap_7_3_314_3641), 417
ActionGroupList (class in pytan3.api_objects.rest_7_3_314_3424), 127
ActionGroupList (class in pytan3.api_objects.rest_7_3_314_3641), 211
ActionGroupList (class in pytan3.api_objects.soap_7_2_314_3181), 288
ActionGroupList (class in pytan3.api_objects.soap_7_3_314_3424), 369
ActionGroupList (class in pytan3.api_objects.soap_7_3_314_3641), 453
ActionList (class in pytan3.api_objects.rest_7_3_314_3424), 110
ActionList (class in pytan3.api_objects.rest_7_3_314_3641), 194
ActionList (class in pytan3.api_objects.soap_7_2_314_3181), 272
ActionList (class in pytan3.api_objects.soap_7_3_314_3424), 353
ActionList (class in pytan3.api_objects.soap_7_3_314_3641), 436
ActionListInfo (class in pytan3.api_objects.rest_7_3_314_3424), 74
ActionListInfo (class in pytan3.api_objects.rest_7_3_314_3641), 158
ActionListInfo (class in pytan3.api_objects.soap_7_2_314_3181), 241
ActionListInfo (class in pytan3.api_objects.soap_7_3_314_3424), 317
ActionListInfo (class in pytan3.api_objects.soap_7_3_314_3641), 400
ActionStop (class in pytan3.api_objects.rest_7_3_314_3424), 75
ActionStop (class in pytan3.api_objects.rest_7_3_314_3641), 159
ActionStop (class in py-

tan3.api_objects.soap_7_2_314_3181), 242
ActionStop (class in pytan3.api_objects.soap_7_3_314_3424), 318
ActionStop (class in pytan3.api_objects.soap_7_3_314_3641), 401
ActionStopList (class in pytan3.api_objects.rest_7_3_314_3424), 110
ActionStopList (class in pytan3.api_objects.rest_7_3_314_3641), 195
ActionStopList (class in pytan3.api_objects.soap_7_2_314_3181), 273
ActionStopList (class in pytan3.api_objects.soap_7_3_314_3424), 353
ActionStopList (class in pytan3.api_objects.soap_7_3_314_3641), 437
Adapter (class in pytan3.adapters), 473
add_file() (in module pytan3.utils.logs), 507
add_null() (in module pytan3.utils.logs), 508
add_stderr() (in module pytan3.utils.logs), 506
add_stdout() (in module pytan3.utils.logs), 506
api_add() (pytan3.adapters.Adapter method), 474
api_add() (pytan3.adapters.Rest method), 482
api_add() (pytan3.adapters.Soap method), 478
api_add_parsed_question() (pytan3.adapters.Adapter method), 475
api_add_parsed_question() (pytan3.adapters.Rest method), 484
api_add_parsed_question() (pytan3.adapters.Soap method), 479
api_attrs() (pytan3.api_models.ApiModel class method), 460
api_attrs_desc() (pytan3.api_models.ApiList class method), 466
api_attrs_desc() (pytan3.api_models.ApiModel class method), 461
api_attrs_repr() (pytan3.api_models.ApiModel class method), 460
api_attrs_str() (pytan3.api_models.ApiModel class method), 460
api_client (pytan3.adapters.Adapter attribute), 473
api_client (pytan3.adapters.Rest attribute), 481
api_client (pytan3.adapters.Soap attribute), 476
api_coerce_complex() (pytan3.api_models.ApiModel class method), 461
api_coerce_float() (pytan3.api_models.ApiModel class method), 461
api_coerce_int() (pytan3.api_models.ApiModel class method), 461
api_coerce_item() (pytan3.api_models.ApiList method), 466
api_coerce_items() (pytan3.api_models.ApiList method), 465
api_coerce_items_hook() (pytan3.api_models.ApiList method), 466
api_coerce_items_hook() (pytan3.api_objects.rest_7_3_314_3424.ApiList method), 49
api_coerce_items_hook() (pytan3.api_objects.rest_7_3_314_3641.ApiList method), 133
api_coerce_items_hook() (pytan3.api_objects.soap_7_2_314_3181.RowColumnList method), 225
api_coerce_items_hook() (pytan3.api_objects.soap_7_3_314_3424.RowColumnList method), 299
api_coerce_items_hook() (pytan3.api_objects.soap_7_3_314_3641.RowColumnList method), 383
api_coerce_list() (pytan3.api_models.ApiModel class method), 461
api_coerce_simple() (pytan3.api_models.ApiModel class method), 461
api_coerce_value() (pytan3.api_models.ApiModel method), 461
API_COLUMN (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 56
API_COLUMN (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_COLUMN (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 225
API_COLUMN (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_COLUMN (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
API_COMPLEX (pytan3.api_models.ApiModel attribute), 459
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Action attribute), 75
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ActionGroup attribute), 91
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ActionGroupList attribute), 127
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ActionList attribute), 110
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ActionListInfo attribute), 74
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ActionStop attribute), 75
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ActionStopList attribute), 111
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestio attribute), 76
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestio attribute), 111
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.AuditData attribute), 62
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.AuditDataList

attribute), 100
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.AdmLog attribute), 63
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.AdmLogList attribute), 100
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.CaptchaImg attribute), 84
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.CaptchaImgList attribute), 120
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.CaptchaInfo attribute), 67
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.CaptchaInfoList attribute), 79
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.CaptchaStatus attribute), 70
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Client attribute), 53
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ClientList attribute), 53
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ComputerGroup attribute), 82
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupExt attribute), 119
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupExtSpec attribute), 82
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupList attribute), 131
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupSpecList attribute), 119
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSet attribute), 85
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetList attribute), 121
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetPrivilege attribute), 87
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetPrivilegeList attribute), 124
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRole attribute), 86
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExt attribute), 122
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExtSpecial attribute), 86
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExtSpecialList attribute), 123
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExtSpecialPrivilege attribute), 88
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExtSpecialPrivilegeList attribute), 124
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExtSpecialRole attribute), 85
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExtSpecialRoleList attribute), 122
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ConfigSetRoleExtSpecialRoleObjectIds attribute), 87
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupRoleExtSpecialRoleObjectIdsList attribute), 123
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 126
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSet attribute), 88
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetList attribute), 125
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetSpecialRoleObjectIdsList attribute), 125
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Filter attribute), 64
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.FilterList attribute), 103
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Group attribute), 65
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.GroupList attribute), 103
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.HashedString attribute), 95
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.HashedStringList attribute), 132
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.IdReference attribute), 65
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDefinition attribute), 84
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDefinitionList attribute), 120
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ImportConflictOption attribute), 121
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnect attribute), 92
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnectExt attribute), 128
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.MergedResultSet attribute), 51
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.MetadataItem attribute), 64
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.MetadataList attribute), 102
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ObjectList attribute), 83
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Options attribute), 84
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageFile attribute), 69
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageFileList

attribute), 106
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatus attribute), 68
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatusList attribute), 105
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate attribute), 68
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplateList attribute), 105
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageSpec attribute), 69
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PackageSpecList attribute), 106
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parameter attribute), 77
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parameterList attribute), 114
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parameterValueList attribute), 114
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_job attribute), 77
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_jobList attribute), 112
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_questionResult attribute), 59
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_questionResultList attribute), 58
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_result attribute), 77
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_resultProbe attribute), 78
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_resultProbeList attribute), 113
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.parse_resultList attribute), 113
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.permissionList attribute), 109
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin attribute), 81
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_argument attribute), 79
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_argumentList attribute), 115
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_commandExist attribute), 117
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_list attribute), 118
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_schedule attribute), 81
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_scheduleList attribute), 118
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_sql attribute), 116
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.plugin_sqlColumnList attribute), 116
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.PluginSqlResultI attribute), 115
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Question attribute), 68
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.QuestionList attribute), 104
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.QuestionListInfo attribute), 67
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ResultInfo attribute), 50
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ResultInfoList attribute), 50
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ResultSet attribute), 52
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ResultSetList attribute), 51
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.RowColumnList attribute), 56
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.RowList attribute), 54
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 58
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 61
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedActionApp attribute), 61
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedActionApp attribute), 98
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedActionList attribute), 99
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedActionPoli attribute), 60
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedActionRow attribute), 99
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedQuestion attribute), 76
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionLi attribute), 112
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPa attribute), 91
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQu attribute), 92
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQu attribute), 127
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Select attribute), 66
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SelectList attribute), 103
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Sensor

attribute), 62
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorList attribute), 97
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorQuery attribute), 59
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorQueryList attribute), 96
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorReference attribute), 78
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorReferenceList attribute), 114
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorStat attribute), 60
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorStatList attribute), 98
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorStatistic attribute), 60
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SensorStatisticList attribute), 96
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 63
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ServerFixlet attribute), 101
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ServerFixletList attribute), 102
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ServerList attribute), 101
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ServerTemplate attribute), 93
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ServerTemplateList attribute), 128
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ServerTemplateStatus attribute), 94
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.ServerTemplateStatusList attribute), 130
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthToken attribute), 93
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthTokenList attribute), 129
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthTokenStatus attribute), 94
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthTokenStatusList attribute), 130
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthTokenUnset attribute), 93
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthTokenUnsetList attribute), 129
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthTokenUnsetStatus attribute), 95
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SiteAuthTokenUnsetStatusList attribute), 131
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SoapError attribute), 71
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SolutionInfo attribute), 90
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 127
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 70
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAggregate attribute), 72
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus attribute), 80
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UserOwnedObject attribute), 73
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.UserRoleList attribute), 110
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.VerifySignature attribute), 83
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.VersionAggregate attribute), 72
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.VersionAggregateList attribute), 107
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.WhiteListedUrl attribute), 71
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.WhiteListedUrlList attribute), 107
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3424.XmlError attribute), 66
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ActionGroupList attribute), 211
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ActionList attribute), 194
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ActionListInfo

attribute), 158
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.AdminStop
attribute), 159
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.AdminStopList
attribute), 195
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.AdminQuestion
attribute), 160
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.AdminQuestionList
attribute), 195
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ApiData
attribute), 147
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ApiDataList
attribute), 184
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ApiLog
attribute), 147
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ApiLogList
attribute), 184
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.CacheInfo
attribute), 168
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.CacheInfoList
attribute), 204
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.CacheInfo
attribute), 151
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.CacheInfoList
attribute), 163
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.CacheStatus
attribute), 154
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Client
attribute), 138
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ClientList
attribute), 137
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup
attribute), 166
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupList
attribute), 203
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupSpec
attribute), 166
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ComputerList
attribute), 215
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ComputerSpecList
attribute), 203
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSet
attribute), 169
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetList
attribute), 205
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilege
attribute), 171
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilegeList
attribute), 208
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole
attribute), 170
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleList
attribute), 206
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembers
attribute), 171
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembersList
attribute), 207
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilege
attribute), 172
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeList
attribute), 208
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivileges
attribute), 170
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegesList
attribute), 206
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupMembers
attribute), 171
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupMembersList
attribute), 207
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Dashboard
attribute), 173
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.DashboardGroup
attribute), 173
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.DashboardList
attribute), 210
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.EffectiveContent
attribute), 172
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentList
attribute), 209
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSpec
attribute), 209
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ErrorList
attribute), 188
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Filter
attribute), 149
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.FilterList
attribute), 187
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Group
attribute), 149
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.GroupList
attribute), 187
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.HashedString
attribute), 180
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.HashedStringList
attribute), 216
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.IdReference
attribute), 149
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDef
attribute), 168
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDefList
attribute), 204
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ImportConflictOp
attribute), 205
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnect
attribute), 176
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnectList
attribute), 212
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.MergedResultSet

attribute), 136
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.MetadataItem attribute), 148
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.MetadataList attribute), 186
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ObjectList attribute), 167
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.OptionsInfo attribute), 169
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageFile attribute), 153
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageFileList attribute), 190
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatus attribute), 153
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatusList attribute), 190
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplate attribute), 152
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplateList attribute), 189
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageSpec attribute), 154
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PackageSpecList attribute), 191
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Parameter attribute), 161
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParameterList attribute), 198
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParameterTemplate attribute), 198
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseJob attribute), 161
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseJobList attribute), 196
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResult attribute), 143
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResultList attribute), 142
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseResult attribute), 162
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup attribute), 163
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroupList attribute), 197
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ParseResultList attribute), 197
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PermissionList attribute), 193
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PlugIn attribute), 165
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PlugInArgument attribute), 164
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PlugInArgumentList attribute), 199
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PluginCommand attribute), 201
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PluginList attribute), 202
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 165
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PluginScheduleL attribute), 202
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PluginSql attribute), 200
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PluginSqlColumn attribute), 200
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.PluginSqlResultL attribute), 200
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Question attribute), 152
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 189
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.QuestionListInfo attribute), 151
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 135
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.RowColumnList attribute), 140
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.RowList attribute), 139
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedAction attribute), 146
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedActionApp attribute), 145
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedActionApp attribute), 182
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedActionList attribute), 183
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedActionPoli attribute), 145
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedActionRow attribute), 183
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion attribute), 160
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionLi

attribute), 196
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionFilter
attribute), 175
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionFilterL
attribute), 176
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuery
attribute), 212
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Select
attribute), 150
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SelectList
attribute), 188
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorQuery
attribute), 146
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorQueryList
attribute), 181
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorQueryQuery
attribute), 143
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorQueryQueryList
attribute), 180
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorReference
attribute), 162
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorReferenceList
attribute), 199
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorStat
attribute), 144
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorStatList
attribute), 182
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorStatSubmitx
attribute), 144
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SensorStatSubmitxList
attribute), 181
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Server
attribute), 148
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ServerFixlet
attribute), 185
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ServerFixletList
attribute), 186
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ServerList
attribute), 185
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ServerTaskMsg
attribute), 177
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ServerTaskMsgList
attribute), 213
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ServerTaskMsgStatus
attribute), 178
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.ServerTaskMsgStatusList
attribute), 214
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SetAdmin
attribute), 177
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SetAdminList
attribute), 213
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SetAdminStatus
attribute), 179
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SetAdminStatusList
attribute), 215
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubn
attribute), 178
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubn
attribute), 214
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubn
attribute), 179
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubn
attribute), 215
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SoapError
attribute), 155
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.Solution
attribute), 174
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SolutionList
attribute), 211
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.StringHintList
attribute), 181
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SystemSetting
attribute), 155
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SystemSettingLis
attribute), 192
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SystemStatusAgg
attribute), 157
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.SystemStatusList
attribute), 192
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UploadFile
attribute), 164
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UploadFileList
attribute), 201
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus
attribute), 164
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.User
attribute), 158
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UserGroup
attribute), 174
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UserGroupList
attribute), 210
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UserList
attribute), 193
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UserOwnedObje
attribute), 157
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UserRole
attribute), 157
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.UserRoleList
attribute), 194
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.VerifySignature
attribute), 167
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.VersionAggregat
attribute), 156
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.VersionAggregat
attribute), 192
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrl
attribute), 156
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrlL

attribute), 191
API_COMPLEX (pytan3.api_objects.rest_7_3_314_3641.XAPIError attribute), 150
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AdhocCommand attribute), 242
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AdhocCommandFilter attribute), 257
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AdhocCommandFilterList attribute), 289
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AdhocCommandList attribute), 272
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AdhocCommandSelect attribute), 242
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AdhocCommandSort attribute), 243
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AdhocCommandSortList attribute), 273
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ArchiveQuestion attribute), 243
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ArchiveQuestionList attribute), 273
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AuditCom attribute), 230
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AuditComList attribute), 263
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 251
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.CacheInfoList attribute), 282
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Client attribute), 234
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ClientCommand attribute), 246
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 237
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupList attribute), 281
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ComputerGroups attribute), 249
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ComputerList attribute), 290
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ComputerSpecial attribute), 281
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 252
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivil attribute), 254
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivil attribute), 285
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 252
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 284
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 253
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 284
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 254
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 286
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 252
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 283
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetUser attribute), 253
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ContentSetUser attribute), 285
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Dashboard attribute), 255
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.DashboardGrou attribute), 256
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 287
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.EffectiveConten attribute), 255
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.EffectiveConten attribute), 287
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.EffectiveConten attribute), 286
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ErrorList attribute), 266
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Filter attribute), 232
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.FilterList attribute), 265
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Group attribute), 233
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.GroupList attribute), 265
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.HashedString attribute), 259
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.HashedStringLis attribute), 291
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.IdReference

attribute), 232
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ImportCommentOptions
attribute), 282
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.IndexSymbolMetaOp
attribute), 259
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.IndexSymbolMetaOpList
attribute), 290
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.MetaGeneral
attribute), 219
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.MetaGeneralEx
attribute), 231
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.MetaGeneralList
attribute), 264
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ObjectCount
attribute), 250
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Options
attribute), 251
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageMe
attribute), 236
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageMeList
attribute), 268
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageMeStats
attribute), 236
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageMeStatsList
attribute), 268
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageMeTemplate
attribute), 236
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageMeTemplateList
attribute), 267
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageSpec
attribute), 237
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PageSpecList
attribute), 269
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Parameter
attribute), 245
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParameterList
attribute), 276
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParameterValueList
attribute), 276
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParseJob
attribute), 244
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParseJobList
attribute), 274
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParseResult
attribute), 245
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParseResultProp
attribute), 246
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParseResultPropList
attribute), 275
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ParseResultList
attribute), 275
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PermissionList
attribute), 272
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginArgument
attribute), 248
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginArgumentOptions
attribute), 247
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginArgumentOptionsList
attribute), 277
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginCommandList
attribute), 279
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginList
attribute), 280
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginSchedule
attribute), 249
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginScheduleList
attribute), 280
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginSql
attribute), 279
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginSqlColumn
attribute), 278
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.PluginSqlResult
attribute), 278
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Question
attribute), 235
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.QuestionList
attribute), 267
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.QuestionListInfo
attribute), 235
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ResultInfo
attribute), 218
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList
attribute), 218
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ResultSet
attribute), 220
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ResultSetList
attribute), 219
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Row
attribute), 223
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.RowColumn
attribute), 226
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.RowColumnList
attribute), 224
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.RowList
attribute), 223
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.RowValue
attribute), 226
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SavedAction
attribute), 229
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SavedActionApply
attribute), 229
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SavedActionApplyList
attribute), 262
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SavedActionList
attribute), 263
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicy
attribute), 229
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SavedActionRow

attribute), 262
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestion attribute), 244
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionList attribute), 274
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionAcceptance attribute), 258
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionQuestion attribute), 258
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionQuestion3 attribute), 289
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Select attribute), 233
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SelectOp attribute), 266
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorCOMPLEX attribute), 230
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorCOMPLEX attribute), 261
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorQueryList attribute), 260
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 245
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorReferenceList attribute), 277
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorSum attribute), 228
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorSumCOMPLEX attribute), 261
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorSumColumn attribute), 228
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SensorSumColumnList attribute), 260
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 238
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SolutionCOMPLEX attribute), 288
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SystemSettingCOMPLEX attribute), 261
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SystemSettingExt attribute), 238
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SystemSettingExtCOMPLEX attribute), 271
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAggregate attribute), 240
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.SystemStatusList attribute), 270
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 247
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 280
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObje attribute), 241
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.UserRoleList attribute), 272
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.VersionAggrega attribute), 239
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.VersionAggrega attribute), 270
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrl attribute), 239
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrlL attribute), 269
API_COMPLEX (pytan3.api_objects.soap_7_2_314_3181.XmlError attribute), 234
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Action attribute), 317
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ActionGroup attribute), 333
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ActionGroupLis attribute), 370
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ActionList attribute), 353
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ActionListInfo attribute), 317
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ActionStop attribute), 318
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ActionStopList attribute), 353
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestio attribute), 318
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestio attribute), 354
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.AuditData attribute), 305
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.AuditDataList attribute), 342
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.AuditLog attribute), 305
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.AuditLogList attribute), 343
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CacheFilter

attribute), 327
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CacheFolderList attribute), 363
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CacheObj attribute), 309
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ClientCount attribute), 322
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ClientStatus attribute), 313
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CommonFilter attribute), 296
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CommonList attribute), 295
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CompositeGroup attribute), 325
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CompositeGroupList attribute), 362
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CompositeGroups attribute), 324
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CompositeList attribute), 374
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.CompositeSplitList attribute), 361
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentFilter attribute), 328
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentFilterList attribute), 364
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentPrivilege attribute), 330
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentPrivilegeList attribute), 366
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRole attribute), 329
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRoleList attribute), 365
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRoleMembership attribute), 329
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRoleMembershipList attribute), 365
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRolePrivilege attribute), 330
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRolePrivilegeList attribute), 367
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRoleObjectsOnRole attribute), 328
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentRoleObjectsOnRoleList attribute), 364
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentUserMembership attribute), 330
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ContentUserMembershipList attribute), 366
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.DashboardObj attribute), 331
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.DashboardList attribute), 368
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentCount attribute), 331
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentCountList attribute), 368
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentStatus attribute), 367
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ErrorList attribute), 347
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Filter attribute), 307
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.FilterList attribute), 346
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.GroupList attribute), 345
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 338
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.HashedStringList attribute), 374
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.IdReference attribute), 307
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetail attribute), 326
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetailMessage attribute), 362
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetailMessageList attribute), 363
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnection attribute), 335
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnectionList attribute), 371
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.MergedResultSet attribute), 294
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 306
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.MetadataList attribute), 345
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Options attribute), 327
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PackageFileList attribute), 349
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatus attribute), 311
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatusList attribute), 348
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemp

attribute), 311
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PageTemplateList
attribute), 348
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PageSpec
attribute), 312
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PageSpecList
attribute), 349
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Parameter
attribute), 320
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParameterList
attribute), 356
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParameterValueList
attribute), 357
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParseJob
attribute), 319
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParseJobList
attribute), 355
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParseResult
attribute), 320
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParseResultProp
attribute), 321
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParseResultPropList
attribute), 355
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ParseResultList
attribute), 356
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PermissionList
attribute), 352
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginArgument
attribute), 323
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginArgumentEx
attribute), 322
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginArgumentExList
attribute), 358
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginCommandList
attribute), 359
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginCon
attribute), 360
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule
attribute), 324
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginSchedulesList
attribute), 361
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginSq
attribute), 359
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginSqColumnList
attribute), 359
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.PluginSqResultList
attribute), 358
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Question
attribute), 310
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.QuestionList
attribute), 347
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.QuestionMatch
attribute), 310
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ResultCon
attribute), 293
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList
attribute), 292
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ResultSet
attribute), 294
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ResultSetList
attribute), 293
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Row
attribute), 298
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.RowColumn
attribute), 300
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.RowColumnList
attribute), 299
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.RowList
attribute), 297
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.RowValue
attribute), 301
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedAction
attribute), 304
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedActionApp
attribute), 304
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedActionApplyList
attribute), 341
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedActionList
attribute), 342
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedActionPolicy
attribute), 303
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedActionRowFilter
attribute), 341
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion
attribute), 319
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionList
attribute), 354
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionPlan
attribute), 334
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuery
attribute), 334
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestion
attribute), 370
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Select
attribute), 308
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SelectList
attribute), 346
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.Sensor
attribute), 305
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SensorList
attribute), 340
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SensorQuery
attribute), 302
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SensorQueryList
attribute), 339
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SensorReference
attribute), 321
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SensorReference

attribute), 357
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerSum
attribute), 303
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerSumList
attribute), 340
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerSumColumn
attribute), 302
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerSumColumnList
attribute), 339
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerT
attribute), 306
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerTom
attribute), 344
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerTomList
attribute), 344
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerTomSum
attribute), 343
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerTomFile
attribute), 335
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerTomFileExt
attribute), 371
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerTomFileStatus
attribute), 337
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.ServerTomFileStatusList
attribute), 372
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTom
attribute), 336
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTomList
attribute), 371
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTomStatus
attribute), 337
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTomStatusList
attribute), 373
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTomSum
attribute), 336
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTomSumList
attribute), 372
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTomSumStatus
attribute), 338
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SettingsTomSumStatusList
attribute), 373
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SoapError
attribute), 314
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SortOrder
attribute), 333
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SortOrderList
attribute), 369
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SyntaxTomList
attribute), 339
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SyntaxTomSaving
attribute), 313
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SyntaxTomSavingExt
attribute), 351
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SyntaxTomSumAggregate
attribute), 315
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.SystemStatusList
attribute), 350
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UploadFile
attribute), 322
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UploadFileList
attribute), 360
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UploadFileStatus
attribute), 323
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.User
attribute), 316
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UserGroup
attribute), 332
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UserGroupList
attribute), 369
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UserList
attribute), 351
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObje
attribute), 316
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UserRole
attribute), 315
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.UserRoleList
attribute), 352
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.VerifySignature
attribute), 325
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.VersionAggrega
attribute), 314
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.VersionAggrega
attribute), 350
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrl
attribute), 314
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrlL
attribute), 349
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3424.XmlError
attribute), 309
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Action
attribute), 401
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ActionGroup
attribute), 417
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ActionGroupLis
attribute), 453
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ActionList
attribute), 436
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ActionListInfo
attribute), 400
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ActionStop
attribute), 401
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ActionStopList
attribute), 437
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestio
attribute), 402
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestio
attribute), 437
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.AuditData

attribute), 389
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.AuditDumpList attribute), 426
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.AuditLog attribute), 389
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.AuditLogList attribute), 426
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CacheItem attribute), 410
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CacheItemList attribute), 446
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CacheObj attribute), 393
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ClientCount attribute), 405
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ClientStatus attribute), 396
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ColumnList attribute), 379
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CombinedGroup attribute), 409
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CombinedGroupList attribute), 445
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CombinedGroupsExpr attribute), 408
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CombinedList attribute), 458
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.CombinedObjectList attribute), 445
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSet attribute), 411
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetList attribute), 447
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetPrivilege attribute), 414
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetPrivilegeList attribute), 450
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRole attribute), 412
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRoleList attribute), 448
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRoleMembership attribute), 413
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRoleMembershipList attribute), 449
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRolePrivilege attribute), 414
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRolePrivilegeList attribute), 450
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRoleObjectPolicy attribute), 412
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ConfigSetRoleObjectPolicyList attribute), 448
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserC attribute), 413
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserC attribute), 449
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Dashboard attribute), 415
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.DashboardGrou attribute), 416
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.DashboardList attribute), 452
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.EffectiveConten attribute), 415
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.EffectiveConten attribute), 451
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.EffectiveConten attribute), 451
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ErrorList attribute), 430
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Filter attribute), 391
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.FilterList attribute), 429
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Group attribute), 392
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.GroupList attribute), 429
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.HashedString attribute), 422
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.HashedStringLis attribute), 458
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.IdReference attribute), 391
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ImportConflictD attribute), 410
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ImportConflictD attribute), 446
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ImportConflictC attribute), 447
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConne attribute), 418
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConne attribute), 454
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.MergedResultSe attribute), 378
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.MetadataItem attribute), 390
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.MetadataList attribute), 428
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ObjectList attribute), 409
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Options attribute), 411
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PackageFile

attribute), 395
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PageMetaList
attribute), 432
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PageMetaStats
attribute), 395
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PageMetaStatsList
attribute), 432
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PageMetaTemplate
attribute), 394
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PageMetaTemplateList
attribute), 431
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PageSpec
attribute), 396
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PageSpecList
attribute), 433
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Parameter
attribute), 403
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParameterList
attribute), 440
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParameterValueList
attribute), 440
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParseJob
attribute), 403
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParseJobList
attribute), 438
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParseResult
attribute), 404
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParseResultInfo
attribute), 405
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParseResultInfoList
attribute), 439
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ParseResultList
attribute), 439
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PermissionList
attribute), 436
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginArgument
attribute), 407
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginArgumentList
attribute), 406
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginCommandList
attribute), 441
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginCommandOptionList
attribute), 443
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginCommand
attribute), 444
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginSchedule
attribute), 408
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginScheduleList
attribute), 444
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginSq
attribute), 443
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginSqColumnList
attribute), 442
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.PluginSqResultInfo
attribute), 442
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Question
attribute), 394
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.QuestionList
attribute), 431
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.QuestionListInfo
attribute), 393
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ResultInfo
attribute), 377
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList
attribute), 376
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ResultSet
attribute), 378
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ResultSetList
attribute), 377
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Row
attribute), 382
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RowColumn
attribute), 384
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RowColumnList
attribute), 383
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RowList
attribute), 381
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RowValue
attribute), 385
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedAction
attribute), 388
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedActionApp
attribute), 387
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedActionApp
attribute), 425
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedActionList
attribute), 425
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedActionPol
attribute), 387
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedActionRow
attribute), 425
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion
attribute), 402
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionL
attribute), 438
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionP
attribute), 417
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQ
attribute), 418
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQ
attribute), 454
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Select
attribute), 392
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SelectList
attribute), 430
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Sensor
attribute), 388
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SensorList

attribute), 424
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotQuery attribute), 385
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotQueryList attribute), 422
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotReference attribute), 404
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotReferenceList attribute), 441
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotSum attribute), 386
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotSumBlock attribute), 424
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotSumBlockLimit attribute), 386
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.RemotSumBlockList attribute), 423
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 427
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ServerLoad attribute), 427
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ServerOnline attribute), 419
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ServerOnlineList attribute), 455
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ServerOnlineStatus attribute), 420
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.ServerOnlineStatusList attribute), 456
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SettingOne attribute), 419
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SettingOneList attribute), 455
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SettingOneStatus attribute), 421
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SettingOneStatusList attribute), 457
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SettingSize attribute), 420
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SettingSizeList attribute), 456
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SettingStatus attribute), 421
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSettingStatusList attribute), 457
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 416
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SystemSettingList attribute), 435
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SystemStatusAge attribute), 399
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.SystemStatusList attribute), 434
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 444
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.User attribute), 400
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UserOwnedObje attribute), 400
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.VerifySignature attribute), 409
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.VersionAggrega attribute), 398
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.VersionAggrega attribute), 434
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrl attribute), 398
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrlL attribute), 433
API_COMPLEX (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 393
API_CONSTANTS (pytan3.api_models.ApiModelList attribute), 459
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ActionStatus attribute), 75
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ActionGroup attribute), 91
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ActionGroupList attribute), 127

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ActionList attribute), 110
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ActionListInfo attribute), 74
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ActionStop attribute), 75
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ActionStopList attribute), 111
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestion attribute), 76
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestionList attribute), 111
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.AuditData attribute), 62
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.AuditDataList attribute), 100
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.AuditLog attribute), 63
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.AuditLogList attribute), 100
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.CacheFilter attribute), 84
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.CacheFilterList attribute), 120
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.CacheInfo attribute), 67
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ClientCount attribute), 79
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ClientStatus attribute), 70
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 54
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ColumnList attribute), 53
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ComputerGroup attribute), 82
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupList attribute), 119
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupSpec attribute), 82
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ComputerIdList attribute), 131
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ComputerSpecList attribute), 119
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSet attribute), 85
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetList attribute), 121
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilege attribute), 87
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilegeList attribute), 124
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRole attribute), 86
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleList attribute), 122
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMembership attribute), 86
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMembership attribute), 123
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilege attribute), 88
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeLis attribute), 124
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeOn attribute), 85
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeOn attribute), 122
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupRoleM attribute), 87
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupRoleM attribute), 123

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 126
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivilege attribute), 88
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivilegeList attribute), 125
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivilegeRequest attribute), 125
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Filter attribute), 64
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.FilterList attribute), 103
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Group attribute), 65
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.GroupList attribute), 103
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.HashedString attribute), 95
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.HashedStringList attribute), 132
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.IdReference attribute), 65
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDetail attribute), 84
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDetailList attribute), 120
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ImportConflictOptions attribute), 121
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnector attribute), 92
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnectorList attribute), 128
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.MergedResultSet attribute), 51
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.MetadataItem attribute), 64
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.MetadataList attribute), 102
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ObjectList attribute), 83
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Options attribute), 85
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageFile attribute), 69
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageFileList attribute), 106
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatus attribute), 69
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatusList attribute), 105
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate attribute), 68
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplateList attribute), 105
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageSpec attribute), 69
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PackageSpecList attribute), 106
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Parameter attribute), 77
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParameterList attribute), 114
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParameterValueList attribute), 114
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseJob attribute), 77

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseJobList attribute), 112
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResult attribute), 59
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResultList attribute), 58
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseResult attribute), 78
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup attribute), 78
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroupList attribute), 113
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ParseResultList attribute), 113
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PermissionList attribute), 109
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Plugin attribute), 81
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginArgument attribute), 79
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginArgumentList attribute), 115
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginCommandList attribute), 117
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginList attribute), 118
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginSchedule attribute), 81
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginScheduleList attribute), 118
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginSql attribute), 116
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginSqlColumnList attribute), 116
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.PluginSqlResultList attribute), 115
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Question attribute), 68
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.QuestionList attribute), 104
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.QuestionListInfo attribute), 67
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ResultInfo attribute), 50
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ResultInfoList attribute), 50
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ResultSet attribute), 52
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ResultSetList attribute), 51
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.RowColumnList attribute), 56
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.RowList attribute), 54
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 58
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 61
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedActionApproval attribute), 61
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedActionApprovalList attribute), 98
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedActionList attribute), 99
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolicy attribute), 61
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedActionRowIdList attribute), 99

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestion attribute), 76
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionList attribute), 112
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPackageSpec attribute), 91
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestion attribute), 92
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestionList attribute), 128
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Select attribute), 66
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SelectList attribute), 104
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Sensor attribute), 62
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorList attribute), 97
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorQuery attribute), 59
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorQueryList attribute), 96
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorReference attribute), 78
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorReferenceList attribute), 115
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorStat attribute), 60
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorStatList attribute), 98
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumn attribute), 60
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumnList attribute), 96
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 63
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ServerHost attribute), 101
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ServerHostList attribute), 102
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ServerList attribute), 101
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottle attribute), 93
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleList attribute), 128
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatus attribute), 94
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatusList attribute), 130
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottle attribute), 93
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleList attribute), 129
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 94
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatusList attribute), 130
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnet attribute), 94
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetList attribute), 129
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatus attribute), 95
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatusLis attribute), 131
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SoapError attribute), 71
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.Solution attribute), 90
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 127

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 70
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAggregate attribute), 72
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus attribute), 80
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UserOwnedObjectIds attribute), 73
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.UserRoleList attribute), 110
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.VerifySignature attribute), 83
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.VersionAggregate attribute), 72
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.VersionAggregateList attribute), 107
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.WhiteListedUrl attribute), 71
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.WhiteListedUrlList attribute), 107
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3424.XmlError attribute), 66
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ActionGroupList attribute), 211
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ActionList attribute), 194
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ActionListInfo attribute), 158
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ActionStop attribute), 159
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ActionStopList attribute), 195
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ArchivedQuestion attribute), 160
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ArchivedQuestionList attribute), 195
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.AuditData attribute), 147
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.AuditDataList attribute), 184
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.AuditLog attribute), 147
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.AuditLogList attribute), 184
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.CacheFilter attribute), 168
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.CacheFilterList attribute), 204

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.CacheInfo attribute), 151
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ClientCount attribute), 163
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ClientStatus attribute), 154
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 138
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ColumnList attribute), 137
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup attribute), 166
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupList attribute), 203
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupSpec attribute), 166
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ComputerIdList attribute), 216
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ComputerSpecList attribute), 203
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSet attribute), 169
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetList attribute), 205
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilege attribute), 172
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilegeList attribute), 208
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole attribute), 170
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleList attribute), 206
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembership attribute), 171
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembershipList attribute), 207
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilege attribute), 172
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeList attribute), 208
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeOnl attribute), 170
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeOnl attribute), 206
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupRoleM attribute), 171
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupRoleM attribute), 207
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Dashboard attribute), 173
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.DashboardGroup attribute), 173
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.DashboardList attribute), 210
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivileg attribute), 172
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivileg attribute), 209
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivileg attribute), 209
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ErrorList attribute), 188
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Filter attribute), 149
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.FilterList attribute), 187
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Group attribute), 150
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.GroupList attribute), 187
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.HashedString attribute), 180

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.HashedStringList attribute), 216
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.IdReference attribute), 149
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDetail attribute), 168
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDetailList attribute), 204
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ImportConflictOptions attribute), 205
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnector attribute), 176
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnectorList attribute), 212
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.MergedResultSet attribute), 136
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.MetadataItem attribute), 148
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.MetadataList attribute), 186
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ObjectList attribute), 167
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Options attribute), 169
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageFile attribute), 153
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageFileList attribute), 190
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatus attribute), 153
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatusList attribute), 190
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplate attribute), 152
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplateList attribute), 189
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageSpec attribute), 154
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PackageSpecList attribute), 191
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Parameter attribute), 161
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParameterList attribute), 198
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParameterValueList attribute), 198
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseJob attribute), 161
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseJobList attribute), 196
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResult attribute), 143
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResultList attribute), 142
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseResult attribute), 162
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup attribute), 163
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroupList attribute), 197
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ParseResultList attribute), 197
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PermissionList attribute), 193
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Plugin attribute), 165
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginArgument attribute), 164
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginArgumentList attribute), 199
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginCommandList attribute), 201

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginList attribute), 202
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 165
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginScheduleList attribute), 202
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginSql attribute), 201
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginSqlColumnList attribute), 200
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.PluginSqlResultList attribute), 200
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Question attribute), 152
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 189
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.QuestionListInfo attribute), 151
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 135
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.RowColumnList attribute), 140
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.RowList attribute), 139
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedAction attribute), 146
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedActionApproval attribute), 145
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedActionApprovalList attribute), 182
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedActionList attribute), 183
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedActionPolicy attribute), 145
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedActionRowIdList attribute), 183
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion attribute), 160
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionList attribute), 196
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionPackageSpec attribute), 175
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestion attribute), 176
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestionList attribute), 212
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Select attribute), 150
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SelectList attribute), 188
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Sensor attribute), 146
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorList attribute), 181
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 143
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorQueryList attribute), 180
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorReference attribute), 162

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorReferenceList attribute), 199
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorStat attribute), 144
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorStatList attribute), 182
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumn attribute), 144
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumnList attribute), 181
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 148
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ServerHost attribute), 185
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ServerHostList attribute), 186
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ServerList attribute), 185
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ServerThrottle attribute), 177
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleList attribute), 213
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 178
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatusList attribute), 214
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle attribute), 177
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleList attribute), 213
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatus attribute), 179
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatusList attribute), 215
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnet attribute), 178
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetList attribute), 214
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetStatus attribute), 179
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetStatusLis attribute), 215
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SoapError attribute), 155
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.Solution attribute), 174
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SolutionList attribute), 211
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.StringHintList attribute), 181
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SystemSetting attribute), 155
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SystemSettingList attribute), 193
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SystemStatusAggregate attribute), 157
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.SystemStatusList attribute), 192
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UploadFile attribute), 164
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UploadFileList attribute), 201
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus attribute), 165
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.User attribute), 158
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UserGroup attribute), 174
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UserGroupList attribute), 210
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UserList attribute), 193

API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UserOwnedObjectIds attribute), 157
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UserRole attribute), 157
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.UserRoleList attribute), 194
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.VerifySignature attribute), 167
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.VersionAggregate attribute), 156
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.VersionAggregateList attribute), 192
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrl attribute), 156
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrlList attribute), 191
API_CONSTANTS (pytan3.api_objects.rest_7_3_314_3641.XmlError attribute), 150
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Action attribute), 242
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ActionGroup attribute), 257
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ActionGroupList attribute), 289
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ActionList attribute), 272
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ActionListInfo attribute), 242
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ActionStop attribute), 243
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ActionStopList attribute), 273
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestion attribute), 243
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionList attribute), 273
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.AuditData attribute), 230
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 263
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.CacheFilter attribute), 251
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.CacheFilterList attribute), 282
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 234
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ClientCount attribute), 246
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 237
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupList attribute), 281
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupSpec attribute), 249
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ComputerIdList attribute), 290
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ComputerSpecList attribute), 281
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 252
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283

API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilege attribute), 254
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilegeList attribute), 285
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 253
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleList attribute), 284
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMembership attribute), 253
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMembershipList attribute), 284
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilege attribute), 254
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeList attribute), 286
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeOnRole attribute), 252
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeOnRoleList attribute), 283
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRoleMembership attribute), 253
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRoleMembershipList attribute), 285
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Dashboard attribute), 255
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.DashboardGroup attribute), 256
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 287
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilege attribute), 255
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilegeList attribute), 287
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilegeObject attribute), 286
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ErrorList attribute), 266
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Filter attribute), 232
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.FilterList attribute), 265
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Group attribute), 233
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.GroupList attribute), 265
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.HashedString attribute), 259
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.HashedStringList attribute), 291
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.IdReference attribute), 232
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ImportConflictOptions attribute), 282
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnector attribute), 259
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnectorList attribute), 290
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.MergedResultSet attribute), 219
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.MetadataItem attribute), 231
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.MetadataList attribute), 264
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ObjectList attribute), 250
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Options attribute), 251
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageFile attribute), 237
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageFileList attribute), 268

API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatus attribute), 236
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatusList attribute), 268
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplate attribute), 236
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplateList attribute), 267
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageSpec attribute), 237
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PackageSpecList attribute), 269
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Parameter attribute), 245
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParameterList attribute), 276
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParameterValueList attribute), 276
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParseJob attribute), 244
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParseJobList attribute), 274
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParseResult attribute), 245
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroup attribute), 246
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroupList attribute), 275
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ParseResultList attribute), 275
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PermissionList attribute), 272
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Plugin attribute), 248
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginArgument attribute), 247
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginArgumentList attribute), 277
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginCommandList attribute), 279
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginList attribute), 280
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginSchedule attribute), 249
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginScheduleList attribute), 281
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginSql attribute), 279
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginSqlColumnList attribute), 278
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.PluginSqlResultList attribute), 278
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Question attribute), 235
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.QuestionList attribute), 267
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.QuestionListInfo attribute), 235
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ResultInfo attribute), 218
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList attribute), 218
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.ResultSetList attribute), 219
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 223
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 226
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.RowColumnList attribute), 224

API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.RowList attribute), 223
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 227
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedAction attribute), 229
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedActionApproval attribute), 229
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedActionApprovalList attribute), 262
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedActionList attribute), 263
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicy attribute), 229
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedActionRowIdList attribute), 262
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestion attribute), 244
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionList attribute), 274
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionPackageSpec attribute), 258
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestion attribute), 258
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestionList attribute), 289
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Select attribute), 233
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SelectList attribute), 266
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Sensor attribute), 230
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorList attribute), 261
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorQueryList attribute), 260
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 246
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorReferenceList attribute), 277
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorStat attribute), 228
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorStatList attribute), 261
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumn attribute), 228
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumnList attribute), 260
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 238
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SolutionList attribute), 288
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.StringHintList attribute), 261
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SystemSetting attribute), 238
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SystemSettingList attribute), 271
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAggregate attribute), 240
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.SystemStatusList attribute), 270
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 247
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 280
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248

API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObjectId attribute), 241
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.UserRoleList attribute), 272
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.VersionAggregate attribute), 239
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.VersionAggregateList attribute), 270
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrl attribute), 239
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrlList attribute), 269
API_CONSTANTS (pytan3.api_objects.soap_7_2_314_3181.XmlError attribute), 234
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Action attribute), 317
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ActionGroup attribute), 333
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ActionGroupList attribute), 370
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ActionList attribute), 353
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ActionListInfo attribute), 317
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ActionStop attribute), 318
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ActionStopList attribute), 353
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestion attribute), 318
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestionList attribute), 354
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.AuditData attribute), 305
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.AuditDataList attribute), 342
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.AuditLog attribute), 306
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.AuditLogList attribute), 343
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.CacheFilter attribute), 327
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.CacheFilterList attribute), 363
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.CacheInfo attribute), 309
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ClientCount attribute), 322
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ClientStatus attribute), 313
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ColumnList attribute), 295
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ComputerGroup attribute), 325
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupList attribute), 362
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupSpec attribute), 324
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ComputerIdList attribute), 374

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ComputerSpecList attribute), 361
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSet attribute), 328
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetList attribute), 364
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilege attribute), 330
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilegeList attribute), 366
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRole attribute), 329
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleList attribute), 365
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMembership attribute), 329
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMembershipList attribute), 365
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilege attribute), 331
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeList attribute), 367
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeOnRole attribute), 328
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeOnRoleList attribute), 364
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupMembership attribute), 330
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupMembershipList attribute), 366
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Dashboard attribute), 331
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.DashboardList attribute), 368
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivilege attribute), 331
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivilegeList attribute), 368
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivilegeOnRole attribute), 367
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ErrorList attribute), 347
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Filter attribute), 307
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.FilterList attribute), 346
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.GroupList attribute), 345
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 338
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.HashedStringList attribute), 374
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.IdReference attribute), 307
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetail attribute), 326
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetailList attribute), 362
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ImportConflictOptions attribute), 363
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnector attribute), 335
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnectorList attribute), 371
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.MergedResultSet attribute), 294
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 306

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.MetadataList attribute), 345
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Options attribute), 327
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageFileList attribute), 349
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatus attribute), 311
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatusList attribute), 348
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplate attribute), 311
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplateList attribute), 348
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageSpec attribute), 312
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PackageSpecList attribute), 349
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Parameter attribute), 320
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParameterList attribute), 356
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParameterValueList attribute), 357
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParseJob attribute), 319
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParseJobList attribute), 355
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParseResult attribute), 320
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroup attribute), 321
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroupList attribute), 355
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ParseResultList attribute), 356
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PermissionList attribute), 352
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Plugin attribute), 323
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginArgument attribute), 322
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginArgumentList attribute), 358
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginCommandList attribute), 359
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginList attribute), 360
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule attribute), 324
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginScheduleList attribute), 361
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginSql attribute), 359
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginSqlColumnList attribute), 359
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.PluginSqlResultList attribute), 358
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Question attribute), 310
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.QuestionList attribute), 347
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.QuestionListInfo attribute), 310
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ResultInfo attribute), 293
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList attribute), 292

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 294
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ResultSetList attribute), 293
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.RowColumnList attribute), 299
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.RowList attribute), 297
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedAction attribute), 304
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedActionApproval attribute), 304
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedActionApprovalList attribute), 341
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedActionList attribute), 342
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedActionPolicy attribute), 303
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedActionRowIdList attribute), 341
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion attribute), 319
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionList attribute), 354
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionPackageSpec attribute), 334
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestion attribute), 334
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestionList attribute), 370
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Select attribute), 308
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SelectList attribute), 346
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Sensor attribute), 305
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorList attribute), 340
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorQuery attribute), 302
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorQueryList attribute), 339
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorReference attribute), 321
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorReferenceList attribute), 357
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorStat attribute), 303
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorStatList attribute), 340
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorSubcolumn attribute), 302
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SensorSubcolumnList attribute), 339
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Server attribute), 306
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ServerHost attribute), 344
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ServerHostList attribute), 344
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ServerList attribute), 343
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ServerThrottle attribute), 335
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleList attribute), 371

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleStatus attribute), 337
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleStatusList attribute), 373
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottle attribute), 336
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleList attribute), 372
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatus attribute), 337
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatusList attribute), 373
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnet attribute), 336
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetList attribute), 372
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatus attribute), 338
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatusList attribute), 374
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SoapError attribute), 314
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.Solution attribute), 333
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SolutionList attribute), 369
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.StringHintList attribute), 340
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SystemSetting attribute), 313
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SystemSettingList attribute), 351
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SystemStatusAggregate attribute), 315
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.SystemStatusList attribute), 350
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UploadFile attribute), 323
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UploadFileList attribute), 360
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UploadFileStatus attribute), 323
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.User attribute), 316
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UserGroup attribute), 332
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UserGroupList attribute), 369
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UserList attribute), 351
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObjectIds attribute), 316
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UserRole attribute), 315
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.UserRoleList attribute), 352
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.VerifySignature attribute), 325
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.VersionAggregate attribute), 315
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.VersionAggregateList attribute), 350
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrl attribute), 314
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrlList attribute), 350
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3424.XmlError attribute), 309
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Action attribute), 401
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ActionGroup attribute), 417

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ActionGroupList attribute), 453
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ActionList attribute), 436
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ActionListInfo attribute), 401
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ActionStop attribute), 401
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ActionStopList attribute), 437
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestion attribute), 402
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestionList attribute), 437
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.AuditData attribute), 389
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.AuditDataList attribute), 426
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.AuditLog attribute), 389
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.AuditLogList attribute), 426
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.CacheFilter attribute), 410
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.CacheFilterList attribute), 446
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.CacheInfo attribute), 393
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ClientCount attribute), 405
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ClientStatus attribute), 396
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ColumnList attribute), 379
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup attribute), 409
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupList attribute), 445
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupSpec attribute), 408
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ComputerIdList attribute), 458
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ComputerSpecList attribute), 445
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSet attribute), 411
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetList attribute), 447
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilege attribute), 414
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilegeList attribute), 450
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRole attribute), 412
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleList attribute), 448
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMembershi attribute), 413
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMembershi attribute), 449
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilege attribute), 414
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeLi attribute), 450
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeOr attribute), 412
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeOr attribute), 448
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGroupRole attribute), 413

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGroupMembershipList attribute), 449
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Dashboard attribute), 415
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.DashboardGroup attribute), 416
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.DashboardList attribute), 452
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivilege attribute), 415
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivilegeList attribute), 451
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivilegeObject attribute), 451
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ErrorList attribute), 430
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Filter attribute), 391
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.FilterList attribute), 429
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Group attribute), 392
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.GroupList attribute), 429
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.HashedString attribute), 422
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.HashedStringList attribute), 458
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.IdReference attribute), 391
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ImportConflictDetail attribute), 410
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ImportConflictDetailList attribute), 446
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ImportConflictOptions attribute), 447
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConnector attribute), 418
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConnectorList attribute), 454
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.MergedResultSet attribute), 378
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.MetadataItem attribute), 390
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.MetadataList attribute), 428
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ObjectList attribute), 409
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Options attribute), 411
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageFile attribute), 395
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageFileList attribute), 432
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatus attribute), 395
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatusList attribute), 432
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplate attribute), 394
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplateList attribute), 431
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageSpec attribute), 396
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PackageSpecList attribute), 433
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Parameter attribute), 403
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParameterList attribute), 440
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParameterValueList attribute), 440

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParseJob attribute), 403
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParseJobList attribute), 438
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParseResult attribute), 404
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroup attribute), 405
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroupList attribute), 439
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ParseResultList attribute), 439
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PermissionList attribute), 436
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Plugin attribute), 407
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginArgument attribute), 406
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginArgumentList attribute), 441
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginCommandList attribute), 443
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginList attribute), 444
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginSchedule attribute), 408
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginScheduleList attribute), 445
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginSql attribute), 443
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginSqlColumnList attribute), 442
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.PluginSqlResultList attribute), 442
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Question attribute), 394
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.QuestionList attribute), 431
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.QuestionListInfo attribute), 394
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ResultInfo attribute), 377
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList attribute), 376
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 378
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ResultSetList attribute), 377
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 382
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.RowColumnList attribute), 383
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.RowList attribute), 381
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 388
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedActionApproval attribute), 387
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedActionApprovalList attribute), 425
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedActionList attribute), 426
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicy attribute), 387
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedActionRowIdList attribute), 425
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion attribute), 402

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionList attribute), 438
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionPackageSpecs attribute), 417
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestion attribute), 418
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestionList attribute), 454
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Select attribute), 392
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SelectList attribute), 430
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Sensor attribute), 388
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorList attribute), 424
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorQuery attribute), 386
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorQueryList attribute), 422
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorReference attribute), 404
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorReferenceList attribute), 441
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorStat attribute), 386
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorStatList attribute), 424
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumn attribute), 386
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumnList attribute), 423
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 427
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottle attribute), 419
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleList attribute), 455
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatus attribute), 420
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatusList attribute), 456
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottle attribute), 419
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatus attribute), 421
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatusList attribute), 457
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnet attribute), 420
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetList attribute), 456
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStatus attribute), 421
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStatusLi attribute), 457
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 417
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423

API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SystemSettingList attribute), 435
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SystemStatusAggregate attribute), 399
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.SystemStatusList attribute), 434
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 444
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.User attribute), 400
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UserOwnedObjectIds attribute), 400
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.VerifySignature attribute), 409
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.VersionAggregate attribute), 398
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.VersionAggregateList attribute), 434
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrl attribute), 398
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrlList attribute), 433
API_CONSTANTS (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 393
API_DATA_SET (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 53
API_DATA_SET (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 137
API_DATA_SET (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 221
API_DATA_SET (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
API_DATA_SET (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
api_delete() (pytan3.adapters.Adapter method), 474
api_delete() (pytan3.adapters.Rest method), 482
api_delete() (pytan3.adapters.Soap method), 478
API_DT (in module pytan3.api_objects.rest_7_3_314_3424), 48
API_DT (in module pytan3.api_objects.rest_7_3_314_3641), 133
API_DT (in module pytan3.api_objects.soap_7_2_314_3181), 217
API_DT (in module pytan3.api_objects.soap_7_3_314_3424), 291
API_DT (in module pytan3.api_objects.soap_7_3_314_3641), 375
api_fixes() (in module pytan3.api_objects.rest_7_3_314_3424), 48
api_fixes() (in module pytan3.api_objects.rest_7_3_314_3641), 133
api_fixes() (in module pytan3.api_objects.soap_7_2_314_3181), 217
api_fixes() (in module pytan3.api_objects.soap_7_3_314_3424), 291
api_fixes() (in module pytan3.api_objects.soap_7_3_314_3641), 375
api_get() (pytan3.adapters.Adapter method), 474
api_get() (pytan3.adapters.Rest method), 482
api_get() (pytan3.adapters.Soap method), 478
api_get_audit_logs() (pytan3.adapters.Adapter method), 474
api_get_audit_logs() (pytan3.adapters.Rest method), 483
api_get_audit_logs() (pytan3.adapters.Soap method), 479
api_get_client_count() (pytan3.adapters.Adapter method), 475
api_get_client_count() (pytan3.adapters.Rest method), 484
api_get_client_count() (pytan3.adapters.Soap method), 479
api_get_merged_result_data() (pytan3.adapters.Adapter method), 475

api_get_merged_result_data() (pytan3.adapters.Rest method), 485
api_get_merged_result_data() (pytan3.adapters.Soap method), 480
api_get_result_data() (pytan3.adapters.Adapter method), 475
api_get_result_data() (pytan3.adapters.Rest method), 485
api_get_result_data() (pytan3.adapters.Soap method), 480
api_get_result_info() (pytan3.adapters.Adapter method), 475
api_get_result_info() (pytan3.adapters.Rest method), 484
api_get_result_info() (pytan3.adapters.Soap method), 479
API_IDX (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 53
API_IDX (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 56
API_IDX (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 137
API_IDX (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_IDX (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 221
API_IDX (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 225
API_IDX (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
API_IDX (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_IDX (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
API_IDX (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
API_ITEM_ATTR (pytan3.api_models.ApiList attribute), 463
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ActionGroupList attribute), 127
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ActionList attribute), 110
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ActionStopList attribute), 111
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestionList attribute), 111
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.AuditDataList attribute), 100
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.AuditLogList attribute), 100
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.CacheFilterList attribute), 120
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ColumnList attribute), 53
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupList attribute), 119
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ComputerIdList attribute), 131
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ComputerSpecList attribute), 119
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ContentSetList attribute), 121
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilegeList attribute), 124
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleList attribute), 122
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMembership attribute), 123
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeLis attribute), 124
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeOn attribute), 122
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupRoleM attribute), 123
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 126
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivileg attribute), 125
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivileg attribute), 125
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.FilterList attribute), 103
API_ITEM_ATTR (pytan3.api_objects.rest_7_3_314_3424.GroupList attribute), 103
API_ITEM_ATTR (py-

tan3.api_objects.rest_7_3_314_3424.HashedStringList attribute), 132
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ImportConflictDetailList attribute), 120
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ImportConflictOptions attribute), 121
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.LdapSyncConnectorList attribute), 128
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.MetadataList attribute), 102
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PackageFileList attribute), 106
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PackageFileStatusList attribute), 106
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PackageFileTemplateList attribute), 105
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PackageSpecList attribute), 107
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ParameterList attribute), 114
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ParameterValueList attribute), 114
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ParseJobList attribute), 112
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ParseQuestionResultList attribute), 58
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ParseResultGroupList attribute), 113
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ParseResultList attribute), 113
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PermissionList attribute), 109
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PluginArgumentList attribute), 115
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PluginCommandList attribute), 117
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PluginList attribute), 118
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PluginScheduleList attribute), 118
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PluginSql attribute), 116
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PluginSqlColumnList attribute), 116
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.PluginSqlResultList attribute), 116
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.QuestionList attribute), 105
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ResultInfoList attribute), 50
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ResultSetList attribute), 51
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.RowColumnList attribute), 56
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.RowList attribute), 54
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SavedActionApprovalList attribute), 98
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SavedActionList attribute), 99
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SavedActionRowIdList attribute), 99
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SavedQuestionList attribute), 112
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestionList attribute), 128
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SelectList attribute), 104
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SensorList attribute), 97
API_ITEM_ATTR (py-

tan3.api_objects.rest_7_3_314_3424.SensorQueryList attribute), 96
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SensorReferenceList attribute), 115
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SensorStatList attribute), 98
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SensorSubcolumnList attribute), 96
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ServerHost attribute), 101
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ServerHostList attribute), 102
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ServerList attribute), 101
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ServerThrottleList attribute), 129
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.ServerThrottleStatusList attribute), 130
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SiteThrottleList attribute), 129
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SiteThrottleStatusList attribute), 131
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetList attribute), 130
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatusList attribute), 131
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 127
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.UserRoleList attribute), 110
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.VersionAggregateList attribute), 107
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3424.WhiteListedUrlList attribute), 107
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ActionGroupList attribute), 211
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ActionList attribute), 194
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ActionStopList attribute), 195
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ArchivedQuestionList attribute), 195
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.AuditDataList attribute), 184
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.AuditLogList attribute), 184
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.CacheFilterList attribute), 204
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ColumnList attribute), 137
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ComputerGroupList attribute), 203
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ComputerIdList attribute), 216
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ComputerSpecList attribute), 203
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ContentSetList attribute), 205
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ContentSetPrivilegeList attribute), 208
API_ITEM_ATTR (py-

tan3.api_objects.rest_7_3_314_3641.ContentSetRoleList attribute), 206
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembersList attribute), 207
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeList attribute), 208
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeObjectList attribute), 206
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupRoleMembersList attribute), 207
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.DashboardList attribute), 210
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivilegeList attribute), 209
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivilegeRequest attribute), 209
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ErrorList attribute), 188
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.FilterList attribute), 187
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.GroupList attribute), 187
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.HashedStringList attribute), 216
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ImportConflictDetailList attribute), 204
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ImportConflictOptions attribute), 205
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.LdapSyncConnectorList attribute), 212
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.MetadataList attribute), 186
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PackageFileList attribute), 190
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PackageFileStatusList attribute), 190
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PackageFileTemplateList attribute), 189
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PackageSpecList attribute), 191
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ParameterList attribute), 198
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ParameterValueList attribute), 198
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ParseJobList attribute), 196
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ParseQuestionResultList attribute), 142
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ParseResultGroupList attribute), 197
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ParseResultList attribute), 197
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PermissionList attribute), 194
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PluginArgumentList attribute), 199
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PluginCommandList attribute), 201
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PluginList attribute), 202
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PluginScheduleList attribute), 202
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PluginSql attribute), 201
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PluginSqlColumnList attribute), 200
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.PluginSqlResultList attribute), 200
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 189
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_ITEM_ATTR (py-

tan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.RowColumnList attribute), 140
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.RowList attribute), 139
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SavedActionApprovalList attribute), 183
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SavedActionList attribute), 183
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SavedActionRowIdList attribute), 183
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SavedQuestionList attribute), 196
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestionList attribute), 212
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SelectList attribute), 188
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SensorList attribute), 182
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SensorQueryList attribute), 180
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SensorReferenceList attribute), 199
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SensorStatList attribute), 182
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SensorSubcolumnList attribute), 181
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ServerHost attribute), 185
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ServerHostList attribute), 186
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ServerList attribute), 185
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ServerThrottleList attribute), 213
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.ServerThrottleStatusList attribute), 214
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SiteThrottleList attribute), 213
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SiteThrottleStatusList attribute), 215
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetList attribute), 214
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetStatusLis attribute), 215
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SolutionList attribute), 211
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.StringHintList attribute), 181
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SystemSettingList attribute), 193
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.SystemStatusList attribute), 192
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.UploadFileList attribute), 202
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.UserGroupList attribute), 210
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.UserList attribute), 193
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.UserRoleList attribute), 194
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.VersionAggregateList attribute), 192
API_ITEM_ATTR (py-tan3.api_objects.rest_7_3_314_3641.WhiteListedUrlList attribute), 191
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ActionGroupList attribute), 289
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ActionList attribute), 273
API_ITEM_ATTR (py-

tan3.api_objects.soap_7_2_314_3181.ActionStopList attribute), 273
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ArchivedQuestionList attribute), 274
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 263
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.CacheFilterList attribute), 282
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ComputerGroupList attribute), 282
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ComputerIdList attribute), 290
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ComputerSpecList attribute), 281
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ContentSetPrivilegeList attribute), 285
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ContentSetRoleList attribute), 284
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ContentSetRoleMembershipList attribute), 284
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeList attribute), 286
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeOnRoleList attribute), 283
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRoleMembershipList attribute), 285
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 287
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilegeList attribute), 287
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivileg attribute), 286
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ErrorList attribute), 266
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.FilterList attribute), 265
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.GroupList attribute), 265
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.HashedStringList attribute), 291
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ImportConflictOptions attribute), 283
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.LdapSyncConnectorList attribute), 290
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.MetadataList attribute), 264
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PackageFileList attribute), 268
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PackageFileStatusList attribute), 268
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PackageFileTemplateList attribute), 267
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PackageSpecList attribute), 269
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ParameterList attribute), 276
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ParameterValueList attribute), 276
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ParseJobList attribute), 274
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ParseResultGroupList attribute), 275
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ParseResultList attribute), 275
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PermissionList attribute), 272
API_ITEM_ATTR (py-

tan3.api_objects.soap_7_2_314_3181.PluginArgumentList attribute), 277
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PluginCommandList attribute), 279
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PluginList attribute), 280
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PluginScheduleList attribute), 281
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PluginSql attribute), 279
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PluginSqlColumnList attribute), 278
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.PluginSqlResultList attribute), 278
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.QuestionList attribute), 267
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ResultInfoList attribute), 218
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.ResultSetList attribute), 219
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 226
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.RowColumnList attribute), 225
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.RowList attribute), 223
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SavedActionApprovalList attribute), 262
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SavedActionList attribute), 263
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SavedActionRowIdList attribute), 263
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SavedQuestionList attribute), 274
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestionList attribute), 289
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SelectList attribute), 266
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SensorList attribute), 261
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SensorQueryList attribute), 260
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SensorReferenceList attribute), 277
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SensorStatList attribute), 262
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SensorSubcolumnList attribute), 260
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SolutionList attribute), 288
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.StringHintList attribute), 261
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SystemSettingList attribute), 271
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.SystemStatusList attribute), 270
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 280
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.UserRoleList attribute), 272
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.VersionAggregateList attribute), 270
API_ITEM_ATTR (py-tan3.api_objects.soap_7_2_314_3181.WhiteListedUrlList attribute), 269
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ActionGroupList attribute), 370
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ActionList attribute), 353
API_ITEM_ATTR (py-

tan3.api_objects.soap_7_3_314_3424.ActionStopList attribute), 353
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ArchivedQuestionList attribute), 354
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.AuditDataList attribute), 342
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.AuditLogList attribute), 343
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.CacheFilterList attribute), 363
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ColumnList attribute), 295
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ComputerGroupList attribute), 362
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ComputerIdList attribute), 374
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ComputerSpecList attribute), 361
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ContentSetList attribute), 364
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ContentSetPrivilegeList attribute), 366
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ContentSetRoleList attribute), 365
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ContentSetRoleMembership attribute), 365
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeList attribute), 367
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeOnRoleList attribute), 364
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupMembership attribute), 366
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.DashboardList attribute), 368
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivilegeList attribute), 368
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivileg attribute), 367
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ErrorList attribute), 347
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.FilterList attribute), 346
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.GroupList attribute), 345
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.HashedStringList attribute), 375
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ImportConflictDetailList attribute), 362
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ImportConflictOptions attribute), 363
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.LdapSyncConnectorList attribute), 371
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.MetadataList attribute), 345
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PackageFileList attribute), 349
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PackageFileStatusList attribute), 348
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PackageFileTemplateList attribute), 348
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PackageSpecList attribute), 349
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ParameterList attribute), 356
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ParameterValueList attribute), 357
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ParseJobList attribute), 355
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ParseResultGroupList attribute), 355
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ParseResultList attribute), 356
API_ITEM_ATTR (py-

tan3.api_objects.soap_7_3_314_3424.PermissionList attribute), 352
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PluginArgumentList attribute), 358
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PluginCommandList attribute), 360
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PluginList attribute), 360
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PluginScheduleList attribute), 361
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PluginSql attribute), 359
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PluginSqlColumnList attribute), 359
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.PluginSqlResultList attribute), 358
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.QuestionList attribute), 347
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ResultInfoList attribute), 292
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ResultSetList attribute), 294
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.RowColumnList attribute), 299
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.RowList attribute), 297
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SavedActionApprovalList attribute), 341
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SavedActionList attribute), 342
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SavedActionRowIdList attribute), 342
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SavedQuestionList attribute), 354
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestionLis attribute), 370
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SelectList attribute), 346
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SensorList attribute), 340
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SensorQueryList attribute), 339
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SensorReferenceList attribute), 357
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SensorStatList attribute), 341
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SensorSubcolumnList attribute), 339
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ServerHost attribute), 344
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ServerHostList attribute), 344
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ServerList attribute), 343
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ServerThrottleList attribute), 371
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.ServerThrottleStatusList attribute), 373
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SiteThrottleList attribute), 372
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SiteThrottleStatusList attribute), 373
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetList attribute), 372
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatusLi attribute), 374
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SolutionList attribute), 369
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.StringHintList attribute), 340
API_ITEM_ATTR (py-

tan3.api_objects.soap_7_3_314_3424.SystemSettingList attribute), 351
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.SystemStatusList attribute), 351
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.UploadFileList attribute), 360
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.UserGroupList attribute), 369
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.UserList attribute), 352
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.UserRoleList attribute), 352
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.VersionAggregateList attribute), 350
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3424.WhiteListedUrlList attribute), 350
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ActionGroupList attribute), 453
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ActionList attribute), 437
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ActionStopList attribute), 437
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ArchivedQuestionList attribute), 438
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.AuditDataList attribute), 426
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.AuditLogList attribute), 427
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.CacheFilterList attribute), 447
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ColumnList attribute), 379
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ComputerGroupList attribute), 446
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ComputerIdList attribute), 458
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ComputerSpecList attribute), 445
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ContentSetList attribute), 447
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ContentSetPrivilegeList attribute), 450
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ContentSetRoleList attribute), 448
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ContentSetRoleMembershi attribute), 449
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeLi attribute), 450
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeOr attribute), 448
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ContentSetUserGroupRole attribute), 449
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.DashboardList attribute), 452
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivileg attribute), 451
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivileg attribute), 451
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ErrorList attribute), 430
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.FilterList attribute), 429
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.GroupList attribute), 429
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.HashedStringList attribute), 458
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ImportConflictDetailList attribute), 446
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ImportConflictOptions attribute), 447
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.LdapSyncConnectorList attribute), 454
API_ITEM_ATTR (py-

tan3.api_objects.soap_7_3_314_3641.MetadataList attribute), 428
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PackageFileList attribute), 432
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PackageFileStatusList attribute), 432
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PackageFileTemplateList attribute), 431
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PackageSpecList attribute), 433
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ParameterList attribute), 440
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ParameterValueList attribute), 440
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ParseJobList attribute), 438
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ParseResultGroupList attribute), 439
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ParseResultList attribute), 439
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PermissionList attribute), 436
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PluginArgumentList attribute), 441
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PluginCommandList attribute), 443
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PluginList attribute), 444
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PluginScheduleList attribute), 445
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PluginSql attribute), 443
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PluginSqlColumnList attribute), 442
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.PluginSqlResultList attribute), 442
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.QuestionList attribute), 431
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ResultInfoList attribute), 376
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ResultSetList attribute), 377
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.RowColumnList attribute), 383
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.RowList attribute), 381
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SavedActionApprovalList attribute), 425
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SavedActionList attribute), 426
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SavedActionRowIdList attribute), 425
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SavedQuestionList attribute), 438
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestionLis attribute), 454
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SelectList attribute), 430
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SensorList attribute), 424
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SensorQueryList attribute), 422
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SensorReferenceList attribute), 441
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SensorStatList attribute), 424
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.SensorSubcolumnList attribute), 423
API_ITEM_ATTR (py-tan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 428
API_ITEM_ATTR (py-

tan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleList attribute), 455
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatusList attribute), 456
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatusList attribute), 457
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetList attribute), 456
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStatusList attribute), 457
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.SystemSettingList attribute), 435
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.SystemStatusList attribute), 434
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 444
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.VersionAggregateList attribute), 434
API_ITEM_ATTR (pytan3.api_objects.soap_7_3_314_3641.WhiteListedURLList attribute), 433
API_ITEM_CLS (pytan3.api_models.ApiList attribute), 463
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ActionGroupList attribute), 127
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ActionList attribute), 110
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ActionStopList attribute), 111
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestio attribute), 111
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.AuditDataList attribute), 100
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.AuditLogList attribute), 100
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.CacheFilterList attribute), 120
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ColumnList attribute), 53
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupI attribute), 119
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ComputerIdList attribute), 132
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ComputerSpecLi attribute), 119
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetList attribute), 121
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivile attribute), 124
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleL attribute), 122
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleM attribute), 123
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleP attribute), 124
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleP attribute), 122
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserG attribute), 123
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 126
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.EffectiveContent attribute), 125
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.EffectiveContent attribute), 125
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.FilterList attribute), 103
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.GroupList attribute), 103
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.HashedStringList attribute), 132
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDe attribute), 120
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ImportConflictOp

attribute), 121
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.LabelSystemCommandsList attribute), 128
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.MetadataItem attribute), 102
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageItemList attribute), 106
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageItemStatusList attribute), 106
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageItemTemplateList attribute), 105
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageItemUpdateList attribute), 107
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.parameterItem attribute), 114
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.parameterValueList attribute), 114
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.parsedJobItem attribute), 112
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.parsedQuestionResultsList attribute), 58
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.parsedRestGroupList attribute), 113
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.parsedRestUserList attribute), 113
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.permissionItem attribute), 109
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PlugInArgumentItem attribute), 115
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PlugInCommandItem attribute), 117
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PlugInItem attribute), 118
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PlugInSchedule attribute), 118
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PlugInSq attribute), 117
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PlugInSqColumnList attribute), 116
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.PlugInSqResultsCol attribute), 116
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.QuestionItem attribute), 105
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ResultInfoItem attribute), 50
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ResultSetItem attribute), 51
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.RowCollItem attribute), 57
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.RowCollItemList attribute), 56
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.RowList attribute), 55
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedActionItem attribute), 98
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedActionList attribute), 99
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedActionRow attribute), 99
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionList attribute), 112
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestion attribute), 128
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SelectList attribute), 104
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorList attribute), 97
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorQueryList attribute), 96
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorReferenceList attribute), 115
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorStatList attribute), 98
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumnList attribute), 97
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ServerHost attribute), 101
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ServerHostList attribute), 102
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ServerList attribute), 101
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleList attribute), 129
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatus attribute), 130
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleList attribute), 129
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 131
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnet attribute), 130
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatus attribute), 131
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 127
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.UserRoleList

attribute), 110
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.VerifyAggregateList attribute), 108
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3424.WhitelistedURLList attribute), 107
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.AdminGroupList attribute), 211
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.AdminList attribute), 195
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.AdminStepList attribute), 195
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ActivityQuestionList attribute), 195
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.AdminDataList attribute), 184
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.AdminLogList attribute), 184
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ComplianceItemList attribute), 204
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ComplianceList attribute), 137
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupList attribute), 203
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ComputerHistoryList attribute), 216
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ComputerSpecList attribute), 203
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetList attribute), 205
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilegeList attribute), 208
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleList attribute), 206
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupList attribute), 207
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserList attribute), 208
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetWorkspaceList attribute), 206
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetWorkspaceRoleList attribute), 207
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.DashboardList attribute), 210
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.EditableContentSetPrivilegeList attribute), 209
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.EditableContentSetPrivilegeRequest attribute), 209
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.EnvList attribute), 188
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.FilterList attribute), 187
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.GroupList attribute), 187
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.HashlistMgmtList attribute), 216
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDe attribute), 204
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ImportConflictOp attribute), 205
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnec attribute), 212
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.MetadataList attribute), 186
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageFileList attribute), 190
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatu attribute), 190
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemp attribute), 189
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageSpecList attribute), 191
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ParameterList attribute), 198
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ParameterValueL attribute), 198
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseJobList attribute), 196
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionRe attribute), 143
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseResultGrou attribute), 197
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseResultList attribute), 197
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PermissionList attribute), 194
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginArgumentL attribute), 199
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginCommandL attribute), 201
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginList attribute), 202
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginScheduleL attribute), 203
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginSql attribute), 201
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginSqlColumn attribute), 200
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginSqlResultL attribute), 200
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 189
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.RowColumnList

attribute), 140
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.RaPlist attribute), 139
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedAction_Apply attribute), 183
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedAction_List attribute), 184
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedAction_Rows attribute), 183
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion_List attribute), 196
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion_Question attribute), 212
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SelectList attribute), 188
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorList attribute), 182
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorQuery_List attribute), 180
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorReference_List attribute), 199
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorStat_List attribute), 182
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumn_List attribute), 181
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ServerHost attribute), 185
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ServerHostList attribute), 186
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ServerList attribute), 185
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ServerTemplate_List attribute), 213
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.ServerTemplate_Status_List attribute), 214
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle_List attribute), 213
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle_Status_List attribute), 215
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle_Subnet_List attribute), 214
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle_Subnet_Status_List attribute), 215
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SolutionList attribute), 211
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.StagingItemList attribute), 181
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SystemSettingList attribute), 193
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.SystemStatusList attribute), 192
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.UploadFileList attribute), 202
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.UserGroupList attribute), 210
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.UserList attribute), 193
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.UserRoleList attribute), 194
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.VersionAggregate attribute), 192
API_ITEM_CLS (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrlL attribute), 191
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ActionGroupLis attribute), 289
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ActionList attribute), 273
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ActionStopList attribute), 273
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestio attribute), 274
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 264
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.CacheFilterList attribute), 282
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 282
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ComputerIdList attribute), 290
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ComputerSpecL attribute), 281
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivil attribute), 285
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 284
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 284
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 286
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolel attribute), 284
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetUser attribute), 285
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 287
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.EffectiveConten attribute), 287
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.EffectiveConten attribute), 286
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ErrorList attribute), 266
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.FilterList

attribute), 265
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ApiItemList attribute), 265
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 291
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ApiItemMetaObjects attribute), 283
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ApiSystemObjectMetaObjects attribute), 290
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ActionDataList attribute), 264
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageItemList attribute), 268
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageItemStatusList attribute), 268
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageItemTemplateList attribute), 267
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageItemSpecList attribute), 269
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ParameterList attribute), 276
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ParameterValueList attribute), 276
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ParseJobList attribute), 275
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroupList attribute), 275
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ParseResultList attribute), 275
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PermissionList attribute), 272
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PluginArgumentList attribute), 277
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PluginCommandList attribute), 279
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PluginList attribute), 280
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PluginSettingsList attribute), 281
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PluginSqlList attribute), 279
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PluginSqlColumnList attribute), 278
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.PluginSqlResultList attribute), 278
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.QuestionList attribute), 267
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList attribute), 218
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.ResultRowList attribute), 219
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.RowCollection attribute), 226
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.RowCollectionList attribute), 225
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.RowList attribute), 223
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedActionApp attribute), 262
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedActionList attribute), 263
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedActionRow attribute), 263
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionL attribute), 274
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQ attribute), 289
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SelectList attribute), 266
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorList attribute), 261
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorQueryLis attribute), 260
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorReferenc attribute), 277
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorStatList attribute), 262
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolun attribute), 260
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SolutionList attribute), 288
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.StringHintList attribute), 261
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SystemSettingL attribute), 271
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.SystemStatusLis attribute), 270
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 280
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.UserRoleList attribute), 272
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.VersionAggrega attribute), 270
API_ITEM_CLS (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrl attribute), 269
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ActionGroupLis attribute), 370
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ActionList attribute), 353
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ActionStopList attribute), 353
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestio attribute), 354
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.AuditDataList

attribute), 342
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.AuditLogList
attribute), 343
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.CacheFilterList
attribute), 363
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.CommentList
attribute), 295
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ComplianceGroupList
attribute), 362
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ComplianceList
attribute), 374
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ComplianceSpecList
attribute), 361
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ConfigSettingList
attribute), 364
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ConfigSettingPrivilegeList
attribute), 366
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ConfigSettingRoleList
attribute), 365
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ConfigSettingUserMembershipList
attribute), 365
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ConfigSettingUserPrivilegeList
attribute), 367
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ConfigSettingUserRoleObjectList
attribute), 364
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ConfigSettingUserUserMembershipList
attribute), 366
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.DashboardList
attribute), 368
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.EffectiveComputerPrivilegeList
attribute), 368
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.EffectiveComputerPrivilegeObject
attribute), 367
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ErrorItem
attribute), 347
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.FilterItem
attribute), 346
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.GroupList
attribute), 345
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.HashedStringList
attribute), 375
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ImportCommandStepList
attribute), 362
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ImportCommandOptions
attribute), 363
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.InstalledSoftwareList
attribute), 371
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.MetadataList
attribute), 345
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageFileList
attribute), 349
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatusList
attribute), 348
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplateList
attribute), 348
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageSpecList
attribute), 349
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ParameterList
attribute), 356
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ParameterValueL
attribute), 357
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ParseJobList
attribute), 355
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ParseResultGrou
attribute), 355
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ParseResultList
attribute), 356
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PermissionList
attribute), 352
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginArgument
attribute), 358
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginCommand
attribute), 360
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginList
attribute), 361
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginScheduleL
attribute), 361
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginSql
attribute), 359
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginSqlColum
attribute), 359
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginSqlResult
attribute), 358
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.PrivilegeList
attribute), 347
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList
attribute), 293
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ResultSetList
attribute), 294
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.RowColumn
attribute), 300
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.RowColumnList
attribute), 299
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.RowList
attribute), 297
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SavedActionApp
attribute), 341
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SavedActionList
attribute), 342
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SavedActionRow
attribute), 342
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionL
attribute), 354
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQ
attribute), 370
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SelectList
attribute), 346
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorList

attribute), 340
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorQueryList attribute), 339
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorReferenceList attribute), 357
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorTemplateList attribute), 341
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorTemplateColumnList attribute), 339
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerHistoryItem attribute), 344
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerHistoryList attribute), 344
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerItem attribute), 343
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerItemMetaList attribute), 371
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerItemMetaObjectsList attribute), 373
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SettingItemList attribute), 372
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SettingItemObjectsList attribute), 373
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SettingItemSubmenuList attribute), 372
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SettingItemSubmenuObjectsList attribute), 374
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SoftwareItem attribute), 369
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SourceItemList attribute), 340
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SystemSettingList attribute), 351
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.SystemStatusItem attribute), 351
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.UploadFileList attribute), 360
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.UserGroupItem attribute), 369
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.UserList attribute), 352
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.UserRoleItem attribute), 352
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.ValidationAggregateList attribute), 350
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3424.WhitelistedURLList attribute), 350
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ActionGroupList attribute), 453
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ActionList attribute), 437
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ActionStepList attribute), 437
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ArchiveQueueCLSList attribute), 438
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.AuditDataList attribute), 426
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.AuditLogList attribute), 427
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.CacheFilterList attribute), 447
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ColumnList attribute), 379
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup attribute), 446
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ComputerIdList attribute), 458
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ComputerSpecL attribute), 445
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetList attribute), 448
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivil attribute), 450
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolel attribute), 448
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolel attribute), 449
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolel attribute), 450
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolel attribute), 448
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetUser attribute), 449
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.DashboardList attribute), 452
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.EffectiveConten attribute), 451
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.EffectiveConten attribute), 451
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ErrorList attribute), 430
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.FilterList attribute), 429
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.GroupList attribute), 429
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.HashedStringLis attribute), 458
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ImportConflictD attribute), 446
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ImportConflictC attribute), 447
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConne attribute), 454
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.MetadataList attribute), 429
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageFileList attribute), 432
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageFileStat

attribute), 432
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageTemplateList attribute), 431
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageSpecList attribute), 433
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ParameterList attribute), 440
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ParameterDefinitionList attribute), 440
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ParseJobList attribute), 439
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroupList attribute), 439
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ParseResultList attribute), 439
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PermissionList attribute), 436
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PluginArgumentList attribute), 441
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PluginCommandList attribute), 443
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PluginList attribute), 444
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PluginSolutionList attribute), 445
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PluginSqlList attribute), 443
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PluginSqlColumnList attribute), 442
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.PluginSqlResultList attribute), 442
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.QuestionList attribute), 431
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList attribute), 376
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ResultSetList attribute), 377
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.RowCollection attribute), 384
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.RowCollectionList attribute), 383
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.RowList attribute), 381
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedActionApplyList attribute), 425
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedActionList attribute), 426
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedActionRollbackList attribute), 425
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionList attribute), 438
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestionList attribute), 454
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SelectList attribute), 430
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorList attribute), 424
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorQueryList attribute), 422
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorReference attribute), 441
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorStatList attribute), 424
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumn attribute), 423
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 428
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleL attribute), 455
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleSt attribute), 456
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatu attribute), 457
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 456
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 457
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SystemSettingL attribute), 435
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SystemStatusLis attribute), 434
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 444
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.VersionAggrega attribute), 434
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrlI attribute), 433
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SelectionList attribute), 438
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SelectionQuestionList attribute), 454
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SelectList attribute), 430
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorList attribute), 424
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorQueryLis attribute), 422
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorReferenc attribute), 441
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorStatList attribute), 424
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolun attribute), 423
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 428
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleL attribute), 455
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleSt attribute), 456
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatu attribute), 457
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 456
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 457
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SystemSettingL attribute), 435
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SystemStatusLis attribute), 434
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 444
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.VersionAggrega attribute), 434
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrlI attribute), 433
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SelectionList attribute), 438
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SelectionQuestionList attribute), 454
API_ITEM_CLS (pytan3.api_objects.soap_7_3_314_3641.SelectList

complex() (pytan3.api_models.ApiList class method), 467

_Question() (pytan3.api_models.ApiList class method), 466

_API_NAME (pytan3.api_models.ApiItem at-

tribute), 462
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Action attribute), 75
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionGroup attribute), 91
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionListInfo attribute), 74
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionStop attribute), 75
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestion attribute), 76
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.AuditData attribute), 63
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.AuditLog attribute), 63
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.CacheFilter attribute), 84
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.CacheInfo attribute), 67
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ClientCount attribute), 79
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ClientStatus attribute), 70
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 54
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ComputerGroup attribute), 82
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupSpec attribute), 82
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSet attribute), 85
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilege attribute), 88
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRole attribute), 86
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMembership attribute), 87
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilege attribute), 88
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeOnl attribute), 86
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupRoleM attribute), 87
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivileg attribute), 88
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Filter attribute), 64
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Group attribute), 65
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.HashedString attribute), 96
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.IdReference attribute), 65
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDetail attribute), 84
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnector attribute), 92
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.MergedResultSet attribute), 52
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.MetadataItem attribute), 64
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ObjectList attribute), 83
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Options attribute), 85
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFile attribute), 69
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatus

attribute), 69
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate attribute), 68
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageSpec attribute), 70
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Parameter attribute), 77
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseJob attribute), 77
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResult attribute), 59
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseResult attribute), 78
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup attribute), 79
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Plugin attribute), 81
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginArgument attribute), 80
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginSchedule attribute), 81
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Question attribute), 68
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.QuestionListInfo attribute), 67
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ResultInfo attribute), 51
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ResultSet attribute), 52
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 58
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 62
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedActionApproval attribute), 61
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolicy attribute), 61
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestion attribute), 76
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPackageSpec attribute), 91
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestion attribute), 92
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Select attribute), 66
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Sensor attribute), 62
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorQuery attribute), 59
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorReference attribute), 78
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorStat attribute), 60
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumn attribute), 60
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 64
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerThrottle attribute), 93
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatus attribute), 94
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottle attribute), 93
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 95
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnet attribute), 94
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatus attribute), 95
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SoapError

attribute), 71
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.Solution attribute), 90
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 71
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAggregate attribute), 72
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus attribute), 80
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserOwnedObjectIds attribute), 73
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.VerifySignature attribute), 83
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.VersionAggregate attribute), 72
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.WhiteListedUrl attribute), 72
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3424.XmlError attribute), 66
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionListInfo attribute), 159
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionStop attribute), 159
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ArchivedQuestion attribute), 160
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.AuditData attribute), 147
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.AuditLog attribute), 147
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.CacheFilter attribute), 168
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.CacheInfo attribute), 151
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ClientCount attribute), 163
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ClientStatus attribute), 154
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 138
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup attribute), 167
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupSpec attribute), 166
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSet attribute), 169
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilege attribute), 172
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole attribute), 170
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembership attribute), 171
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilege attribute), 172
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeOnl attribute), 170
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupRoleM attribute), 171
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Dashboard attribute), 173
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.DashboardGroup

attribute), 174
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivilege attribute), 173
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Filter attribute), 149
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Group attribute), 150
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.HashedString attribute), 180
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.IdReference attribute), 149
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDetail attribute), 168
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnector attribute), 176
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.MergedResultSet attribute), 136
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.MetadataItem attribute), 148
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ObjectList attribute), 167
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Options attribute), 169
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFile attribute), 153
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatus attribute), 153
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplate attribute), 152
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageSpec attribute), 154
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Parameter attribute), 161
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseJob attribute), 161
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResult attribute), 143
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseResult attribute), 162
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup attribute), 163
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Plugin attribute), 165
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginArgument attribute), 164
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 166
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Question attribute), 152
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.QuestionListInfo attribute), 152
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 135
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedAction attribute), 146
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedActionApproval attribute), 145
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedActionPolicy attribute), 145
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion attribute), 160
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionPackageSpec attribute), 175
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestion attribute), 176
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Select

attribute), 150
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Sensor attribute), 146
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 144
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorReference attribute), 162
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorStat attribute), 144
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumn attribute), 144
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 148
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerThrottle attribute), 177
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 178
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle attribute), 177
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatus attribute), 179
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnet attribute), 178
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetStatus attribute), 179
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SoapError attribute), 155
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.Solution attribute), 175
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SystemSetting attribute), 155
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.SystemStatusAggregate attribute), 157
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.UploadFile attribute), 164
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus attribute), 165
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.User attribute), 158
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserGroup attribute), 174
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserOwnedObjectIds attribute), 158
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserRole attribute), 157
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.VerifySignature attribute), 167
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.VersionAggregate attribute), 156
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrl attribute), 156
API_LIST_API_NAME (pytan3.api_objects.rest_7_3_314_3641.XmlError attribute), 151
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Action attribute), 242
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionGroup attribute), 257
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionListInfo attribute), 242
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionStop attribute), 243
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestion attribute), 243
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.AuditData attribute), 231
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.CacheFilter attribute), 251
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 234
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ClientCount

attribute), 247
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 238
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupSpec attribute), 249
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 252
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilege attribute), 254
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 253
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMembership attribute), 253
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilege attribute), 255
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeOnRole attribute), 252
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRoleMembership attribute), 254
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Dashboard attribute), 256
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.DashboardGroup attribute), 256
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilege attribute), 255
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Filter attribute), 232
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Group attribute), 233
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.HashedString attribute), 259
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.IdReference attribute), 232
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnector attribute), 259
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.MergedResultSet attribute), 219
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.MetadataItem attribute), 232
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ObjectList attribute), 250
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Options attribute), 251
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFile attribute), 237
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatus attribute), 236
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplate attribute), 236
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageSpec attribute), 237
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Parameter attribute), 245
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseJob attribute), 244
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseResult attribute), 245
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroup attribute), 246
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Plugin attribute), 248
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginArgument attribute), 247
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginSchedule attribute), 249
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Question attribute), 235
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.QuestionListInfo

attribute), 235
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ResultInfo attribute), 218
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 223
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 227
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedAction attribute), 230
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedActionApproval attribute), 229
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicy attribute), 229
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestion attribute), 244
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionPackageSpec attribute), 258
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestion attribute), 258
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Select attribute), 233
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Sensor attribute), 230
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 246
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorStat attribute), 228
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumn attribute), 228
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 239
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SystemSetting attribute), 238
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAggregate attribute), 240
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 248
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObjectIds attribute), 241
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.VersionAggregate attribute), 240
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrl attribute), 239
API_LIST_API_NAME (pytan3.api_objects.soap_7_2_314_3181.XmlError attribute), 234
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Action attribute), 317
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionGroup attribute), 334
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionListInfo attribute), 317
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionStop attribute), 318
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestion attribute), 318
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.AuditData attribute), 305
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.AuditLog

attribute), 306
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.CacheFilter attribute), 327
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.CacheInfo attribute), 309
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ClientCount attribute), 322
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ClientStatus attribute), 313
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ComputerGroup attribute), 325
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupSpec attribute), 325
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSet attribute), 328
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilege attribute), 330
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRole attribute), 329
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMembership attribute), 329
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilege attribute), 331
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeOnRole attribute), 328
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupRoleMembership attribute), 330
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Dashboard attribute), 332
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivilege attribute), 331
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Filter attribute), 307
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 338
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.IdReference attribute), 308
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetail attribute), 326
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnector attribute), 335
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.MergedResultSet attribute), 294
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 307
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Options attribute), 327
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatus attribute), 311
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplate attribute), 311
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageSpec attribute), 312
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Parameter attribute), 320
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseJob attribute), 319
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseResult attribute), 320
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroup attribute), 321
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Plugin

attribute), 324
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginArgument attribute), 322
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule attribute), 324
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Question attribute), 310
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.QuestionListInfo attribute), 310
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ResultInfo attribute), 293
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 295
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedAction attribute), 304
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedActionApproval attribute), 304
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedActionPolicy attribute), 303
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion attribute), 319
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionPackageSpec attribute), 334
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestion attribute), 334
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Select attribute), 309
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Sensor attribute), 305
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorQuery attribute), 302
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorReference attribute), 321
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorStat attribute), 303
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorSubcolumn attribute), 302
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Server attribute), 306
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerThrottle attribute), 335
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleStatus attribute), 337
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottle attribute), 336
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatus attribute), 337
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnet attribute), 336
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatus attribute), 338
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SoapError attribute), 314
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.Solution attribute), 333
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SystemSetting attribute), 313
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.SystemStatusAggregate attribute), 315
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.UploadFile attribute), 323
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.UploadFileStatus attribute), 323
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.User attribute), 317
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserGroup attribute), 333
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObjectIds

attribute), 316
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserRole attribute), 316
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.VerifySignature attribute), 325
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.VersionAggregate attribute), 315
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrl attribute), 314
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3424.XmlError attribute), 309
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Action attribute), 401
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionGroup attribute), 417
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionListInfo attribute), 401
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionStop attribute), 402
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestion attribute), 402
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.AuditData attribute), 389
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.AuditLog attribute), 389
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.CacheFilter attribute), 411
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.CacheInfo attribute), 393
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ClientCount attribute), 405
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ClientStatus attribute), 397
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup attribute), 409
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupSpec attribute), 408
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSet attribute), 411
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilege attribute), 414
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRole attribute), 412
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMembershi attribute), 413
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilege attribute), 414
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeOr attribute), 412
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGroupRole attribute), 413
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Dashboard attribute), 415
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.DashboardGroup attribute), 416
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivileg attribute), 415
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Filter attribute), 391
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Group attribute), 392
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.HashedString attribute), 422
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.IdReference attribute), 391
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ImportConflictDetail attribute), 410
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConnector attribute), 419
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.MergedResultSet

attribute), 378
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.MetadataItem attribute), 390
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ObjectList attribute), 410
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Options attribute), 411
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFile attribute), 396
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatus attribute), 395
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplate attribute), 395
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageSpec attribute), 396
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Parameter attribute), 404
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseJob attribute), 403
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseResult attribute), 404
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroup attribute), 405
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Plugin attribute), 407
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginArgument attribute), 406
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginSchedule attribute), 408
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Question attribute), 394
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.QuestionListInfo attribute), 394
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ResultInfo attribute), 377
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 378
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 382
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 388
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedActionApproval attribute), 388
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicy attribute), 387
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion attribute), 403
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionPackageSpe attribute), 418
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestion attribute), 418
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Select attribute), 392
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Sensor attribute), 389
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorQuery attribute), 386
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorReference attribute), 404
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorStat attribute), 387
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumn attribute), 386
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerThrottle attribute), 419
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatus attribute), 420
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottle

attribute), 420
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatus attribute), 421
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnet attribute), 420
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStatus attribute), 421
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 417
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.SystemStatusAggregate attribute), 399
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.User attribute), 400
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserOwnedObjectIds attribute), 400
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.VerifySignature attribute), 409
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.VersionAggregate attribute), 398
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrl attribute), 398
API_LIST_API_NAME (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 393
API_LIST_CLS (pytan3.api_models.ApiItem attribute), 462
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Action attribute), 75
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ActionGroup attribute), 91
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ActionListInfo attribute), 74
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ActionStop attribute), 75
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestion attribute), 76
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.AuditData attribute), 62
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.AuditLog attribute), 63
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.CacheFilter attribute), 84
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.CacheInfo attribute), 67
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ClientCount attribute), 79
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ClientStatus attribute), 70
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 54
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ComputerGroup attribute), 82
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupS attribute), 82
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSet attribute), 85
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivile attribute), 87
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRole attribute), 86
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleM attribute), 86
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePr attribute), 88
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePr attribute), 86
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGr attribute), 87
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentS attribute), 88
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Filter attribute), 64
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Group attribute), 65
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.HashedString attribute), 96

API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.IdRefList attribute), 65
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ImportConfiguration attribute), 84
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.LdapSyncHistory attribute), 92
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.MergedResultSet attribute), 52
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.MetadataItem attribute), 64
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ObjectList attribute), 83
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.OpenIns attribute), 85
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageFile attribute), 69
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatus attribute), 69
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate attribute), 68
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.PackageSpec attribute), 70
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Parameter attribute), 77
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ParseJob attribute), 77
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResult attribute), 59
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ParseResult attribute), 78
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup attribute), 79
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.PluginArgument attribute), 81
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.PluginArgumentList attribute), 79
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.PluginSchedule attribute), 81
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.QuestionInfo attribute), 68
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.QuestionSchedule attribute), 67
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ResultInfo attribute), 51
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ResultSet attribute), 52
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 58
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 62
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedActionApproval attribute), 61
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolic attribute), 61
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestion attribute), 76
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPac attribute), 91
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQu attribute), 92
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Select attribute), 66
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Sensor attribute), 62
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorQuery attribute), 59
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorReference attribute), 78
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorStat attribute), 60
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumn attribute), 60
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 63
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottle attribute), 93
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStat attribute), 94
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottle attribute), 93
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 95
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubne attribute), 94
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubne attribute), 95
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SoapError attribute), 71
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.Solution attribute), 90
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 71
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAgg attribute), 72
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus attribute), 80
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.UserOwnedObjec attribute), 73
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73

API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.VerifySignature attribute), 83
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.VersionAggregate attribute), 72
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.WhatIfResult attribute), 71
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3424.XmlError attribute), 66
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ActionListInfo attribute), 158
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ActionStop attribute), 159
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ArchiveQuestion attribute), 160
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.AuditDate attribute), 147
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.AuditLog attribute), 147
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.CalledFile attribute), 168
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.CalledInfo attribute), 151
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ClientCount attribute), 163
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ClientStatus attribute), 154
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ColumnInfo attribute), 138
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup attribute), 166
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupSpec attribute), 166
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSet attribute), 169
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilege attribute), 172
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole attribute), 170
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleCMS (pytan3.api_objects.rest_7_3_314_3641.PluginArgument attribute), 171
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleCPS (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 172
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleCPSViewGroup (pytan3.api_objects.rest_7_3_314_3641.Question attribute), 170
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroup (pytan3.api_objects.rest_7_3_314_3641.QuestionListInfo attribute), 171
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.DashboardInfo attribute), 173
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.DashboardGroup attribute), 174
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentS attribute), 173
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Filter attribute), 149
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Group attribute), 150
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.HashedString attribute), 180
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.IdReference attribute), 149
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDef attribute), 168
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnect attribute), 176
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.MergedResultSet attribute), 136
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.MetadataItem attribute), 148
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ObjectList attribute), 167
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Options attribute), 169
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageFile attribute), 153
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatus attribute), 153
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemp attribute), 152
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.PackageSpec attribute), 154
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Parameter attribute), 161
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseJob attribute), 161
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionRes attribute), 143
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseResult attribute), 162
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup attribute), 163
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Plugin attribute), 165
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginArgument attribute), 164
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 166
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Question attribute), 152
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.QuestionListInfo attribute), 151
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 135
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136

API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedList attribute), 146
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedListApply attribute), 145
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedListPolicy attribute), 145
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion attribute), 160
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionPackageSpecs attribute), 175
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestion attribute), 176
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 150
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 146
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 143
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorReference attribute), 162
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorStat attribute), 144
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SensorSubstitution attribute), 144
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 148
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ServerThrottle attribute), 177
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 178
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SitaThrottle attribute), 177
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SitaThrottleStatus attribute), 179
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SitaThrottleOther attribute), 178
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SitaThrottleOtherStatus attribute), 179
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SoapError attribute), 155
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SoapFault attribute), 174
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SystemSetting attribute), 155
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.SystemStatusAggregate attribute), 157
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.UploadFile attribute), 164
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus attribute), 165
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.User attribute), 158
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.UserGroup attribute), 174
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.UserOwnedObjec attribute), 158
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.UserRole attribute), 157
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.VerifySignature attribute), 167
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.VersionAggregate attribute), 156
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrl attribute), 156
API_LIST_CLS (pytan3.api_objects.rest_7_3_314_3641.XmlError attribute), 151
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Action attribute), 242
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ActionGroup attribute), 257
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ActionListInfo attribute), 242
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ActionStop attribute), 243
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestio attribute), 243
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.AuditData attribute), 231
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.CacheFilter attribute), 251
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 234
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ClientCount attribute), 247
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 238
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupS attribute), 249
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 252
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivile attribute), 254
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 253
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleM attribute), 253
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleP attribute), 255

API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.CurrentUserRole attribute), 252
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.CurrentUserSession attribute), 254
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Dashboard attribute), 255
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.DashboardGroup attribute), 256
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ExtendedConfigPrivilege attribute), 255
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Filter attribute), 232
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Group attribute), 233
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.HashedString attribute), 259
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.KeyValue attribute), 232
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.LastSyncTime attribute), 259
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.MergedResultsets attribute), 219
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.MetaItem attribute), 231
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ObjectList attribute), 250
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.OptionsMap attribute), 251
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageFile attribute), 237
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatus attribute), 236
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplate attribute), 236
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.PackageSpec attribute), 237
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Parameter attribute), 245
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ParseJob attribute), 244
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ParseResult attribute), 245
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroup attribute), 246
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.PlugIn attribute), 248
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.PlugInArgument attribute), 247
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.PlugInSchedule attribute), 249
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Question attribute), 235
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.QuestionInstance attribute), 235
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ResultInfo attribute), 218
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 223
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 227
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedAction attribute), 230
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedActionApp attribute), 229
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedActionPoli attribute), 229
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestion attribute), 244
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionPa attribute), 258
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQ attribute), 258
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Select attribute), 233
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Sensor attribute), 230
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 246
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorStat attribute), 228
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolum attribute), 228
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 239
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SystemSetting attribute), 238
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAgg attribute), 240
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 247
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObje attribute), 241
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.VersionAggregat attribute), 239

API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.WhitelistUrl attribute), 239
API_LIST_CLS (pytan3.api_objects.soap_7_2_314_3181.XmlErrors attribute), 234
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.AdminLIST attribute), 317
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.AdminGlobal attribute), 333
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.AdminLISTInfo attribute), 317
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.AdminSlot attribute), 318
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.AdminVisibilityGroup attribute), 318
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ApiDatas attribute), 305
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ApiLog attribute), 306
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.CacheFilter attribute), 327
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.CacheInfo attribute), 309
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.CacheConfig attribute), 322
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.CacheStats attribute), 313
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.CalmLIST attribute), 296
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ComputerGroup attribute), 325
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupSpec attribute), 324
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ContentSet attribute), 328
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilege attribute), 330
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRole attribute), 329
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMembership attribute), 329
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilege attribute), 331
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleOwnerRole attribute), 328
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupMembership attribute), 330
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Dashboard attribute), 332
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.EffectiveSettingsPrivilege attribute), 331
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Fact attribute), 307
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 338
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.IdReference attribute), 308
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDe attribute), 326
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnec attribute), 335
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.MergedResultSet attribute), 294
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 307
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Options attribute), 327
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatu attribute), 311
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemp attribute), 311
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.PackageSpec attribute), 312
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Parameter attribute), 320
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ParseJob attribute), 319
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ParseResult attribute), 320
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ParseResultGrou attribute), 321
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Plugin attribute), 324
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginArgument attribute), 322
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule attribute), 324
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Question attribute), 310
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.QuestionListInfo attribute), 310
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ResultInfo attribute), 293
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 294
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SavedAction attribute), 304

API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SaveAdmin attribute), 304
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SaveAdminRoles attribute), 303
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SaveQuestion attribute), 319
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SaveQuestionGroup attribute), 334
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SaveQuestionQuestion attribute), 334
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SelectLIST_CLS attribute), 308
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorLIST_CLS attribute), 305
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorQueryCLS attribute), 302
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorReferenceCLS attribute), 321
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorSetLIST_CLS attribute), 303
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SensorSetColumn attribute), 302
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerLIST_CLS attribute), 306
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerTitleCLS attribute), 335
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.ServerTitleStatus attribute), 337
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SetThreadLIST_CLS attribute), 336
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SetThreadSTATUSCLS attribute), 337
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SetThreadSTATUSColumn attribute), 336
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SetThreadSTATUSStatus attribute), 338
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SoapInfo attribute), 314
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SolutionLIST_CLS attribute), 333
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SystemSettingCLS attribute), 313
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.SystemStatusAggregate attribute), 315
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.UploadLIST attribute), 323
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.UploadLISTStatus attribute), 323
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.UserLIST_CLS attribute), 316
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.UserGroupLIST attribute), 332
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObjectsCLS attribute), 316
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.UserRole attribute), 316
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.VerifySignature attribute), 325
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.VersionAggregate attribute), 315
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrl attribute), 314
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3424.XmlError attribute), 309
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Action attribute), 401
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ActionGroup attribute), 417
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ActionListInfo attribute), 401
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ActionStop attribute), 402
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestio attribute), 402
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.AuditData attribute), 389
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.AuditLog attribute), 389
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.CacheFilter attribute), 410
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.CacheInfo attribute), 393
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ClientCount attribute), 405
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ClientStatus attribute), 396
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup attribute), 409
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupS attribute), 408
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSet attribute), 411
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivile attribute), 414
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRole attribute), 412
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleM attribute), 413
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleP attribute), 414
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleP attribute), 412
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserG attribute), 413
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Dashboard attribute), 415

API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.DashboardGroup attribute), 416
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.EffectiveFunctionClass attribute), 415
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Filter attribute), 391
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Group attribute), 392
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.HashedString attribute), 422
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.IdReference attribute), 391
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ImportConflictStep attribute), 410
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.LapsyUnlockTask attribute), 418
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.MergedResultsSet attribute), 378
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.MetadataItem attribute), 390
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ObjectList attribute), 410
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.OptionsList attribute), 411
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageFile attribute), 395
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatus attribute), 395
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplate attribute), 395
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.PackageSpec attribute), 396
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ParameterList attribute), 403
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ParseJob attribute), 403
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ParseResult attribute), 404
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroup attribute), 405
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.PlugIn attribute), 407
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.PlugInArgument attribute), 406
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.PlugInSchedule attribute), 408
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Question attribute), 394
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.QuestionStatus attribute), 394
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ResultInfo attribute), 377
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 378
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 382
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 388
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedActionApp attribute), 387
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedActionPoli attribute), 387
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion attribute), 402
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionPa attribute), 418
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQ attribute), 418
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Select attribute), 392
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Sensor attribute), 388
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorQuery attribute), 386
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorReference attribute), 404
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorStat attribute), 387
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolum attribute), 386
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottle attribute), 419
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleSta attribute), 420
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottle attribute), 419
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatu attribute), 421
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 420
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 421
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 417
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.SystemStatusAgg attribute), 399
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407

API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.User attribute), 400
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.UserOwnedObjectId attribute), 400
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.VerifySignature attribute), 409
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.VersionAggregate attribute), 398
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrl attribute), 398
API_LIST_CLS (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 393
API_NAME (pytan3.api_models.ApiModel attribute), 459
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Action attribute), 74
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionGroup attribute), 91
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionGroupList attribute), 127
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionList attribute), 110
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionListLine attribute), 74
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionSetOp attribute), 75
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ActionSetOpList attribute), 111
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestion attribute), 75
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestionList attribute), 111
API_NAME (pytan3.api_objects.rest_7_3_314_3424.AuditData attribute), 62
API_NAME (pytan3.api_objects.rest_7_3_314_3424.AuditDataList attribute), 100
API_NAME (pytan3.api_objects.rest_7_3_314_3424.AuditLog attribute), 63
API_NAME (pytan3.api_objects.rest_7_3_314_3424.AuditLogList attribute), 100
API_NAME (pytan3.api_objects.rest_7_3_314_3424.CacheFilter attribute), 84
API_NAME (pytan3.api_objects.rest_7_3_314_3424.CacheFilterList attribute), 120
API_NAME (pytan3.api_objects.rest_7_3_314_3424.CacheInfo attribute), 67
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ClientCount attribute), 79
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ClientStatus attribute), 70
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 53
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ColumnList attribute), 52
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ComputerGroup attribute), 82
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupList attribute), 119
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupSpec attribute), 82
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ComputerIdList attribute), 131
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ComputerSpecList attribute), 119
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSet attribute), 85
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetList attribute), 121
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilege attribute), 87
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilegeLi attribute), 123
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRole attribute), 86
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleList attribute), 122
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMemb attribute), 86
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMemb attribute), 122
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivile attribute), 88
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivile attribute), 124
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivile attribute), 85
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivile attribute), 122
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroup attribute), 87
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroup attribute), 123
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_NAME (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_NAME (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 125
API_NAME (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPr attribute), 88
API_NAME (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPr attribute), 125
API_NAME (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPr attribute), 124

API_NAME (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Filter attribute), 64
API_NAME (pytan3.api_objects.rest_7_3_314_3424.FilterList attribute), 103
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Group attribute), 65
API_NAME (pytan3.api_objects.rest_7_3_314_3424.GroupList attribute), 102
API_NAME (pytan3.api_objects.rest_7_3_314_3424.HashedString attribute), 95
API_NAME (pytan3.api_objects.rest_7_3_314_3424.HashedStringList attribute), 132
API_NAME (pytan3.api_objects.rest_7_3_314_3424.IdReference attribute), 65
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ImportConfigMap attribute), 83
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ImportConfigMapList attribute), 120
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ImportConfigOpt attribute), 121
API_NAME (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnection attribute), 92
API_NAME (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnectionList attribute), 128
API_NAME (pytan3.api_objects.rest_7_3_314_3424.MergeResultSet attribute), 51
API_NAME (pytan3.api_objects.rest_7_3_314_3424.MetadataItem attribute), 64
API_NAME (pytan3.api_objects.rest_7_3_314_3424.MetadataList attribute), 102
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ObjectList attribute), 83
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Options attribute), 84
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFile attribute), 69
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFileList attribute), 106
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFileSample attribute), 68
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFileSampleList attribute), 105
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate attribute), 68
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplateList attribute), 105
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageSpec attribute), 69
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PackageSpecList attribute), 106
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Parameter attribute), 77
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParameterList attribute), 113
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParameterValueList attribute), 114
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseJob attribute), 76
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseJobList attribute), 112
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResult attribute), 58
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResultL attribute), 58
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseResult attribute), 77
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup attribute), 78
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroupList attribute), 112
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ParseResultList attribute), 113
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PermissionList attribute), 109
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Plugin attribute), 81
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginArgument attribute), 79
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginArgumentList attribute), 115
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginCommandList attribute), 117
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginList attribute), 118
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginSchedule attribute), 81
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginScheduleList attribute), 118
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginSql attribute), 116
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginSqlColumnList attribute), 116
API_NAME (pytan3.api_objects.rest_7_3_314_3424.PluginSqlResultList attribute), 115
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Question attribute), 67
API_NAME (pytan3.api_objects.rest_7_3_314_3424.QuestionList attribute), 104
API_NAME (pytan3.api_objects.rest_7_3_314_3424.QuestionListInfo attribute), 67
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ResultInfo attribute), 50
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ResultInfoList attribute), 50
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ResultSet attribute), 52

API_NAME (pytan3.api_objects.rest_7_3_314_3424.ResultSetList attribute), 51
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
API_NAME (pytan3.api_objects.rest_7_3_314_3424.RowCell attribute), 56
API_NAME (pytan3.api_objects.rest_7_3_314_3424.RowCellList attribute), 56
API_NAME (pytan3.api_objects.rest_7_3_314_3424.RowList attribute), 54
API_NAME (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 57
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 61
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedActionApply attribute), 61
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedActionApplyList attribute), 98
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedActionList attribute), 99
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolicy attribute), 60
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolicyList attribute), 99
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestion attribute), 76
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionList attribute), 111
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionMetaspace attribute), 91
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestion attribute), 91
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestionList attribute), 127
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Select attribute), 66
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SelectList attribute), 103
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Sensor attribute), 62
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorList attribute), 97
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorQuery attribute), 59
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorQueryList attribute), 96
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorReferenced attribute), 78
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorReferencedList attribute), 114
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorSplit attribute), 60
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorSplitList attribute), 98
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumn attribute), 59
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumnList attribute), 96
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 63
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerHost attribute), 101
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerHostList attribute), 101
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerList attribute), 100
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerThrottle attribute), 92
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleList attribute), 128
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatus attribute), 94
API_NAME (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatusL attribute), 130
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottle attribute), 93
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleList attribute), 129
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 94
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatusList attribute), 130
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnet attribute), 93
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetLis attribute), 129
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetSta attribute), 95
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetSta attribute), 131
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SoapError attribute), 71
API_NAME (pytan3.api_objects.rest_7_3_314_3424.Solution attribute), 90
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 126
API_NAME (pytan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 70
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAggrega attribute), 72
API_NAME (pytan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80

API_NAME (pytan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus attribute), 80
API_NAME (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserOwnedObjects attribute), 73
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73
API_NAME (pytan3.api_objects.rest_7_3_314_3424.UserRoleList attribute), 110
API_NAME (pytan3.api_objects.rest_7_3_314_3424.VerifySignature attribute), 83
API_NAME (pytan3.api_objects.rest_7_3_314_3424.VersionAggregate attribute), 72
API_NAME (pytan3.api_objects.rest_7_3_314_3424.VersionAggregateList attribute), 107
API_NAME (pytan3.api_objects.rest_7_3_314_3424.WhitelistedURL attribute), 71
API_NAME (pytan3.api_objects.rest_7_3_314_3424.WhitelistedURLList attribute), 107
API_NAME (pytan3.api_objects.rest_7_3_314_3424.XmlEnum attribute), 66
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionGroupList attribute), 211
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionList attribute), 194
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionMatch attribute), 158
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionStep attribute), 159
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ActionStepList attribute), 195
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ArchiveQuestion attribute), 160
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ArchiveQuestionList attribute), 195
API_NAME (pytan3.api_objects.rest_7_3_314_3641.AuditData attribute), 147
API_NAME (pytan3.api_objects.rest_7_3_314_3641.AuditDataList attribute), 184
API_NAME (pytan3.api_objects.rest_7_3_314_3641.AuditLog attribute), 147
API_NAME (pytan3.api_objects.rest_7_3_314_3641.AuditLogList attribute), 184
API_NAME (pytan3.api_objects.rest_7_3_314_3641.CacheFilter attribute), 168
API_NAME (pytan3.api_objects.rest_7_3_314_3641.CacheFilterList attribute), 204
API_NAME (pytan3.api_objects.rest_7_3_314_3641.CacheInfo attribute), 151
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ClientCount attribute), 163
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ClientStatus attribute), 154
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 138
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ColumnList attribute), 137
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup attribute), 166
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupList attribute), 203
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupSpec attribute), 166
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ComputerIdList attribute), 215
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ComputerSpecList attribute), 203
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSet attribute), 169
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetList attribute), 205
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilege attribute), 171
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilegeLi attribute), 208
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole attribute), 170
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleList attribute), 206
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMemb attribute), 170
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMemb attribute), 207
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivile attribute), 172
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivile attribute), 208
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivile attribute), 169
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivile attribute), 206
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroup attribute), 171
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroup attribute), 207

API_NAME (pytan3.api_objects.rest_7_3_314_3641.DashboardList attribute), 173
API_NAME (pytan3.api_objects.rest_7_3_314_3641.DashboardMap attribute), 173
API_NAME (pytan3.api_objects.rest_7_3_314_3641.DashboardMapList attribute), 210
API_NAME (pytan3.api_objects.rest_7_3_314_3641.EffectiveCommentMap attribute), 172
API_NAME (pytan3.api_objects.rest_7_3_314_3641.EffectiveCommentMapList attribute), 209
API_NAME (pytan3.api_objects.rest_7_3_314_3641.EffectiveCommentMapObject attribute), 209
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ErrorList attribute), 188
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Filter attribute), 148
API_NAME (pytan3.api_objects.rest_7_3_314_3641.FilterList attribute), 187
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Group attribute), 149
API_NAME (pytan3.api_objects.rest_7_3_314_3641.GroupList attribute), 187
API_NAME (pytan3.api_objects.rest_7_3_314_3641.HashedString attribute), 179
API_NAME (pytan3.api_objects.rest_7_3_314_3641.HashedStringList attribute), 216
API_NAME (pytan3.api_objects.rest_7_3_314_3641.IdReference attribute), 149
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ImportConfMap attribute), 168
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ImportConfMapList attribute), 204
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ImportConfMapObject attribute), 205
API_NAME (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnection attribute), 176
API_NAME (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnectionList attribute), 212
API_NAME (pytan3.api_objects.rest_7_3_314_3641.MergeAttribute attribute), 135
API_NAME (pytan3.api_objects.rest_7_3_314_3641.MetadataItem attribute), 148
API_NAME (pytan3.api_objects.rest_7_3_314_3641.MetadataList attribute), 186
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ObjectList attribute), 167
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Options attribute), 169
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFile attribute), 153
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFileList attribute), 190
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFileSample attribute), 153
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatusList attribute), 189
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplate attribute), 152
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplateL attribute), 189
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageSpec attribute), 154
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PackageSpecList attribute), 190
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Parameter attribute), 161
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParameterList attribute), 198
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParameterValueList attribute), 198
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseJob attribute), 161
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseJobList attribute), 196
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResult attribute), 143
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResultL attribute), 142
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseResult attribute), 162
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup attribute), 162
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroupList attribute), 197
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ParseResultList attribute), 197
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PermissionList attribute), 193
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Plugin attribute), 165
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginArgument attribute), 163
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginArgumentList attribute), 199
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginCommandList attribute), 201
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginList attribute), 202
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 165
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginScheduleList attribute), 202
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginSql attribute), 200
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginSqlColumnList attribute), 200
API_NAME (pytan3.api_objects.rest_7_3_314_3641.PluginSqlResultList attribute), 199

API_NAME (pytan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 188
API_NAME (pytan3.api_objects.rest_7_3_314_3641.QuestionListName attribute), 151
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 134
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139
API_NAME (pytan3.api_objects.rest_7_3_314_3641.RowCellm attribute), 141
API_NAME (pytan3.api_objects.rest_7_3_314_3641.RowCellmList attribute), 140
API_NAME (pytan3.api_objects.rest_7_3_314_3641.RowList attribute), 138
API_NAME (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedAction attribute), 146
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedActionApproval attribute), 145
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedActionApprovalList attribute), 182
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedActionList attribute), 183
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedActionPolicy attribute), 145
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedActionPolicyList attribute), 183
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion attribute), 160
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionList attribute), 196
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionMetaSpec attribute), 175
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestion attribute), 176
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestionList attribute), 211
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Select attribute), 150
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SelectList attribute), 188
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Sensor attribute), 146
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorList attribute), 181
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 143
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorQueryList attribute), 180
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorReference attribute), 162
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorReferenceList attribute), 198
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorStat attribute), 144
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorStatList attribute), 182
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumn attribute), 144
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumnList attribute), 180
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 147
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerHost attribute), 185
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerHostList attribute), 186
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerList attribute), 185
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerThrottle attribute), 177
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleList attribute), 212
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 178
API_NAME (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatusL attribute), 214
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle attribute), 177
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleList attribute), 213
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatus attribute), 178
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatusList attribute), 214
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnet attribute), 178
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetLis attribute), 213
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetSta attribute), 179
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetSta attribute), 215
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SoapError attribute), 155
API_NAME (pytan3.api_objects.rest_7_3_314_3641.Solution attribute), 174
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SolutionList attribute), 211

API_NAME (pytan3.api_objects.rest_7_3_314_3641.StringSetting attribute), 181
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SystemSetting attribute), 155
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SystemSettingList attribute), 192
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SystemStatusAggregate attribute), 156
API_NAME (pytan3.api_objects.rest_7_3_314_3641.SystemStatusList attribute), 192
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UploadFile attribute), 164
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UploadFileList attribute), 201
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus attribute), 164
API_NAME (pytan3.api_objects.rest_7_3_314_3641.User attribute), 158
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserGroup attribute), 174
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserGroupList attribute), 210
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserList attribute), 193
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserOwnedObjects attribute), 157
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserRole attribute), 157
API_NAME (pytan3.api_objects.rest_7_3_314_3641.UserRoleList attribute), 194
API_NAME (pytan3.api_objects.rest_7_3_314_3641.VerifySignature attribute), 167
API_NAME (pytan3.api_objects.rest_7_3_314_3641.VersionAggregate attribute), 156
API_NAME (pytan3.api_objects.rest_7_3_314_3641.VersionAggregateList attribute), 191
API_NAME (pytan3.api_objects.rest_7_3_314_3641.WhitelistedURL attribute), 155
API_NAME (pytan3.api_objects.rest_7_3_314_3641.WhitelistedURLList attribute), 191
API_NAME (pytan3.api_objects.rest_7_3_314_3641.XmlError attribute), 150
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Action attribute), 242
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionGroup attribute), 257
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionGroupList attribute), 289
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionList attribute), 272
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionMatch attribute), 242
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionStop attribute), 242
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ActionStopList attribute), 273
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestion attribute), 243
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionList attribute), 273
API_NAME (pytan3.api_objects.soap_7_2_314_3181.AuditData attribute), 230
API_NAME (pytan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 263
API_NAME (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_NAME (pytan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_NAME (pytan3.api_objects.soap_7_2_314_3181.CacheFilter attribute), 250
API_NAME (pytan3.api_objects.soap_7_2_314_3181.CacheFilterList attribute), 282
API_NAME (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 234
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ClientCount attribute), 246
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 237
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 221
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupList attribute), 281
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupSpec attribute), 249
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ComputerIdList attribute), 290
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ComputerSpecList attribute), 281
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 251
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilege attribute), 254
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilegeList attribute), 285
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 252
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleList attribute), 284
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMember attribute), 253
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMemberList attribute), 284

API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleProvider attribute), 254
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleProvider attribute), 286
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleProvider attribute), 252
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleProvider attribute), 283
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRoleMembership attribute), 253
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRoleMembership attribute), 285
API_NAME (pytan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 255
API_NAME (pytan3.api_objects.soap_7_2_314_3181.DashboardGroup attribute), 256
API_NAME (pytan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 287
API_NAME (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilege attribute), 255
API_NAME (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilegeList attribute), 287
API_NAME (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivilegeRequest attribute), 286
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ErrorList attribute), 266
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Filter attribute), 232
API_NAME (pytan3.api_objects.soap_7_2_314_3181.FilterList attribute), 265
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Group attribute), 233
API_NAME (pytan3.api_objects.soap_7_2_314_3181.GroupList attribute), 265
API_NAME (pytan3.api_objects.soap_7_2_314_3181.HashedString attribute), 259
API_NAME (pytan3.api_objects.soap_7_2_314_3181.HashedStringList attribute), 290
API_NAME (pytan3.api_objects.soap_7_2_314_3181.IdReference attribute), 232
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ImportConnectOptions attribute), 282
API_NAME (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnector attribute), 258
API_NAME (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnectorList attribute), 290
API_NAME (pytan3.api_objects.soap_7_2_314_3181.MergeResultSet attribute), 219
API_NAME (pytan3.api_objects.soap_7_2_314_3181.MetadataItem attribute), 231
API_NAME (pytan3.api_objects.soap_7_2_314_3181.MetadataList attribute), 264
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ObjectList attribute), 250
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Options attribute), 251
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFile attribute), 236
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFileList attribute), 268
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatus attribute), 236
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatusList attribute), 268
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplate attribute), 235
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplate attribute), 267
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageSpec attribute), 237
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PackageSpecList attribute), 269
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Parameter attribute), 244
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParameterList attribute), 276
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParameterValueList attribute), 276
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseJob attribute), 244
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseJobList attribute), 274
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseResult attribute), 245
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroup attribute), 246
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroupList attribute), 275
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ParseResultList attribute), 275
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PermissionList attribute), 271
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Plugin attribute), 248
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginArgument attribute), 247
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginArgumentList attribute), 277
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginCommandList attribute), 279
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginList attribute), 280
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginSchedule attribute), 249
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginScheduleList attribute), 280
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginSql attribute), 278

API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginSqlColumnList attribute), 278
API_NAME (pytan3.api_objects.soap_7_2_314_3181.PluginSqlResultList attribute), 278
API_NAME (pytan3.api_objects.soap_7_2_314_3181.QuestionAnswer attribute), 235
API_NAME (pytan3.api_objects.soap_7_2_314_3181.QuestionList attribute), 267
API_NAME (pytan3.api_objects.soap_7_2_314_3181.QuestionInfo attribute), 234
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ResultInfo attribute), 218
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList attribute), 218
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
API_NAME (pytan3.api_objects.soap_7_2_314_3181.ResultSetList attribute), 219
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 223
API_NAME (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 225
API_NAME (pytan3.api_objects.soap_7_2_314_3181.RowColumnList attribute), 224
API_NAME (pytan3.api_objects.soap_7_2_314_3181.RowList attribute), 222
API_NAME (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 226
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedAction attribute), 229
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedActionApproval attribute), 229
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedActionApprovalList attribute), 262
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedActionList attribute), 263
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicy attribute), 228
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicyList attribute), 262
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestion attribute), 243
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionList attribute), 274
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionMetadata attribute), 258
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionMetadataList attribute), 258
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestionList attribute), 289
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SelectAll attribute), 233
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SelectList attribute), 266
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Sensor attribute), 230
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorList attribute), 261
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorQueryList attribute), 259
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 245
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorReferenceList attribute), 277
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorStat attribute), 228
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorStatList attribute), 261
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumn attribute), 227
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumnList attribute), 260
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 238
API_NAME (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SolutionList attribute), 288
API_NAME (pytan3.api_objects.soap_7_2_314_3181.StringHintList attribute), 260
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SystemSetting attribute), 238
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SystemSettingList attribute), 270
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAggregateList attribute), 240
API_NAME (pytan3.api_objects.soap_7_2_314_3181.SystemStatusList attribute), 270
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 247
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 279
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248
API_NAME (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObjectId attribute), 241
API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240

API_NAME (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 272
API_NAME (pytan3.api_objects.soap_7_2_314_3181.VersionAggregate attribute), 239
API_NAME (pytan3.api_objects.soap_7_2_314_3181.VersionAggregateList attribute), 269
API_NAME (pytan3.api_objects.soap_7_2_314_3181.WhitelistedIP attribute), 239
API_NAME (pytan3.api_objects.soap_7_2_314_3181.WhitelistedIPList attribute), 269
API_NAME (pytan3.api_objects.soap_7_2_314_3181.XmlError attribute), 234
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Action attribute), 317
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionGroup attribute), 333
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionGroupList attribute), 369
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionList attribute), 353
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionMap attribute), 317
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionProp attribute), 318
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ActionPropList attribute), 353
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestion attribute), 318
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestionList attribute), 354
API_NAME (pytan3.api_objects.soap_7_3_314_3424.AuditData attribute), 305
API_NAME (pytan3.api_objects.soap_7_3_314_3424.AuditDataList attribute), 342
API_NAME (pytan3.api_objects.soap_7_3_314_3424.AuditLog attribute), 305
API_NAME (pytan3.api_objects.soap_7_3_314_3424.AuditLogList attribute), 343
API_NAME (pytan3.api_objects.soap_7_3_314_3424.CacheFilter attribute), 327
API_NAME (pytan3.api_objects.soap_7_3_314_3424.CacheFilterList attribute), 363
API_NAME (pytan3.api_objects.soap_7_3_314_3424.CacheInfo attribute), 309
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ClientCount attribute), 321
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ClientStatus attribute), 312
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ColumnList attribute), 295
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ComparGroup attribute), 325
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupList attribute), 362
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupSpec attribute), 324
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ComputerIdList attribute), 374
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ComputerSpecList attribute), 361
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSet attribute), 327
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetList attribute), 364
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilege attribute), 330
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilegeL attribute), 366
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRole attribute), 328
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleList attribute), 364
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMem attribute), 329
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMem attribute), 365
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivi attribute), 330
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivi attribute), 366
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivi attribute), 328
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivi attribute), 364
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGrou attribute), 329
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGrou attribute), 365
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Dashboard attribute), 331
API_NAME (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_NAME (pytan3.api_objects.soap_7_3_314_3424.DashboardList attribute), 368
API_NAME (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetP attribute), 331
API_NAME (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetP attribute), 367
API_NAME (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetP attribute), 367
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ErrorList attribute), 346
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Filter attribute), 307
API_NAME (pytan3.api_objects.soap_7_3_314_3424.FilterList attribute), 346

API_NAME (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_NAME (pytan3.api_objects.soap_7_3_314_3424.GroupList attribute), 345
API_NAME (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 338
API_NAME (pytan3.api_objects.soap_7_3_314_3424.HashedStringList attribute), 374
API_NAME (pytan3.api_objects.soap_7_3_314_3424.IdReferences attribute), 307
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ImportCommandDetail attribute), 326
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ImportCommandDetailList attribute), 362
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ImportCommandOpts attribute), 363
API_NAME (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnect attribute), 335
API_NAME (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnectList attribute), 370
API_NAME (pytan3.api_objects.soap_7_3_314_3424.MergedResultSet attribute), 294
API_NAME (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 306
API_NAME (pytan3.api_objects.soap_7_3_314_3424.MetadataList attribute), 345
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_NAME (pytan3.api_objects.soap_7_3_314_3424.OptionsAll attribute), 327
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFileList attribute), 348
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatus attribute), 311
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatusList attribute), 348
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplate attribute), 311
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplateList attribute), 347
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageSpec attribute), 312
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PackageSpecList attribute), 349
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Parameter attribute), 320
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParameterList attribute), 356
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParameterValueList attribute), 356
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseJob attribute), 319
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseJobList attribute), 355
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseResult attribute), 320
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroup attribute), 321
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroupList attribute), 355
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ParseResultList attribute), 356
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PermissionList attribute), 352
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Plugin attribute), 323
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginArgument attribute), 322
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginArgumentList attribute), 357
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginCommandList attribute), 359
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginList attribute), 360
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule attribute), 324
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginScheduleList attribute), 361
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginSql attribute), 359
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginSqlColumnList attribute), 358
API_NAME (pytan3.api_objects.soap_7_3_314_3424.PluginSqlResultList attribute), 358
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Question attribute), 310
API_NAME (pytan3.api_objects.soap_7_3_314_3424.QuestionList attribute), 347
API_NAME (pytan3.api_objects.soap_7_3_314_3424.QuestionListInfo attribute), 310
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ResultInfo attribute), 293
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList attribute), 292
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 294
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ResultSetList attribute), 293
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
API_NAME (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_NAME (pytan3.api_objects.soap_7_3_314_3424.RowColumnList attribute), 299
API_NAME (pytan3.api_objects.soap_7_3_314_3424.RowList attribute), 297

API_NAME (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedAction attribute), 304
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedActionApproval attribute), 303
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedActionApprovalList attribute), 341
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedActionList attribute), 342
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedActionPolicy attribute), 303
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedActionRowFilter attribute), 341
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion attribute), 319
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionList attribute), 354
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionPackageSpace attribute), 334
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestion attribute), 334
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestionList attribute), 370
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Select attribute), 308
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SelectList attribute), 346
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Sensor attribute), 304
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorList attribute), 340
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorQuery attribute), 302
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorQueryList attribute), 338
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorReference attribute), 320
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorReferenceList attribute), 357
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorStat attribute), 303
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorStatList attribute), 340
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorSubColumn attribute), 302
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SensorSubColumnList attribute), 339
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Server attribute), 306
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerHost attribute), 344
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerHostList attribute), 344
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerList attribute), 343
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerThrottle attribute), 335
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleList attribute), 371
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleStatus attribute), 336
API_NAME (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleStatusL attribute), 372
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottle attribute), 336
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleList attribute), 371
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatus attribute), 337
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatusLis attribute), 373
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnet attribute), 336
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetLi attribute), 372
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetSt attribute), 337
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetSt attribute), 373
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SoapError attribute), 313
API_NAME (pytan3.api_objects.soap_7_3_314_3424.Solution attribute), 333
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SolutionList attribute), 369
API_NAME (pytan3.api_objects.soap_7_3_314_3424.StringHintList attribute), 339
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SystemSetting attribute), 313
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SystemSettingList attribute), 351
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SystemStatusAggreg attribute), 315
API_NAME (pytan3.api_objects.soap_7_3_314_3424.SystemStatusList attribute), 350
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UploadFile attribute), 322
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UploadFileList attribute), 360
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UploadFileStatus attribute), 323
API_NAME (pytan3.api_objects.soap_7_3_314_3424.User attribute), 316
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserGroup attribute), 332
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserGroupList attribute), 368

API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserList attribute), 351
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObjects attribute), 316
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserRole attribute), 315
API_NAME (pytan3.api_objects.soap_7_3_314_3424.UserRoleList attribute), 352
API_NAME (pytan3.api_objects.soap_7_3_314_3424.VerifySignature attribute), 325
API_NAME (pytan3.api_objects.soap_7_3_314_3424.VersionAggregate attribute), 314
API_NAME (pytan3.api_objects.soap_7_3_314_3424.VersionAggregateList attribute), 350
API_NAME (pytan3.api_objects.soap_7_3_314_3424.WhiteListedURL attribute), 314
API_NAME (pytan3.api_objects.soap_7_3_314_3424.WhiteListedURLs attribute), 349
API_NAME (pytan3.api_objects.soap_7_3_314_3424.XmlError attribute), 309
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Action attribute), 401
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionGroup attribute), 417
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionGroupList attribute), 453
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionList attribute), 436
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionMap attribute), 400
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionStop attribute), 401
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ActionStopList attribute), 437
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ArchiveQuestion attribute), 402
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ArchiveQuestionList attribute), 437
API_NAME (pytan3.api_objects.soap_7_3_314_3641.AuditData attribute), 389
API_NAME (pytan3.api_objects.soap_7_3_314_3641.AuditDataList attribute), 426
API_NAME (pytan3.api_objects.soap_7_3_314_3641.AuditLog attribute), 389
API_NAME (pytan3.api_objects.soap_7_3_314_3641.AuditLogList attribute), 426
API_NAME (pytan3.api_objects.soap_7_3_314_3641.CacheItem attribute), 410
API_NAME (pytan3.api_objects.soap_7_3_314_3641.CacheItemList attribute), 446
API_NAME (pytan3.api_objects.soap_7_3_314_3641.CacheInfo attribute), 393
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ClientCount attribute), 405
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ClientStatus attribute), 396
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ColumnList attribute), 379
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup attribute), 408
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupList attribute), 445
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupSpec attribute), 408
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ComputerIdList attribute), 457
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ComputerSpecList attribute), 445
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSet attribute), 411
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetList attribute), 447
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilege attribute), 414
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilegeL attribute), 450
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRole attribute), 412
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleList attribute), 448
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMem attribute), 413
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMem attribute), 449
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivi attribute), 414
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivi attribute), 450
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivi attribute), 412
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivi attribute), 448
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGrou attribute), 413
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGrou attribute), 449
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Dashboard attribute), 415
API_NAME (pytan3.api_objects.soap_7_3_314_3641.DashboardGroup attribute), 415
API_NAME (pytan3.api_objects.soap_7_3_314_3641.DashboardList attribute), 452
API_NAME (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetP attribute), 414
API_NAME (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetP attribute), 451

API_NAME (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivileges.object attribute), 451
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ErrorList attribute), 430
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Filter attribute), 391
API_NAME (pytan3.api_objects.soap_7_3_314_3641.FilterList attribute), 429
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Group attribute), 391
API_NAME (pytan3.api_objects.soap_7_3_314_3641.GroupList attribute), 429
API_NAME (pytan3.api_objects.soap_7_3_314_3641.HashedString attribute), 422
API_NAME (pytan3.api_objects.soap_7_3_314_3641.HashedStringList attribute), 458
API_NAME (pytan3.api_objects.soap_7_3_314_3641.IdReference attribute), 391
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ImportConnectDetail attribute), 410
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ImportConnectDetailList attribute), 446
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ImportConnectOptions attribute), 447
API_NAME (pytan3.api_objects.soap_7_3_314_3641.LdapSync_Connector attribute), 418
API_NAME (pytan3.api_objects.soap_7_3_314_3641.LdapSync_ConnectorList attribute), 454
API_NAME (pytan3.api_objects.soap_7_3_314_3641.MergedResultSet attribute), 378
API_NAME (pytan3.api_objects.soap_7_3_314_3641.MetadataItem attribute), 390
API_NAME (pytan3.api_objects.soap_7_3_314_3641.MetadataList attribute), 428
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ObjectList attribute), 409
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Options attribute), 411
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFile attribute), 395
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFileList attribute), 432
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatus attribute), 395
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatusList attribute), 432
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplate attribute), 394
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplateList attribute), 431
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageSpec attribute), 396
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PackageSpecList attribute), 433
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Parameter attribute), 403
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParameterList attribute), 440
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParameterValueList attribute), 440
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseJob attribute), 403
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseJobList attribute), 438
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseResult attribute), 404
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroup attribute), 405
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroupList attribute), 439
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ParseResultList attribute), 439
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PermissionList attribute), 435
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Plugin attribute), 407
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginArgument attribute), 406
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginArgumentList attribute), 441
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginCommandList attribute), 443
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginList attribute), 444
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginSchedule attribute), 407
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginScheduleList attribute), 444
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginSql attribute), 442
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginSqlColumnList attribute), 442
API_NAME (pytan3.api_objects.soap_7_3_314_3641.PluginSqlResultList attribute), 442
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Question attribute), 394
API_NAME (pytan3.api_objects.soap_7_3_314_3641.QuestionList attribute), 431
API_NAME (pytan3.api_objects.soap_7_3_314_3641.QuestionListInfo attribute), 393
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ResultInfo attribute), 377
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList attribute), 376
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 378
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ResultSetList attribute), 377

API_NAME (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 381
API_NAME (pytan3.api_objects.soap_7_3_314_3641.RowCollection attribute), 384
API_NAME (pytan3.api_objects.soap_7_3_314_3641.RowCollectionList attribute), 383
API_NAME (pytan3.api_objects.soap_7_3_314_3641.RowList attribute), 381
API_NAME (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 388
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedActionApproval attribute), 387
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedActionApprovalList attribute), 424
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedActionList attribute), 425
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicy attribute), 387
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicyList attribute), 425
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion attribute), 402
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionList attribute), 438
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionManageS3api attribute), 417
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestion attribute), 418
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestionList attribute), 454
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Select attribute), 392
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SelectList attribute), 430
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Sensor attribute), 388
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorList attribute), 423
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorQuery attribute), 385
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorQueryList attribute), 422
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorReference attribute), 404
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorReferenceList attribute), 441
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorStat attribute), 386
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorStatList attribute), 424
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumn attribute), 386
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumnList attribute), 423
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 427
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerThrottle attribute), 419
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleList attribute), 455
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatus attribute), 420
API_NAME (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatusList attribute), 456
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottle attribute), 419
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatus attribute), 421
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatusList attribute), 456
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnet attribute), 420
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetList attribute), 456
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStat attribute), 421
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStatList attribute), 457
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_NAME (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 416
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_NAME (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SystemSettingList attribute), 434
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SystemStatusAggregate attribute), 399
API_NAME (pytan3.api_objects.soap_7_3_314_3641.SystemStatusList attribute), 434
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 443

API_NAME (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407
API_NAME (pytan3.api_objects.soap_7_3_314_3641.User attribute), 400
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserOwnedObjectIds attribute), 399
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_NAME (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_NAME (pytan3.api_objects.soap_7_3_314_3641.VerifySignature attribute), 409
API_NAME (pytan3.api_objects.soap_7_3_314_3641.VersionAggregate attribute), 398
API_NAME (pytan3.api_objects.soap_7_3_314_3641.VersionAggregateList attribute), 433
API_NAME (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrl attribute), 398
API_NAME (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrlList attribute), 433
API_NAME (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 392
API_NAME_SRC (pytan3.api_models.ApiModel attribute), 459
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Action attribute), 75
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ActionGroup attribute), 91
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ActionGroupList attribute), 127
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ActionList attribute), 110
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ActionListInfo attribute), 74
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ActionStop attribute), 75
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ActionStopList attribute), 111
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestion attribute), 75
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ArchivedQuestionList attribute), 111
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.AuditData attribute), 62
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.AuditDataList attribute), 100
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.AuditLog attribute), 63
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.AuditLogList attribute), 100
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.CacheFilter attribute), 84
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.CacheFilterList attribute), 120
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.CacheInfo attribute), 67
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ClientCount attribute), 79
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ClientStatus attribute), 70
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 53
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ColumnList attribute), 53
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ComputerGroup attribute), 82
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupList attribute), 119
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupSpec attribute), 82
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ComputerIdList attribute), 131
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ComputerSpecList attribute), 119
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSet attribute), 85

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetList attribute), 121
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilege attribute), 87
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilegeList attribute), 124
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRole attribute), 86
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleList attribute), 122
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMembership attribute), 86
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMembershipList attribute), 123
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilege attribute), 88
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeList attribute), 124
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeOnRole attribute), 85
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeOnRoleList attribute), 122
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupRoleMembership attribute), 87
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupRoleMembershipList attribute), 123
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 125
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivilege attribute), 88
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivilegeList attribute), 125
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetPrivilege attribute), 125
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Filter attribute), 64
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.FilterList attribute), 103
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Group attribute), 65
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.GroupList attribute), 102
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.HashedString attribute), 95
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.HashedStringList attribute), 132
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.IdReference attribute), 65
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDetail attribute), 83
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ImportConflictDetailList attribute), 120
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ImportConflictOptions attribute), 121
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnector attribute), 92
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.LdapSyncConnectorList attribute), 128
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.MergedResultSet attribute), 51
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.MetadataItem attribute), 64
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.MetadataList attribute), 102
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ObjectList attribute), 83

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Options attribute), 84
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageFile attribute), 69
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageFileList attribute), 106
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatus attribute), 68
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatusList attribute), 105
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate attribute), 68
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplateList attribute), 105
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageSpec attribute), 69
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PackageSpecList attribute), 106
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Parameter attribute), 77
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParameterList attribute), 113
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParameterValueList attribute), 114
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseJob attribute), 76
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseJobList attribute), 112
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResult attribute), 58
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResultList attribute), 58
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseResult attribute), 77
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup attribute), 78
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroupList attribute), 112
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ParseResultList attribute), 113
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PermissionList attribute), 109
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Plugin attribute), 81
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginArgument attribute), 79
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginArgumentList attribute), 115
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginCommandList attribute), 117
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginList attribute), 118
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginSchedule attribute), 81
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginScheduleList attribute), 118
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginSql attribute), 116
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginSqlColumnList attribute), 116
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.PluginSqlResultList attribute), 115
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Question attribute), 67
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.QuestionList attribute), 104
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.QuestionListInfo attribute), 67
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ResultInfo attribute), 50
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ResultInfoList attribute), 50

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ResultSet attribute), 52
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ResultSetList attribute), 51
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.RowColumnList attribute), 56
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.RowList attribute), 54
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 57
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 61
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedActionApproval attribute), 61
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedActionApprovalList attribute), 98
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedActionList attribute), 99
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolicy attribute), 60
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedActionRowIdList attribute), 99
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedQuestion attribute), 76
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionList attribute), 112
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPackageSpecs attribute), 91
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestion attribute), 91
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionQuestionList attribute), 127
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Select attribute), 66
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SelectList attribute), 103
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Sensor attribute), 62
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorList attribute), 97
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorQuery attribute), 59
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorQueryList attribute), 96
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorReference attribute), 78
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorReferenceList attribute), 114
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorStat attribute), 60
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorStatList attribute), 98
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumn attribute), 59
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumnList attribute), 96
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 63
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ServerHost attribute), 101
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ServerHostList attribute), 101
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ServerList attribute), 101
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ServerThrottle attribute), 92
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleList attribute), 128

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatus attribute), 94
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatusList attribute), 130
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottle attribute), 93
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleList attribute), 129
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 94
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatusList attribute), 130
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnet attribute), 93
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetList attribute), 129
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatus attribute), 95
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatusList attribute), 131
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SoapError attribute), 71
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.Solution attribute), 90
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 126
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 70
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAggregate attribute), 72
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus attribute), 80
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UserOwnedObjectIds attribute), 73
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.UserRoleList attribute), 110
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.VerifySignature attribute), 83
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.VersionAggregate attribute), 72
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.VersionAggregateList attribute), 107
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.WhiteListedUrl attribute), 71
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.WhiteListedUrlList attribute), 107
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3424.XmlError attribute), 66
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ActionGroupList attribute), 211
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ActionList attribute), 194
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ActionListInfo attribute), 158
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ActionStop attribute), 159
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ActionStopList attribute), 195
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ArchivedQuestion attribute), 160
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ArchivedQuestionList attribute), 195
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.AuditData attribute), 147
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.AuditDataList attribute), 184
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.AuditLog attribute), 147
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.AuditLogList attribute), 184
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.CacheFilter attribute), 168
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.CacheFilterList attribute), 204
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.CacheInfo attribute), 151
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ClientCount attribute), 163
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ClientStatus attribute), 154
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 138
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ColumnList attribute), 137
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup attribute), 166
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupList attribute), 203
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupSpec attribute), 166
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ComputerIdList attribute), 215
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ComputerSpecList attribute), 203
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSet attribute), 169
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetList attribute), 205
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilege attribute), 171
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilegeList attribute), 208
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole attribute), 170
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleList attribute), 206
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembership attribute), 170
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMembership attribute), 207
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilege attribute), 172
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeLis attribute), 208
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeOn attribute), 169
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivilegeOn attribute), 206
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupRoleM attribute), 171

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGroupRoleMembership attribute), 207
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Dashboard attribute), 173
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.DashboardGroup attribute), 173
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.DashboardList attribute), 210
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivilege attribute), 172
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivilegeList attribute), 209
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetPrivilegeRequest attribute), 209
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ErrorList attribute), 188
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Filter attribute), 148
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.FilterList attribute), 187
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Group attribute), 149
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.GroupList attribute), 187
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.HashedString attribute), 179
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.HashedStringList attribute), 216
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.IdReference attribute), 149
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDetail attribute), 168
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ImportConflictDetailList attribute), 204
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ImportConflictOptions attribute), 205
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnector attribute), 176
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnectorList attribute), 212
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.MergedResultSet attribute), 135
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.MetadataItem attribute), 148
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.MetadataList attribute), 186
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ObjectList attribute), 167
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Options attribute), 169
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageFile attribute), 153
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageFileList attribute), 190
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatus attribute), 153
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatusList attribute), 190
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplate attribute), 152
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplateList attribute), 189
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageSpec attribute), 154
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PackageSpecList attribute), 190
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Parameter attribute), 161
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParameterList attribute), 198
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParameterValueList attribute), 198

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseJob attribute), 161
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseJobList attribute), 196
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResult attribute), 143
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResultList attribute), 142
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseResult attribute), 162
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup attribute), 163
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroupList attribute), 197
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ParseResultList attribute), 197
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PermissionList attribute), 193
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Plugin attribute), 165
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginArgument attribute), 163
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginArgumentList attribute), 199
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginCommandList attribute), 201
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginList attribute), 202
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 165
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginScheduleList attribute), 202
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginSql attribute), 200
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginSqlColumnList attribute), 200
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.PluginSqlResultList attribute), 199
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Question attribute), 152
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 189
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.QuestionListInfo attribute), 151
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 134
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.RowColumnList attribute), 140
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.RowList attribute), 138
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedAction attribute), 146
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedActionApproval attribute), 145
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedActionApprovalList attribute), 182
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedActionList attribute), 183
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedActionPolicy attribute), 145

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedActionRowIdList attribute), 183
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion attribute), 160
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionList attribute), 196
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionPackageSpecs attribute), 175
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestion attribute), 176
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestionList attribute), 212
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Select attribute), 150
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SelectList attribute), 188
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Sensor attribute), 146
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorList attribute), 181
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 143
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorQueryList attribute), 180
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorReference attribute), 162
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorReferenceList attribute), 199
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorStat attribute), 144
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorStatList attribute), 182
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumn attribute), 144
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumnList attribute), 180
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 148
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ServerHost attribute), 185
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ServerHostList attribute), 186
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ServerList attribute), 185
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ServerThrottle attribute), 177
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleList attribute), 212
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 178
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatusList attribute), 214
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle attribute), 177
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleList attribute), 213
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatus attribute), 179
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatusList attribute), 214
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnet attribute), 178
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetList attribute), 213
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetStatus attribute), 179
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetStatusLis attribute), 215
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SoapError attribute), 155
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.Solution attribute), 174

API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SolutionList attribute), 211
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.StringHintList attribute), 181
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SystemSetting attribute), 155
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SystemSettingList attribute), 192
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SystemStatusAggregate attribute), 156
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.SystemStatusList attribute), 192
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UploadFile attribute), 164
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UploadFileList attribute), 201
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus attribute), 164
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.User attribute), 158
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UserGroup attribute), 174
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UserGroupList attribute), 210
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UserList attribute), 193
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UserOwnedObjectIds attribute), 157
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UserRole attribute), 157
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.UserRoleList attribute), 194
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.VerifySignature attribute), 167
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.VersionAggregate attribute), 156
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.VersionAggregateList attribute), 191
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrl attribute), 155
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.WhiteListedUrlList attribute), 191
API_NAME_SRC (pytan3.api_objects.rest_7_3_314_3641.XmlError attribute), 150
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Action attribute), 242
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ActionGroup attribute), 257
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ActionGroupList attribute), 289
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ActionList attribute), 272
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ActionListInfo attribute), 242
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ActionStop attribute), 243
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ActionStopList attribute), 273
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestion attribute), 243
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionList attribute), 273
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.AuditData attribute), 230
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 263
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.CacheFilter attribute), 251

API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.CacheFilterList attribute), 282
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 234
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ClientCount attribute), 246
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 237
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 221
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupList attribute), 281
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupSpec attribute), 249
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ComputerIdList attribute), 290
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ComputerSpecList attribute), 281
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 251
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilege attribute), 254
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilegeList attribute), 285
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 252
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleList attribute), 284
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMembership attribute), 253
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMembershi attribute), 284
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilege attribute), 254
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeLi attribute), 286
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeOr attribute), 252
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeOr attribute), 283
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRole attribute), 253
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupRole attribute), 285
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Dashboard attribute), 255
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.DashboardGroup attribute), 256
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 287
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivile attribute), 255
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivile attribute), 287
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentSetPrivile attribute), 286
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ErrorList attribute), 266
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Filter attribute), 232
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.FilterList attribute), 265
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Group attribute), 233
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.GroupList attribute), 265

API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.HashedString attribute), 259
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.HashedStringList attribute), 291
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.IdReference attribute), 232
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ImportConflictOptions attribute), 282
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnector attribute), 259
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnectorList attribute), 290
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.MergedResultSet attribute), 219
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.MetadataItem attribute), 231
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.MetadataList attribute), 264
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ObjectList attribute), 250
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Options attribute), 251
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageFile attribute), 236
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageFileList attribute), 268
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatus attribute), 236
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatusList attribute), 268
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplate attribute), 235
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplateList attribute), 267
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageSpec attribute), 237
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PackageSpecList attribute), 269
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Parameter attribute), 244
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParameterList attribute), 276
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParameterValueList attribute), 276
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParseJob attribute), 244
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParseJobList attribute), 274
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParseResult attribute), 245
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroup attribute), 246
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroupList attribute), 275
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ParseResultList attribute), 275
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PermissionList attribute), 271
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Plugin attribute), 248
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginArgument attribute), 247
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginArgumentList attribute), 277
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginCommandList attribute), 279
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginList attribute), 280
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginSchedule attribute), 249
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginScheduleList attribute), 280

API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginSql attribute), 279
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginSqlColumnList attribute), 278
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.PluginSqlResultList attribute), 278
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Question attribute), 235
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.QuestionList attribute), 267
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.QuestionListInfo attribute), 235
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ResultInfo attribute), 218
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList attribute), 218
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.ResultSetList attribute), 219
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 223
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 225
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.RowColumnList attribute), 224
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.RowList attribute), 223
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 226
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedAction attribute), 229
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedActionApproval attribute), 229
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedActionApprovalList attribute), 262
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedActionList attribute), 263
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicy attribute), 228
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedActionRowIdList attribute), 262
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedQuestion attribute), 243
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionList attribute), 274
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionPackageSpe attribute), 258
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestion attribute), 258
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestionLis attribute), 289
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Select attribute), 233
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SelectList attribute), 266
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Sensor attribute), 230
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorList attribute), 261
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorQueryList attribute), 259
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 245
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorReferenceList attribute), 277
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorStat attribute), 228
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorStatList attribute), 261

API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumn attribute), 227
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumnList attribute), 260
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 238
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SolutionList attribute), 288
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.StringHintList attribute), 260
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SystemSetting attribute), 238
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SystemSettingList attribute), 270
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAggregate attribute), 240
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.SystemStatusList attribute), 270
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 247
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 279
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObjectIds attribute), 241
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.UserRoleList attribute), 272
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.VersionAggregate attribute), 239
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.VersionAggregateList attribute), 270
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrl attribute), 239
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrlList attribute), 269
API_NAME_SRC (pytan3.api_objects.soap_7_2_314_3181.XmlError attribute), 234
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Action attribute), 317
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ActionGroup attribute), 333
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ActionGroupList attribute), 369
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ActionList attribute), 353
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ActionListInfo attribute), 317
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ActionStop attribute), 318
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ActionStopList attribute), 353
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestion attribute), 318
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestionList attribute), 354
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.AuditData attribute), 305
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.AuditDataList attribute), 342

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.AuditLog attribute), 305
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.AuditLogList attribute), 343
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.CacheFilter attribute), 327
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.CacheFilterList attribute), 363
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.CacheInfo attribute), 309
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ClientCount attribute), 321
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ClientStatus attribute), 313
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ColumnList attribute), 295
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ComputerGroup attribute), 325
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupList attribute), 362
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupSpec attribute), 324
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ComputerIdList attribute), 374
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ComputerSpecList attribute), 361
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSet attribute), 328
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetList attribute), 364
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilege attribute), 330
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilegeList attribute), 366
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRole attribute), 328
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleList attribute), 365
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMembershi attribute), 329
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMembershi attribute), 365
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilege attribute), 330
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeLi attribute), 367
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeOr attribute), 328
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeOr attribute), 364
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupRole attribute), 329
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupRole attribute), 366
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Dashboard attribute), 331
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.DashboardList attribute), 368
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivile attribute), 331
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivile attribute), 368
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSetPrivile attribute), 367
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ErrorList attribute), 347
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Filter attribute), 307

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.FilterList attribute), 346
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.GroupList attribute), 345
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 338
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.HashedStringList attribute), 374
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.IdReference attribute), 307
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetail attribute), 326
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDetailList attribute), 362
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ImportConflictOptions attribute), 363
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnector attribute), 335
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnectorList attribute), 370
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.MergedResultSet attribute), 294
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 306
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.MetadataList attribute), 345
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Options attribute), 327
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageFileList attribute), 348
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatus attribute), 311
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatusList attribute), 348
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplate attribute), 311
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplateList attribute), 347
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageSpec attribute), 312
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PackageSpecList attribute), 349
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Parameter attribute), 320
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParameterList attribute), 356
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParameterValueList attribute), 357
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParseJob attribute), 319
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParseJobList attribute), 355
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParseResult attribute), 320
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroup attribute), 321
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroupList attribute), 355
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ParseResultList attribute), 356
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PermissionList attribute), 352
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Plugin attribute), 323
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginArgument attribute), 322

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginArgumentList attribute), 357
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginCommandList attribute), 359
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginList attribute), 360
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule attribute), 324
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginScheduleList attribute), 361
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginSql attribute), 359
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginSqlColumnList attribute), 358
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.PluginSqlResultList attribute), 358
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Question attribute), 310
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.QuestionList attribute), 347
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.QuestionListInfo attribute), 310
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ResultInfo attribute), 293
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList attribute), 292
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 294
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ResultSetList attribute), 293
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.RowColumnList attribute), 299
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.RowList attribute), 297
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedAction attribute), 304
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedActionApproval attribute), 303
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedActionApprovalList attribute), 341
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedActionList attribute), 342
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedActionPolicy attribute), 303
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedActionRowIdList attribute), 341
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion attribute), 319
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionList attribute), 354
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionPackageSpe attribute), 334
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestion attribute), 334
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestionLis attribute), 370
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Select attribute), 308
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SelectList attribute), 346
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Sensor attribute), 304
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorList attribute), 340
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorQuery attribute), 302

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorQueryList attribute), 338
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorReference attribute), 321
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorReferenceList attribute), 357
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorStat attribute), 303
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorStatList attribute), 340
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorSubcolumn attribute), 302
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SensorSubcolumnList attribute), 339
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Server attribute), 306
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ServerHost attribute), 344
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ServerHostList attribute), 344
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ServerList attribute), 343
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ServerThrottle attribute), 335
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleList attribute), 371
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleStatus attribute), 337
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleStatusList attribute), 372
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottle attribute), 336
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleList attribute), 371
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatus attribute), 337
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatusList attribute), 373
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnet attribute), 336
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetList attribute), 372
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatus attribute), 337
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatusLi attribute), 373
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SoapError attribute), 313
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.Solution attribute), 333
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SolutionList attribute), 369
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.StringHintList attribute), 339
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SystemSetting attribute), 313
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SystemSettingList attribute), 351
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SystemStatusAggregate attribute), 315
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.SystemStatusList attribute), 350
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UploadFile attribute), 322
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UploadFileList attribute), 360
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UploadFileStatus attribute), 323
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.User attribute), 316
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UserGroup attribute), 332

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UserGroupList attribute), 368
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UserList attribute), 351
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObjectIds attribute), 316
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UserRole attribute), 315
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.UserRoleList attribute), 352
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.VerifySignature attribute), 325
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.VersionAggregate attribute), 314
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.VersionAggregateList attribute), 350
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrl attribute), 314
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrlList attribute), 349
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3424.XmlError attribute), 309
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Action attribute), 401
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ActionGroup attribute), 417
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ActionGroupList attribute), 453
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ActionList attribute), 436
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ActionListInfo attribute), 400
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ActionStop attribute), 401
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ActionStopList attribute), 437
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestion attribute), 402
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ArchivedQuestionList attribute), 437
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.AuditData attribute), 389
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.AuditDataList attribute), 426
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.AuditLog attribute), 389
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.AuditLogList attribute), 426
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.CacheFilter attribute), 410
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.CacheFilterList attribute), 446
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.CacheInfo attribute), 393
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ClientCount attribute), 405
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ClientStatus attribute), 396
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ColumnList attribute), 379
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup attribute), 408
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupList attribute), 445
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupSpec attribute), 408
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ComputerIdList attribute), 457
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ComputerSpecList attribute), 445

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSet attribute), 411
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetList attribute), 447
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilege attribute), 414
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilegeList attribute), 450
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRole attribute), 412
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleList attribute), 448
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMembership attribute), 413
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMembershipList attribute), 449
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilege attribute), 414
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeList attribute), 450
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeOnRole attribute), 412
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeOnRoleObject attribute), 448
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGroupMembership attribute), 413
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGroupMembershipList attribute), 449
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Dashboard attribute), 415
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.DashboardGroup attribute), 415
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.DashboardList attribute), 452
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivilege attribute), 415
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivilegeList attribute), 451
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetPrivilegeOnRole attribute), 451
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ErrorList attribute), 430
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Filter attribute), 391
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.FilterList attribute), 429
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Group attribute), 392
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.GroupList attribute), 429
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.HashedString attribute), 422
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.HashedStringList attribute), 458
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.IdReference attribute), 391
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ImportConflictDetail attribute), 410
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ImportConflictDetailList attribute), 446
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ImportConflictOptions attribute), 447
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConnector attribute), 418
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConnectorList attribute), 454
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.MergedResultSet attribute), 378
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.MetadataItem attribute), 390
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.MetadataList attribute), 428

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ObjectList attribute), 409
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Options attribute), 411
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageFile attribute), 395
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageFileList attribute), 432
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatus attribute), 395
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatusList attribute), 432
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplate attribute), 394
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplateList attribute), 431
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageSpec attribute), 396
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PackageSpecList attribute), 433
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Parameter attribute), 403
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParameterList attribute), 440
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParameterValueList attribute), 440
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParseJob attribute), 403
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParseJobList attribute), 438
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParseResult attribute), 404
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroup attribute), 405
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroupList attribute), 439
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ParseResultList attribute), 439
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PermissionList attribute), 435
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Plugin attribute), 407
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginArgument attribute), 406
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginArgumentList attribute), 441
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginCommandList attribute), 443
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginList attribute), 444
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginSchedule attribute), 407
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginScheduleList attribute), 444
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginSql attribute), 443
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginSqlColumnList attribute), 442
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.PluginSqlResultList attribute), 442
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Question attribute), 394
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.QuestionList attribute), 431
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.QuestionListInfo attribute), 393
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ResultInfo attribute), 377
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList attribute), 376
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 378

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ResultSetList attribute), 377
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 381
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.RowColumnList attribute), 383
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.RowList attribute), 381
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 388
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedActionApproval attribute), 387
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedActionApprovalList attribute), 424
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedActionList attribute), 425
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicy attribute), 387
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedActionRowIdList attribute), 425
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion attribute), 402
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionList attribute), 438
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionPackageSpec attribute), 417
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestion attribute), 418
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestionList attribute), 454
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Select attribute), 392
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SelectList attribute), 430
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Sensor attribute), 388
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorList attribute), 423
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorQuery attribute), 385
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorQueryList attribute), 422
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorReference attribute), 404
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorReferenceList attribute), 441
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorStat attribute), 386
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorStatList attribute), 424
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumn attribute), 386
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SensorSubcolumnList attribute), 423
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 427
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ServerThrottle attribute), 419
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleList attribute), 455
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatus attribute), 420

API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatusList attribute), 456
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottle attribute), 419
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatus attribute), 421
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatusList attribute), 457
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnet attribute), 420
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetList attribute), 456
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStatus attribute), 421
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetStatusList attribute), 457
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 416
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SystemSettingList attribute), 434
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SystemStatus attribute), 399
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.SystemStatusList attribute), 434
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 443
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.User attribute), 400
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UserOwnedObjectIds attribute), 399
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.VerifySignature attribute), 409
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.VersionAggregate attribute), 398
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.VersionAggregateList attribute), 434
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrl attribute), 398
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrlList attribute), 433
API_NAME_SRC (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 392
api_objects (pytan3.adapters.Adapter attribute), 473
api_objects (pytan3.adapters.Rest attribute), 481
api_objects (pytan3.adapters.Soap attribute), 476
api_objects (pytan3.results.CommonMixin attribute), 493
api_objects() (pytan3.results.Result method), 490
api_parse_question() (pytan3.adapters.Adapter method), 475
api_parse_question() (pytan3.adapters.Rest method), 483
api_parse_question() (pytan3.adapters.Soap method), 479

API_SIMPLE (pytan3.api_models.ApiModel attribute), 459
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Action attribute), 75
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ActionGroup attribute), 91
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ActionGroupList attribute), 127
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ActionList attribute), 110
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ActionMenu attribute), 74
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ActionStep attribute), 75
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ActionStepList attribute), 111
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ArchiveQuestion attribute), 76
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ArchiveQuestionList attribute), 111
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.AuditAct attribute), 62
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.AuditActList attribute), 100
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.AuditObj attribute), 63
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.AuditObjList attribute), 100
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.CacheFilter attribute), 84
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.CacheFilterList attribute), 120
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.CacheInfo attribute), 67
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ClientCount attribute), 79
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ClientStatus attribute), 70
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 53
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ColumnList attribute), 53
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ComputerSimple attribute), 82
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ComputerSimpleList attribute), 119
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ComputerSimpleSpec attribute), 82
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ComputerSpec attribute), 131
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ComputerSpecList attribute), 119
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSet attribute), 85
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetList attribute), 121
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilege attribute), 87
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilegeList attribute), 124
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRole attribute), 86
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleList attribute), 122
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMember attribute), 86
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMemberList attribute), 123
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilege attribute), 88
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeList attribute), 124
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeMap attribute), 85
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeMapList attribute), 122
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroup attribute), 87
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupList attribute), 123
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 126
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSet attribute), 88
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetMap attribute), 125
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetMapList attribute), 125
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Filter attribute), 64
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.FilterList attribute), 103
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Group attribute), 65
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.GroupList attribute), 102
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.HashedString attribute), 95
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.HashedStringList attribute), 132
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.IdReference attribute), 65

API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ImportJobSimpleDetail attribute), 83
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ImportJobSimpleDetailList attribute), 120
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ImportJobSimpleInfo attribute), 121
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.LdapSyncSimpleInfo attribute), 92
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.LdapSyncSimpleInfoList attribute), 128
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.MergeRuleSet attribute), 51
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.MetaAttribute attribute), 64
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.MetaAttributeList attribute), 102
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ObjectIdList attribute), 83
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.OptionSet attribute), 84
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageFileSet attribute), 69
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageFileSetList attribute), 106
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatus attribute), 68
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageFileStatusList attribute), 105
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate attribute), 68
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplateList attribute), 105
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageSpec attribute), 69
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PackageSpecList attribute), 106
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParameterSet attribute), 77
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParameterSetList attribute), 113
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParameterSetTemplate attribute), 114
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseAction attribute), 76
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseActionList attribute), 112
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResult attribute), 59
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionResultList attribute), 58
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseResult attribute), 77
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup attribute), 78
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroupList attribute), 113
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ParseResultList attribute), 113
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PermissionList attribute), 109
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Plugin attribute), 81
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginArgument attribute), 79
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginArgumentList attribute), 115
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginCommandList attribute), 117
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginList attribute), 118
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginSchedule attribute), 81
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginScheduleList attribute), 118
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginSql attribute), 116
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginSqlColumnList attribute), 116
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.PluginSqlResultList attribute), 115
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Question attribute), 67
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.QuestionList attribute), 104
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.QuestionListInfo attribute), 67
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ResultInfo attribute), 50
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ResultInfoList attribute), 50
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ResultSet attribute), 52
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ResultSetList attribute), 51
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.RowColumnList attribute), 56
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.RowList attribute), 54
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 57
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 61
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SavedActionApprov attribute), 61

API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveActionApprovalList attribute), 98
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveActionMap attribute), 99
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveActionPolicy attribute), 60
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveActionPolicyList attribute), 99
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveQuestion attribute), 76
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveQuestionList attribute), 112
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveQuestionPackageSpecs attribute), 91
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveQuestionQuery attribute), 92
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SaveQuestionQueryList attribute), 127
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SelectAll attribute), 66
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SelectAllList attribute), 103
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Sensor attribute), 62
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorList attribute), 97
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorQuery attribute), 59
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorQueryList attribute), 96
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorResult attribute), 78
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorResultList attribute), 114
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorStat attribute), 60
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorStatList attribute), 98
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumn attribute), 59
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SensorSubcolumnList attribute), 96
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 63
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ServerPost attribute), 101
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ServerPostList attribute), 102
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ServerList attribute), 101
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ServerThrottle attribute), 92
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleList attribute), 128
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatus attribute), 94
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatusList attribute), 130
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottle attribute), 93
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleList attribute), 129
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 94
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatusList attribute), 130
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnet attribute), 93
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetList attribute), 129
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatus attribute), 95
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatusList attribute), 131
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SoapError attribute), 71
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.Solution attribute), 90
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 126
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 70
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAggregate attribute), 72
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus attribute), 80
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UserOwnedObjectIdentifier attribute), 73
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73

API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 110
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.VerifySignature attribute), 83
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.VersionAggregate attribute), 72
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.VersionAggregateList attribute), 107
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.WhitelistSettings attribute), 71
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.WhitelistSettingsList attribute), 107
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3424.XmlError attribute), 66
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ActionGroupList attribute), 211
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ActionList attribute), 194
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ActionMap attribute), 158
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ActionStep attribute), 159
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ActionStepList attribute), 195
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ArchiveQuestion attribute), 160
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ArchiveQuestionList attribute), 195
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.AuditData attribute), 147
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.AuditDataList attribute), 184
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.AuditLog attribute), 147
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.AuditLogList attribute), 184
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.CacheFilter attribute), 168
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.CacheFilterList attribute), 204
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.CacheInfo attribute), 151
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ClientCount attribute), 163
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ClientStatus attribute), 154
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 138
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ColumnList attribute), 137
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup attribute), 166
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupList attribute), 203
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupSpec attribute), 166
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ComputerIdList attribute), 215
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ComputerSpecList attribute), 203
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSet attribute), 169
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetList attribute), 205
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilege attribute), 171
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivilegeL attribute), 208
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole attribute), 170
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleList attribute), 206
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMem attribute), 170
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleMem attribute), 207
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivi attribute), 172
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivi attribute), 208
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivi attribute), 170
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePrivi attribute), 206
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGrou attribute), 171
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserGrou attribute), 207
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Dashboard attribute), 173
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.DashboardGroup attribute), 173
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.DashboardList attribute), 210
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSet attribute), 172
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSet attribute), 209
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSet attribute), 209
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ErrorList attribute), 188
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Filter attribute), 149

API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.FilterList attribute), 187
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Group attribute), 149
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.GroupList attribute), 187
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.HashedString attribute), 180
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.HashedStringList attribute), 216
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.IdReference attribute), 149
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ImportConfDetail attribute), 168
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ImportConfDetailList attribute), 204
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ImportConfOpt attribute), 205
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnection attribute), 176
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnectionList attribute), 212
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.MergeResultSet attribute), 136
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.MetaAttribute attribute), 148
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.MetaAttributeList attribute), 186
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ObjectList attribute), 167
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.OptionS attribute), 169
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageFile attribute), 153
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageFileList attribute), 190
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatus attribute), 153
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageFileStatusList attribute), 190
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplate attribute), 152
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplateList attribute), 189
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageSpec attribute), 154
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PackageSpecList attribute), 191
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Parameter attribute), 161
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParameterSimple attribute), 198
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParameterSimpleList attribute), 198
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseJob attribute), 161
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseJobList attribute), 196
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResul attribute), 143
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResul attribute), 142
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseResult attribute), 162
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup attribute), 163
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroupLi attribute), 197
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ParseResultList attribute), 197
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PermissionList attribute), 193
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Plugin attribute), 165
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginArgument attribute), 163
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginArgumentList attribute), 199
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginCommandLis attribute), 201
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginList attribute), 202
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule attribute), 165
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginScheduleList attribute), 202
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginSql attribute), 200
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginSqlColumnLi attribute), 200
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.PluginSqlResultList attribute), 200
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Question attribute), 152
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 189
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.QuestionListInfo attribute), 151
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 134
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139

API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.RowCollection attribute), 141
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.RowCollectionList attribute), 140
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.RowList attribute), 138
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveAction attribute), 146
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveActionApprovalEvent attribute), 145
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveActionApprovalList attribute), 182
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveActionList attribute), 183
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveActionPolicy attribute), 145
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveActionPolicyList attribute), 183
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveQuestion attribute), 160
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveQuestionList attribute), 196
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveQuestionMacExpanse attribute), 175
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveQuestionQuestion attribute), 176
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SaveQuestionQuestionList attribute), 212
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SelectAction attribute), 150
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SelectActionList attribute), 188
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Sensor attribute), 146
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorList attribute), 181
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 143
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorQueryList attribute), 180
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorReference attribute), 162
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorReferenceList attribute), 199
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorStat attribute), 144
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorStatList attribute), 182
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorSubmitted attribute), 144
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SensorSubmittedList attribute), 180
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 148
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ServerHost attribute), 185
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ServerHostList attribute), 186
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ServerList attribute), 185
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ServerThrottle attribute), 177
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleList attribute), 213
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 178
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 214
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle attribute), 177
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleList attribute), 213
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatus attribute), 179
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatusLi attribute), 214
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnet attribute), 178
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetL attribute), 213
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetS attribute), 179
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetS attribute), 215
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SoapError attribute), 155
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.Solution attribute), 174
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SolutionList attribute), 211
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.StringHintList attribute), 181
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SystemSetting attribute), 155
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SystemSettingList attribute), 192
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SystemStatusAggreg attribute), 156
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.SystemStatusList attribute), 192
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UploadFile attribute), 164
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UploadFileList attribute), 201
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus attribute), 164

API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UserGroup attribute), 174
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UserGroupList attribute), 210
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UserList attribute), 193
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UserOwnedObjectIds attribute), 157
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UserRole attribute), 157
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.UserRoleList attribute), 194
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.VerifyAgainst attribute), 167
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.VersionAggregate attribute), 156
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.VersionAggregateList attribute), 191
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.WhitelistItem attribute), 156
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.WhitelistItemList attribute), 191
API_SIMPLE (pytan3.api_objects.rest_7_3_314_3641.XmlError attribute), 150
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Action attribute), 242
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ActionGroup attribute), 257
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ActionGroupList attribute), 289
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ActionList attribute), 272
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ActionListItem attribute), 242
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ActionStep attribute), 243
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ActionStepList attribute), 273
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestion attribute), 243
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestionList attribute), 273
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.AuditData attribute), 230
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 263
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.CacheFilter attribute), 251
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.CacheFilterList attribute), 282
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 234
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ClientCount attribute), 246
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 237
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 221
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupList attribute), 281
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupSpec attribute), 249
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ComputerIdList attribute), 290
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ComputerSpecList attribute), 281
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 251
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilege attribute), 254
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivilegeList attribute), 285
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 252
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleList attribute), 284
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMember attribute), 253
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleMemberList attribute), 284
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilege attribute), 254
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeList attribute), 286
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeList attribute), 252
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetRolePrivilegeList attribute), 283
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroup attribute), 253
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ContentSetUserGroupList attribute), 285
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Dashboard attribute), 255
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.DashboardGroup attribute), 256

API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.DashboardList attribute), 287
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.EffectiveContents attribute), 255
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentsList attribute), 287
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.EffectiveContentsObject attribute), 286
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ErrorList attribute), 266
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Filter attribute), 232
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.FilterList attribute), 265
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Group attribute), 233
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.GroupList attribute), 265
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.HashedSing attribute), 259
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.HashedSingList attribute), 291
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.IdReference attribute), 232
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ImportCommandOptions attribute), 282
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnection attribute), 259
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.LdapSyncConnectionList attribute), 290
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.MergedResultSet attribute), 219
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.MetadataItem attribute), 231
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.MetadataList attribute), 264
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ObjectList attribute), 250
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.OptionS attribute), 251
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageFile attribute), 236
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageFileList attribute), 268
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatus attribute), 236
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatusList attribute), 268
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplate attribute), 235
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemplateList attribute), 267
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageSpec attribute), 237
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PackageSpecList attribute), 269
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Parameter attribute), 244
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParameterList attribute), 276
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParameterValueList attribute), 276
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParseJob attribute), 244
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParseJobList attribute), 274
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParseResult attribute), 245
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroup attribute), 246
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParseResultGroupL attribute), 275
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ParseResultList attribute), 275
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PermissionList attribute), 271
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Plugin attribute), 248
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginArgument attribute), 247
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginArgumentLis attribute), 277
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginCommandLi attribute), 279
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginList attribute), 280
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginSchedule attribute), 249
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginScheduleList attribute), 280
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginSql attribute), 279
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginSqlColumnL attribute), 278
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.PluginSqlResultLis attribute), 278
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Question attribute), 235
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.QuestionList attribute), 267
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.QuestionListInfo attribute), 235
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ResultInfo attribute), 218
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList attribute), 218
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220

API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 219
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 223
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.RowCount attribute), 226
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.RowFilter attribute), 224
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.RowList attribute), 223
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 226
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedAction attribute), 229
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedActionApproval attribute), 229
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedActionApprovalList attribute), 262
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedActionList attribute), 263
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicy attribute), 228
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedActionRowFilter attribute), 262
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedQuestion attribute), 244
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionList attribute), 274
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionPerms attribute), 258
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestion attribute), 258
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestionList attribute), 289
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Select attribute), 233
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SelectList attribute), 266
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Sensor attribute), 230
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorList attribute), 261
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorQueryList attribute), 260
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 245
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorReferenceList attribute), 277
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorStat attribute), 228
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorStatList attribute), 261
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumn attribute), 228
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumnList attribute), 260
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 238
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SolutionList attribute), 288
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.StringHintList attribute), 260
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SystemSetting attribute), 238
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SystemSettingList attribute), 271
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAggregate attribute), 240
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.SystemStatusList attribute), 270
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 247
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 279
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObjectID attribute), 241
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.UserRoleList attribute), 272
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.VersionAggregate attribute), 239
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.VersionAggregateList attribute), 270
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrl attribute), 239
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.WhiteListedUrlList attribute), 269
API_SIMPLE (pytan3.api_objects.soap_7_2_314_3181.XmlError attribute), 234
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Action attribute), 317
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ActionGroup attribute), 333

API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ActionGroup attribute), 369
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ActionList attribute), 353
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ActionListMap attribute), 317
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ActionStep attribute), 318
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ActionStepList attribute), 353
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestion attribute), 318
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ArchivedQuestionList attribute), 354
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.AuditData attribute), 305
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.AuditDataList attribute), 342
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.AuditLog attribute), 305
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.AuditLogList attribute), 343
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.CacheFilter attribute), 327
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.CacheFilterList attribute), 363
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.CacheInfo attribute), 309
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ClientConn attribute), 322
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ClientStatus attribute), 313
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ColumnList attribute), 295
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ComputerGroup attribute), 325
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupList attribute), 362
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ComputerGroupSpec attribute), 324
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ComputerList attribute), 374
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ComputerSpecList attribute), 361
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ConnInfo attribute), 328
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ConnInfoList attribute), 364
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ConnInfoPrivilege attribute), 330
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ConnInfoPrivilegeList attribute), 366
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRole attribute), 329
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleList attribute), 365
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMe attribute), 329
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleMe attribute), 365
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePriv attribute), 330
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePriv attribute), 367
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePriv attribute), 328
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePriv attribute), 364
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGro attribute), 329
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGro attribute), 366
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Dashboard attribute), 331
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.DashboardList attribute), 368
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSe attribute), 331
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSe attribute), 368
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentSe attribute), 367
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ErrorList attribute), 347
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Filter attribute), 307
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.FilterList attribute), 346
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.GroupList attribute), 345
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 338
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.HashedStringList attribute), 374
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.IdReference attribute), 307
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDeta attribute), 326
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ImportConflictDeta attribute), 362
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ImportConflictOpti attribute), 363

API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnect attribute), 335
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.LdapSyncConnectList attribute), 370
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.MergeResultSet attribute), 294
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 306
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.MetadataList attribute), 345
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Options attribute), 327
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageFileList attribute), 348
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatus attribute), 311
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatusList attribute), 348
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageFileTmpFile attribute), 311
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageFileTmpFileList attribute), 348
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageSpec attribute), 312
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PackageSpecList attribute), 349
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Parameter attribute), 320
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParameterList attribute), 356
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParameterValueList attribute), 357
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParseJob attribute), 319
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParseJobList attribute), 355
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParseResult attribute), 320
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroup attribute), 321
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroupList attribute), 355
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ParseResultList attribute), 356
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PermissionList attribute), 352
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Plugin attribute), 323
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginArgument attribute), 322
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginArgumentList attribute), 358
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginCommandList attribute), 359
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginList attribute), 360
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule attribute), 324
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginScheduleList attribute), 361
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginSql attribute), 359
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginSqlColumnList attribute), 358
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.PluginSqlResultList attribute), 358
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Question attribute), 310
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.QuestionList attribute), 347
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.QuestionListInfo attribute), 310
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ResultInfo attribute), 293
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList attribute), 292
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 294
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ResultSetList attribute), 293
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.RowColumnList attribute), 299
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.RowList attribute), 297
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedAction attribute), 304
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedActionApprovalGroup attribute), 304
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedActionApprovalGroupList attribute), 341
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedActionList attribute), 342
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedActionPolicy attribute), 303
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedActionRowId attribute), 341
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion attribute), 319

API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionList attribute), 354
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionPacket attribute), 334
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion attribute), 334
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestion attribute), 370
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Select attribute), 308
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SelectList attribute), 346
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Sensor attribute), 304
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorList attribute), 340
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorQuery attribute), 302
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorQueryList attribute), 338
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorResult attribute), 321
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorResultList attribute), 357
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorTest attribute), 303
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorTestList attribute), 340
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorValidation attribute), 302
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SensorValidationList attribute), 339
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Server attribute), 306
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ServerHost attribute), 344
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ServerHostList attribute), 344
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ServerList attribute), 343
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ServerTaskHost attribute), 335
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ServerTaskHostList attribute), 371
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ServerTaskHostStatus attribute), 337
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.ServerTaskHostStatusList attribute), 372
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteHostle attribute), 336
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteHostleList attribute), 371
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteHostleStatus attribute), 337
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatusL attribute), 373
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnet attribute), 336
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetl attribute), 372
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetS attribute), 338
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetS attribute), 373
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SoapError attribute), 314
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.Solution attribute), 333
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SolutionList attribute), 369
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.StringHintList attribute), 339
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SystemSetting attribute), 313
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SystemSettingList attribute), 351
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SystemStatusAggre attribute), 315
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.SystemStatusList attribute), 350
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UploadFile attribute), 322
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UploadFileList attribute), 360
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UploadFileStatus attribute), 323
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.User attribute), 316
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UserGroup attribute), 332
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UserGroupList attribute), 369
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UserList attribute), 351
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObjectI attribute), 316
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UserRole attribute), 315
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.UserRoleList attribute), 352
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.VerifySignature attribute), 325
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.VersionAggregate attribute), 314
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.VersionAggregateL attribute), 350
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.WhiteListedUrl attribute), 314

API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.WhiteListSimple attribute), 349
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3424.XmlInfo attribute), 309
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Action attribute), 401
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ActionGroup attribute), 417
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ActionGroupList attribute), 453
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ActionList attribute), 436
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ActionSimple attribute), 400
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ActionStep attribute), 401
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ActionStepList attribute), 437
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ArchiveQuestion attribute), 402
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ArchiveQuestionList attribute), 437
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.AuditAsk attribute), 389
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.AuditAskList attribute), 426
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.AuditLog attribute), 389
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.AuditLogList attribute), 426
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.CacheFilter attribute), 410
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.CacheFilterList attribute), 446
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.CacheInfo attribute), 393
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ClientConn attribute), 405
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ClientStatus attribute), 396
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ColumnInfo attribute), 380
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ColumnInfoList attribute), 379
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup attribute), 408
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupList attribute), 445
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupSpec attribute), 408
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ComputerSpecList attribute), 458
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ComputerSpecs attribute), 445
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSet attribute), 411
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetList attribute), 447
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilege attribute), 414
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivilegeGroup attribute), 450
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRole attribute), 412
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleList attribute), 448
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMember attribute), 413
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleMemberGroup attribute), 449
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilege attribute), 414
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeGroup attribute), 450
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeList attribute), 412
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetRolePrivilegeListGroup attribute), 448
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGroup attribute), 413
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserGroupGroup attribute), 449
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Dashboard attribute), 415
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.DashboardGroup attribute), 416
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.DashboardList attribute), 452
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSet attribute), 415
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetList attribute), 451
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.EffectiveContentSetListGroup attribute), 451
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ErrorList attribute), 430
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Filter attribute), 391
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.FilterList attribute), 429
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Group attribute), 392
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.GroupList attribute), 429
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.HashedString attribute), 422
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.HashedStringList attribute), 458

API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.IdReference attribute), 391
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ImportCommandDetail attribute), 410
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ImportCommandDetailList attribute), 446
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ImportOptions attribute), 447
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConnection attribute), 418
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.LdapSyncConnectionList attribute), 454
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.MergedResultSet attribute), 378
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.MetadataItem attribute), 390
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.MetadataList attribute), 428
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ObjectList attribute), 409
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.OptionS attribute), 411
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageFile attribute), 395
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageFileList attribute), 432
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatus attribute), 395
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatusList attribute), 432
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplate attribute), 394
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplateList attribute), 431
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageSpec attribute), 396
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PackageSpecList attribute), 433
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Parameter attribute), 403
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParameterList attribute), 440
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParameterMultiList attribute), 440
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParseJob attribute), 403
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParseJobList attribute), 438
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParseResult attribute), 404
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroup attribute), 405
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParseResultGroupList attribute), 439
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ParseResultList attribute), 439
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PermissionDetail attribute), 435
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PermissionList attribute), 435
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Plugin attribute), 407
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginArgument attribute), 406
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginArgumentList attribute), 441
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginCommandList attribute), 443
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginList attribute), 444
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginSchedule attribute), 408
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginScheduleList attribute), 444
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginSql attribute), 443
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginSqlColumnList attribute), 442
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.PluginSqlResultList attribute), 442
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Question attribute), 394
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.QuestionList attribute), 431
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.QuestionListInfo attribute), 393
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ResultInfo attribute), 377
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList attribute), 376
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 378
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ResultSetList attribute), 377
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 382
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.RowColumnList attribute), 383
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.RowList attribute), 381
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 388
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedActionApproval attribute), 387
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedActionApprovalList attribute), 424

API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 425
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedActionList attribute), 425
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicy attribute), 387
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicyList attribute), 425
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion attribute), 402
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionList attribute), 438
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionFolder attribute), 417
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionFolderList attribute), 418
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuery attribute), 454
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SelectFilter attribute), 392
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SelectFilterList attribute), 430
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Sensor attribute), 388
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorList attribute), 424
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorQuery attribute), 385
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorQueryList attribute), 422
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorResult attribute), 404
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorResultList attribute), 441
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorStat attribute), 386
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorStatList attribute), 424
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorStatColumn attribute), 386
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SensorStatColumnList attribute), 423
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 427
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ServerThrottle attribute), 419
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleList attribute), 455
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatus attribute), 420
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleStatu attribute), 456
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottle attribute), 419
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatus attribute), 421
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatusL attribute), 457
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnet attribute), 420
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetl attribute), 456
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetS attribute), 421
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubnetS attribute), 457
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 416
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SystemSettingList attribute), 435
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SystemStatusAggre attribute), 399
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.SystemStatusList attribute), 434
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 443
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.User attribute), 400
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UserOwnedObjectI attribute), 400
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436

API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.VerifySignature attribute), 53
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.VersionAggregate attribute), 398
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.VersionAggregateList attribute), 434
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrl attribute), 398
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.WhiteListedUrlList attribute), 433
API_SIMPLE (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 393
API_STR (pytan3.api_models.ApiModel attribute), 459
API_STR_ADD (pytan3.api_models.ApiModel attribute), 459
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AcknowledgedAlert attribute), 75
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AcknowledgedAlertGroup attribute), 91
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AcknowledgedAlertGroupList attribute), 127
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AcknowledgedAlertList attribute), 110
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AcknowledgedAlertInfo attribute), 74
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AcknowledgedAlertStop attribute), 75
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AcknowledgedAlertStopList attribute), 111
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ArchiveQuestion attribute), 76
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ArchiveQuestionList attribute), 111
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AuditStatus attribute), 62
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AuditStatusList attribute), 100
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AuditLog attribute), 63
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.AuditLogList attribute), 100
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.CamelFilter attribute), 84
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.CamelFilterList attribute), 120
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.CamelInfo attribute), 67
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ClientStatus attribute), 79
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ClientStatusInfo attribute), 70
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.CommandInfo attribute), 54
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.CommandStatus attribute), 53
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ComputerGroup attribute), 82
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupList attribute), 119
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ComputerGroupSmart attribute), 82
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ComputerIdList attribute), 131
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ComputerSpecList attribute), 119
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSet attribute), 85
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetList attribute), 121
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilege attribute), 87
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetPrivilegeGroup attribute), 124
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRole attribute), 86
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleList attribute), 122
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMap attribute), 86
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRoleMapList attribute), 123
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilege attribute), 88
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeGroup attribute), 124
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeGroupList attribute), 85
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetRolePrivilegeList attribute), 122
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroup attribute), 87
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ContentSetUserGroupList attribute), 123
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Dashboard attribute), 89
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.DashboardGroup attribute), 89
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.DashboardList attribute), 126
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSet attribute), 88
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetGroup attribute), 125
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.EffectiveContentSetGroupList attribute), 125
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ErrorList attribute), 104
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Filter

attribute), 64
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.FileList
attribute), 103
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Group
attribute), 65
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.GroupList
attribute), 103
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.HashedString
attribute), 95
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.HashedStringList
attribute), 132
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.IdReference
attribute), 65
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ImportConfiguration
attribute), 84
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ImportConfigurationList
attribute), 120
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ImportConfigurationOption
attribute), 121
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.LoadSyncCommand
attribute), 92
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.LoadSyncCommandList
attribute), 128
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.MergeRestriction
attribute), 52
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.MetadataItem
attribute), 64
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.MetadataList
attribute), 102
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ObjectList
attribute), 83
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.OptionsSet
attribute), 85
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageFile
attribute), 69
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageFileList
attribute), 106
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageFileSaved
attribute), 69
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageFileSavedList
attribute), 106
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplate
attribute), 68
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageFileTemplateList
attribute), 105
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageSpec
attribute), 70
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PackageSpecList
attribute), 106
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParameterSet
attribute), 77
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParameterSetList
attribute), 114
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParameterValueList
attribute), 114
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseJob
attribute), 77
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseJobList
attribute), 112
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionRes
attribute), 59
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseQuestionRes
attribute), 58
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseResult
attribute), 78
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup
attribute), 79
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseResultGroup
attribute), 113
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ParseResultList
attribute), 113
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PermissionList
attribute), 109
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Plugin
attribute), 81
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginArgument
attribute), 79
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginArgumentL
attribute), 115
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginCommandL
attribute), 117
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginList
attribute), 118
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginSchedule
attribute), 81
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginScheduleLi
attribute), 118
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginSql
attribute), 116
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginSqlColumn
attribute), 116
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.PluginSqlResultL
attribute), 116
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Question
attribute), 68
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.QuestionList
attribute), 67
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.QuestionListInfo
attribute), 67
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ResultInfo
attribute), 50
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ResultInfoList
attribute), 50
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ResultSet
attribute), 52
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ResultSetList
attribute), 51
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Row

attribute), 55
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.RowCollection attribute), 57
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.RowCollectionList attribute), 56
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.RowList attribute), 54
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 58
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedAction attribute), 61
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedActionApproval attribute), 61
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedActionApprovalList attribute), 98
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedActionList attribute), 99
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolicy attribute), 61
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedActionPolicyList attribute), 99
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedQuestion attribute), 76
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionList attribute), 112
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPackage attribute), 91
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPackageList attribute), 92
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SavedQuestionPackageSubpackage attribute), 128
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchFilter attribute), 66
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchFilterList attribute), 104
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchOrder attribute), 62
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchOrderList attribute), 97
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchQuery attribute), 59
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchQueryList attribute), 96
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchSelectedCol attribute), 78
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchSelectedColList attribute), 115
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchStat attribute), 60
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchStatList attribute), 98
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchSubColumn attribute), 60
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SearchSubColumnList attribute), 96
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Server attribute), 63
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ServerHost attribute), 101
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ServerHostList attribute), 102
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ServerList attribute), 101
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ServerThrottle attribute), 93
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleList attribute), 129
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStat attribute), 94
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.ServerThrottleStatList attribute), 130
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottle attribute), 93
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleList attribute), 129
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatus attribute), 95
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleStatusList attribute), 130
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnet attribute), 94
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetList attribute), 129
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStat attribute), 95
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SiteThrottleSubnetStatList attribute), 131
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SoapError attribute), 71
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.Solution attribute), 90
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SolutionList attribute), 127
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.StringHintList attribute), 97
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SystemSetting attribute), 70
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SystemSettingList attribute), 108
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SystemStatusAggr attribute), 72
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.SystemStatusList attribute), 108
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UploadFile attribute), 80
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UploadFileList attribute), 117
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UploadFileStatus

attribute), 80
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.User attribute), 74
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UserGroup attribute), 90
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UserGroupList attribute), 126
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UserList attribute), 109
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UserObjects attribute), 73
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UserRole attribute), 73
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.UserRoleList attribute), 110
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.VersionInstance attribute), 83
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.VersionObjects attribute), 72
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.VersionObjectsList attribute), 107
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.WhitelistedURI attribute), 71
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.WhitelistedURIList attribute), 107
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3424.XmlErrors attribute), 66
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Action attribute), 159
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActionGroup attribute), 175
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActionGroupList attribute), 211
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActionList attribute), 194
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActionInfo attribute), 158
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActionStop attribute), 159
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActionStopList attribute), 195
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActiveQuestion attribute), 160
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ActiveQuestionList attribute), 195
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.AuditStr attribute), 147
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.AuditStrList attribute), 184
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.AuditLogStr attribute), 147
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.AuditLogStrList attribute), 184
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.CacheFilter attribute), 168
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.CacheFilterList attribute), 204
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.CacheInfo attribute), 151
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ClientCount attribute), 163
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ClientStatus attribute), 154
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 138
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ColumnList attribute), 137
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ComputerGroup attribute), 166
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupL attribute), 203
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ComputerGroupS attribute), 166
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ComputerIdList attribute), 216
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ComputerSpecLis attribute), 203
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSet attribute), 169
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetList attribute), 205
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivile attribute), 172
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetPrivile attribute), 208
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRole attribute), 170
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleLi attribute), 206
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleM attribute), 171
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRoleM attribute), 207
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePr attribute), 172
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePr attribute), 208
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePr attribute), 170
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetRolePr attribute), 206
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserG attribute), 171
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ContentSetUserG attribute), 207
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Dashboard attribute), 173
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.DashboardGroup

attribute), 173
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.DashboardList
attribute), 210
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSet
attribute), 173
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetList
attribute), 209
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.EffectiveContentSetRequest
attribute), 209
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ErrorList
attribute), 188
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.File
attribute), 149
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.FileList
attribute), 187
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Group
attribute), 150
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.GroupList
attribute), 187
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.HashedString
attribute), 180
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.HashedStringList
attribute), 216
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.IdReferenceSet
attribute), 149
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ImportConfiguration
attribute), 168
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ImportConfigurationList
attribute), 204
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ImportConfigurationOptions
attribute), 205
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnection
attribute), 176
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.LdapSyncConnectionList
attribute), 212
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.MergeRuleSet
attribute), 136
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.MetadataItem
attribute), 148
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.MetadataList
attribute), 186
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ObjectList
attribute), 167
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.OptionSet
attribute), 169
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageFile
attribute), 153
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageFileList
attribute), 190
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageFileSAD
attribute), 153
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageFileSADList
attribute), 190
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplate
attribute), 152
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageFileTemplateList
attribute), 189
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageSpec
attribute), 154
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PackageSpecList
attribute), 191
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Parameter
attribute), 161
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParameterList
attribute), 198
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParameterValueList
attribute), 198
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseJob
attribute), 161
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseJobList
attribute), 196
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResult
attribute), 143
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseQuestionResultList
attribute), 142
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseResult
attribute), 162
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroup
attribute), 163
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseResultGroupList
attribute), 197
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ParseResultList
attribute), 197
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PermissionList
attribute), 194
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Plugin
attribute), 165
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginArgument
attribute), 164
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginArgumentList
attribute), 199
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginCommandList
attribute), 201
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginList
attribute), 202
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginSchedule
attribute), 165
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginScheduleList
attribute), 202
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginSql
attribute), 201
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginSqlColumnList
attribute), 200
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.PluginSqlResultList
attribute), 200
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Question
attribute), 152
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.QuestionList

attribute), 189
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.QuestionList attribute), 151
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ResultInfo attribute), 135
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ResultInfoList attribute), 134
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ResultSet attribute), 136
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ResultSetList attribute), 135
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 139
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.RowColumnList attribute), 140
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.RowList attribute), 139
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedAction attribute), 146
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedActionApproval attribute), 145
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedActionApprovalList attribute), 182
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedActionList attribute), 183
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedActionPolicy attribute), 145
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedActionPolicyList attribute), 183
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedQuestion attribute), 160
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionList attribute), 196
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionPackageSpecs attribute), 175
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestion attribute), 176
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SavedQuestionQuestionList attribute), 212
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Sensor attribute), 150
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorList attribute), 188
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorQuery attribute), 146
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorQueryList attribute), 182
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorQueryRowFilter attribute), 143
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorQueryRowFilterList attribute), 180
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorReference attribute), 162
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorReferenceList attribute), 199
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorStat attribute), 144
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorStatList attribute), 182
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumn attribute), 144
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SensorSubcolumnList attribute), 181
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Server attribute), 148
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ServerHost attribute), 185
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ServerHostList attribute), 186
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ServerList attribute), 185
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ServerThrottle attribute), 177
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleList attribute), 213
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatus attribute), 178
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.ServerThrottleStatusList attribute), 214
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottle attribute), 177
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleList attribute), 213
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatus attribute), 179
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleStatusList attribute), 215
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnet attribute), 178
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetList attribute), 214
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetV3 attribute), 179
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SiteThrottleSubnetV3List attribute), 215
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SoapError attribute), 155
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.Solution attribute), 174
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SolutionList attribute), 211
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.StringHintList attribute), 181
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SystemSetting

attribute), 155
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SystemSettingsList attribute), 193
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SystemStatus attribute), 157
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.SystemStatusList attribute), 192
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UploadFile attribute), 164
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UploadFileList attribute), 201
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UploadFileStatus attribute), 165
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.User attribute), 158
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UserGroup attribute), 174
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UserGroupList attribute), 210
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UserList attribute), 193
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UserOwnerObjectIds attribute), 158
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UserRole attribute), 157
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.UserRoleList attribute), 194
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.VersionStatus attribute), 167
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.VersionStatusAggregate attribute), 156
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.VersionStatusAggregateList attribute), 192
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.WildcardSearchAll attribute), 156
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.WildcardSearchAllList attribute), 191
API_STR_ADD (pytan3.api_objects.rest_7_3_314_3641.XmlPrint attribute), 151
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminGroup attribute), 242
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminGroupPrivilege attribute), 257
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminGroupPrivilegeList attribute), 289
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminGroupList attribute), 273
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminUserAdd attribute), 242
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminUserDelete attribute), 243
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminUserList attribute), 273
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AdminUserQuestion attribute), 243
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ArchivedQuestion attribute), 273
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AuditAggregate attribute), 230
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AuditDataList attribute), 263
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AuditLog attribute), 231
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.AuditLogList attribute), 264
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.CacheFilter attribute), 251
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.CacheFilterList attribute), 282
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.CacheInfo attribute), 234
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ClientCount attribute), 247
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ClientStatus attribute), 238
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ComputerGroup attribute), 250
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupI attribute), 282
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ComputerGroupS attribute), 249
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ComputerIdList attribute), 290
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ComputerSpecLi attribute), 281
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSet attribute), 252
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetList attribute), 283
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivile attribute), 254
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetPrivile attribute), 285
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetRole attribute), 253
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleL attribute), 284
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleM attribute), 253
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleM attribute), 284
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleP attribute), 254
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ContentSetRoleP

attribute), 286
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.CaptureSetAuditRecord
attribute), 252
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.CaptureSetAuditRecordList
attribute), 283
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.CaptureSetUserGroupMembership
attribute), 254
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.CaptureSetUserGroupMembershipList
attribute), 285
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.DashboardTab
attribute), 255
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.DashboardTabGroup
attribute), 256
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.DashboardTabList
attribute), 287
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.EffectiveRoleDS
attribute), 255
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.EffectiveRoleDSList
attribute), 287
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.EffectiveRoleDSObject
attribute), 286
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.FactList
attribute), 266
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Filter
attribute), 232
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.FilterList
attribute), 265
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Group
attribute), 233
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.GroupList
attribute), 265
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.HashedString
attribute), 259
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.HashedStringList
attribute), 291
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.IdReference
attribute), 232
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ImportCollectionOptions
attribute), 282
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.LastSyncAndCount
attribute), 259
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.LastSyncAndCountList
attribute), 290
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.MergeSearchResult
attribute), 219
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.MetadataItem
attribute), 231
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.MetadataList
attribute), 264
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ObjectList
attribute), 250
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.OptionsSet
attribute), 251
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageFile
attribute), 237
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageFileList
attribute), 268
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatus
attribute), 236
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageFileStatusList
attribute), 268
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageFileTemp
attribute), 236
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageFileTempList
attribute), 267
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageSpec
attribute), 237
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PackageSpecList
attribute), 269
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Parameter
attribute), 245
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParameterList
attribute), 276
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParameterValueL
attribute), 276
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParseJob
attribute), 244
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParseJobList
attribute), 274
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParseResult
attribute), 245
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParseResultGrou
attribute), 246
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParseResultGrou
attribute), 275
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ParseResultList
attribute), 275
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PermissionList
attribute), 272
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Plugin
attribute), 248
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginArgument
attribute), 247
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginArgument
attribute), 277
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginCommand
attribute), 279
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginList
attribute), 280
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginSchedule
attribute), 249
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginScheduleL
attribute), 281
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginSql
attribute), 279
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginSqlColum
attribute), 278
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.PluginSqlResultI

API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.QuestionSet attribute), 278
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.QuestionSetList attribute), 235
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.QuestionSetInstance attribute), 267
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.QuestionSetInstanceInfo attribute), 235
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ResultInfo attribute), 218
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ResultInfoList attribute), 218
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.ResultSetList attribute), 219
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 223
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.RowCollection attribute), 226
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.RowCollectionInfo attribute), 224
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.RowList attribute), 223
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 227
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedAction attribute), 230
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedActionApproval attribute), 229
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedActionApprovalList attribute), 262
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedActionList attribute), 263
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicy attribute), 229
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedActionPolicyList attribute), 263
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedQuestion attribute), 244
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionList attribute), 274
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionPackageSpec attribute), 258
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestion attribute), 258
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SavedQuestionQuestionList attribute), 289
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Select attribute), 233
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SelectList attribute), 266
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Sensor attribute), 230
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorInstance attribute), 261
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorQuery attribute), 227
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorQueryList attribute), 260
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorReference attribute), 246
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorReferenceInfo attribute), 277
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorStat attribute), 228
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorStatList attribute), 262
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumn attribute), 228
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SensorSubcolumnList attribute), 260
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SoapError attribute), 238
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.Solution attribute), 257
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SolutionList attribute), 288
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.StringHintList attribute), 261
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SystemSetting attribute), 238
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SystemSettingList attribute), 271
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SystemStatusAggregate attribute), 240
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.SystemStatusList attribute), 270
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UploadFile attribute), 247
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UploadFileList attribute), 280
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UploadFileStatus attribute), 248
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.User attribute), 241
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UserGroup attribute), 256
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UserGroupList attribute), 288
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UserList attribute), 271
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UserOwnedObject attribute), 241
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UserRole attribute), 240
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.UserRoleList attribute), 272
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.VersionAggregate

attribute), 239
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.VariableAggregate attribute), 270
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.WhitelistedURL attribute), 239
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.WhitelistedURLs attribute), 269
API_STR_ADD (pytan3.api_objects.soap_7_2_314_3181.XmlStr attribute), 234
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminAccount attribute), 317
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminGroup attribute), 333
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminGroupList attribute), 370
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminStr attribute), 353
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminTask attribute), 317
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminTaskInstance attribute), 318
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminTaskList attribute), 353
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminTaskQuestion attribute), 318
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AdminTaskQuestionList attribute), 354
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AuditData attribute), 305
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AuditDataList attribute), 342
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AuditLogin attribute), 306
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.AuditLoginList attribute), 343
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.CacheFilter attribute), 327
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.CacheFilterList attribute), 363
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.CacheInfo attribute), 309
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.CacheStatus attribute), 322
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.CacheStatusInfo attribute), 313
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.CmdStr attribute), 296
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.CmdStrList attribute), 295
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ComplexGroup attribute), 325
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ComplexGroupList attribute), 362
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ComplexGroupSpec attribute), 324
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ComputerIdList attribute), 374
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ComputerSpecList attribute), 361
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSet attribute), 328
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetList attribute), 364
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilege attribute), 330
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetPrivilegeList attribute), 366
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRole attribute), 329
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleList attribute), 365
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleName attribute), 329
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleNameList attribute), 365
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilege attribute), 331
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRolePrivilegeList attribute), 367
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleRestriction attribute), 328
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetRoleRestrictionList attribute), 364
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroup attribute), 330
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ContentSetUserGroupList attribute), 366
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Dashboard attribute), 332
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.DashboardGroup attribute), 332
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.DashboardList attribute), 368
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.EffectiveContent attribute), 331
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentList attribute), 368
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.EffectiveContentStatus attribute), 367
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ErrorList attribute), 347
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Filter attribute), 307
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.FilterList attribute), 346
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Group attribute), 308
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.GroupList

API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.HashedString attribute), 345
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.HashedStringList attribute), 338
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.IdRef attribute), 374
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.IdRefStr attribute), 307
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ImportConfigDetail attribute), 326
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ImportConfigDetailList attribute), 362
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ImportConfigOptions attribute), 363
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.LastSyncCmdDetail attribute), 335
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.LastSyncCmdDetailList attribute), 371
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.MergeResultSet attribute), 294
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.MetadataItem attribute), 307
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.MetadataList attribute), 345
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ObjectList attribute), 326
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.OptionSet attribute), 327
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageFile attribute), 312
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageFileList attribute), 349
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatus attribute), 311
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageFileStatusList attribute), 348
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplate attribute), 311
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageFileTemplateList attribute), 348
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageSpec attribute), 312
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PackageSpecList attribute), 349
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Parameter attribute), 320
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParameterList attribute), 356
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParameterValueList attribute), 357
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParseJob attribute), 319
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParseJobList attribute), 355
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParseResult attribute), 320
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroup attribute), 321
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParseResultGroupList attribute), 355
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ParseResultList attribute), 356
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PermissionList attribute), 352
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Plugin attribute), 323
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginArgument attribute), 322
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginArgumentList attribute), 358
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginCommand attribute), 360
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginList attribute), 360
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginSchedule attribute), 324
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginScheduleList attribute), 361
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginSql attribute), 359
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginSqlColumn attribute), 359
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.PluginSqlResultInfo attribute), 358
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Question attribute), 310
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.QuestionList attribute), 347
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.QuestionListInfo attribute), 310
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ResultInfo attribute), 293
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ResultInfoList attribute), 292
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 294
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ResultSetList attribute), 294
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.RowColumnList attribute), 299
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.RowList attribute), 297
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedAction

attribute), 304
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedStrings attribute), 304
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedStringList attribute), 341
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedStringsList attribute), 342
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedStringRoot attribute), 303
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedStringRootList attribute), 341
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedQuestion attribute), 319
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionList attribute), 354
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionPackageSpec attribute), 334
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestion attribute), 334
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SavedQuestionQuestionList attribute), 370
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Sensor attribute), 308
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorList attribute), 346
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorString attribute), 305
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorStringList attribute), 340
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorQuery attribute), 302
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorQueryList attribute), 339
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorReference attribute), 321
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorReferenceList attribute), 357
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorStar attribute), 303
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorStarList attribute), 340
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorStringCount attribute), 302
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SensorStringCountList attribute), 339
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Server attribute), 306
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ServerHost attribute), 344
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ServerHostList attribute), 344
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ServerList attribute), 343
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ServerThrottle attribute), 335
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleApproval attribute), 371
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleApprovalList attribute), 337
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.ServerThrottleList attribute), 373
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottle attribute), 336
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleList attribute), 372
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatus attribute), 337
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleStatusList attribute), 373
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnet attribute), 336
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetList attribute), 372
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatus attribute), 338
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SiteThrottleSubnetStatusList attribute), 374
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SoapError attribute), 314
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.Solution attribute), 333
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SolutionList attribute), 369
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.StringHintList attribute), 340
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SystemSetting attribute), 313
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SystemSettingList attribute), 351
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SystemStatusAggr attribute), 315
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.SystemStatusList attribute), 351
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UploadFile attribute), 323
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UploadFileList attribute), 360
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UploadFileStatus attribute), 323
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.User attribute), 316
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UserGroup attribute), 332
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UserGroupList attribute), 369
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UserList attribute), 351
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UserOwnedObje

attribute), 316
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UserSet
attribute), 315
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.UserSetList
attribute), 352
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.VarPlyStrata
attribute), 325
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.VarIosStrata
attribute), 315
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.VarIosStrataList
attribute), 350
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.WhitelistedIP
attribute), 314
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.WhitelistedIPList
attribute), 350
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3424.XmlError
attribute), 309
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActionGroup
attribute), 401
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActionGroupList
attribute), 417
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActionList
attribute), 453
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActionStep
attribute), 437
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActionStepAction
attribute), 401
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActionStepList
attribute), 401
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActionStepQuestion
attribute), 437
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActivityQuestion
attribute), 402
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ActivityQuestionList
attribute), 437
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.AuditData
attribute), 389
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.AuditDataList
attribute), 426
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.AuditLogin
attribute), 389
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.AuditLoginList
attribute), 427
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.CacheFilter
attribute), 410
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.CacheFilterList
attribute), 446
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.CacheInfo
attribute), 393
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.CacheInfoCount
attribute), 405
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.CacheInfoStatus
attribute), 396
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.CalcMap
attribute), 380
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ColumnList
attribute), 379
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ComputerGroup
attribute), 409
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupI
attribute), 446
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ComputerGroupS
attribute), 408
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ComputerIdList
attribute), 458
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ComputerSpecLi
attribute), 445
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSet
attribute), 411
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetList
attribute), 447
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivil
attribute), 414
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetPrivil
attribute), 450
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRole
attribute), 412
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleL
attribute), 448
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleM
attribute), 413
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleM
attribute), 449
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleP
attribute), 414
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleP
attribute), 450
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleP
attribute), 412
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetRoleP
attribute), 448
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserG
attribute), 413
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ContentSetUserG
attribute), 449
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Dashboard
attribute), 415
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.DashboardGroup
attribute), 416
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.DashboardList
attribute), 452
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.EffectiveContent
attribute), 415
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.EffectiveContent
attribute), 451
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.EffectiveContent
attribute), 451
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ErrorList

attribute), 430
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.FilterSet
attribute), 391
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.FilterList
attribute), 429
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Group
attribute), 392
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.GroupList
attribute), 429
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.HashedString
attribute), 422
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.HashedStringList
attribute), 458
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.IdReference
attribute), 391
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ImportCollection
attribute), 410
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ImportCollectionList
attribute), 446
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ImportCollectionOptions
attribute), 447
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.LapiSyncCommand
attribute), 418
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.LapiSyncCommandList
attribute), 454
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.MergeResultSet
attribute), 378
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.MetadataItem
attribute), 390
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.MetadataList
attribute), 428
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ObjectList
attribute), 410
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.OptionSet
attribute), 411
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageFile
attribute), 395
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageFileList
attribute), 432
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatus
attribute), 395
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageFileStatusList
attribute), 432
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplate
attribute), 394
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageFileTemplateList
attribute), 431
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageSpec
attribute), 396
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PackageSpecList
attribute), 433
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParameterSet
attribute), 403
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParameterSetList
attribute), 440
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParameterValueL
attribute), 440
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParseJob
attribute), 403
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParseJobList
attribute), 438
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParseResult
attribute), 404
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParseResultGrou
attribute), 405
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParseResultGrou
attribute), 439
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ParseResultList
attribute), 439
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PermissionList
attribute), 436
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Plugin
attribute), 407
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginArgument
attribute), 406
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginArgumentL
attribute), 441
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginCommand
attribute), 443
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginList
attribute), 444
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginSchedule
attribute), 408
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginScheduleL
attribute), 445
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginSql
attribute), 443
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginSqlColum
attribute), 442
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.PluginSqlResultI
attribute), 442
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Question
attribute), 394
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.QuestionList
attribute), 431
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.QuestionListInfo
attribute), 394
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ResultInfo
attribute), 377
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ResultInfoList
attribute), 376
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ResultSet
attribute), 378
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ResultSetList
attribute), 377
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Row
attribute), 382
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.RowColumn

attribute), 384
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.RawCustomAdd attribute), 383
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.RawList attribute), 381
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.RawVariable attribute), 385
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedAction attribute), 388
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedActionApproval attribute), 387
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedActionApprovalList attribute), 425
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedActionList attribute), 426
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicy attribute), 387
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedActionPolicyList attribute), 425
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedQuestion attribute), 402
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionList attribute), 438
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionPackageSpecs attribute), 418
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestion attribute), 418
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SavedQuestionQuestionList attribute), 454
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Select attribute), 392
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SelectList attribute), 430
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Sensor attribute), 388
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorList attribute), 424
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorQuery attribute), 386
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorQueryList attribute), 422
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorReference attribute), 404
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorReferenceList attribute), 441
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorStar attribute), 387
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorStarList attribute), 424
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorStarCombin attribute), 386
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SensorStarCombinList attribute), 423
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Server attribute), 390
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ServerHost attribute), 427
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ServerHostList attribute), 428
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ServerList attribute), 427
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ServerThrottle attribute), 419
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleLi attribute), 455
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleSta attribute), 420
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.ServerThrottleSta attribute), 456
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottle attribute), 419
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleList attribute), 455
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatu attribute), 421
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleStatu attribute), 457
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 420
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 456
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 421
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SiteThrottleSubn attribute), 457
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SoapError attribute), 397
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.Solution attribute), 417
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SolutionList attribute), 453
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.StringHintList attribute), 423
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SystemSetting attribute), 397
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SystemSettingLi attribute), 435
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SystemStatusAgg attribute), 399
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.SystemStatusList attribute), 434
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UploadFile attribute), 406
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UploadFileList attribute), 444
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UploadFileStatus attribute), 407
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.User

attribute), 400
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UserGroup attribute), 416
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UserGroupList attribute), 452
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UserList attribute), 435
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UserModel attribute), 400
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UserRole attribute), 399
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.UserRoleList attribute), 436
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.VariableSignature attribute), 409
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.VersionAggregation attribute), 398
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.VersionAggregationList attribute), 434
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.WhitelistedURL attribute), 398
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.WhitelistedURLList attribute), 433
API_STR_ADD (pytan3.api_objects.soap_7_3_314_3641.XmlError attribute), 393
API_TYPES (in module pytan3.api_objects), 43
api_update() (pytan3.adapters.Adapter method), 474
api_update() (pytan3.adapters.Rest method), 483
api_update() (pytan3.adapters.Soap method), 478
ApiClient (class in pytan3.api_clients), 37
ApiItem (class in pytan3.api_models), 462
ApiItem (class in pytan3.api_objects.rest_7_3_314_3424), 49
ApiItem (class in pytan3.api_objects.rest_7_3_314_3641), 133
ApiItem (class in pytan3.api_objects.soap_7_2_314_3181), 217
ApiItem (class in pytan3.api_objects.soap_7_3_314_3424), 292
ApiItem (class in pytan3.api_objects.soap_7_3_314_3641), 376
ApiItem (pytan3.api_objects.ApiObjects attribute), 44
ApiList (class in pytan3.api_models), 463
ApiList (class in pytan3.api_objects.rest_7_3_314_3424), 49
ApiList (class in pytan3.api_objects.rest_7_3_314_3641), 133
ApiList (class in pytan3.api_objects.soap_7_2_314_3181), 217
ApiList (class in pytan3.api_objects.soap_7_3_314_3424), 292
ApiList (class in pytan3.api_objects.soap_7_3_314_3641), 376
ApiList (pytan3.api_objects.ApiObjects attribute), 44
ApiModel (class in pytan3.api_models), 459
ApiModel (class in pytan3.api_objects.rest_7_3_314_3424), 49
ApiModel (class in pytan3.api_objects.rest_7_3_314_3641), 133
ApiModel (class in pytan3.api_objects.soap_7_2_314_3181), 217
ApiModel (class in pytan3.api_objects.soap_7_3_314_3424), 292
ApiModel (class in pytan3.api_objects.soap_7_3_314_3641), 376
ApiModelList (pytan3.api_objects.ApiObjects attribute), 44
ApiObjects (class in pytan3.api_objects), 43
ApiSignatureRequestType, 501
append() (pytan3.api_models.ApiList method), 467
ArchivedQuestion (class in pytan3.api_objects.rest_7_3_314_3424), 75
ArchivedQuestionList (class in pytan3.api_objects.rest_7_3_314_3641), 160
ArchivedQuestion (class in pytan3.api_objects.soap_7_2_314_3181), 243
ArchivedQuestionList (class in pytan3.api_objects.soap_7_3_314_3424), 318
ArchivedQuestion (class in pytan3.api_objects.soap_7_3_314_3641), 402
ArchivedQuestionList (class in pytan3.api_objects.rest_7_3_314_3424), 111
ArchivedQuestionList (class in pytan3.api_objects.rest_7_3_314_3641), 195
ArchivedQuestionList (class in pytan3.api_objects.soap_7_2_314_3181), 273
ArchivedQuestionList (class in pytan3.api_objects.soap_7_3_314_3424), 354
ArchivedQuestionList (class in pytan3.api_objects.soap_7_3_314_3641), 437
ask_bool() (pytan3.utils.prompts.Promptness method), 512
ask_choice() (pytan3.utils.prompts.Promptness method), 512
ask_dict() (pytan3.utils.prompts.Promptness method), 513
ask_int() (pytan3.utils.prompts.Promptness method), 512
ask_str() (pytan3.utils.prompts.Promptness method), 513
attr (pytan3.api_models.exceptions.AttrTypeError attribute), 471
attr (pytan3.api_models.exceptions.AttrUndefinedError attribute), 470
attr (pytan3.api_models.exceptions.AttrUndefinedWarning attribute), 470
attr (pytan3.api_models.exceptions.GetSingleItemError attribute), 473
attr (pytan3.api_models.exceptions.ListItemTypeError attribute), 472
attr (pytan3.api_models.exceptions.ListTypeError at-

tribute), 471
AttrTypeError, 471
AttrUndefinedError, 470
AttrUndefinedWarning, 470
AUDIT_LOG_TYPES (pytan3.adapters.Rest attribute), 480
AUDIT_LOG_TYPES (pytan3.adapters.Soap attribute), 475
AuditData (class in pytan3.api_objects.rest_7_3_314_3424), 62
AuditData (class in pytan3.api_objects.rest_7_3_314_3641), 146
AuditData (class in pytan3.api_objects.soap_7_2_314_3181), 230
AuditData (class in pytan3.api_objects.soap_7_3_314_3424), 305
AuditData (class in pytan3.api_objects.soap_7_3_314_3641), 389
AuditDataList (class in pytan3.api_objects.rest_7_3_314_3424), 99
AuditDataList (class in pytan3.api_objects.rest_7_3_314_3641), 184
AuditDataList (class in pytan3.api_objects.soap_7_2_314_3181), 263
AuditDataList (class in pytan3.api_objects.soap_7_3_314_3424), 342
AuditDataList (class in pytan3.api_objects.soap_7_3_314_3641), 426
AuditLog (class in pytan3.api_objects.rest_7_3_314_3424), 63
AuditLog (class in pytan3.api_objects.rest_7_3_314_3641), 147
AuditLog (class in pytan3.api_objects.soap_7_2_314_3181), 231
AuditLog (class in pytan3.api_objects.soap_7_3_314_3424), 305
AuditLog (class in pytan3.api_objects.soap_7_3_314_3641), 389
AuditLogList (class in pytan3.api_objects.rest_7_3_314_3424), 100
AuditLogList (class in pytan3.api_objects.rest_7_3_314_3641), 184
AuditLogList (class in pytan3.api_objects.soap_7_2_314_3181), 264
AuditLogList (class in pytan3.api_objects.soap_7_3_314_3424), 343
AuditLogList (class in pytan3.api_objects.soap_7_3_314_3641), 426
auth_method (pytan3.adapters.Adapter attribute), 474
auth_method (pytan3.adapters.Rest attribute), 481
auth_method (pytan3.adapters.Soap attribute), 476
auth_method (pytan3.api_clients.ApiClient attribute), 37
auth_method (pytan3.api_clients.Rest attribute), 41
auth_method (pytan3.api_clients.Soap attribute), 39
AuthMethod (class in pytan3.auth_methods), 20
AuthStore (class in pytan3.auth_store), 32

B

b64_decode() (in module pytan3.utils.tools), 516
b64_encode() (in module pytan3.utils.tools), 516
be_type (pytan3.api_models.exceptions.AttrTypeError attribute), 471
be_type (pytan3.api_models.exceptions.ListItemTypeError attribute), 472
build_endpoint() (in module pytan3.adapters), 488
BUILD_META (in module pytan3.api_objects.rest_7_3_314_3424), 132
BUILD_META (in module pytan3.api_objects.rest_7_3_314_3641), 216
BUILD_META (in module pytan3.api_objects.soap_7_2_314_3181), 291
BUILD_META (in module pytan3.api_objects.soap_7_3_314_3424), 375
BUILD_META (in module pytan3.api_objects.soap_7_3_314_3641), 458
build_options_from_kwargs() (pytan3.adapters.Rest method), 482
build_options_from_kwargs() (pytan3.adapters.Soap method), 477
by_name (pytan3.results.RestUrlPath attribute), 500

C

CacheFilter (class in pytan3.api_objects.rest_7_3_314_3424), 84
CacheFilter (class in pytan3.api_objects.rest_7_3_314_3641), 168
CacheFilter (class in pytan3.api_objects.soap_7_2_314_3181), 250
CacheFilter (class in pytan3.api_objects.soap_7_3_314_3424), 326
CacheFilter (class in pytan3.api_objects.soap_7_3_314_3641), 410
CacheFilterList (class in pytan3.api_objects.rest_7_3_314_3424), 120
CacheFilterList (class in pytan3.api_objects.rest_7_3_314_3641), 204
CacheFilterList (class in pytan3.api_objects.soap_7_2_314_3181), 282
CacheFilterList (class in pytan3.api_objects.soap_7_3_314_3424), 363
CacheFilterList (class in pytan3.api_objects.soap_7_3_314_3641), 446
CacheInfo (class in pytan3.api_objects.rest_7_3_314_3424), 66
CacheInfo (class in pytan3.api_objects.rest_7_3_314_3641), 151
CacheInfo (class in pytan3.api_objects.soap_7_2_314_3181), 234

CacheInfo (class in pytan3.api_objects.soap_7_3_314_3424), 309
CacheInfo (class in pytan3.api_objects.soap_7_3_314_3641), 393
CERT_FILE (in module pytan3.http_client), 11
CERT_VALID (in module pytan3.http_client), 11
CertificateInvalidError, 19
CertificateNotFoundWarning, 19
Certify (class in pytan3.http_client), 15
certify (pytan3.http_client.HttpClient attribute), 12
check_adapter_types() (in module pytan3.adapters), 486
check_adapter_version() (in module pytan3.adapters), 486
check_default() (pytan3.http_client.Certify method), 17
check_object_attrs() (in module pytan3.adapters), 486
check_object_type() (in module pytan3.adapters), 486
check_path() (pytan3.http_client.Certify method), 17
CLEAN_AUTH_KEYS (pytan3.http_client.HttpClient attribute), 11
CLEAN_HIDE (pytan3.http_client.HttpClient attribute), 11
clean_hook_auth() (pytan3.http_client.HttpClient static method), 14
clean_hook_auth_rest() (pytan3.http_client.HttpClient static method), 14
CLEAN_HOOKS (pytan3.http_client.HttpClient attribute), 11
ClientCount (class in pytan3.api_objects.rest_7_3_314_3424), 79
ClientCount (class in pytan3.api_objects.rest_7_3_314_3641), 163
ClientCount (class in pytan3.api_objects.soap_7_2_314_3181), 246
ClientCount (class in pytan3.api_objects.soap_7_3_314_3424), 321
ClientCount (class in pytan3.api_objects.soap_7_3_314_3641), 405
ClientStatus (class in pytan3.api_objects.rest_7_3_314_3424), 70
ClientStatus (class in pytan3.api_objects.rest_7_3_314_3641), 154
ClientStatus (class in pytan3.api_objects.soap_7_2_314_3181), 237
ClientStatus (class in pytan3.api_objects.soap_7_3_314_3424), 312
ClientStatus (class in pytan3.api_objects.soap_7_3_314_3641), 396
cls_all (pytan3.api_objects.ApiObjects attribute), 45
cls_by_name() (pytan3.api_objects.ApiObjects method), 45
cls_item (pytan3.api_objects.ApiObjects attribute), 45
cls_item_by_name() (pytan3.api_objects.ApiObjects method), 45
cls_list (pytan3.api_objects.ApiObjects attribute), 45
cls_list_by_name() (pytan3.api_objects.ApiObjects method), 45
cls_name_map_all (pytan3.api_objects.ApiObjects attribute), 45
cls_name_map_item (pytan3.api_objects.ApiObjects attribute), 45
cls_name_map_list (pytan3.api_objects.ApiObjects attribute), 45
ColorWrap (class in pytan3.utils.prompts), 509
Column (class in pytan3.api_objects.rest_7_3_314_3424), 53
Column (class in pytan3.api_objects.rest_7_3_314_3641), 137
Column (class in pytan3.api_objects.soap_7_2_314_3181), 221
Column (class in pytan3.api_objects.soap_7_3_314_3424), 296
Column (class in pytan3.api_objects.soap_7_3_314_3641), 380
ColumnList (class in pytan3.api_objects.rest_7_3_314_3424), 52
ColumnList (class in pytan3.api_objects.rest_7_3_314_3641), 137
ColumnList (class in pytan3.api_objects.soap_7_2_314_3181), 220
ColumnList (class in pytan3.api_objects.soap_7_3_314_3424), 295
ColumnList (class in pytan3.api_objects.soap_7_3_314_3641), 379
columns (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
columns (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 140
columns (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
columns (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 224
columns (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 295
columns (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
columns (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 379
columns (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 382
command_request (pytan3.results.Soap attribute), 495
command_response (pytan3.results.Soap attribute), 495
COMMANDS (in module pytan3.api_objects.rest_7_3_314_3424), 132
COMMANDS (in module pytan3.api_objects.rest_7_3_314_3641), 216
COMMANDS (in module pytan3.api_objects.soap_7_2_314_3181), 291
COMMANDS (in module py-

tan3.api_objects.soap_7_3_314_3424), 375
COMMANDS (in module pytan3.api_objects.soap_7_3_314_3641), 458
CommonMixin (class in pytan3.auth_methods), 22
CommonMixin (class in pytan3.results), 492
ComputerGroup (class in pytan3.api_objects.rest_7_3_314_3424), 82
ComputerGroup (class in pytan3.api_objects.rest_7_3_314_3641), 166
ComputerGroup (class in pytan3.api_objects.soap_7_2_314_3181), 249
ComputerGroup (class in pytan3.api_objects.soap_7_3_314_3424), 325
ComputerGroup (class in pytan3.api_objects.soap_7_3_314_3641), 408
ComputerGroupList (class in pytan3.api_objects.rest_7_3_314_3424), 119
ComputerGroupList (class in pytan3.api_objects.rest_7_3_314_3641), 203
ComputerGroupList (class in pytan3.api_objects.soap_7_2_314_3181), 281
ComputerGroupList (class in pytan3.api_objects.soap_7_3_314_3424), 362
ComputerGroupList (class in pytan3.api_objects.soap_7_3_314_3641), 445
ComputerGroupSpec (class in pytan3.api_objects.rest_7_3_314_3424), 81
ComputerGroupSpec (class in pytan3.api_objects.rest_7_3_314_3641), 166
ComputerGroupSpec (class in pytan3.api_objects.soap_7_2_314_3181), 249
ComputerGroupSpec (class in pytan3.api_objects.soap_7_3_314_3424), 324
ComputerGroupSpec (class in pytan3.api_objects.soap_7_3_314_3641), 408
ComputerIdList (class in pytan3.api_objects.rest_7_3_314_3424), 131
ComputerIdList (class in pytan3.api_objects.rest_7_3_314_3641), 215
ComputerIdList (class in pytan3.api_objects.soap_7_2_314_3181), 290
ComputerIdList (class in pytan3.api_objects.soap_7_3_314_3424), 374
ComputerIdList (class in pytan3.api_objects.soap_7_3_314_3641), 457
ComputerSpecList (class in pytan3.api_objects.rest_7_3_314_3424), 119
ComputerSpecList (class in pytan3.api_objects.rest_7_3_314_3641), 203
ComputerSpecList (class in pytan3.api_objects.soap_7_2_314_3181), 281
ComputerSpecList (class in pytan3.api_objects.soap_7_3_314_3424), 361
ComputerSpecList (class in pytan3.api_objects.soap_7_3_314_3641), 445
config (pytan3.api_clients.ApiClient attribute), 37
config (pytan3.api_clients.Rest attribute), 41
config (pytan3.api_clients.Soap attribute), 39
ContentSet (class in pytan3.api_objects.rest_7_3_314_3424), 85
ContentSet (class in pytan3.api_objects.rest_7_3_314_3641), 169
ContentSet (class in pytan3.api_objects.soap_7_2_314_3181), 251
ContentSet (class in pytan3.api_objects.soap_7_3_314_3424), 327
ContentSet (class in pytan3.api_objects.soap_7_3_314_3641), 411
ContentSetList (class in pytan3.api_objects.rest_7_3_314_3424), 121
ContentSetList (class in pytan3.api_objects.rest_7_3_314_3641), 205
ContentSetList (class in pytan3.api_objects.soap_7_2_314_3181), 283
ContentSetList (class in pytan3.api_objects.soap_7_3_314_3424), 363
ContentSetList (class in pytan3.api_objects.soap_7_3_314_3641), 447
ContentSetPrivilege (class in pytan3.api_objects.rest_7_3_314_3424), 87
ContentSetPrivilege (class in pytan3.api_objects.rest_7_3_314_3641), 171
ContentSetPrivilege (class in pytan3.api_objects.soap_7_2_314_3181), 254
ContentSetPrivilege (class in pytan3.api_objects.soap_7_3_314_3424), 330
ContentSetPrivilege (class in pytan3.api_objects.soap_7_3_314_3641), 413
ContentSetPrivilegeList (class in pytan3.api_objects.rest_7_3_314_3424), 123
ContentSetPrivilegeList (class in pytan3.api_objects.rest_7_3_314_3641), 207
ContentSetPrivilegeList (class in pytan3.api_objects.soap_7_2_314_3181), 285
ContentSetPrivilegeList (class in pytan3.api_objects.soap_7_3_314_3424), 366
ContentSetPrivilegeList (class in pytan3.api_objects.soap_7_3_314_3641), 450
ContentSetRole (class in pytan3.api_objects.rest_7_3_314_3424), 86
ContentSetRole (class in pytan3.api_objects.rest_7_3_314_3641), 170
ContentSetRole (class in pytan3.api_objects.soap_7_2_314_3181), 252
ContentSetRole (class in pytan3.api_objects.soap_7_3_314_3424), 328
ContentSetRole (class in pytan3.api_objects.soap_7_3_314_3641), 412

ContentSetRoleList (class in pytan3.api_objects.rest_7_3_314_3424), 122
ContentSetRoleList (class in pytan3.api_objects.rest_7_3_314_3641), 206
ContentSetRoleList (class in pytan3.api_objects.soap_7_2_314_3181), 284
ContentSetRoleList (class in pytan3.api_objects.soap_7_3_314_3424), 364
ContentSetRoleList (class in pytan3.api_objects.soap_7_3_314_3641), 448
ContentSetRoleMembership (class in pytan3.api_objects.rest_7_3_314_3424), 86
ContentSetRoleMembership (class in pytan3.api_objects.rest_7_3_314_3641), 170
ContentSetRoleMembership (class in pytan3.api_objects.soap_7_2_314_3181), 253
ContentSetRoleMembership (class in pytan3.api_objects.soap_7_3_314_3424), 329
ContentSetRoleMembership (class in pytan3.api_objects.soap_7_3_314_3641), 412
ContentSetRoleMembershipList (class in pytan3.api_objects.rest_7_3_314_3424), 122
ContentSetRoleMembershipList (class in pytan3.api_objects.rest_7_3_314_3641), 206
ContentSetRoleMembershipList (class in pytan3.api_objects.soap_7_2_314_3181), 284
ContentSetRoleMembershipList (class in pytan3.api_objects.soap_7_3_314_3424), 365
ContentSetRoleMembershipList (class in pytan3.api_objects.soap_7_3_314_3641), 449
ContentSetRolePrivilege (class in pytan3.api_objects.rest_7_3_314_3424), 88
ContentSetRolePrivilege (class in pytan3.api_objects.rest_7_3_314_3641), 172
ContentSetRolePrivilege (class in pytan3.api_objects.soap_7_2_314_3181), 254
ContentSetRolePrivilege (class in pytan3.api_objects.soap_7_3_314_3424), 330
ContentSetRolePrivilege (class in pytan3.api_objects.soap_7_3_314_3641), 414
ContentSetRolePrivilegeList (class in pytan3.api_objects.rest_7_3_314_3424), 124
ContentSetRolePrivilegeList (class in pytan3.api_objects.rest_7_3_314_3641), 208
ContentSetRolePrivilegeList (class in pytan3.api_objects.soap_7_2_314_3181), 286
ContentSetRolePrivilegeList (class in pytan3.api_objects.soap_7_3_314_3424), 366
ContentSetRolePrivilegeList (class in pytan3.api_objects.soap_7_3_314_3641), 450
ContentSetRolePrivilegeOnRole (class in pytan3.api_objects.rest_7_3_314_3424), 85
ContentSetRolePrivilegeOnRole (class in pytan3.api_objects.rest_7_3_314_3641), 169
ContentSetRolePrivilegeOnRole (class in pytan3.api_objects.soap_7_2_314_3181), 252
ContentSetRolePrivilegeOnRole (class in pytan3.api_objects.soap_7_3_314_3424), 328
ContentSetRolePrivilegeOnRole (class in pytan3.api_objects.soap_7_3_314_3641), 412
ContentSetRolePrivilegeOnRoleList (class in pytan3.api_objects.rest_7_3_314_3424), 121
ContentSetRolePrivilegeOnRoleList (class in pytan3.api_objects.rest_7_3_314_3641), 205
ContentSetRolePrivilegeOnRoleList (class in pytan3.api_objects.soap_7_2_314_3181), 283
ContentSetRolePrivilegeOnRoleList (class in pytan3.api_objects.soap_7_3_314_3424), 364
ContentSetRolePrivilegeOnRoleList (class in pytan3.api_objects.soap_7_3_314_3641), 448
ContentSetUserGroupRoleMembership (class in pytan3.api_objects.rest_7_3_314_3424), 87
ContentSetUserGroupRoleMembership (class in pytan3.api_objects.rest_7_3_314_3641), 171
ContentSetUserGroupRoleMembership (class in pytan3.api_objects.soap_7_2_314_3181), 253
ContentSetUserGroupRoleMembership (class in pytan3.api_objects.soap_7_3_314_3424), 329
ContentSetUserGroupRoleMembership (class in pytan3.api_objects.soap_7_3_314_3641), 413
ContentSetUserGroupRoleMembershipList (class in pytan3.api_objects.rest_7_3_314_3424), 123
ContentSetUserGroupRoleMembershipList (class in pytan3.api_objects.rest_7_3_314_3641), 207
ContentSetUserGroupRoleMembershipList (class in pytan3.api_objects.soap_7_2_314_3181), 285
ContentSetUserGroupRoleMembershipList (class in pytan3.api_objects.soap_7_3_314_3424), 365
ContentSetUserGroupRoleMembershipList (class in pytan3.api_objects.soap_7_3_314_3641), 449
control_adhoc_warnings() (pytan3.api_objects.ApiObjects method), 44
control_hook() (pytan3.http_client.HttpClient method), 13
control_hook_record_disk() (pytan3.http_client.HttpClient method), 13
control_hook_record_history() (pytan3.http_client.HttpClient method), 13
create_method() (pytan3.auth_store.AuthStore method), 33
create_store() (pytan3.auth_methods.AuthMethod method), 21
create_store() (pytan3.auth_methods.CommonMixin method), 24
Credentials (class in pytan3.auth_methods), 27
customformatwarning() (in module pytan3.utils.logs), 504

D

Dashboard (class in pytan3.api_objects.rest_7_3_314_3424), 89
Dashboard (class in pytan3.api_objects.rest_7_3_314_3641), 173
Dashboard (class in pytan3.api_objects.soap_7_2_314_3181), 255
Dashboard (class in pytan3.api_objects.soap_7_3_314_3424), 331
Dashboard (class in pytan3.api_objects.soap_7_3_314_3641), 415
DashboardGroup (class in pytan3.api_objects.rest_7_3_314_3424), 89
DashboardGroup (class in pytan3.api_objects.rest_7_3_314_3641), 173
DashboardGroup (class in pytan3.api_objects.soap_7_2_314_3181), 256
DashboardGroup (class in pytan3.api_objects.soap_7_3_314_3424), 332
DashboardGroup (class in pytan3.api_objects.soap_7_3_314_3641), 415
DashboardList (class in pytan3.api_objects.rest_7_3_314_3424), 125
DashboardList (class in pytan3.api_objects.rest_7_3_314_3641), 209
DashboardList (class in pytan3.api_objects.soap_7_2_314_3181), 287
DashboardList (class in pytan3.api_objects.soap_7_3_314_3424), 368
DashboardList (class in pytan3.api_objects.soap_7_3_314_3641), 452
data_api() (pytan3.results.Rest method), 498
data_api() (pytan3.results.Result method), 491
data_api() (pytan3.results.Soap method), 495
data_obj (pytan3.results.Rest attribute), 498
data_obj (pytan3.results.Result attribute), 491
data_obj (pytan3.results.Soap attribute), 495
DATA_ROUTES (pytan3.results.Rest attribute), 496
DATA_ROUTES (pytan3.results.Soap attribute), 494
data_xml (pytan3.results.Soap attribute), 495
decrypt() (in module pytan3.utils.crypt), 503
DEFAULT_NAME (in module pytan3.adapters), 473
DEFAULT_NAME (in module pytan3.api_clients), 36
DEFAULT_NAME (in module pytan3.auth_methods), 19
DEFAULT_NAME (in module pytan3.auth_store), 32
DEFAULT_OPTIONS (pytan3.adapters.Rest attribute), 480
DEFAULT_OPTIONS (pytan3.adapters.Soap attribute), 475
DEFAULT_TYPE (in module pytan3.adapters), 473
DEFAULT_TYPE (in module pytan3.api_clients), 36
DEFAULT_TYPE (in module pytan3.api_objects), 43
DictionaryPathError, 502
disable_capture_exc() (in module pytan3.utils.logs), 504
disable_capture_warn() (in module pytan3.utils.logs), 504
disable_format_warning() (in module pytan3.utils.logs), 504

E

EffectiveContentSetPrivilege (class in pytan3.api_objects.rest_7_3_314_3424), 88
EffectiveContentSetPrivilege (class in pytan3.api_objects.rest_7_3_314_3641), 172
EffectiveContentSetPrivilege (class in pytan3.api_objects.soap_7_2_314_3181), 255
EffectiveContentSetPrivilege (class in pytan3.api_objects.soap_7_3_314_3424), 331
EffectiveContentSetPrivilege (class in pytan3.api_objects.soap_7_3_314_3641), 414
EffectiveContentSetPrivilegeList (class in pytan3.api_objects.rest_7_3_314_3424), 125
EffectiveContentSetPrivilegeList (class in pytan3.api_objects.rest_7_3_314_3641), 209
EffectiveContentSetPrivilegeList (class in pytan3.api_objects.soap_7_2_314_3181), 287
EffectiveContentSetPrivilegeList (class in pytan3.api_objects.soap_7_3_314_3424), 367
EffectiveContentSetPrivilegeList (class in pytan3.api_objects.soap_7_3_314_3641), 451
EffectiveContentSetPrivilegeRequest (class in pytan3.api_objects.rest_7_3_314_3424), 124
EffectiveContentSetPrivilegeRequest (class in pytan3.api_objects.rest_7_3_314_3641), 208
EffectiveContentSetPrivilegeRequest (class in pytan3.api_objects.soap_7_2_314_3181), 286
EffectiveContentSetPrivilegeRequest (class in pytan3.api_objects.soap_7_3_314_3424), 367
EffectiveContentSetPrivilegeRequest (class in pytan3.api_objects.soap_7_3_314_3641), 451
elapsed (pytan3.utils.tools.Timer attribute), 518
elapsed_delta (pytan3.utils.tools.Timer attribute), 517
elapsed_int (pytan3.utils.tools.Timer attribute), 518
EmptyAttributeError, 489
EmptyValueError, 514
enable_capture_exc() (in module pytan3.utils.logs), 504
enable_capture_warn() (in module pytan3.utils.logs), 504
enable_format_warning() (in module pytan3.utils.logs), 504
encrypt() (in module pytan3.utils.crypt), 503
end (pytan3.utils.tools.Timer attribute), 517
error (pytan3.api_models.exceptions.AttrTypeError attribute), 471
error (pytan3.api_models.exceptions.AttrUndefinedError attribute), 470
error (pytan3.api_models.exceptions.AttrUndefinedWarning attribute), 470

error (pytan3.api_models.exceptions.GetSingleItemError attribute), 473
error (pytan3.api_models.exceptions.ListItemTypeError attribute), 472
error (pytan3.api_models.exceptions.ListTypeError attribute), 472
error (pytan3.api_objects.exceptions.UnknownApiNameError attribute), 48
error (pytan3.auth_methods.exceptions.MethodError attribute), 26
error (pytan3.results.exceptions.ApiWrongRequestType attribute), 502
error (pytan3.results.exceptions.DictionaryPathError attribute), 502
error (pytan3.results.exceptions.ResponseError attribute), 501
error (pytan3.results.exceptions.TextDeserializeError attribute), 501
error_check() (pytan3.results.Rest method), 497
error_check() (pytan3.results.Result method), 490
error_check() (pytan3.results.Soap method), 494
error_check_code() (pytan3.results.Rest method), 498
error_check_code() (pytan3.results.Soap method), 495
error_check_response() (pytan3.results.Rest method), 497
error_check_response() (pytan3.results.Soap method), 495
error_map (pytan3.results.Rest attribute), 497
error_map (pytan3.results.Soap attribute), 494
error_text (pytan3.results.Rest attribute), 498
error_text (pytan3.results.Result attribute), 490
error_text (pytan3.results.Soap attribute), 495
ErrorList (class in pytan3.api_objects.rest_7_3_314_3424), 104
ErrorList (class in pytan3.api_objects.rest_7_3_314_3641), 188
ErrorList (class in pytan3.api_objects.soap_7_2_314_3181), 266
ErrorList (class in pytan3.api_objects.soap_7_3_314_3424), 346
ErrorList (class in pytan3.api_objects.soap_7_3_314_3641), 430
exc (pytan3.results.exceptions.DictionaryPathError attribute), 502
exc (pytan3.results.exceptions.TextDeserializeError attribute), 501
exception_hook() (in module pytan3.utils.logs), 504
expand_cls_globals() (in module pytan3.api_objects.rest_7_3_314_3424), 49
expand_cls_globals() (in module pytan3.api_objects.rest_7_3_314_3641), 133
expand_cls_globals() (in module pytan3.api_objects.soap_7_2_314_3181), 217
expand_cls_globals() (in module pytan3.api_objects.soap_7_3_314_3424), 291
expand_cls_globals() (in module pytan3.api_objects.soap_7_3_314_3641), 375
expand_global() (in module pytan3.api_objects.rest_7_3_314_3424), 49
expand_global() (in module pytan3.api_objects.rest_7_3_314_3641), 133
expand_global() (in module pytan3.api_objects.soap_7_2_314_3181), 217
expand_global() (in module pytan3.api_objects.soap_7_3_314_3424), 292
expand_global() (in module pytan3.api_objects.soap_7_3_314_3641), 375
expired (pytan3.auth_methods.CommonMixin attribute), 23

F

Filter (class in pytan3.api_objects.rest_7_3_314_3424), 64
Filter (class in pytan3.api_objects.rest_7_3_314_3641), 148
Filter (class in pytan3.api_objects.soap_7_2_314_3181), 232
Filter (class in pytan3.api_objects.soap_7_3_314_3424), 307
Filter (class in pytan3.api_objects.soap_7_3_314_3641), 390
FilterList (class in pytan3.api_objects.rest_7_3_314_3424), 103
FilterList (class in pytan3.api_objects.rest_7_3_314_3641), 187
FilterList (class in pytan3.api_objects.soap_7_2_314_3181), 265
FilterList (class in pytan3.api_objects.soap_7_3_314_3424), 345
FilterList (class in pytan3.api_objects.soap_7_3_314_3641), 429
find_handler_by_name() (in module pytan3.utils.logs), 508
find_version() (in module pytan3.api_objects), 46
float_types (in module pytan3.api_models), 459
float_types (in module pytan3.api_objects.rest_7_3_314_3424), 48
float_types (in module pytan3.api_objects.rest_7_3_314_3641), 132
float_types (in module pytan3.api_objects.soap_7_2_314_3181), 216
float_types (in module pytan3.api_objects.soap_7_3_314_3424), 291
float_types (in module pytan3.api_objects.soap_7_3_314_3641), 375
from_path() (pytan3.auth_store.AuthStore class method), 35

from_response() (pytan3.results.CommonMixin class method), 492
from_response() (pytan3.results.Result class method), 490
from_store() (pytan3.auth_methods.AuthMethod class method), 20
from_store() (pytan3.auth_methods.CommonMixin class method), 22
from_stream() (pytan3.auth_store.AuthStore class method), 34
from_string() (pytan3.auth_store.AuthStore class method), 34

G

get() (pytan3.auth_store.AuthStore method), 33
get_api_all_item() (in module pytan3.api_objects.rest_7_3_314_3424), 49
get_api_all_item() (in module pytan3.api_objects.rest_7_3_314_3641), 133
get_api_all_item() (in module pytan3.api_objects.soap_7_2_314_3181), 217
get_api_all_item() (in module pytan3.api_objects.soap_7_3_314_3424), 292
get_api_all_item() (in module pytan3.api_objects.soap_7_3_314_3641), 375
get_api_all_list() (in module pytan3.api_objects.rest_7_3_314_3424), 49
get_api_all_list() (in module pytan3.api_objects.rest_7_3_314_3641), 133
get_api_all_list() (in module pytan3.api_objects.soap_7_2_314_3181), 217
get_api_all_list() (in module pytan3.api_objects.soap_7_3_314_3424), 292
get_api_all_list() (in module pytan3.api_objects.soap_7_3_314_3641), 375
get_api_all_model() (in module pytan3.api_objects.rest_7_3_314_3424), 49
get_api_all_model() (in module pytan3.api_objects.rest_7_3_314_3641), 133
get_api_all_model() (in module pytan3.api_objects.soap_7_2_314_3181), 217
get_api_all_model() (in module pytan3.api_objects.soap_7_3_314_3424), 292
get_api_all_model() (in module pytan3.api_objects.soap_7_3_314_3641), 376
get_args() (pytan3.auth_methods.AuthMethod class method), 20
get_args() (pytan3.auth_methods.Credentials class method), 28
get_args() (pytan3.auth_methods.RestCredentials class method), 29
get_args() (pytan3.auth_methods.SessionId class method), 31
get_args_required() (pytan3.auth_methods.AuthMethod class method), 20
get_args_required() (pytan3.auth_methods.Credentials class method), 28
get_args_required() (pytan3.auth_methods.RestCredentials class method), 29
get_args_required() (pytan3.auth_methods.SessionId class method), 31
get_args_secure() (pytan3.auth_methods.AuthMethod class method), 20
get_args_secure() (pytan3.auth_methods.Credentials class method), 28
get_args_secure() (pytan3.auth_methods.RestCredentials class method), 29
get_args_secure() (pytan3.auth_methods.SessionId class method), 31
get_config() (in module pytan3.api_clients), 42
get_dict_path() (in module pytan3.utils.tools), 516
get_dict_path() (pytan3.results.CommonMixin method), 493
get_env() (in module pytan3.utils.tools), 515
get_item_by_attr() (pytan3.api_models.ApiList method), 467
get_items_by_attr() (pytan3.api_models.ApiList method), 467
get_log() (in module pytan3.utils.logs), 505
get_name() (pytan3.adapters.Adapter class method), 474
get_name() (pytan3.adapters.Rest class method), 481
get_name() (pytan3.adapters.Soap class method), 476
get_name() (pytan3.api_clients.ApiClient class method), 37
get_name() (pytan3.api_clients.Rest class method), 41
get_name() (pytan3.api_clients.Soap class method), 38
get_name() (pytan3.auth_methods.AuthMethod class method), 20
get_name() (pytan3.auth_methods.Credentials class method), 27
get_name() (pytan3.auth_methods.RestCredentials class method), 29
get_name() (pytan3.auth_methods.SessionId class method), 31
get_obj_log() (in module pytan3.utils.logs), 505
get_output_handlers() (in module pytan3.utils.logs), 509
get_prompter() (pytan3.utils.prompts.Promptness method), 511
get_storage_dir() (in module pytan3.utils.tools), 515
get_type() (pytan3.adapters.Adapter class method), 474
get_type() (pytan3.adapters.Rest class method), 481
get_type() (pytan3.adapters.Soap class method), 476
get_type() (pytan3.api_clients.ApiClient class method), 37
get_type() (pytan3.api_clients.Rest class method), 41
get_type() (pytan3.api_clients.Soap class method), 39

get_values() (pytan3.api_objects.rest_7_3_314_3424.Column method), 54
get_values() (pytan3.api_objects.rest_7_3_314_3424.Row method), 56
get_values() (pytan3.api_objects.rest_7_3_314_3424.RowColumn method), 57
get_values() (pytan3.api_objects.rest_7_3_314_3641.Column method), 138
get_values() (pytan3.api_objects.rest_7_3_314_3641.Row method), 140
get_values() (pytan3.api_objects.rest_7_3_314_3641.RowColumn method), 141
get_values() (pytan3.api_objects.soap_7_2_314_3181.Column method), 222
get_values() (pytan3.api_objects.soap_7_2_314_3181.Row method), 224
get_values() (pytan3.api_objects.soap_7_2_314_3181.RowColumn method), 226
get_values() (pytan3.api_objects.soap_7_3_314_3424.Column method), 297
get_values() (pytan3.api_objects.soap_7_3_314_3424.Row method), 298
get_values() (pytan3.api_objects.soap_7_3_314_3424.RowColumn method), 301
get_values() (pytan3.api_objects.soap_7_3_314_3641.Column method), 381
get_values() (pytan3.api_objects.soap_7_3_314_3641.Row method), 382
get_values() (pytan3.api_objects.soap_7_3_314_3641.RowColumn method), 384
get_version() (in module pytan3.api_clients), 42
get_version_req() (pytan3.adapters.Adapter class method), 474
get_version_req() (pytan3.adapters.Rest class method), 481
get_version_req() (pytan3.adapters.Soap class method), 476
get_version_req() (pytan3.api_clients.ApiClient class method), 37
get_version_req() (pytan3.api_clients.Rest class method), 41
get_version_req() (pytan3.api_clients.Soap class method), 39
get_version_req() (pytan3.auth_methods.AuthMethod class method), 20
get_version_req() (pytan3.auth_methods.Credentials class method), 27
get_version_req() (pytan3.auth_methods.RestCredentials class method), 29
get_version_req() (pytan3.auth_methods.SessionId class method), 31
get_versions() (in module pytan3.api_objects), 46
get_wsdl() (in module pytan3.api_clients), 42
GetPlatformVersionWarning, 43
GetSingleItemError, 472
Group (class in pytan3.api_objects.rest_7_3_314_3424), 65
Group (class in pytan3.api_objects.rest_7_3_314_3641), 149
Group (class in pytan3.api_objects.soap_7_2_314_3181), 233
Group (class in pytan3.api_objects.soap_7_3_314_3424), 308
Group (class in pytan3.api_objects.soap_7_3_314_3641), 391
GroupList (class in pytan3.api_objects.rest_7_3_314_3424), 102
GroupList (class in pytan3.api_objects.rest_7_3_314_3641), 186
GroupList (class in pytan3.api_objects.soap_7_2_314_3181), 265
GroupList (class in pytan3.api_objects.soap_7_3_314_3424), 345
GroupList (class in pytan3.api_objects.soap_7_3_314_3641), 429

H

handler_str() (in module pytan3.utils.logs), 506
hash (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
hash (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
hash (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
hash (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 226
hash (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 227
hash (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
hash (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 301
hash (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
hash (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
hash (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
hash (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
HashedString (class in pytan3.api_objects.rest_7_3_314_3424), 95
HashedString (class in pytan3.api_objects.rest_7_3_314_3641), 179
HashedString (class in pytan3.api_objects.soap_7_2_314_3181), 259
HashedString (class in pytan3.api_objects.soap_7_3_314_3424), 338

HashedString (class in pytan3.api_objects.soap_7_3_314_3641), 421
HashedStringList (class in pytan3.api_objects.rest_7_3_314_3424), 132
HashedStringList (class in pytan3.api_objects.rest_7_3_314_3641), 216
HashedStringList (class in pytan3.api_objects.soap_7_2_314_3181), 290
HashedStringList (class in pytan3.api_objects.soap_7_3_314_3424), 374
HashedStringList (class in pytan3.api_objects.soap_7_3_314_3641), 458
history (pytan3.http_client.HttpClient attribute), 12
hostname (pytan3.http_client.UrlParser attribute), 18
http_client (pytan3.adapters.Adapter attribute), 473
http_client (pytan3.adapters.Rest attribute), 481
http_client (pytan3.adapters.Soap attribute), 476
http_client (pytan3.api_clients.ApiClient attribute), 37
http_client (pytan3.api_clients.Rest attribute), 41
http_client (pytan3.api_clients.Soap attribute), 39
http_client (pytan3.auth_methods.AuthMethod attribute), 20
http_client (pytan3.auth_methods.CommonMixin attribute), 22
http_client (pytan3.auth_store.AuthStore attribute), 32
http_client (pytan3.http_client.Certify attribute), 15
HttpClient (class in pytan3.http_client), 11
human_delta() (in module pytan3.utils.tools), 517
human_size() (in module pytan3.utils.tools), 516

I

IdReference (class in pytan3.api_objects.rest_7_3_314_3424), 65
IdReference (class in pytan3.api_objects.rest_7_3_314_3641), 149
IdReference (class in pytan3.api_objects.soap_7_2_314_3181), 232
IdReference (class in pytan3.api_objects.soap_7_3_314_3424), 307
IdReference (class in pytan3.api_objects.soap_7_3_314_3641), 391
ImportConflictDetail (class in pytan3.api_objects.rest_7_3_314_3424), 83
ImportConflictDetail (class in pytan3.api_objects.rest_7_3_314_3641), 167
ImportConflictDetail (class in pytan3.api_objects.soap_7_3_314_3424), 326
ImportConflictDetail (class in pytan3.api_objects.soap_7_3_314_3641), 410
ImportConflictDetailList (class in pytan3.api_objects.rest_7_3_314_3424), 119
ImportConflictDetailList (class in pytan3.api_objects.rest_7_3_314_3641), 204
ImportConflictDetailList (class in pytan3.api_objects.soap_7_3_314_3424), 362
ImportConflictDetailList (class in pytan3.api_objects.soap_7_3_314_3641), 446
ImportConflictOptions (class in pytan3.api_objects.rest_7_3_314_3424), 120
ImportConflictOptions (class in pytan3.api_objects.rest_7_3_314_3641), 205
ImportConflictOptions (class in pytan3.api_objects.soap_7_2_314_3181), 282
ImportConflictOptions (class in pytan3.api_objects.soap_7_3_314_3424), 363
ImportConflictOptions (class in pytan3.api_objects.soap_7_3_314_3641), 447
info (pytan3.api_clients.ApiClient attribute), 37
info (pytan3.api_clients.Rest attribute), 41
info (pytan3.api_clients.Soap attribute), 39
input_stream (pytan3.utils.prompts.Promptness attribute), 510
integer_types (in module pytan3.api_models), 459
integer_types (in module pytan3.api_objects.rest_7_3_314_3424), 48
integer_types (in module pytan3.api_objects.rest_7_3_314_3641), 132
integer_types (in module pytan3.api_objects.soap_7_2_314_3181), 217
integer_types (in module pytan3.api_objects.soap_7_3_314_3424), 291
integer_types (in module pytan3.api_objects.soap_7_3_314_3641), 375
InvalidToken, 26
InvalidTypeError, 489
InvalidValueError, 514
is_disabled() (in module pytan3.utils.logs), 504
is_enabled() (in module pytan3.utils.logs), 503
isatty() (in module pytan3.utils.prompts), 515
item (pytan3.api_models.exceptions.ListItemTypeError attribute), 472
items (pytan3.api_models.exceptions.GetSingleItemError attribute), 473
items (pytan3.api_models.exceptions.ListItemTypeError attribute), 472

J

join_ver() (in module pytan3.utils.versions), 520

L

last_request (pytan3.http_client.HttpClient attribute), 12
last_response (pytan3.http_client.HttpClient attribute), 12
last_used (pytan3.auth_methods.CommonMixin attribute), 23
LdapSyncConnector (class in pytan3.api_objects.rest_7_3_314_3424), 92

LdapSyncConnector (class in pytan3.api_objects.rest_7_3_314_3641), 176
LdapSyncConnector (class in pytan3.api_objects.soap_7_2_314_3181), 258
LdapSyncConnector (class in pytan3.api_objects.soap_7_3_314_3424), 334
LdapSyncConnector (class in pytan3.api_objects.soap_7_3_314_3641), 418
LdapSyncConnectorList (class in pytan3.api_objects.rest_7_3_314_3424), 128
LdapSyncConnectorList (class in pytan3.api_objects.rest_7_3_314_3641), 212
LdapSyncConnectorList (class in pytan3.api_objects.soap_7_2_314_3181), 289
LdapSyncConnectorList (class in pytan3.api_objects.soap_7_3_314_3424), 370
LdapSyncConnectorList (class in pytan3.api_objects.soap_7_3_314_3641), 454
level_int() (in module pytan3.utils.logs), 505
level_name() (in module pytan3.utils.logs), 505
LIST (pytan3.api_models.ApiList attribute), 464
ListItemTypeError, 472
ListTypeError, 471
load() (in module pytan3.adapters), 486
load() (in module pytan3.api_clients), 42
load() (in module pytan3.api_objects), 47
load() (in module pytan3.auth_methods), 25
load() (pytan3.api_objects.ApiObjects class method), 45
load_type() (in module pytan3.adapters), 486
load_type() (in module pytan3.api_clients), 42
LOG (in module pytan3.utils.logs), 503
log (pytan3.adapters.Rest attribute), 481
log (pytan3.adapters.Soap attribute), 476
log (pytan3.api_clients.Rest attribute), 40
log (pytan3.api_clients.Soap attribute), 38
log (pytan3.auth_methods.CommonMixin attribute), 22
log (pytan3.http_client.Certify attribute), 15
log (pytan3.http_client.HttpClient attribute), 11
log (pytan3.results.CommonMixin attribute), 492
log (pytan3.utils.prompts.Promptness attribute), 510
LOG_CON_FMT (in module pytan3.utils.logs), 503
LOG_FILE (in module pytan3.utils.logs), 503
LOG_PATH_FMT (in module pytan3.utils.logs), 503
log_str() (in module pytan3.utils.logs), 506
logged_in (pytan3.auth_methods.AuthMethod attribute), 21
logged_in (pytan3.auth_methods.CommonMixin attribute), 23
login() (pytan3.auth_methods.AuthMethod method), 21
login() (pytan3.auth_methods.CommonMixin method), 23
login() (pytan3.auth_methods.RestCredentials method), 29
login() (pytan3.auth_methods.SessionId method), 31
LoginError, 26
logout() (pytan3.auth_methods.AuthMethod method), 21
logout() (pytan3.auth_methods.CommonMixin method), 23
logout() (pytan3.auth_methods.RestCredentials method), 29
logout_all() (pytan3.auth_methods.AuthMethod method), 21
logout_all() (pytan3.auth_methods.CommonMixin method), 24
logout_all() (pytan3.auth_methods.RestCredentials method), 30
LogoutError, 26
LVL_DICT (in module pytan3.utils.logs), 503
LVL_STR (in module pytan3.utils.logs), 503

M

magic_endpoint() (in module pytan3.adapters), 488
make_netloc() (pytan3.http_client.UrlParser method), 18
MANUAL_OBJECT_ROUTES (pytan3.results.Rest attribute), 496
MergedResultSet (class in pytan3.api_objects.rest_7_3_314_3424), 51
MergedResultSet (class in pytan3.api_objects.rest_7_3_314_3641), 135
MergedResultSet (class in pytan3.api_objects.soap_7_2_314_3181), 219
MergedResultSet (class in pytan3.api_objects.soap_7_3_314_3424), 294
MergedResultSet (class in pytan3.api_objects.soap_7_3_314_3641), 377
MetadataItem (class in pytan3.api_objects.rest_7_3_314_3424), 64
MetadataItem (class in pytan3.api_objects.rest_7_3_314_3641), 148
MetadataItem (class in pytan3.api_objects.soap_7_2_314_3181), 231
MetadataItem (class in pytan3.api_objects.soap_7_3_314_3424), 306
MetadataItem (class in pytan3.api_objects.soap_7_3_314_3641), 390
MetadataList (class in pytan3.api_objects.rest_7_3_314_3424), 102
MetadataList (class in pytan3.api_objects.rest_7_3_314_3641), 186
MetadataList (class in pytan3.api_objects.soap_7_2_314_3181), 264
MetadataList (class in pytan3.api_objects.soap_7_3_314_3424), 344
MetadataList (class in pytan3.api_objects.soap_7_3_314_3641), 428
method (pytan3.auth_store.AuthStore attribute), 33
method (pytan3.results.CommonMixin attribute), 493
method (pytan3.results.Result attribute), 490

MethodError, 25
MODE (pytan3.utils.prompts.ColorWrap attribute), 509
MODE_MAP (pytan3.utils.prompts.ColorWrap attribute), 509
module (pytan3.api_objects.ApiObjects attribute), 44
module (pytan3.api_objects.exceptions.UnknownApiNameError attribute), 48
module_dt (pytan3.api_objects.ApiObjects attribute), 44
module_dt_format() (pytan3.api_objects.ApiObjects method), 44
module_type (pytan3.api_objects.ApiObjects attribute), 44
module_version (pytan3.api_objects.ApiObjects attribute), 44
module_version_dict (pytan3.api_objects.ApiObjects attribute), 44
ModuleError, 19, 25, 36, 43, 47, 469, 489, 500, 520
ModuleWarning, 19, 25, 36, 43, 47, 469, 489, 500, 521
msg (pytan3.auth_methods.exceptions.InvalidToken attribute), 26
msg (pytan3.auth_methods.exceptions.LoginError attribute), 26
msg (pytan3.auth_methods.exceptions.LogoutError attribute), 26
msg (pytan3.auth_methods.exceptions.MethodError attribute), 25
msg (pytan3.auth_methods.exceptions.NotLoggedInError attribute), 26
msg (pytan3.utils.prompts.EmptyValueError attribute), 514
msg (pytan3.utils.prompts.InvalidValueError attribute), 514
msg (pytan3.utils.prompts.PromptError attribute), 514

N

name (pytan3.api_objects.exceptions.UnknownApiNameError attribute), 48
name (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
name (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
name (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
name (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 226
name (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 296
name (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
name (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
name (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
name_map (pytan3.api_objects.exceptions.UnknownApiNameError attribute), 48
names (pytan3.api_objects.rest_7_3_314_3424.ColumnList attribute), 53
names (pytan3.api_objects.rest_7_3_314_3424.Row attribute), 55
names (pytan3.api_objects.rest_7_3_314_3641.ColumnList attribute), 137
names (pytan3.api_objects.rest_7_3_314_3641.Row attribute), 140
names (pytan3.api_objects.soap_7_2_314_3181.ColumnList attribute), 221
names (pytan3.api_objects.soap_7_2_314_3181.Row attribute), 224
names (pytan3.api_objects.soap_7_3_314_3424.ColumnList attribute), 296
names (pytan3.api_objects.soap_7_3_314_3424.Row attribute), 298
names (pytan3.api_objects.soap_7_3_314_3641.ColumnList attribute), 379
names (pytan3.api_objects.soap_7_3_314_3641.Row attribute), 382
NO_VALUES (pytan3.utils.prompts.Promptness attribute), 510
NotLoggedInError, 26
NoTtyError, 514
NoVersionFoundError, 47

O

obj (pytan3.api_models.exceptions.AttrTypeError attribute), 471
obj (pytan3.api_models.exceptions.AttrUndefinedError attribute), 470
obj (pytan3.api_models.exceptions.AttrUndefinedWarning attribute), 470
obj (pytan3.api_models.exceptions.GetSingleItemError attribute), 473
obj (pytan3.api_models.exceptions.ListItemTypeError attribute), 472
obj (pytan3.api_models.exceptions.ListTypeError attribute), 471
obj (pytan3.results.exceptions.DictionaryPathError attribute), 502
obj_to_api() (pytan3.results.CommonMixin method), 493
obj_to_api() (pytan3.results.Result method), 491
object_api() (pytan3.results.Rest method), 498
object_api() (pytan3.results.Result method), 491
object_api() (pytan3.results.Soap method), 496
object_obj (pytan3.results.Rest attribute), 498
object_obj (pytan3.results.Result attribute), 491
object_obj (pytan3.results.Soap attribute), 496
ObjectExistsError, 501
ObjectList (class in pytan3.api_objects.rest_7_3_314_3424), 83

ObjectList (class in pytan3.api_objects.rest_7_3_314_3641), 167
ObjectList (class in pytan3.api_objects.soap_7_2_314_3181), 250
ObjectList (class in pytan3.api_objects.soap_7_3_314_3424), 326
ObjectList (class in pytan3.api_objects.soap_7_3_314_3641), 409
ObjectNotFoundError, 501
op (pytan3.api_models.exceptions.ListItemTypeError attribute), 472
op (pytan3.api_models.exceptions.ListTypeError attribute), 472
Options (class in pytan3.api_objects.rest_7_3_314_3424), 84
Options (class in pytan3.api_objects.rest_7_3_314_3641), 168
Options (class in pytan3.api_objects.soap_7_2_314_3181), 251
Options (class in pytan3.api_objects.soap_7_3_314_3424), 327
Options (class in pytan3.api_objects.soap_7_3_314_3641), 411
origin (pytan3.results.CommonMixin attribute), 492
output_stream (pytan3.utils.prompts.Promptness attribute), 510
OVERRIDES (pytan3.utils.prompts.Promptness attribute), 510

P

PackageFile (class in pytan3.api_objects.rest_7_3_314_3424), 69
PackageFile (class in pytan3.api_objects.rest_7_3_314_3641), 153
PackageFile (class in pytan3.api_objects.soap_7_2_314_3181), 236
PackageFile (class in pytan3.api_objects.soap_7_3_314_3424), 311
PackageFile (class in pytan3.api_objects.soap_7_3_314_3641), 395
PackageFileList (class in pytan3.api_objects.rest_7_3_314_3424), 106
PackageFileList (class in pytan3.api_objects.rest_7_3_314_3641), 190
PackageFileList (class in pytan3.api_objects.soap_7_2_314_3181), 268
PackageFileList (class in pytan3.api_objects.soap_7_3_314_3424), 348
PackageFileList (class in pytan3.api_objects.soap_7_3_314_3641), 432
PackageFileStatus (class in pytan3.api_objects.rest_7_3_314_3424), 68
PackageFileStatus (class in pytan3.api_objects.rest_7_3_314_3641), 153
PackageFileStatus (class in pytan3.api_objects.soap_7_2_314_3181), 236
PackageFileStatus (class in pytan3.api_objects.soap_7_3_314_3424), 311
PackageFileStatus (class in pytan3.api_objects.soap_7_3_314_3641), 395
PackageFileStatusList (class in pytan3.api_objects.rest_7_3_314_3424), 105
PackageFileStatusList (class in pytan3.api_objects.rest_7_3_314_3641), 189
PackageFileStatusList (class in pytan3.api_objects.soap_7_2_314_3181), 267
PackageFileStatusList (class in pytan3.api_objects.soap_7_3_314_3424), 348
PackageFileStatusList (class in pytan3.api_objects.soap_7_3_314_3641), 431
PackageFileTemplate (class in pytan3.api_objects.rest_7_3_314_3424), 68
PackageFileTemplate (class in pytan3.api_objects.rest_7_3_314_3641), 152
PackageFileTemplate (class in pytan3.api_objects.soap_7_2_314_3181), 235
PackageFileTemplate (class in pytan3.api_objects.soap_7_3_314_3424), 310
PackageFileTemplate (class in pytan3.api_objects.soap_7_3_314_3641), 394
PackageFileTemplateList (class in pytan3.api_objects.rest_7_3_314_3424), 105
PackageFileTemplateList (class in pytan3.api_objects.rest_7_3_314_3641), 189
PackageFileTemplateList (class in pytan3.api_objects.soap_7_2_314_3181), 267
PackageFileTemplateList (class in pytan3.api_objects.soap_7_3_314_3424), 347
PackageFileTemplateList (class in pytan3.api_objects.soap_7_3_314_3641), 431
PackageSpec (class in pytan3.api_objects.rest_7_3_314_3424), 69
PackageSpec (class in pytan3.api_objects.rest_7_3_314_3641), 153
PackageSpec (class in pytan3.api_objects.soap_7_2_314_3181), 237
PackageSpec (class in pytan3.api_objects.soap_7_3_314_3424), 312
PackageSpec (class in pytan3.api_objects.soap_7_3_314_3641), 396
PackageSpecList (class in pytan3.api_objects.rest_7_3_314_3424), 106
PackageSpecList (class in pytan3.api_objects.rest_7_3_314_3641), 190
PackageSpecList (class in pytan3.api_objects.soap_7_2_314_3181), 268
PackageSpecList (class in pytan3.api_objects.soap_7_3_314_3424), 349

PackageSpecList (class in pytan3.api_objects.soap_7_3_314_3641), 432
Parameter (class in pytan3.api_objects.rest_7_3_314_3424), 77
Parameter (class in pytan3.api_objects.rest_7_3_314_3641), 161
Parameter (class in pytan3.api_objects.soap_7_2_314_3181), 244
Parameter (class in pytan3.api_objects.soap_7_3_314_3424), 319
Parameter (class in pytan3.api_objects.soap_7_3_314_3641), 403
ParameterList (class in pytan3.api_objects.rest_7_3_314_3424), 113
ParameterList (class in pytan3.api_objects.rest_7_3_314_3641), 197
ParameterList (class in pytan3.api_objects.soap_7_2_314_3181), 276
ParameterList (class in pytan3.api_objects.soap_7_3_314_3424), 356
ParameterList (class in pytan3.api_objects.soap_7_3_314_3641), 440
ParameterValueList (class in pytan3.api_objects.rest_7_3_314_3424), 114
ParameterValueList (class in pytan3.api_objects.rest_7_3_314_3641), 198
ParameterValueList (class in pytan3.api_objects.soap_7_2_314_3181), 276
ParameterValueList (class in pytan3.api_objects.soap_7_3_314_3424), 356
ParameterValueList (class in pytan3.api_objects.soap_7_3_314_3641), 440
parse_url() (pytan3.http_client.HttpClient method), 15
parsed (pytan3.http_client.UrlParser attribute), 18
parsed_str (pytan3.http_client.UrlParser attribute), 18
parsed_url (pytan3.http_client.HttpClient attribute), 11
ParseJob (class in pytan3.api_objects.rest_7_3_314_3424), 76
ParseJob (class in pytan3.api_objects.rest_7_3_314_3641), 160
ParseJob (class in pytan3.api_objects.soap_7_2_314_3181), 244
ParseJob (class in pytan3.api_objects.soap_7_3_314_3424), 319
ParseJob (class in pytan3.api_objects.soap_7_3_314_3641), 403
ParseJobList (class in pytan3.api_objects.rest_7_3_314_3424), 112
ParseJobList (class in pytan3.api_objects.rest_7_3_314_3641), 196
ParseJobList (class in pytan3.api_objects.soap_7_2_314_3181), 274
ParseJobList (class in pytan3.api_objects.soap_7_3_314_3424), 354
ParseJobList (class in pytan3.api_objects.soap_7_3_314_3641), 438
ParseQuestionResult (class in pytan3.api_objects.rest_7_3_314_3424), 58
ParseQuestionResult (class in pytan3.api_objects.rest_7_3_314_3641), 143
ParseQuestionResultList (class in pytan3.api_objects.rest_7_3_314_3424), 58
ParseQuestionResultList (class in pytan3.api_objects.rest_7_3_314_3641), 142
ParseResult (class in pytan3.api_objects.rest_7_3_314_3424), 77
ParseResult (class in pytan3.api_objects.rest_7_3_314_3641), 161
ParseResult (class in pytan3.api_objects.soap_7_2_314_3181), 245
ParseResult (class in pytan3.api_objects.soap_7_3_314_3424), 320
ParseResult (class in pytan3.api_objects.soap_7_3_314_3641), 404
ParseResultGroup (class in pytan3.api_objects.rest_7_3_314_3424), 78
ParseResultGroup (class in pytan3.api_objects.rest_7_3_314_3641), 162
ParseResultGroup (class in pytan3.api_objects.soap_7_2_314_3181), 246
ParseResultGroup (class in pytan3.api_objects.soap_7_3_314_3424), 321
ParseResultGroup (class in pytan3.api_objects.soap_7_3_314_3641), 405
ParseResultGroupList (class in pytan3.api_objects.rest_7_3_314_3424), 112
ParseResultGroupList (class in pytan3.api_objects.rest_7_3_314_3641), 197
ParseResultGroupList (class in pytan3.api_objects.soap_7_2_314_3181), 275
ParseResultGroupList (class in pytan3.api_objects.soap_7_3_314_3424), 355
ParseResultGroupList (class in pytan3.api_objects.soap_7_3_314_3641), 439
ParseResultList (class in pytan3.api_objects.rest_7_3_314_3424), 113
ParseResultList (class in pytan3.api_objects.rest_7_3_314_3641), 197
ParseResultList (class in pytan3.api_objects.soap_7_2_314_3181), 275
ParseResultList (class in pytan3.api_objects.soap_7_3_314_3424), 355
ParseResultList (class in pytan3.api_objects.soap_7_3_314_3641), 439
path (pytan3.results.exceptions.DictionaryPathError attribute), 502
path_parts (pytan3.results.RestUrlPath attribute), 499
PATTERN (in module pytan3.api_objects), 43

PermissionList (class in pytan3.api_objects.rest_7_3_314_3424), 109
PermissionList (class in pytan3.api_objects.rest_7_3_314_3641), 193
PermissionList (class in pytan3.api_objects.soap_7_2_314_3181), 271
PermissionList (class in pytan3.api_objects.soap_7_3_314_3424), 352
PermissionList (class in pytan3.api_objects.soap_7_3_314_3641), 435
Plugin (class in pytan3.api_objects.rest_7_3_314_3424), 81
Plugin (class in pytan3.api_objects.rest_7_3_314_3641), 165
Plugin (class in pytan3.api_objects.soap_7_2_314_3181), 248
Plugin (class in pytan3.api_objects.soap_7_3_314_3424), 323
Plugin (class in pytan3.api_objects.soap_7_3_314_3641), 407
PluginArgument (class in pytan3.api_objects.rest_7_3_314_3424), 79
PluginArgument (class in pytan3.api_objects.rest_7_3_314_3641), 163
PluginArgument (class in pytan3.api_objects.soap_7_2_314_3181), 247
PluginArgument (class in pytan3.api_objects.soap_7_3_314_3424), 322
PluginArgument (class in pytan3.api_objects.soap_7_3_314_3641), 405
PluginArgumentList (class in pytan3.api_objects.rest_7_3_314_3424), 115
PluginArgumentList (class in pytan3.api_objects.rest_7_3_314_3641), 199
PluginArgumentList (class in pytan3.api_objects.soap_7_2_314_3181), 277
PluginArgumentList (class in pytan3.api_objects.soap_7_3_314_3424), 357
PluginArgumentList (class in pytan3.api_objects.soap_7_3_314_3641), 441
PluginCommandList (class in pytan3.api_objects.rest_7_3_314_3424), 117
PluginCommandList (class in pytan3.api_objects.rest_7_3_314_3641), 201
PluginCommandList (class in pytan3.api_objects.soap_7_2_314_3181), 279
PluginCommandList (class in pytan3.api_objects.soap_7_3_314_3424), 359
PluginCommandList (class in pytan3.api_objects.soap_7_3_314_3641), 443
PluginList (class in pytan3.api_objects.rest_7_3_314_3424), 118
PluginList (class in pytan3.api_objects.rest_7_3_314_3641), 202
PluginList (class in pytan3.api_objects.soap_7_2_314_3181), 280
PluginList (class in pytan3.api_objects.soap_7_3_314_3424), 360
PluginList (class in pytan3.api_objects.soap_7_3_314_3641), 444
PluginSchedule (class in pytan3.api_objects.rest_7_3_314_3424), 81
PluginSchedule (class in pytan3.api_objects.rest_7_3_314_3641), 165
PluginSchedule (class in pytan3.api_objects.soap_7_2_314_3181), 249
PluginSchedule (class in pytan3.api_objects.soap_7_3_314_3424), 324
PluginSchedule (class in pytan3.api_objects.soap_7_3_314_3641), 407
PluginScheduleList (class in pytan3.api_objects.rest_7_3_314_3424), 118
PluginScheduleList (class in pytan3.api_objects.rest_7_3_314_3641), 202
PluginScheduleList (class in pytan3.api_objects.soap_7_2_314_3181), 280
PluginScheduleList (class in pytan3.api_objects.soap_7_3_314_3424), 361
PluginScheduleList (class in pytan3.api_objects.soap_7_3_314_3641), 444
PluginSql (class in pytan3.api_objects.rest_7_3_314_3424), 116
PluginSql (class in pytan3.api_objects.rest_7_3_314_3641), 200
PluginSql (class in pytan3.api_objects.soap_7_2_314_3181), 278
PluginSql (class in pytan3.api_objects.soap_7_3_314_3424), 359
PluginSql (class in pytan3.api_objects.soap_7_3_314_3641), 442
PluginSqlColumnList (class in pytan3.api_objects.rest_7_3_314_3424), 116
PluginSqlColumnList (class in pytan3.api_objects.rest_7_3_314_3641), 200
PluginSqlColumnList (class in pytan3.api_objects.soap_7_2_314_3181), 278
PluginSqlColumnList (class in pytan3.api_objects.soap_7_3_314_3424), 358
PluginSqlColumnList (class in pytan3.api_objects.soap_7_3_314_3641), 442
PluginSqlResultList (class in pytan3.api_objects.rest_7_3_314_3424), 115
PluginSqlResultList (class in pytan3.api_objects.rest_7_3_314_3641), 199
PluginSqlResultList (class in pytan3.api_objects.soap_7_2_314_3181), 277
PluginSqlResultList (class in pytan3.api_objects.soap_7_3_314_3424), 358

PluginSqlResultList (class in pytan3.api_objects.soap_7_3_314_3641), 441
pop() (pytan3.api_models.ApiList method), 467
pop_item_by_attr() (pytan3.api_models.ApiList method), 468
pop_items_by_attr() (pytan3.api_models.ApiList method), 468
port (pytan3.http_client.UrlParser attribute), 18
prepare() (pytan3.utils.prompts.Promptness method), 511
prompt() (pytan3.utils.prompts.Promptness method), 511
PromptError, 514
Promptness (class in pytan3.utils.prompts), 510
promptness (in module pytan3.utils.prompts), 515
pytan3 (module), 11
pytan3.adapters (module), 473
pytan3.adapters.exceptions (module), 489
pytan3.api_clients (module), 36
pytan3.api_clients.exceptions (module), 43
pytan3.api_models (module), 459
pytan3.api_models.exceptions (module), 469
pytan3.api_objects (module), 43
pytan3.api_objects.exceptions (module), 47
pytan3.api_objects.rest_7_3_314_3424 (module), 48
pytan3.api_objects.rest_7_3_314_3641 (module), 132
pytan3.api_objects.soap_7_2_314_3181 (module), 216
pytan3.api_objects.soap_7_3_314_3424 (module), 291
pytan3.api_objects.soap_7_3_314_3641 (module), 375
pytan3.auth_methods (module), 19
pytan3.auth_methods.exceptions (module), 25
pytan3.auth_store (module), 32
pytan3.auth_store.exceptions (module), 36
pytan3.exceptions (module), 522
pytan3.http_client (module), 11
pytan3.http_client.exceptions (module), 19
pytan3.results (module), 489
pytan3.results.exceptions (module), 500
pytan3.utils (module), 502
pytan3.utils.crypt (module), 503
pytan3.utils.exceptions (module), 520
pytan3.utils.logs (module), 503
pytan3.utils.prompts (module), 509
pytan3.utils.tools (module), 515
pytan3.utils.versions (module), 518
pytan3.version (module), 522
pytan3.workflows (module), 521
PyTanError, 522
PyTanWarning, 522

Q

Question (class in pytan3.api_objects.rest_7_3_314_3424), 67
Question (class in pytan3.api_objects.rest_7_3_314_3641), 152
Question (class in pytan3.api_objects.soap_7_2_314_3181), 235
Question (class in pytan3.api_objects.soap_7_3_314_3424), 310
Question (class in pytan3.api_objects.soap_7_3_314_3641), 394
QuestionList (class in pytan3.api_objects.rest_7_3_314_3424), 104
QuestionList (class in pytan3.api_objects.rest_7_3_314_3641), 188
QuestionList (class in pytan3.api_objects.soap_7_2_314_3181), 266
QuestionList (class in pytan3.api_objects.soap_7_3_314_3424), 347
QuestionList (class in pytan3.api_objects.soap_7_3_314_3641), 431
QuestionListInfo (class in pytan3.api_objects.rest_7_3_314_3424), 67
QuestionListInfo (class in pytan3.api_objects.rest_7_3_314_3641), 151
QuestionListInfo (class in pytan3.api_objects.soap_7_2_314_3181), 234
QuestionListInfo (class in pytan3.api_objects.soap_7_3_314_3424), 310
QuestionListInfo (class in pytan3.api_objects.soap_7_3_314_3641), 393

R

re_soap_tag() (in module pytan3.adapters), 487
RECORD_FILE (in module pytan3.http_client), 11
record_path (pytan3.http_client.HttpClient attribute), 12
regex_value (pytan3.api_models.exceptions.GetSingleItemError attribute), 473
remove() (pytan3.api_models.ApiList method), 467
remove_file() (in module pytan3.utils.logs), 508
remove_handler() (in module pytan3.utils.logs), 508
remove_null() (in module pytan3.utils.logs), 508
remove_stderr() (in module pytan3.utils.logs), 507
remove_stdout() (in module pytan3.utils.logs), 507
reparse() (pytan3.http_client.UrlParser method), 18
request_body_obj (pytan3.results.Rest attribute), 498
request_body_obj (pytan3.results.Result attribute), 490
request_body_obj (pytan3.results.Soap attribute), 495
request_body_str (pytan3.results.CommonMixin attribute), 493
request_body_str (pytan3.results.Result attribute), 490
request_object_obj (pytan3.results.exceptions.ResponseError attribute), 500
request_object_obj (pytan3.results.Rest attribute), 498
request_object_obj (pytan3.results.Result attribute), 491
request_object_obj (pytan3.results.Soap attribute), 495
response_body (pytan3.results.exceptions.ResponseError attribute), 500

response_body_obj (pytan3.results.Rest attribute), 498
response_body_obj (pytan3.results.Result attribute), 491
response_body_obj (pytan3.results.Soap attribute), 495
response_body_str (pytan3.results.CommonMixin attribute), 493
response_body_str (pytan3.results.Result attribute), 491
response_hook_clean() (pytan3.http_client.HttpClient method), 14
response_hook_disk() (pytan3.http_client.HttpClient method), 14
response_hook_history() (pytan3.http_client.HttpClient method), 14
response_hook_log_debug() (pytan3.http_client.HttpClient method), 14
ResponseError, 500
Rest (class in pytan3.adapters), 480
Rest (class in pytan3.api_clients), 39
Rest (class in pytan3.results), 496
rest_version (pytan3.api_clients.Rest attribute), 41
rest_version (pytan3.auth_methods.RestCredentials attribute), 29
RestCredentials (class in pytan3.auth_methods), 28
RestUrlPath (class in pytan3.results), 499
Result (class in pytan3.results), 490
result (pytan3.results.exceptions.ApiWrongRequestType attribute), 502
result (pytan3.results.exceptions.DictionaryPathError attribute), 502
result (pytan3.results.exceptions.ResponseError attribute), 500
result (pytan3.results.exceptions.TextDeserializeError attribute), 501
result_cls (pytan3.adapters.Adapter attribute), 474
result_cls (pytan3.adapters.Rest attribute), 482
result_cls (pytan3.adapters.Soap attribute), 477
result_type (pytan3.api_objects.rest_7_3_314_3424.Column attribute), 54
result_type (pytan3.api_objects.rest_7_3_314_3424.RowColumn attribute), 57
result_type (pytan3.api_objects.rest_7_3_314_3641.Column attribute), 138
result_type (pytan3.api_objects.rest_7_3_314_3641.RowColumn attribute), 141
result_type (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
result_type (pytan3.api_objects.soap_7_2_314_3181.RowColumn attribute), 226
result_type (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 297
result_type (pytan3.api_objects.soap_7_3_314_3424.RowColumn attribute), 300
result_type (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
result_type (pytan3.api_objects.soap_7_3_314_3641.RowColumn attribute), 384
ResultInfo (class in pytan3.api_objects.rest_7_3_314_3424), 50
ResultInfo (class in pytan3.api_objects.rest_7_3_314_3641), 134
ResultInfo (class in pytan3.api_objects.soap_7_2_314_3181), 218
ResultInfo (class in pytan3.api_objects.soap_7_3_314_3424), 293
ResultInfo (class in pytan3.api_objects.soap_7_3_314_3641), 376
ResultInfoList (class in pytan3.api_objects.rest_7_3_314_3424), 50
ResultInfoList (class in pytan3.api_objects.rest_7_3_314_3641), 134
ResultInfoList (class in pytan3.api_objects.soap_7_2_314_3181), 217
ResultInfoList (class in pytan3.api_objects.soap_7_3_314_3424), 292
ResultInfoList (class in pytan3.api_objects.soap_7_3_314_3641), 376
ResultSet (class in pytan3.api_objects.rest_7_3_314_3424), 52
ResultSet (class in pytan3.api_objects.rest_7_3_314_3641), 136
ResultSet (class in pytan3.api_objects.soap_7_2_314_3181), 220
ResultSet (class in pytan3.api_objects.soap_7_3_314_3424), 294
ResultSet (class in pytan3.api_objects.soap_7_3_314_3641), 378
ResultSetList (class in pytan3.api_objects.rest_7_3_314_3424), 51
ResultSetList (class in pytan3.api_objects.rest_7_3_314_3641), 135
ResultSetList (class in pytan3.api_objects.soap_7_2_314_3181), 219
ResultSetList (class in pytan3.api_objects.soap_7_3_314_3424), 293
ResultSetList (class in pytan3.api_objects.soap_7_3_314_3641), 377
revalidate_after (pytan3.auth_methods.CommonMixin attribute), 22
reverse() (pytan3.api_models.ApiList method), 467
route (pytan3.results.RestUrlPath attribute), 500
Row (class in pytan3.api_objects.rest_7_3_314_3424), 55
Row (class in pytan3.api_objects.rest_7_3_314_3641), 139
Row (class in pytan3.api_objects.soap_7_2_314_3181), 223
Row (class in pytan3.api_objects.soap_7_3_314_3424), 298
Row (class in pytan3.api_objects.soap_7_3_314_3641), 381

RowColumn (class in pytan3.api_objects.rest_7_3_314_3424), 56
RowColumn (class in pytan3.api_objects.rest_7_3_314_3641), 141
RowColumn (class in pytan3.api_objects.soap_7_2_314_3181), 225
RowColumn (class in pytan3.api_objects.soap_7_3_314_3424), 300
RowColumn (class in pytan3.api_objects.soap_7_3_314_3641), 384
RowColumnList (class in pytan3.api_objects.rest_7_3_314_3424), 56
RowColumnList (class in pytan3.api_objects.rest_7_3_314_3641), 140
RowColumnList (class in pytan3.api_objects.soap_7_2_314_3181), 224
RowColumnList (class in pytan3.api_objects.soap_7_3_314_3424), 299
RowColumnList (class in pytan3.api_objects.soap_7_3_314_3641), 383
RowList (class in pytan3.api_objects.rest_7_3_314_3424), 54
RowList (class in pytan3.api_objects.rest_7_3_314_3641), 138
RowList (class in pytan3.api_objects.soap_7_2_314_3181), 222
RowList (class in pytan3.api_objects.soap_7_3_314_3424), 297
RowList (class in pytan3.api_objects.soap_7_3_314_3641), 381
rows (pytan3.api_objects.soap_7_2_314_3181.ResultSet attribute), 220
rows (pytan3.api_objects.soap_7_3_314_3424.ResultSet attribute), 295
rows (pytan3.api_objects.soap_7_3_314_3641.ResultSet attribute), 379
RowValue (class in pytan3.api_objects.rest_7_3_314_3424), 57
RowValue (class in pytan3.api_objects.rest_7_3_314_3641), 142
RowValue (class in pytan3.api_objects.soap_7_2_314_3181), 226
RowValue (class in pytan3.api_objects.soap_7_3_314_3424), 301
RowValue (class in pytan3.api_objects.soap_7_3_314_3641), 385

S

SavedAction (class in pytan3.api_objects.rest_7_3_314_3424), 61
SavedAction (class in pytan3.api_objects.rest_7_3_314_3641), 145
SavedAction (class in pytan3.api_objects.soap_7_2_314_3181), 229
SavedAction (class in pytan3.api_objects.soap_7_3_314_3424), 304
SavedAction (class in pytan3.api_objects.soap_7_3_314_3641), 388
SavedActionApproval (class in pytan3.api_objects.rest_7_3_314_3424), 61
SavedActionApproval (class in pytan3.api_objects.rest_7_3_314_3641), 145
SavedActionApproval (class in pytan3.api_objects.soap_7_2_314_3181), 229
SavedActionApproval (class in pytan3.api_objects.soap_7_3_314_3424), 303
SavedActionApproval (class in pytan3.api_objects.soap_7_3_314_3641), 387
SavedActionApprovalList (class in pytan3.api_objects.rest_7_3_314_3424), 98
SavedActionApprovalList (class in pytan3.api_objects.rest_7_3_314_3641), 182
SavedActionApprovalList (class in pytan3.api_objects.soap_7_2_314_3181), 262
SavedActionApprovalList (class in pytan3.api_objects.soap_7_3_314_3424), 341
SavedActionApprovalList (class in pytan3.api_objects.soap_7_3_314_3641), 424
SavedActionList (class in pytan3.api_objects.rest_7_3_314_3424), 99
SavedActionList (class in pytan3.api_objects.rest_7_3_314_3641), 183
SavedActionList (class in pytan3.api_objects.soap_7_2_314_3181), 263
SavedActionList (class in pytan3.api_objects.soap_7_3_314_3424), 342
SavedActionList (class in pytan3.api_objects.soap_7_3_314_3641), 425
SavedActionPolicy (class in pytan3.api_objects.rest_7_3_314_3424), 60
SavedActionPolicy (class in pytan3.api_objects.rest_7_3_314_3641), 145
SavedActionPolicy (class in pytan3.api_objects.soap_7_2_314_3181), 228
SavedActionPolicy (class in pytan3.api_objects.soap_7_3_314_3424), 303
SavedActionPolicy (class in pytan3.api_objects.soap_7_3_314_3641), 387
SavedActionRowIdList (class in pytan3.api_objects.rest_7_3_314_3424), 99
SavedActionRowIdList (class in pytan3.api_objects.rest_7_3_314_3641), 183
SavedActionRowIdList (class in pytan3.api_objects.soap_7_2_314_3181), 262
SavedActionRowIdList (class in pytan3.api_objects.soap_7_3_314_3424), 341
SavedActionRowIdList (class in pytan3.api_objects.soap_7_3_314_3641), 425

SavedQuestion (class in pytan3.api_objects.rest_7_3_314_3424), 76
SavedQuestion (class in pytan3.api_objects.rest_7_3_314_3641), 160
SavedQuestion (class in pytan3.api_objects.soap_7_2_314_3181), 243
SavedQuestion (class in pytan3.api_objects.soap_7_3_314_3424), 318
SavedQuestion (class in pytan3.api_objects.soap_7_3_314_3641), 402
SavedQuestionList (class in pytan3.api_objects.rest_7_3_314_3424), 111
SavedQuestionList (class in pytan3.api_objects.rest_7_3_314_3641), 196
SavedQuestionList (class in pytan3.api_objects.soap_7_2_314_3181), 274
SavedQuestionList (class in pytan3.api_objects.soap_7_3_314_3424), 354
SavedQuestionList (class in pytan3.api_objects.soap_7_3_314_3641), 438
SavedQuestionPackageSpecs (class in pytan3.api_objects.rest_7_3_314_3424), 91
SavedQuestionPackageSpecs (class in pytan3.api_objects.rest_7_3_314_3641), 175
SavedQuestionPackageSpecs (class in pytan3.api_objects.soap_7_2_314_3181), 257
SavedQuestionPackageSpecs (class in pytan3.api_objects.soap_7_3_314_3424), 334
SavedQuestionPackageSpecs (class in pytan3.api_objects.soap_7_3_314_3641), 417
SavedQuestionQuestion (class in pytan3.api_objects.rest_7_3_314_3424), 91
SavedQuestionQuestion (class in pytan3.api_objects.rest_7_3_314_3641), 176
SavedQuestionQuestion (class in pytan3.api_objects.soap_7_2_314_3181), 258
SavedQuestionQuestion (class in pytan3.api_objects.soap_7_3_314_3424), 334
SavedQuestionQuestion (class in pytan3.api_objects.soap_7_3_314_3641), 418
SavedQuestionQuestionList (class in pytan3.api_objects.rest_7_3_314_3424), 127
SavedQuestionQuestionList (class in pytan3.api_objects.rest_7_3_314_3641), 211
SavedQuestionQuestionList (class in pytan3.api_objects.soap_7_2_314_3181), 289
SavedQuestionQuestionList (class in pytan3.api_objects.soap_7_3_314_3424), 370
SavedQuestionQuestionList (class in pytan3.api_objects.soap_7_3_314_3641), 453
scheme (pytan3.http_client.UrlParser attribute), 18
secret (pytan3.auth_store.AuthStore attribute), 33
secs_age() (in module pytan3.utils.tools), 516
secs_ago() (in module pytan3.utils.tools), 516
Select (class in pytan3.api_objects.rest_7_3_314_3424), 65
Select (class in pytan3.api_objects.rest_7_3_314_3641), 150
Select (class in pytan3.api_objects.soap_7_2_314_3181), 233
Select (class in pytan3.api_objects.soap_7_3_314_3424), 308
Select (class in pytan3.api_objects.soap_7_3_314_3641), 392
SelectList (class in pytan3.api_objects.rest_7_3_314_3424), 103
SelectList (class in pytan3.api_objects.rest_7_3_314_3641), 187
SelectList (class in pytan3.api_objects.soap_7_2_314_3181), 266
SelectList (class in pytan3.api_objects.soap_7_3_314_3424), 346
SelectList (class in pytan3.api_objects.soap_7_3_314_3641), 430
send() (pytan3.adapters.Soap method), 477
Sensor (class in pytan3.api_objects.rest_7_3_314_3424), 62
Sensor (class in pytan3.api_objects.rest_7_3_314_3641), 146
Sensor (class in pytan3.api_objects.soap_7_2_314_3181), 230
Sensor (class in pytan3.api_objects.soap_7_3_314_3424), 304
Sensor (class in pytan3.api_objects.soap_7_3_314_3641), 388
SensorList (class in pytan3.api_objects.rest_7_3_314_3424), 97
SensorList (class in pytan3.api_objects.rest_7_3_314_3641), 181
SensorList (class in pytan3.api_objects.soap_7_2_314_3181), 261
SensorList (class in pytan3.api_objects.soap_7_3_314_3424), 340
SensorList (class in pytan3.api_objects.soap_7_3_314_3641), 423
SensorQuery (class in pytan3.api_objects.rest_7_3_314_3424), 59
SensorQuery (class in pytan3.api_objects.rest_7_3_314_3641), 143
SensorQuery (class in pytan3.api_objects.soap_7_2_314_3181), 227
SensorQuery (class in pytan3.api_objects.soap_7_3_314_3424), 301
SensorQuery (class in pytan3.api_objects.soap_7_3_314_3641), 385
SensorQueryList (class in pytan3.api_objects.rest_7_3_314_3424), 96
SensorQueryList (class in py-

tan3.api_objects.rest_7_3_314_3641), 180
SensorQueryList (class in pytan3.api_objects.soap_7_2_314_3181), 259
SensorQueryList (class in pytan3.api_objects.soap_7_3_314_3424), 338
SensorQueryList (class in pytan3.api_objects.soap_7_3_314_3641), 422
SensorReference (class in pytan3.api_objects.rest_7_3_314_3424), 78
SensorReference (class in pytan3.api_objects.rest_7_3_314_3641), 162
SensorReference (class in pytan3.api_objects.soap_7_2_314_3181), 245
SensorReference (class in pytan3.api_objects.soap_7_3_314_3424), 320
SensorReference (class in pytan3.api_objects.soap_7_3_314_3641), 404
SensorReferenceList (class in pytan3.api_objects.rest_7_3_314_3424), 114
SensorReferenceList (class in pytan3.api_objects.rest_7_3_314_3641), 198
SensorReferenceList (class in pytan3.api_objects.soap_7_2_314_3181), 276
SensorReferenceList (class in pytan3.api_objects.soap_7_3_314_3424), 357
SensorReferenceList (class in pytan3.api_objects.soap_7_3_314_3641), 440
SensorStat (class in pytan3.api_objects.rest_7_3_314_3424), 60
SensorStat (class in pytan3.api_objects.rest_7_3_314_3641), 144
SensorStat (class in pytan3.api_objects.soap_7_2_314_3181), 228
SensorStat (class in pytan3.api_objects.soap_7_3_314_3424), 302
SensorStat (class in pytan3.api_objects.soap_7_3_314_3641), 386
SensorStatList (class in pytan3.api_objects.rest_7_3_314_3424), 98
SensorStatList (class in pytan3.api_objects.rest_7_3_314_3641), 182
SensorStatList (class in pytan3.api_objects.soap_7_2_314_3181), 261
SensorStatList (class in pytan3.api_objects.soap_7_3_314_3424), 340
SensorStatList (class in pytan3.api_objects.soap_7_3_314_3641), 424
SensorSubcolumn (class in pytan3.api_objects.rest_7_3_314_3424), 59
SensorSubcolumn (class in pytan3.api_objects.rest_7_3_314_3641), 144
SensorSubcolumn (class in pytan3.api_objects.soap_7_2_314_3181), 227
SensorSubcolumn (class in pytan3.api_objects.soap_7_3_314_3424), 302
SensorSubcolumn (class in pytan3.api_objects.soap_7_3_314_3641), 386
SensorSubcolumnList (class in pytan3.api_objects.rest_7_3_314_3424), 96
SensorSubcolumnList (class in pytan3.api_objects.rest_7_3_314_3641), 180
SensorSubcolumnList (class in pytan3.api_objects.soap_7_2_314_3181), 260
SensorSubcolumnList (class in pytan3.api_objects.soap_7_3_314_3424), 339
SensorSubcolumnList (class in pytan3.api_objects.soap_7_3_314_3641), 422
serialize() (pytan3.api_models.ApiItem method), 463
serialize() (pytan3.api_models.ApiList method), 469
serialize_json() (in module pytan3.adapters), 488
serialize_response() (pytan3.http_client.HttpClient method), 15
serialize_xml() (in module pytan3.adapters), 487
Server (class in pytan3.api_objects.rest_7_3_314_3424), 63
Server (class in pytan3.api_objects.rest_7_3_314_3641), 147
Server (class in pytan3.api_objects.soap_7_3_314_3424), 306
Server (class in pytan3.api_objects.soap_7_3_314_3641), 390
ServerHost (class in pytan3.api_objects.rest_7_3_314_3424), 101
ServerHost (class in pytan3.api_objects.rest_7_3_314_3641), 185
ServerHost (class in pytan3.api_objects.soap_7_3_314_3424), 344
ServerHost (class in pytan3.api_objects.soap_7_3_314_3641), 427
ServerHostList (class in pytan3.api_objects.rest_7_3_314_3424), 101
ServerHostList (class in pytan3.api_objects.rest_7_3_314_3641), 186
ServerHostList (class in pytan3.api_objects.soap_7_3_314_3424), 344
ServerHostList (class in pytan3.api_objects.soap_7_3_314_3641), 428
ServerList (class in pytan3.api_objects.rest_7_3_314_3424), 100
ServerList (class in pytan3.api_objects.rest_7_3_314_3641), 185
ServerList (class in pytan3.api_objects.soap_7_3_314_3424), 343
ServerList (class in pytan3.api_objects.soap_7_3_314_3641), 427
ServerThrottle (class in pytan3.api_objects.rest_7_3_314_3424), 92
ServerThrottle (class in py-

tan3.api_objects.rest_7_3_314_3641), 176
ServerThrottle (class in pytan3.api_objects.soap_7_3_314_3424), 335
ServerThrottle (class in pytan3.api_objects.soap_7_3_314_3641), 419
ServerThrottleList (class in pytan3.api_objects.rest_7_3_314_3424), 128
ServerThrottleList (class in pytan3.api_objects.rest_7_3_314_3641), 212
ServerThrottleList (class in pytan3.api_objects.soap_7_3_314_3424), 371
ServerThrottleList (class in pytan3.api_objects.soap_7_3_314_3641), 454
ServerThrottleStatus (class in pytan3.api_objects.rest_7_3_314_3424), 94
ServerThrottleStatus (class in pytan3.api_objects.rest_7_3_314_3641), 178
ServerThrottleStatus (class in pytan3.api_objects.soap_7_3_314_3424), 336
ServerThrottleStatus (class in pytan3.api_objects.soap_7_3_314_3641), 420
ServerThrottleStatusList (class in pytan3.api_objects.rest_7_3_314_3424), 130
ServerThrottleStatusList (class in pytan3.api_objects.rest_7_3_314_3641), 214
ServerThrottleStatusList (class in pytan3.api_objects.soap_7_3_314_3424), 372
ServerThrottleStatusList (class in pytan3.api_objects.soap_7_3_314_3641), 456
session (pytan3.http_client.HttpClient attribute), 12
SessionId (class in pytan3.auth_methods), 30
SessionNotFoundWarning, 489
set() (pytan3.auth_store.AuthStore method), 33
set_level() (in module pytan3.utils.logs), 505
SHOW_CERT (in module pytan3.http_client), 11
SHOW_CHAIN (in module pytan3.http_client), 11
simple_types (in module pytan3.api_models), 459
simple_types (in module pytan3.api_objects.rest_7_3_314_3424), 48
simple_types (in module pytan3.api_objects.rest_7_3_314_3641), 132
simple_types (in module pytan3.api_objects.soap_7_2_314_3181), 217
simple_types (in module pytan3.api_objects.soap_7_3_314_3424), 291
simple_types (in module pytan3.api_objects.soap_7_3_314_3641), 375
SiteThrottle (class in pytan3.api_objects.rest_7_3_314_3424), 93
SiteThrottle (class in pytan3.api_objects.rest_7_3_314_3641), 177
SiteThrottle (class in pytan3.api_objects.soap_7_3_314_3424), 335
SiteThrottle (class in pytan3.api_objects.soap_7_3_314_3641), 419
SiteThrottleList (class in pytan3.api_objects.rest_7_3_314_3424), 129
SiteThrottleList (class in pytan3.api_objects.rest_7_3_314_3641), 213
SiteThrottleList (class in pytan3.api_objects.soap_7_3_314_3424), 371
SiteThrottleList (class in pytan3.api_objects.soap_7_3_314_3641), 455
SiteThrottleStatus (class in pytan3.api_objects.rest_7_3_314_3424), 94
SiteThrottleStatus (class in pytan3.api_objects.rest_7_3_314_3641), 178
SiteThrottleStatus (class in pytan3.api_objects.soap_7_3_314_3424), 337
SiteThrottleStatus (class in pytan3.api_objects.soap_7_3_314_3641), 421
SiteThrottleStatusList (class in pytan3.api_objects.rest_7_3_314_3424), 130
SiteThrottleStatusList (class in pytan3.api_objects.rest_7_3_314_3641), 214
SiteThrottleStatusList (class in pytan3.api_objects.soap_7_3_314_3424), 373
SiteThrottleStatusList (class in pytan3.api_objects.soap_7_3_314_3641), 456
SiteThrottleSubnet (class in pytan3.api_objects.rest_7_3_314_3424), 93
SiteThrottleSubnet (class in pytan3.api_objects.rest_7_3_314_3641), 177
SiteThrottleSubnet (class in pytan3.api_objects.soap_7_3_314_3424), 336
SiteThrottleSubnet (class in pytan3.api_objects.soap_7_3_314_3641), 420
SiteThrottleSubnetList (class in pytan3.api_objects.rest_7_3_314_3424), 129
SiteThrottleSubnetList (class in pytan3.api_objects.rest_7_3_314_3641), 213
SiteThrottleSubnetList (class in pytan3.api_objects.soap_7_3_314_3424), 372
SiteThrottleSubnetList (class in pytan3.api_objects.soap_7_3_314_3641), 455
SiteThrottleSubnetStatus (class in pytan3.api_objects.rest_7_3_314_3424), 95
SiteThrottleSubnetStatus (class in pytan3.api_objects.rest_7_3_314_3641), 179
SiteThrottleSubnetStatus (class in pytan3.api_objects.soap_7_3_314_3424), 337
SiteThrottleSubnetStatus (class in pytan3.api_objects.soap_7_3_314_3641), 421
SiteThrottleSubnetStatusList (class in pytan3.api_objects.rest_7_3_314_3424), 131
SiteThrottleSubnetStatusList (class in pytan3.api_objects.rest_7_3_314_3641), 215
SiteThrottleSubnetStatusList (class in py-

tan3.api_objects.soap_7_3_314_3424), 373
SiteThrottleSubnetStatusList (class in pytan3.api_objects.soap_7_3_314_3641), 457
Soap (class in pytan3.adapters), 475
Soap (class in pytan3.api_clients), 38
Soap (class in pytan3.results), 494
soap_envelope() (in module pytan3.adapters), 487
SoapError (class in pytan3.api_objects.rest_7_3_314_3424), 71
SoapError (class in pytan3.api_objects.rest_7_3_314_3641), 155
SoapError (class in pytan3.api_objects.soap_7_2_314_3181), 238
SoapError (class in pytan3.api_objects.soap_7_3_314_3424), 313
SoapError (class in pytan3.api_objects.soap_7_3_314_3641), 397
Solution (class in pytan3.api_objects.rest_7_3_314_3424), 90
Solution (class in pytan3.api_objects.rest_7_3_314_3641), 174
Solution (class in pytan3.api_objects.soap_7_2_314_3181), 257
Solution (class in pytan3.api_objects.soap_7_3_314_3424), 333
Solution (class in pytan3.api_objects.soap_7_3_314_3641), 416
SolutionList (class in pytan3.api_objects.rest_7_3_314_3424), 126
SolutionList (class in pytan3.api_objects.rest_7_3_314_3641), 210
SolutionList (class in pytan3.api_objects.soap_7_2_314_3181), 288
SolutionList (class in pytan3.api_objects.soap_7_3_314_3424), 369
SolutionList (class in pytan3.api_objects.soap_7_3_314_3641), 453
sort() (pytan3.api_models.ApiList method), 468
spew() (pytan3.utils.prompts.Promptness method), 511
split_ver() (in module pytan3.utils.versions), 520
src (pytan3.results.exceptions.DictionaryPathError attribute), 502
src (pytan3.results.exceptions.TextDeserializeError attribute), 501
start (pytan3.utils.tools.Timer attribute), 517
status_code (pytan3.results.CommonMixin attribute), 493
status_code (pytan3.results.Result attribute), 490
STORAGE_DIR (in module pytan3.utils.tools), 515
STORAGE_PATH (in module pytan3.utils.tools), 515
store (pytan3.http_client.Certify attribute), 17
store_chain (pytan3.http_client.Certify attribute), 17
STORE_FILE (in module pytan3.auth_store), 32
str_to_intfloat() (in module pytan3.utils.tools), 515
str_to_obj() (pytan3.results.Rest method), 498
str_to_obj() (pytan3.results.Result method), 491
str_to_obj() (pytan3.results.Soap method), 496
stream_name() (in module pytan3.utils.prompts), 514
string_types (in module pytan3.api_models), 459
string_types (in module pytan3.api_objects.rest_7_3_314_3424), 48
string_types (in module pytan3.api_objects.rest_7_3_314_3641), 132
string_types (in module pytan3.api_objects.soap_7_2_314_3181), 217
string_types (in module pytan3.api_objects.soap_7_3_314_3424), 291
string_types (in module pytan3.api_objects.soap_7_3_314_3641), 375
StringHintList (class in pytan3.api_objects.rest_7_3_314_3424), 97
StringHintList (class in pytan3.api_objects.rest_7_3_314_3641), 181
StringHintList (class in pytan3.api_objects.soap_7_2_314_3181), 260
StringHintList (class in pytan3.api_objects.soap_7_3_314_3424), 339
StringHintList (class in pytan3.api_objects.soap_7_3_314_3641), 423
SystemSetting (class in pytan3.api_objects.rest_7_3_314_3424), 70
SystemSetting (class in pytan3.api_objects.rest_7_3_314_3641), 154
SystemSetting (class in pytan3.api_objects.soap_7_2_314_3181), 238
SystemSetting (class in pytan3.api_objects.soap_7_3_314_3424), 313
SystemSetting (class in pytan3.api_objects.soap_7_3_314_3641), 397
SystemSettingList (class in pytan3.api_objects.rest_7_3_314_3424), 108
SystemSettingList (class in pytan3.api_objects.rest_7_3_314_3641), 192
SystemSettingList (class in pytan3.api_objects.soap_7_2_314_3181), 270
SystemSettingList (class in pytan3.api_objects.soap_7_3_314_3424), 351
SystemSettingList (class in pytan3.api_objects.soap_7_3_314_3641), 434
SystemStatusAggregate (class in pytan3.api_objects.rest_7_3_314_3424), 72
SystemStatusAggregate (class in pytan3.api_objects.rest_7_3_314_3641), 156
SystemStatusAggregate (class in pytan3.api_objects.soap_7_2_314_3181), 240
SystemStatusAggregate (class in pytan3.api_objects.soap_7_3_314_3424), 315
SystemStatusAggregate (class in pytan3.api_objects.soap_7_3_314_3641), 398

SystemStatusList (class in pytan3.api_objects.rest_7_3_314_3424), 108
SystemStatusList (class in pytan3.api_objects.rest_7_3_314_3641), 192
SystemStatusList (class in pytan3.api_objects.soap_7_2_314_3181), 270
SystemStatusList (class in pytan3.api_objects.soap_7_3_314_3424), 350
SystemStatusList (class in pytan3.api_objects.soap_7_3_314_3641), 434

T

T_ATTR_DESC (pytan3.api_models.ApiModel attribute), 459
T_ATTR_JOIN (pytan3.api_models.ApiModel attribute), 459
T_ATTR_REPR (pytan3.api_models.ApiModel attribute), 459
T_ATTR_STR (pytan3.api_models.ApiModel attribute), 459
T_CLS_REPR (pytan3.api_models.ApiModel attribute), 459
T_CLS_STR (pytan3.api_models.ApiList attribute), 463
T_CLS_STR (pytan3.api_models.ApiModel attribute), 459
T_DESC (pytan3.api_models.ApiModel attribute), 459
target (pytan3.results.RestUrlPath attribute), 500
text (pytan3.results.exceptions.TextDeserializeError attribute), 501
TextDeserializeError, 501
timeout (pytan3.http_client.HttpClient attribute), 11
Timer (class in pytan3.utils.tools), 517
TMPLS (pytan3.utils.prompts.Promptness attribute), 510
to_path() (pytan3.auth_store.AuthStore method), 33
to_stream() (pytan3.auth_store.AuthStore method), 33
to_string() (pytan3.auth_store.AuthStore method), 34
token (pytan3.auth_methods.AuthMethod attribute), 20
token (pytan3.auth_methods.CommonMixin attribute), 23
token (pytan3.auth_methods.SessionId attribute), 31
token_headers (pytan3.auth_methods.AuthMethod attribute), 21
token_headers (pytan3.auth_methods.CommonMixin attribute), 23
trim_txt() (in module pytan3.utils.tools), 516
try_int_xml() (in module pytan3.results), 499
TYPE (in module pytan3.api_objects.rest_7_3_314_3424), 48
TYPE (in module pytan3.api_objects.rest_7_3_314_3641), 132
TYPE (in module pytan3.api_objects.soap_7_2_314_3181), 217
TYPE (in module pytan3.api_objects.soap_7_3_314_3424), 291
TYPE (in module pytan3.api_objects.soap_7_3_314_3641), 375
type (pytan3.api_objects.soap_7_2_314_3181.Column attribute), 222
type (pytan3.api_objects.soap_7_3_314_3424.Column attribute), 297
type (pytan3.api_objects.soap_7_3_314_3641.Column attribute), 380
TypeMismatchError, 489

U

uid (pytan3.auth_methods.AuthMethod attribute), 21
uid (pytan3.auth_methods.CommonMixin attribute), 23
UnknownApiNameError, 48
unparse_all() (pytan3.http_client.UrlParser method), 19
unparse_base() (pytan3.http_client.UrlParser method), 19
UploadFile (class in pytan3.api_objects.rest_7_3_314_3424), 80
UploadFile (class in pytan3.api_objects.rest_7_3_314_3641), 164
UploadFile (class in pytan3.api_objects.soap_7_2_314_3181), 247
UploadFile (class in pytan3.api_objects.soap_7_3_314_3424), 322
UploadFile (class in pytan3.api_objects.soap_7_3_314_3641), 406
UploadFileList (class in pytan3.api_objects.rest_7_3_314_3424), 117
UploadFileList (class in pytan3.api_objects.rest_7_3_314_3641), 201
UploadFileList (class in pytan3.api_objects.soap_7_2_314_3181), 279
UploadFileList (class in pytan3.api_objects.soap_7_3_314_3424), 360
UploadFileList (class in pytan3.api_objects.soap_7_3_314_3641), 443
UploadFileStatus (class in pytan3.api_objects.rest_7_3_314_3424), 80
UploadFileStatus (class in pytan3.api_objects.rest_7_3_314_3641), 164
UploadFileStatus (class in pytan3.api_objects.soap_7_2_314_3181), 248
UploadFileStatus (class in pytan3.api_objects.soap_7_3_314_3424), 323
UploadFileStatus (class in pytan3.api_objects.soap_7_3_314_3641), 406
url (pytan3.api_clients.ApiClient attribute), 37
url (pytan3.api_clients.Rest attribute), 41
url (pytan3.api_clients.Soap attribute), 39
url (pytan3.http_client.HttpClient attribute), 12
url (pytan3.http_client.UrlParser attribute), 18
url (pytan3.results.CommonMixin attribute), 493
url (pytan3.results.RestUrlPath attribute), 499
url() (pytan3.results.Result method), 490

url_full (pytan3.http_client.UrlParser attribute), 18
url_original (pytan3.results.RestUrlPath attribute), 499
url_path (pytan3.results.Rest attribute), 498
url_path (pytan3.results.RestUrlPath attribute), 499
UrlParser (class in pytan3.http_client), 17
USE_COLOR (pytan3.utils.prompts.Promptness attribute), 510
use_gmt() (in module pytan3.utils.logs), 504
use_localtime() (in module pytan3.utils.logs), 504
User (class in pytan3.api_objects.rest_7_3_314_3424), 73
User (class in pytan3.api_objects.rest_7_3_314_3641), 158
User (class in pytan3.api_objects.soap_7_2_314_3181), 241
User (class in pytan3.api_objects.soap_7_3_314_3424), 316
User (class in pytan3.api_objects.soap_7_3_314_3641), 400
user_agent (pytan3.http_client.HttpClient attribute), 15
UserGroup (class in pytan3.api_objects.rest_7_3_314_3424), 89
UserGroup (class in pytan3.api_objects.rest_7_3_314_3641), 174
UserGroup (class in pytan3.api_objects.soap_7_2_314_3181), 256
UserGroup (class in pytan3.api_objects.soap_7_3_314_3424), 332
UserGroup (class in pytan3.api_objects.soap_7_3_314_3641), 416
UserGroupList (class in pytan3.api_objects.rest_7_3_314_3424), 126
UserGroupList (class in pytan3.api_objects.rest_7_3_314_3641), 210
UserGroupList (class in pytan3.api_objects.soap_7_2_314_3181), 288
UserGroupList (class in pytan3.api_objects.soap_7_3_314_3424), 368
UserGroupList (class in pytan3.api_objects.soap_7_3_314_3641), 452
UserList (class in pytan3.api_objects.rest_7_3_314_3424), 109
UserList (class in pytan3.api_objects.rest_7_3_314_3641), 193
UserList (class in pytan3.api_objects.soap_7_2_314_3181), 271
UserList (class in pytan3.api_objects.soap_7_3_314_3424), 351
UserList (class in pytan3.api_objects.soap_7_3_314_3641), 435
UserOwnedObjectIds (class in pytan3.api_objects.rest_7_3_314_3424), 73
UserOwnedObjectIds (class in pytan3.api_objects.rest_7_3_314_3641), 157
UserOwnedObjectIds (class in pytan3.api_objects.soap_7_2_314_3181), 241
UserOwnedObjectIds (class in pytan3.api_objects.soap_7_3_314_3424), 316
UserOwnedObjectIds (class in pytan3.api_objects.soap_7_3_314_3641), 399
UserRole (class in pytan3.api_objects.rest_7_3_314_3424), 73
UserRole (class in pytan3.api_objects.rest_7_3_314_3641), 157
UserRole (class in pytan3.api_objects.soap_7_2_314_3181), 240
UserRole (class in pytan3.api_objects.soap_7_3_314_3424), 315
UserRole (class in pytan3.api_objects.soap_7_3_314_3641), 399
UserRoleList (class in pytan3.api_objects.rest_7_3_314_3424), 109
UserRoleList (class in pytan3.api_objects.rest_7_3_314_3641), 194
UserRoleList (class in pytan3.api_objects.soap_7_2_314_3181), 272
UserRoleList (class in pytan3.api_objects.soap_7_3_314_3424), 352
UserRoleList (class in pytan3.api_objects.soap_7_3_314_3641), 436
using_custom_cert (pytan3.http_client.Certify attribute), 15

V

valid_codes (pytan3.results.Rest attribute), 498
valid_codes (pytan3.results.Soap attribute), 495
validate() (pytan3.auth_methods.AuthMethod method), 21
validate() (pytan3.auth_methods.CommonMixin method), 24
validate() (pytan3.auth_methods.RestCredentials method), 30
validate_token() (in module pytan3.auth_methods), 24
value (pytan3.api_models.exceptions.AttrTypeError attribute), 471
value (pytan3.api_models.exceptions.AttrUndefinedError attribute), 470
value (pytan3.api_models.exceptions.AttrUndefinedWarning attribute), 470
value (pytan3.api_models.exceptions.GetSingleItemError attribute), 473
value (pytan3.api_models.exceptions.ListTypeError attribute), 471
value (pytan3.api_objects.rest_7_3_314_3424.RowValue attribute), 58
value (pytan3.api_objects.rest_7_3_314_3641.RowValue attribute), 142

value (pytan3.api_objects.soap_7_2_314_3181.RowValue attribute), 227
value (pytan3.api_objects.soap_7_3_314_3424.RowValue attribute), 301
value (pytan3.api_objects.soap_7_3_314_3641.RowValue attribute), 385
verify_hook() (pytan3.http_client.Certify static method), 16
VerifySignature (class in pytan3.api_objects.rest_7_3_314_3424), 82
VerifySignature (class in pytan3.api_objects.rest_7_3_314_3641), 167
VerifySignature (class in pytan3.api_objects.soap_7_3_314_3424), 325
VerifySignature (class in pytan3.api_objects.soap_7_3_314_3641), 409
VERSION (in module pytan3.api_objects.rest_7_3_314_3424), 132
VERSION (in module pytan3.api_objects.rest_7_3_314_3641), 216
VERSION (in module pytan3.api_objects.soap_7_2_314_3181), 291
VERSION (in module pytan3.api_objects.soap_7_3_314_3424), 375
VERSION (in module pytan3.api_objects.soap_7_3_314_3641), 458
version (pytan3.api_clients.ApiClient attribute), 37
version (pytan3.api_clients.Rest attribute), 41
version (pytan3.api_clients.Soap attribute), 39
version (pytan3.results.RestUrlPath attribute), 499
version_check() (in module pytan3.utils.versions), 519
version_check_obj_req() (in module pytan3.utils.versions), 520
version_eq() (in module pytan3.utils.versions), 518
version_max() (in module pytan3.utils.versions), 519
version_min() (in module pytan3.utils.versions), 519
version_recomp() (in module pytan3.utils.versions), 518
VersionAggregate (class in pytan3.api_objects.rest_7_3_314_3424), 72
VersionAggregate (class in pytan3.api_objects.rest_7_3_314_3641), 156
VersionAggregate (class in pytan3.api_objects.soap_7_2_314_3181), 239
VersionAggregate (class in pytan3.api_objects.soap_7_3_314_3424), 314
VersionAggregate (class in pytan3.api_objects.soap_7_3_314_3641), 398
VersionAggregateList (class in pytan3.api_objects.rest_7_3_314_3424), 107
VersionAggregateList (class in pytan3.api_objects.rest_7_3_314_3641), 191
VersionAggregateList (class in pytan3.api_objects.soap_7_2_314_3181), 269
VersionAggregateList (class in pytan3.api_objects.soap_7_3_314_3424), 350
VersionAggregateList (class in pytan3.api_objects.soap_7_3_314_3641), 433
VersionMismatchError, 521

W

warning_hook() (in module pytan3.utils.logs), 504
WhiteListedUrl (class in pytan3.api_objects.rest_7_3_314_3424), 71
WhiteListedUrl (class in pytan3.api_objects.rest_7_3_314_3641), 155
WhiteListedUrl (class in pytan3.api_objects.soap_7_2_314_3181), 239
WhiteListedUrl (class in pytan3.api_objects.soap_7_3_314_3424), 314
WhiteListedUrl (class in pytan3.api_objects.soap_7_3_314_3641), 397
WhiteListedUrlList (class in pytan3.api_objects.rest_7_3_314_3424), 107
WhiteListedUrlList (class in pytan3.api_objects.rest_7_3_314_3641), 191
WhiteListedUrlList (class in pytan3.api_objects.soap_7_2_314_3181), 269
WhiteListedUrlList (class in pytan3.api_objects.soap_7_3_314_3424), 349
WhiteListedUrlList (class in pytan3.api_objects.soap_7_3_314_3641), 433
will_print_at() (in module pytan3.utils.logs), 509
write_pem() (pytan3.http_client.Certify method), 16
WSDL_PATH (in module pytan3.api_clients), 36

X

XmlError (class in pytan3.api_objects.rest_7_3_314_3424), 66
XmlError (class in pytan3.api_objects.rest_7_3_314_3641), 150
XmlError (class in pytan3.api_objects.soap_7_2_314_3181), 233
XmlError (class in pytan3.api_objects.soap_7_3_314_3424), 309
XmlError (class in pytan3.api_objects.soap_7_3_314_3641), 392

Y

YES_VALUES (pytan3.utils.prompts.Promptness attribute), 510